



Radio-echo sounding measurements and ice-core synchronization at Dome C, Antarctica

Anna Winter¹, Daniel Steinhage¹, Emily J. Arnold², Donald D. Blankenship³, Marie G. P. Cavitte³, Hugh F. J. Corr⁴, John D. Paden², Stefano Urbini⁵, Duncan A. Young³, and Olaf Eisen^{1,6}

¹Alfred-Wegener-Institut Helmholtz-Zentrum für Polar- und Meeresforschung, Bremerhaven, Germany

²Center for Remote Sensing of Ice Sheets, Lawrence, KS, USA

³University of Texas Institute for Geophysics, Austin, TX, USA

⁴British Antarctic Survey, Cambridge, UK

⁵Istituto Nazionale di Geofisica e Vulcanologia, Rome, Italy

⁶Fachbereich Geowissenschaften, Universität Bremen, Bremen, Germany

Correspondence to: Winter, Anna (anna.winter@awi.de)

Abstract. We present a compilation of radio-echo sounding (RES) measurements of five radar systems (AWI, BAS, CReSIS, INGV and UTIG) around the EPICA Dome C (EDC) drill site, East Antarctica. The aim of our study is to investigate the differences of the various systems in their resolution of internal reflection horizons (IRHs) and bedrock topography, penetration depth, and quality of imaging the basal layer. We address the questions of the compatibility of existing radar data for common interpretation, and the suitability of the individual systems for Oldest Ice reconnaissance surveys. We find that the most distinct IRHs and IRH patterns can be identified and transferred between most data sets. Considerable differences between the RES systems exist in range resolution and depiction of the basal layer. Considering both aspects, which we judge as crucial factors in the search for old ice, the CReSIS and the UTIG systems are the most valuable ones. In addition to the RES data set comparison we calculate a synthetic radar trace from EDC density and conductivity profiles. We identify ten common IRHs in the measured RES data and the synthetic trace. The reflection-causing conductivity sections are determined by sensitivity studies with the synthetic trace. In this way, we accomplish an accurate two-way travel time to depth conversion for the reflectors, without having to use a precise velocity-depth function that would accumulate depth uncertainties with increasing depth. The identified IRHs are assigned with the AICC2012 time scale age. Due to the isochronous character of these conductivity-caused IRHs, they are a means to extend the Dome C age structure by tracing the IRHs along the RES profiles.

1 Introduction

To predict the future evolution of ice sheets, the knowledge of their past response to climate changes is inevitable. Ice cores are the perfect archives to study the climate of the past. In contrast to other climate archives, they contain actual paleo-atmosphere in the form of air bubbles that are trapped in the ice. With this advantage, they are the only means to answer some important questions in climate studies with respect to greenhouse gases, e.g., why did the glacial-interglacial cycles change from 40 ka to 100 ka at the mid-Pleistocene transition (MPT) and what drove the 40 ka cycles (Raymo et al., 2006)? For this reason the International Partnerships in Ice Core Sciences (IPICS) included the retrieval of the “Oldest-Ice” ice core as one of their



scientific goals (IPICS, 2006). This core should contain ice with an age of at least 1.2 Ma, preferably 1.5 Ma, at some distance above the ice-bedrock interface. As compared to the oldest continuous ice currently on record (retrieved at Dome C (Augustin et al., 2004) and has an estimated age of 800 ka), this new, older core is likely to include the MPT and some 40 ka cycles.

There are only few promising regions for the Oldest Ice ice core, all of them located close to dome or saddle positions on the East Antarctic Plateau (Fischer et al., 2013). As many conditions have to be fulfilled at a site for old ice to exist and, equally important, to be retrievable in an analyzable way, extensive pre-site surveys are necessary. They will examine ice thickness, basal conditions, ice flow, englacial stratigraphy and age structure, which are important for an ultimate site selection. Radio-echo sounding (RES) is a widely used method to investigate these parameters (e.g., Karlsson et al., 2012; Rodriguez-Morales et al., 2014; MacGregor et al., 2015; Winter et al., 2015). Variations in the dielectric properties density, conductivity, or crystal orientation fabric (COF) cause the partial reflection of electromagnetic-wave energy, and thus appear as internal reflectors (internal reflection horizons, IRHs) in radargrams. The IRHs from changes in density and conductivity are formed at the same time near the surface (Vaughan et al., 1999; Dowdeswell and Evans, 2004) and then advected by compaction and ice flow. Density variations are the primary cause for IRHs in the uppermost few 100 m of the ice sheet, but do not occur in deeper parts (Millar, 1981). The IRHs from conductivity changes, in contrast, can be found throughout the ice sheet and provide information about ice dynamics and basal conditions. A change of crystal orientation fabric (COF) can be the reason for reflections in the deeper parts of the ice column (Fujita et al., 1999). These IRHs are not necessarily isochronous, but influenced by the stress and flow regime (Eisen et al., 2007; Diez et al., 2015).

Apart from ensuring an undisturbed stratigraphy at a potential drill site, RES data provide information about the englacial age structure away from any ice core. The isochronous conductivity IRHs can be traced continuously over long distances in the ice sheets (e.g., Steinhage et al., 2013), and thus be used for extrapolating the age-depth distribution from ice cores along the RES profiles. This, in comparison with ice core data sets, larger amount of information about the age structure of ice sheets is useful for the evaluation of ice-flow models and an important criterion at the current stage of the models (Sime et al., 2014).

The great value of RES data for the investigation of the ice sheets has led to numerous campaigns with gradually more sophisticated radar systems over the years. Searching for the Oldest Ice, it would be beneficiary to include all the radar data that already exist in the regions of interest. However, it is not even clear yet if the data, measured with different radar systems at different times and having different characteristics, are comparable and can be assembled to one data set suitable for this purpose or if there are less confident data sets.

In this study we address these questions and, for the first time, compile the data of five different RES systems for comparison of the various systems' strengths and weaknesses. For an accurate depth inversion and reliable dating of the horizons, identified in the data, we synchronize the RES data with the EPICA Dome C (EDC) ice-core record via modeling synthetic radar traces, as established by Eisen et al. (2004) and Eisen et al. (2006). As EDC yielded the oldest continuously dated ice so far, it is a good starting point for tracing the oldest possible layers.

The ice-core data and the method used for modeling synthetic radar traces are described in Sect. 2. Section 3 introduces the different RES data. All the measurements we use for the comparison were conducted within a 2 km radius around the EDC drill site. In Sect. 4 we describe the assembling of the different data sets and Sect. 5 gives the results of the assembling. This



includes differences in the RES systems, features that can be found in all RES data, the comparison with the modeled radar data and the selection of some distinct horizons, comprising their depths and ages. In Sect. 6 we discuss the comparability of the different RES data sets and their synchronization with the ice-core data and Sect. 7 gives a conclusion.

2 Synthetic radar traces

5 To relate measured RES data to the physical properties and age of the ice, synthetic radar traces are calculated from measured ice-core data. The modeled traces are then compared to the measured RES data with respect to the questions of depth origin and nature of the RES reflections. In the sections below we describe the data used for calculating the synthetic traces (Sect. 2.1) and the actual modeling (Sect. 2.2). In Sect. 2.3 we shortly discuss the input parameter permittivity of ice and its influence on the synthetic modeling results.

10 2.1 Ice-core data

We use the records of the second EDC ice core (EDC99) that was drilled in the austral seasons 2000–2004. The drill site is located on the East Antarctic Plateau at 123.35° E and 75.10° S, 3233 m above sea level. It has a yearly accumulation rate of 25 kg m⁻² a⁻¹ and a mean annual surface temperature of –54.5°C. The ice thickness at this location is 3309 ± 22 m. In 1999, the first drilling attempt had to be abandoned because the drill got stuck in a depth of almost 800 m. In the second attempt a
15 depth of 3260 m was reached, with only a few meters missing to the bedrock (Augustin et al., 2004). The core was dated back to roughly 800 ka BP by e.g., Bazin et al. (2013), and thus comprises the oldest continuously retrieved ice to date.

Dielectric profiling (DEP, Moore (1993)) measurements on the core were conducted in the field at temperatures of –20 ± 2°C and a frequency of 100 kHz. The data set consists of conductivity values (σ) for the depth range of 6.8 m to 3165.2 m with a resolution of 0.02 m. The data were corrected to a temperature of –15°C and cleaned of data points where the core was broken
20 (Parrenin et al., 2012; NOAA, 2011). The record is extended up to the surface by linear interpolation to a value of 4.05 $\mu\text{S m}^{-1}$. Gaps due to removed data points are also linearly interpolated and the record is linearly resampled to 5 mm.

The density (ρ) of the EDC99 core was measured with the γ -absorption method at the Alfred Wegener Institute, Bremerhaven, Germany for the depth range of 6.8 m to 112.7 m in 1mm increments (Hörhold et al., 2011). Gaps in the record are linearly interpolated and the record is also resampled to 5 mm. For depths outside the measuring range the density is logarithmically
25 extrapolated up to the density of ice $\rho_{ice} = 917 \text{ kg m}^{-3}$.

The records for density and conductivity are then combined to one record of depth, density and conductivity from the surface to 3165.2 m depth in 5mm increments.

2.2 Modeling radar traces

To convert radar travel times to depth, we need the depth-dependent electromagnetic wave speed in firn and ice:

$$30 \quad c(z) = \frac{c_0}{\sqrt{\varepsilon'(z)}}, \quad (1)$$



with the vacuum wave speed c_0 and the real part of the complex relative dielectric permittivity

$$\varepsilon = \varepsilon' - i\varepsilon'' = \varepsilon' - i \frac{\sigma}{\varepsilon_0 \omega}, \quad (2)$$

where ε_0 is the ordinary dielectric permittivity of vacuum and ω the circular frequency.

As the accuracy of the DEP measurement performed at EDC does not allow for an inversion of the complex-valued permittivity of a two-phase mixture, as described by Eisen et al. (2006), we use the real-valued dielectric mixture equation by Looyenga (1965) to calculate $\varepsilon'(z)$ from $\rho(z)$:

$$\varepsilon'(z) = \left(\frac{\rho(z)}{\rho_{ice}} \left(\varepsilon'_{ice}{}^{\frac{1}{3}} - 1 \right) + 1 \right)^3, \quad (3)$$

with the measured density $\rho(z)$ and the pure-ice values for density and permittivity $\rho_{ice} = 917 \text{ kg m}^{-3}$ and $\varepsilon'_{ice} = 3.17$. The determination of the latter value is described in Sect. 2.3. Neglecting the complex character of the relative permittivity in the two-phase mixture leads to errors in the permittivity, especially in the firn (Wilhelms, 2005). However, for the purpose of reproducing reflections, not the absolute value but the changes of conductivity are important. Though the positions of the reflections in the two-way travel time (TWT) domain are shifted for incorrect ordinary permittivities (the real part of the complex relative permittivity), we avoid these errors by calibrating the synthetic with the measured radar trace (see Sect. 2.3). The permittivity record is smoothed with a 0.2m running mean to prevent the masking of the conductivity-induced reflections and the too quick reduction of the propagating energy in the synthetic radar trace by a multitude of permittivity-induced reflections in the firn section. More extensive reasoning and effects of this proceeding can be found in Eisen et al. (2006).

Permittivity and conductivity, processed as described above, are input parameters for the 1D-FD model “emice” (Eisen et al., 2004) that calculates synthetic radar traces by solving Maxwell’s equations. The depth increment of the model domain is 0.02 m. The maximum depth is 3165.2 m and an absorbing boundary is implemented. The time increment is 0.02 ns, which fulfills the Courant Criterion.

Following Eisen et al. (2006), we use a source wavelet of two and a half 150MHz cycles that is relatively short for determining reflector depth in high resolution, but long enough to reproduce some interference effects.

The envelope of the calculated trace corresponding to the reflected energy is obtained by conducting a Hilbert magnitude transformation. Finally, the trace is smoothed with a Gaussian running mean of 150 ns. The result of this step is the synthetic trace that we use for comparison with the measured RES data, as described in Sect. 5.

2.3 The relative permittivity of ice

Equation (1) defines the dependence of the electromagnetic wave speed in ice on the relative permittivity of ice. For a smaller permittivity the wave speed is higher and a distinct reflection does thus appear earlier. This time difference increases with the absolute depth of the reflector. We determine ε'_{ice} for the Dome C region by comparing the synthetic traces of model runs with different ε'_{ice} in reference to the AWI RES data (see Sect. 3.1). For too small or too large values of ε'_{ice} , the time lags between RES and synthetic trace for identified reflections increase with depth. The best result is obtained with $\varepsilon'_{ice} = 3.17$. For this value, the identified reflections occur at the same TWT for both traces. This value is close to the commonly used $\varepsilon'_{ice} = 3.15$ (e.g.,



Rodriguez-Morales et al., 2014) and to the pure isotropic ice value of $\varepsilon'_{ice} = 3.16$ found in laboratory experiments (Bohleber et al., 2012).

3 Radio-echo sounding data

The profiles closest to the drill site were selected from the RES data in the Dome C area. The distance between the drill site
5 and the furthest profile is less than 2 km. The positions of the RES profiles relative to Dome C are shown in Fig. 1. As the
influence of different radar systems on the recorded radargram is to be examined, we use the data of five different institutes:
the Alfred Wegener Institute (AWI), Bremerhaven, Germany, the British Antarctic Survey (BAS), Cambridge, UK, the Center
for Remote Sensing of Ice Sheets (CReSIS), Lawrence, USA, the Istituto Nazionale di Geofisica e Vulcanologia, Rome, Italy
(INGV) and the University of Texas Institute for Geophysics (UTIG), Austin, USA. The characteristics of the different systems
10 and the data processing are described next. The system characteristics are summarized in Table 1.

3.1 AWI

The airborne radar system of AWI is a burst system with a carrier frequency of 150 MHz that was operated in toggle mode
with 60 ns and 600 ns bursts (Nixdorf et al., 1999). Measurements were conducted in austral season 2007/08 with the DC-3T
aircraft Polar 5. We use the data with 60 ns bursts and stack it 10-fold. The stacked data have a trace distance of about 75 m
15 and a vertical sampling interval of 13.33 ns. The profile passes the Dome C drill site in 280 m distance.

3.2 BAS

The BAS profile was recorded in season 2005/06 with an airborne radar system on a Twin Otter in 450 m distance to the drill
site. The source is a $4\mu\text{s}$ chirp wavelet with a center frequency of 150 MHz and a bandwidth of 10 MHz. The vertical sampling
interval is 45.45 ns. The data are unprocessed except for a horizontal smoothing with a 49 sample moving-average filter and
20 10-fold stacking. The trace distance after stacking is 45 m.

3.3 CReSIS

CReSIS had one campaign in the Dome C area in season 2013/14, using a 15-channel radar system on an Orion P3 aircraft.
The source wavelets are a 1, 3, and $10\mu\text{s}$ chirps, each running linearly through the frequency range of 180 MHz to 210 MHz
(Gogineni, 2012). We use the L1B-data CSARP_standard file, processed with pulse compression, focused SAR processing,
25 and array processing with multilooking (CReSIS, 2016). The final product has a vertical sampling interval of 33 ns and a trace
distance of 30 m. The profile passes the drill site at 1745 m distance.

3.4 INGV

The INGV profile was measured in December 2011 during a test of a 200ns pulse envelope radar system with a carrier frequency
of 150 MHz. The horizontal trace distance is about 0.25 m and the vertical sampling interval is 40 ns. The 2.7km long profile



passes the drill site in 65 m distance. A spiking deconvolution, low pass filtering and gain adjustment is conducted. We stack the data 10-fold.

3.5 UTIG

The radar profile of the UTIG was collected in season 2008/09 from a DC-3T aircraft in 150 m distance to the drill site. The system uses a $1\mu\text{s}$ chirp wavelet running linearly through the frequencies from 52.5 MHz to 67.5 MHz. The recorded data were filtered with a 10MHz band notch filter and a convolution. An automatic gain control is conducted and the data are stacked horizontally coherently ten times, log detected and incoherently stacked five times so the final trace rate is 4 Hz. This gives a trace distance of about 22 m for this product (Young et al., 2011; Cavitte et al., 2016). The vertical sampling interval is 20 ns.

4 Assembling the data sets

Different system characteristics and processing result in different appearance of the RES data. Our aim is to compare the RES and synthetic radar data in terms of identifying distinct reflectors that can be found in all data sets and that can confidently be matched in between the different data sets. Our basis for determining the origin of the IRHs in the RES data is by relating them to the conductivity record. For this reason, we neglect the first few microseconds, i.e., the upper few hundred meters, where most reflections are due to density changes.

Like Karlsson et al. (2016), we found that this matching can best be achieved manually. But additionally we use a combination of two different ways of imaging:

1. Single traces as reflected energy versus TWT (A-scope) to compare the reflection peaks' shapes and positions. For every RES profile, the trace (of stacked data) closest to the EDC drill site is selected and plotted as a single trace. This is described in Sect. 5.1 and shown in Fig. 2. To make the different data comparable, we first shift them in time so that the surface reflections are at TWT zero. Here, we use the maximum of the surface reflection peaks for the systems with chirp wavelet (BAS, CReSIS and UTIG), but its steepest slope for the pulse systems. This is motivated by the systems differing in signal generation and digitization. The depth of a reflector is depicted by the maximum of its reflection for the chirp systems, but by the rise of its reflection for pulse systems. Note that this is also valid for internal reflections. The position of the surface-reflection pick for all traces is marked by the vertical black line in the left panel of Fig. 2. The exponential trend is removed from every trace. The peak amplitudes of the reflections decline in a different manner for the different data, depending on the source wavelet of the radar system and the processing. For the data with strongly declining peak amplitudes we plot the logarithm of the amplitude for the deepest part (right panel) to make potential reflections in the basal layer more visible.

2. Radar profiles of several kilometer length around the closest trace to the drill site, plotted as TWT vs. trace number with amplitude values in gray scale (Z-scope), as shown in Fig. 3 and described in Sect. 5.2. This way of imaging is especially suitable to compare specific sequences of reflections and to check whether the reflections matched in the A-scope image are spatially coherent and representative over larger regions, e.g. for extrapolation. Again, the surface reflections are shifted to



TWT zero and we plot the logarithm of the amplitudes for all RES data. For the deepest approximately third (bottom panel) we use differently processed, i.e. 2d-focused, CReSIS and UTIG data for an improved visibility of the deep internal structure.

5 Results

In this section we compare the different RES data and the synthetic radar data in order to match some reflections or reflection patterns distributed over the depth range. In Sect. 5.3 we determine the depth origin of the identified horizons by means of sensitivity studies with the conductivity record.

5.1 Single traces, A-scope

Figure 2 shows the traces closest to EDC of all RES profiles, and the synthetic trace. The positions of the measured traces are marked by crosses in Fig. 1. The left panel of Fig. 2 shows the reflections of the air–ice interface, which marks TWT zero for each trace. The air–ice interface is determined by the location of the maximum, or of the first break of the peak for the chirp, and the pulse systems, respectively.

The second part of Fig. 2 shows the traces for the majority of the ice column. In this section we find a number of distinct reflections that can be identified in some or all of the traces. We highlight ten of them (H1–H10), shaded in gray, for which we are confident to have them matched correctly and use them for further discussion. Those events are also used for the sensitivity studies with the conductivity record. The conductivity profile that is used for calculating the synthetic trace is plotted in the bottom panel of Fig. 2. The parts of the profile plotted in red color are the conductivity signals that have to be removed for the identified reflections to disappear from the synthetic trace. In that way, we are able to assign the reflections with their depth and age, as described in Sect. 5.3. What is striking, when comparing the different RES traces, is the comparatively low resolution of the INGV and BAS data. Multitudes of peaks from the other data are not separately resolved by the INGV and BAS systems, but combined to wider peaks. However, it is not always obvious, which peaks join together into one peak. Nevertheless, there are still reflections that are visibly similar to those in the other traces. E.g. the INGV and BAS peaks at about $15 \mu\text{s}$ (H5) can be matched with the one in the AWI data or the INGV peak just before $14 \mu\text{s}$ (H4) and the double peak at $17 \mu\text{s}$ (H6) with the UTIG data. In between these reflections, though, the appearance differs considerably from the other data.

There are small time shifts for the identified reflections in the different RES data. In the CReSIS trace, for example, the peaks are usually about 50–100 ns earlier than in the other traces. The time differences for the peaks in between the other data are much smaller.

The third panel shows the bed reflections of the measured RES data and, just before the bed reflection, the section of the basal layer. In this last section, a reflection can be found at about $30 \mu\text{s}$ that fits well in the CReSIS, UTIG high gain, INGV, BAS and synthetic data (H10).

The TWTs for the bed reflections fit well for AWI and UTIG data, with the UTIG reflections having a longer slope than the AWI, and the UTIG high gain a longer one than the low gain bed reflection. In the BAS, INGV and CReSIS trace the bed



reflections occur a few hundred nanoseconds earlier. Possible reasons for the differences in the timing of the bed reflections and internal reflections are discussed in Sect. 6.1.2.

5.2 Radargrams, Z-scope

Figure 3 shows Z-scopes of the five RES profiles. Unlike in Fig. 2, here the TWT serves as the y-axis. In the leftmost panel the synthetic trace is shown. In the second panel this trace is adjacently plotted 200 times with the amplitude in gray scale. White noise is superimposed on each synthetic trace to get the appearance of a measured radargram. The other panels show the measured radar data of the five radar systems, processed as described in Sect. 3. We use about 5 km profile length for all of the images with the exception of the INGV profile, which is only 2.7 km long.

Like with the single traces, again some reflectors can be matched nicely. Here, especially sequences of IRHs are striking. For example the three closely spaced reflectors at about $6.5 \mu\text{s}$ TWT in the synthetic radargram (red arrow in Fig. 3) that can also be found in the measured data, although with a slightly different appearance. In the AWI data, the first reflector is the most pronounced one, and in the UTIG data they are rather blurred into one broad reflector. Another nice example is the strong reflector just below $8 \mu\text{s}$, followed by the wider sequence below $9 \mu\text{s}$ (H1 and H2, yellow double arrow) that catch one's eye in all of the RES data. Those can also be matched with events in the synthetic data, whereas in the latter, there exist more strong reflectors in between. Hereby, the one at $9 \mu\text{s}$ is especially distinct and has a counterpart only in the CReSIS data. The section from about 13 to $16 \mu\text{s}$ TWT (blue lines), with densely spaced, relatively strong reflectors, is also similar in all of the RES data. It is starting with a double-reflection, corresponding to H3 in Fig. 2, that can also be found in the synthetic radargram. In the middle section of Fig. 3 the reflectors at $19.8 \mu\text{s}$ and $20.5 \mu\text{s}$ (H7) are the most striking ones in the synthetic data (light blue double arrow). The most alike counterpart of this sequence is to be found in the BAS data. But there is also a match in the other RES data. Notable is that the first of the two reflectors is more pronounced in the UTIG and INGV data, whereas it is the second in the CReSIS data.

Striking differences between the RES systems exist in the quality of recording reflections from the basal layer, shown in the lowermost panels of Fig. 3. In the AWI data, where the IRHs are nicely resolved in the upper two thirds, the visibility of reflectors ceases at 28 to $29 \mu\text{s}$. The only distinct reflector after that is the bed reflection $10 \mu\text{s}$ later, leaving about 800 m of echo-free zone. The same is the case for the INGV data. In contrast, IRHs are clearly visible down to about 33.5 to $34.0 \mu\text{s}$ TWT in the BAS, CReSIS and UTIG data, ending with a relative strong continuous reflector with strong vertical variation (green arrows). In the BAS data there even are some signals, spatially coherent for a few kilometers, as deep as approximately $36 \mu\text{s}$ TWT. The same can be found in the CReSIS and UTIG profiles a few tens of kilometers away from EDC, which are not shown here.

At the very bottom of the figure, the bed reflections of the RES data can be seen. These measured bed-reflection depths are not to be compared with the strong reflection at the bottom of the synthetic radargram. The latter marks solely the margin of the model, which is equal to the end of the DEP record. At least 100 m are missing to the actual bed, which makes a difference of more than $1 \mu\text{s}$ in TWT.



5.3 Depths of the RES reflectors

We determine the depths of the IRHs, identified in Fig. 2 and Fig. 3, by sensitivity studies with the measured conductivity record (bottom panel of Fig. 2). This is possible, because the conductivity profile, measured on the ice core, is closely resembled by the synthetic radar trace and strong peaks can be matched confidently. The resemblance is not as obvious when comparing the conductivity profile and synthetic trace as a whole, but it clearly is, when looking at subsections. An exception is the very uppermost part (~400 m), where the reflectivity is also influenced by density variations. The identified peaks are removed from the conductivity profile and the model is run with the changed profile as input. In the calculated synthetic radargram the according reflections are missing. The bottom trace of Fig. 2 shows the synthetic trace calculated with original (red) and changed (black) conductivity profile, and the bottom panel shows the corresponding conductivity profiles. If a reflection in the RES data can confidently be matched with one of the synthetic radargram, the depth of the reflection can immediately be transferred from the conductivity profile. It has to be taken into account, however, that the determined depth is the horizon's depth at the ice-core location, and may differ from its depth at the RES trace. Even so, the horizon can be assigned with an age. Due to the conductivity-induced IRHs being isochronous, their age is the same at the position of the RES profile, even if the depth is somewhat different. If matched correctly, the uncertainty of the reflector's age depends only on the width and number of the reflection-causing conductivity peaks and the accuracy of the age scale. The advantage over converting TWT to depth using ice-core densities and a velocity function is that the depth uncertainties do not accumulate with depth, but are independent of the absolute depth.

We remove sections from the conductivity record so that the gray-shaded reflections from Fig. 2 disappear from the synthetic trace. In that way we find that e.g., reflection H1 is caused by the conductivity peaks in the depth range of 700.54 m–702.64 m, or that the sequence H2 is caused by a multitude of conductivity peaks, spanning about 22 m depth. All identified reflections, the depth ranges of their inducing conductivity sections, and their age ranges with standard deviation according to the AICC2012 timescale (Veres et al., 2013; Bazin et al., 2013) are listed in Table 2. Age uncertainties for the IRHs due to reflector width or shifts in TWT are discussed in Sect. 6.2.2.

6 Discussion

In the sections below we discuss the results of our comparison of the different data sets. Section 6.1 addresses the comparison of the measured RES data among each other and gives possible reasons for differences between the data. In Sect. 6.2 we look at the connection of the RES data with the synthetic radar trace, and thus the ice-core data, including an uncertainty assessment

6.1 Comparability of RES data

As pointed out in Sect. 5.1 and 5.2, the RES systems depict the major characteristics of the conductivity profile in a very similar way and there are common features notable in all of the RES data (e.g., the strong IRH at 8 μ s). Especially the AWI, BAS, CRISIS and UTIG radargrams show the same patterns of reflectors, like many densely spaced reflectors (e.g., starting from



13 μs), or of lacking reflectors (22 μs , 32 μs) at the same depths. The distinct reflectors (that are usually chosen for tracing) can be identified and traced (at least for the lengths of the investigated profile sections) in those RES data. However, there are conspicuous differences, when comparing the data with respect to resolution and penetration depth. The differences and reasons are discussed in the sections below.

5 6.1.1 Resolution

There are dissimilarities in the RES data in markedness and vertical expansion of the reflectors. Those can partly be explained by the different range resolutions of the various radar systems, due to different source wavelets, receiver bandwidths, sampling rates and post-processing. The sampling intervals vertically range from 13.33 ns (AWI) to 45.45 ns (BAS) (see Sect. 3). This gives approximately one sample every meter, and 3.8 m, respectively. The vertical resolution due to source wavelet and received-antenna system bandwidth ranges from about 3 m to 17 m, as listed in Table 1. To some extent, the differences in the RES data can therefore be attributed to the varying range resolution of the different systems. The systems with lower range resolution are not able to capture multiple closely-spaced conductivity changes, and these closely-spaced layer variations are only represented by a single reflector (of potentially complex shape). Regarding the resolution of IRHs at intermediate depths, we attest the AWI, CReSIS and UTIG systems the best quality, which is expected per the smaller range resolution identified in Table 1. The CReSIS system shows the most detailed structure, while the AWI system has the least penetration depth of the three systems. Obviously in the INGV and BAS radargrams, but also in the AWI and UTIG data, there are examples (at 10 μs and 20 μs) where a series of reflectors in CReSIS data are depicted as only one wider reflection. The detailed structure in the CReSIS data is advantageous for synchronizing IRHs at a specific location in high resolution, like we do in this study. However, Cavitte et al. (2016), who use several radar data sets to connect the EDC and Vostok drill sites, point out that the high vertical resolution might make it difficult to trace the IRHs over wide distances as the IRHs can thin out more easily than for systems with lower vertical resolution and therefore more robust IRH returns. As for the compatibility of the data sets, we assume that there are no major issues in combining AWI, CReSIS and UTIG data at one location where the profiles are close to each other, due to their very similar reflector patterns. Yet, the additional resolution of the CReSIS data could add ambiguity to combined data interpretations that include tracing of IRHs (Cavitte et al., 2016). A similar problem arises if the lower resolved BAS and INGV data are included, as it might become difficult to decide which reflector to continue when going from lower to higher resolution data.

The horizontal resolution of the bed reflection is best in the CReSIS data. Whereas in the other data the bed reflection is somewhat blurred, we get a well-defined bedrock topography from the CReSIS data. However, these quality differences could easily be induced solely by the different processing techniques, or to some extent influenced by the different locations of the profiles. Thus a comparison at this stage is of little help for judging the actual systems' capabilities in depicting the bed topography. If a more quantitative comparison of this aspect is required, we propose a survey with all systems measuring a common profile with a length of five to ten ice thicknesses.



6.1.2 Spatial coherence

The other reason for the reflector dissimilarities is that the measurements were not conducted at exactly the same location, and the measurements have different path orientations as well. Urbini et al. (2008), Frezzotti et al. (2005) and others found significant spatial variability in snow accumulation on the scale of a few kilometers around Dome C (2% within 2 km in direction SW–NE, inferred from Urbini et al., 2008, Fig. 7b). This can have the effect that reflectors are more pronounced or wider in one profile than in another, or that some signals are even completely missing at one location, due to erosion processes (Frezzotti et al., 2005). Spatial accumulation variability, even if small, also causes spatial variations in reflector depths. This is certainly the case for greater depths, where the effect accumulated over thousands of years. We see the reflector-depth variations as TWT shifts of identified reflections in the traces in Fig. 2 and in the slopes of IRHs in Fig. 3. For instance the reflector at 11 μs in the CReSIS data has a slope of about 0.1 $\mu\text{s km}^{-1}$, corresponding to about 8.4 m km^{-1} . For the reflector at 26 μs in the same data it is 0.15 $\mu\text{s km}^{-1}$ or 12.6 m km^{-1} . The spatial variations are thus big enough to explain the differences in TWT for the identified IRHs in the different RES data, e.g. about 0.1 μs TWT shifts for reflectors in the CReSIS profile, which is more than 1.5 km apart from the other data. Moreover, Urbini et al. report a temporal change in the accumulation distribution. That would cause a non-linearity of the shifts/change of slope steepness with depth also depending on position.

The slopes of IRHs are also influenced by the bed topography. We find quite steep slopes in the bed reflections in Fig. 3. The ice thickness varies significantly, even on the scale of the distances between the RES profiles. The bed reflection varies about 1.0 μs TWT over 1 km profile length at the steepest slopes of the bed reflections. This variation corresponds to approximately 80 m km^{-1} in bed elevation change. This is consistent with results by Rémy and Tabacco (2000), who established a 50 km \times 50 km bedrock map for the Dome C region with 1 km horizontal resolution. They found valleys, a few tens of meters deep, close to the Dome C drill site. So, again, the differences in the RES data, e.g. the 0.5 μs earlier bed reflection in the CReSIS trace (Fig. 2), can be explained by their spatial separation.

Another factor that is worthwhile considering are the different directions of the RES profiles. They could be the reason for some reflectors, fully or partly induced by COF changes, to be weaker or not existent in some of the data, as the power, reflected by those horizons is dependent on the electric-polarization direction (Matsuoka et al., 2003; Eisen et al., 2007).

6.1.3 Penetration depth

The IRHs cease to be visible at different depths in the bottom section of Fig. 3. This happens in a different manner for the different RES data. In the AWI and INGV data it is a rather slow process, with IRHs gradually becoming weaker. The weaker IRH response is due to the attenuation of the RES signal as it propagates through the ice. As such, weak internal reflectors are difficult to detect, whereas the strong return from the ice–bedrock interface can still be detected. In contrast, the UTIG, CReSIS and BAS data clearly show reflectors down to approximately 33 μs , with comparably strong “last” reflectors (green arrows) and below that depth no continuous IRHs are visible. The lack of continuous IRHs below is not an issue of the systems’ power, but rather means that the former horizons are in some way deformed, amalgamated, or disrupted into small scale structures, not resolvable by the radar systems. This is the section usually referred to as “basal layer”, which is described by e.g., Drews



et al. (2009) under the former name echo-free zone. The lack of IRHs in this range not being an issue of the systems' power is also supported by the fact that there are regions with to some extent spatially coherent signals almost down to the bedrock, like in the BAS data and also in the UTIG and CReSIS profiles, outside the 5km range shown in Fig. 3. It is difficult to give a comparing judgement on the quality of the three RES systems in this deepest part. The profiles were not measured at the same location and the internal structure in the ice close to the bed differs strongly. But as we still see some small scale structures and coherent signals, we are confident that all three systems are able to image structures in the basal layer reliably. As the basal layer comprises the old ice, this is a crucial factor for Oldest Ice reconnaissance surveys. The lower range resolution of the BAS system, compared to the other two systems, applies also for the basal layer.

6.2 Synchronization of RES and ice-core data

We find that distinct patterns of IRHs in the RES data can also be found in the synthetic trace. The pronounced reflectors that are identified in all RES data can also be matched with the synthetic data. In this way their depth origin at the drill site and thus their age can be determined, as described in Sect. 5.3. The uncertainties on depth and age are discussed in Sect. 6.2.2. However, like for the measured RES data, there are also pronounced differences in appearance between the RES and synthetic data. Possible reasons are discussed in Sect. 6.2.1.

6.2.1 Spatial variability

The dissimilarities in the appearance of reflectors described for the comparison of the different RES data are even stronger when comparing any of the measured RES data with the synthetic trace. This is consistent with the explanation by different measuring sites and spatial variability in accumulation and ice thickness. The synthetic trace is calculated from the ice-core data. The EDC99 core and the RES profiles are a few hundred to two thousand meters apart. Additionally, the core, with its 0.1m diameter, samples a much smaller area than a radar system that averages over a footprint on the 10–100m scale. There were discussions about the spatial significance of ice-core signals (e.g., Fisher et al., 1985; Richardson and Holmlund, 1999; Veen and Bolzan, 1999). Palais et al. (1982) and Münch et al. (2015) examine the representativity of cores, using snow accumulation variability and stable-water isotope variations, respectively. Frezzotti et al. (2005), too, get slightly different accumulation rates from ice core and radar measurements and explain them with the different sample area. However, they find that for the Dome C region the differences of core and radar measurements of 3% and the spatial variability of accumulation are relatively small compared to other East Antarctic regions, and the smallest of their Dome C–Terra Nova Bay traverse.

Wolff et al. (2005) compare the conductivity record of the EDC99 core with the one of the first drilling attempt (EDC96) that is 10 m away. They find that only in 45% of the cases the largest conductivity peak in a 10m section is also the largest peak in a 10m section of the parallel core. This is typical of low accumulation sites, because significant parts of a single year's signal can be lost at a location by post-depositional processes like snow drift. Gautier et al. (2016) evaluate the variability of the volcanic signal at the EDC site, using five 100m firn cores, drilled 1 m apart from each other. They find that the probability of missing volcanic events is 30% when using only a single core. The Tambora event (1815 CE), for instance, is not detected by their algorithm in two out of five cores. Wolff et al. (2005) suggest to use methods that sample a larger volume of ice to smooth out



the spatial inhomogeneity. RES being such a method explains that the RES data are more similar among each other than RES versus synthetic data. This implies also that a very strong RES reflector does not necessarily have to be a large peak in the conductivity profile or synthetic trace.

6.2.2 Uncertainty assessment

5 Uncertainties incorporated in the synthetic data are the uncertainties from the ice-core measurements, inaccuracies in determining the permittivity and the neglect of temperature and anisotropy. The uncertainties on the density decrease with depth, due to higher absolute densities and Hörhold et al. (2011) give a value of 0.66% at 100 m depth. The errors in the permittivity, induced by neglecting the complex character in the air-ice mixture, are negligible, as we exclude the firn section and look only at depths greater than 600 m, where the air partition is minor. Uncertainties on wave velocity due to the dependence of the
10 permittivity on temperature and anisotropy both stay below 1% (Gough, 1972; Matsuoka et al., 1997; Fujita et al., 2000). The errors in the synthetic trace have an influence only on the TWT of the synthetic reflectors, and thus eventually on matching those with the RES reflectors, but not on the actual depth and age assignment. Sensitivity studies with the conductivity profile define the depth range in which a synthetic reflection peak has its origin. Thus the depth uncertainties of the IRHs are given by the depth uncertainties of the DEP measurements and the resolution of IRHs in the synthetic trace The latter is adjustable, as
15 it is defined by the bandwidth of the used source wavelet and the smoothing filter, as shown by e.g., Cavitte et al. (2016). The depth uncertainties of the DEP measurement are reported as about 2 mm by Wolff et al. (1999). Added to that comes the depth uncertainty of the ice core itself, which is difficult to quantify. Due to breaks in an ice core, an inclined borehole, and core relaxation after drilling the logged ice-core length is always different from the true depth. Parrenin et al. (2012, Section 2.2.1) estimate the offset to reach up to several meters for a deep drilling. The direct transfer of reflector depths by the sensitivity
20 studies is not completely true for the RES reflectors. Because of different bandwidths used in the RES data, there is an uncertainty associated in matching the peaks between the synthetic and RES data sets. All of the BAS and INGV reflections, for example, are wider than the ones in the synthetic trace and thus it is not clear which conductivity peaks are incorporated in one RES reflector. The age uncertainties due to reflector width increase with depth and can be inferred from Fig. 4, which shows the gradient of age with depth (blue curve), and with TWT (black), respectively. Added to that comes the age uncertainties
25 from the AICC2012 age scale itself, given in Table 2 (Veres et al., 2013; Bazin et al., 2013). The curves of Fig. 4 also give the magnitude of error in age that is avoided by our method compared to using only a RES profile, in some distance to the core, and the age scale of the core. For example: The RES profile is 1 km away from the core and the IRH of interest has a slope of 10 m km^{-1} in the direction drill site–RES profile. When using only the RES profile, we would assign the reflector with an age off by 10 m on the ice core time scale. For a reflector at about $10 \mu\text{s}$ TWT that would correspond to an age shift of about
30 1 ka, for a reflector at $32 \mu\text{s}$ of about 8 ka. This shows the advantage of our approach of first matching the RES IRHs with the synthetic radargram and only then determining the depth and age of the reflectors at the ice-core location, as it eliminates one possible source of error. The extent of error reduction, however, does depend on IRH slopes and distances of the RES profiles to the ice-core site.



7 Conclusions

In our study we compare the data sets of five different RES systems, addressing the questions of their compatibility for combined usage and suitability for informing potential “Oldest Ice” site characterization. All RES profiles were recorded within a 2km radius around the EPICA Dome C drill site, where the current oldest ice sample was retrieved. We find that the data are broadly comparable at that location and that the most-pronounced reflectors can be found in the RES data. The main differences between the RES systems are constituted by their resolution of englacial structure and bedrock and their quality in imaging the basal layer. The CReSIS data have the best horizontal resolution in the depth of the bed and are thus providing a well-defined subglacial bedrock topography. At this stage it is inconclusive, if this can be attributed to the CReSIS system, or rather to the different processing technique and profile location. If interested in well resolved IRHs at intermediate depths, the radar systems with the highest bandwidths, the AWI, CReSIS, and UTIG systems, are most suitable. However, we did not investigate the continuity of the IRHs beyond the 5 km profile lengths. Based on their close similarity in reflection patterns at the investigated location we assume that the AWI, CReSIS and UTIG data are smoothly combinable for common interpretation, although this yet has to be double-checked at cross-over points. The best quality in imaging the basal layer have the CReSIS, UTIG and BAS data, the latter, however, with comparably low resolution. For this reason we attest the CReSIS and UTIG systems the best suitability in our comparison for Oldest Ice reconnaissance surveys, as here the basal layer plays an important role. The AWI and INGV data in the current version are not as convenient for this purpose, as they fail to depict the internal structure in the deepest approximately third of the ice thickness at EDC. Nevertheless, the profiles could be used to close data gaps with respect to IRHs at intermediate depths and ice thickness.

In addition to the profound comparison of the RES data, we synchronize the measured RES data with a synthetic radar trace for depth conversion. Input for the forward model for the synthetic trace are the EDC ice-core conductivity and density. We find that the RES data are more similar among each other than compared to the synthetic trace. This can be explained by the spatial variability of the strengths of single conductivity signals as sampled by ice cores and the smoothing effect of RES measurements due to their larger footprint and lower vertical resolution. Nevertheless, we are able to match 10 pronounced reflectors in the RES and synthetic data. The identified IRHs are conductivity-caused and thus isochronous. Hence the IRHs can be used to extend the age structure, provided by the Dome C ice core, to regions of interest for an Oldest Ice drill site.

Acknowledgements. We acknowledge that several CReSIS faculty, staff and students contributed to the development of radars and antenna arrays used to collect data reported here.

The UTIG line was funded as part of NSF’s International Polar Year activities (grant ANT-0733025) to the University of Texas at Austin, and the UK’s NERC grant NE/D003733/1 to University of Edinburgh.

Operational support was provided by the U. S. Antarctic Program and by the Institut Polaire Français Paul- Emile Victor (IPEV) and the Italian Antarctic Program (PNRA and ENEA), Additional support was provided by the French ANR Dome C project (ANR-07-BLAN-0125). This is UTIG contribution #####.



References

- Augustin, L., Barbante, C., Barnes, P. R., Barnola, J. M., Bigler, M., Castellano, E., Cattani, O., Chappellaz, J., Dahl-Jensen, D., Delmonte, B., et al.: Eight glacial cycles from an Antarctic ice core, *Nature*, 429, 623–628, doi:10.1038/nature02599, 2004.
- Bazin, L., Landais, A., Lemieux-Dudon, B., Toyé Mahamadou Kele, H., Veres, D., Parrenin, F., Martinerie, P., Ritz, C., Capron, E., Lipenkov, V., et al.: An optimized multi-proxy, multi-site Antarctic ice and gas orbital chronology (AICC2012): 120-800 ka, *Climate of the Past*, 9, 1715–1731, doi:10.5194/cp-9-1715-2013, 2013.
- Bohleber, P., Wagner, N., and Eisen, O.: Permittivity of ice at radio frequencies: Part II. Artificial and natural polycrystalline ice, *Cold Regions Science and Technology*, 83, 13–19, doi:10.1016/j.coldregions.2012.05.010, 2012.
- Cavitte, M. G., Blankenship, D. D., Young, D. A., Schroeder, D. M., Parrenin, F., Lemeur, E., Macgregor, J. A., and Siegert, M. J.: Deep radiostratigraphy of the East Antarctic plateau: connecting the Dome C and Vostok ice core sites, *Journal of Glaciology*, Available on CJO, doi:10.1017/jog.2016.11, 2016.
- CREStS: Radar depth sounder readme, ftp://data.cresis.ku.edu/data/rds/rds_readme.pdf, 2016.15.03, 2016.
- Diez, A., Eisen, O., Hofstede, C., Lambrecht, A., Mayer, C., Miller, H., Steinhage, D., Binder, T., and Weikusat, I.: Seismic wave propagation in anisotropic ice—Part 2: Effects of crystal anisotropy in geophysical data, *The Cryosphere*, 9, 385–398, doi:10.5194/tc-9-385-2015, 2015.
- Dowdeswell, J. A. and Evans, S.: Investigations of the form and flow of ice sheets and glaciers using radio-echo sounding, *Reports on Progress in Physics*, 67, 1821, doi:10.1088/0034-4885/67/10/R03, 2004.
- Drews, R., Eisen, O., Weikusat, I., Kipfstuhl, S., Lambrecht, A., Steinhage, D., Wilhelms, F., and Miller, H.: Layer disturbances and the radio-echo free zone in ice sheets, *The Cryosphere*, 3, 195–203, doi:10.5194/tc-3-195-2009, 2009.
- Eisen, O., Nixdorf, U., Wilhelms, F., and Miller, H.: Age estimates of isochronous reflection horizons by combining ice core, survey, and synthetic radar data, *Journal of Geophysical Research: Solid Earth* (1978–2012), 109, doi:10.1029/2003JB002858, 2004.
- Eisen, O., Wilhelms, F., Steinhage, D., and Schwander, J.: Improved method to determine radio-echo sounding reflector depths from ice-core profiles of permittivity and conductivity, *Journal of Glaciology*, 52, 299–310, doi:10.3189/172756506781828674, 2006.
- Eisen, O., Hamann, I., Kipfstuhl, S., Steinhage, D., and Wilhelms, F.: Direct evidence for continuous radar reflector originating from changes in crystal-orientation fabric, *The Cryosphere*, 1, 1–10, doi:10.5194/tc-1-1-2007, 2007.
- Fischer, H., Severinghaus, J., Brook, E., Wolff, E., Albert, M., Alemany, O., Arthern, R., Bentley, C., Blankenship, D., Chappellaz, J., et al.: Where to find 1.5 million year old ice for the IPICS “Oldest Ice” ice core, *Climate of the Past*, 9, 2489–2505, doi:10.5194/cp-9-2489-2013, 2013.
- Fisher, D. A., Reeh, N., and Clausen, H.: Stratigraphic noise in time series derived from ice cores, *Ann. Glaciol*, 7, 76–83, 1985.
- Frezzotti, M., Pouchet, M., Flora, O., Gandolfi, S., Gay, M., Urbini, S., Vincent, C., Becagli, S., Gagnani, R., Proposito, M., et al.: Spatial and temporal variability of snow accumulation in East Antarctica from traverse data, *Journal of Glaciology*, 51, 113–124, doi:10.3189/172756505781829502, 2005.
- Fujita, S., Maeno, H., Uratsuka, S., Furukawa, T., Mae, S., Fujii, Y., and Watanabe, O.: Nature of radio echo layering in the Antarctic ice sheet detected by a two-frequency experiment, *Journal of Geophysical Research*, 104, 13 013–13 024, 1999.
- Fujita, S., Matsuoka, T., Ishida, T., Matsuoka, K., and Mae, S.: *The Physics of Ice Core Records*. chap. A summary of the complex dielectric permittivity of ice in the megahertz range and its application for radar sounding of polar ice sheets, 2000.
- Gautier, E., Savarino, J., Erbland, J., Lanciki, A., and Possenti, P.: Variability of sulfate signal in ice core records based on five replicate cores, *Climate of the Past*, 12, 103–113, doi:10.5194/cp-12-103-2016, 2016.



- Gogineni, P.: CRISIS radar depth sounder data, Center for Remote Sensing of Ice Sheets, Lawrence, KS <https://data.cresis-ku.edu>, 2012.
- Gough, S.: A low temperature dielectric cell and the permittivity of hexagonal ice to 2 K, *Canadian Journal of Chemistry*, 50, 3046–3051, doi:10.1139/v72-483, 1972.
- Hörhold, M., Kipfstuhl, S., Wilhelms, F., Freitag, J., and Frenzel, A.: The densification of layered polar firn, *Journal of Geophysical Research: Earth Surface* (2003–2012), 116, doi:10.1029/2009JF001630, 2011.
- IPICS: White paper: The oldest ice core, <http://www.pages-igbp.org/ini/end-aff/ipics/white-papers>, 2016.04.04, 2006.
- Karlsson, N. B., Rippin, D. M., Bingham, R. G., and Vaughan, D. G.: A ‘continuity-index’ for assessing ice-sheet dynamics from radar-sounded internal layers, *Earth and Planetary Science Letters*, 335, 88–94, doi:10.1016/j.epsl.2012.04.034, 2012.
- Karlsson, N. B., Eisen, O., Dahl-Jensen, D., Freitag, J., Kipfstuhl, S., Lewis, C., Nielsen, L. T., Paden, J. D., Winter, A., and Wilhelms, F.: 700a accumulation rates in North Central Greenland derived from radar data, in review, 2016.
- Looyenga, H.: Dielectric constants of heterogeneous mixtures, *Physica*, 31, 401–406, doi:10.1016/0031-8914(65)90045-5, 1965.
- MacGregor, J. A., Fahnestock, M. A., Catania, G. A., Paden, J. D., Prasad Gogineni, S., Young, S. K., Rybarski, S. C., Mabrey, A. N., Wagman, B. M., and Morlighem, M.: Radiostratigraphy and age structure of the Greenland Ice Sheet, *Journal of Geophysical Research: Earth Surface*, 120, 212–241, doi:10.1002/2014JF003215, 2015.
- 15 Matsuoka, K., Furukawa, T., Fujita, S., Maeno, H., Uratsuka, S., Naruse, R., and Watanabe, O.: Crystal orientation fabrics within the Antarctic ice sheet revealed by a multipolarization plane and dual-frequency radar survey, *Journal of Geophysical Research: Solid Earth*, 108, doi:10.1029/2003JB002425, 2003.
- Matsuoka, T., Fujita, S., Morishima, S., and Mae, S.: Precise measurement of dielectric anisotropy in ice Ih at 39 GHz, *Journal of Applied Physics*, 81, 2344–2348, doi:10.1063/1.364238, 1997.
- 20 Millar, D.: Radio-echo layering in polar ice sheets and past volcanic activity, doi:10.1038/292441a0, 1981.
- Moore, J.: High-resolution dielectric profiling of ice cores, *Journal of Glaciology*, 39, 245–248, 1993.
- Münch, T., Kipfstuhl, S., Freitag, J., Meyer, H., and Laepple, T.: Regional climate signal vs. local noise: a two-dimensional view of water isotopes in Antarctic firn at Kohnen station, Dronning Maud Land, *Climate of the Past Discuss.*, 11, 5605–5649, doi:10.5194/cpd-11-5605-2015, 2015.
- 25 Nixdorf, U., Steinhage, D., Meyer, U., Hempel, L., Jenett, M., Wachs, P., and Miller, H.: The newly developed airborne radio-echo sounding system of the AWI as a glaciological tool, *Annals of Glaciology*, 29, 231–238, doi:10.3189/172756499781821346, 1999.
- NOAA: EPICA Dome C Ice Cores Dielectrical Profiling (DEP) Data, ftp://ftp.ncdc.noaa.gov/pub/data/paleo/icecore/antarctica/epica_domec/edc2011dep.txt, 2016.26.02, 2011.
- Palais, J. M., Whillans, I. M., and Bull, C.: Snow stratigraphic studies at Dome C, East Antarctica: an investigation of depositional and diagenetic processes, *Ann. Glaciol.*, 3, 239–242, 1982.
- 30 Parrenin, F., Petit, J.-R., Masson-Delmotte, V., Wolff, E., Basile-Doelsch, I., Jouzel, J., Lipenkov, V., Rasmussen, S. O., Schwander, J., Severi, M., et al.: Volcanic synchronisation between the EPICA Dome C and Vostok ice cores (Antarctica) 0–145 kyr BP, *Climate of the Past*, 8, 1031–1045, doi:10.5194/cp-8-1031-2012, 2012.
- Raymo, M., Lisiecki, L., and Nisancioglu, K. H.: Plio-Pleistocene ice volume, Antarctic climate, and the global $\delta^{18}\text{O}$ record, *Science*, 313, 492–495, doi:10.1126/science.1123296, 2006.
- 35 Rémy, F. and Tabacco, I. E.: Bedrock features and ice flow near the EPICA ice core site (Dome C, Antarctica), *Geophysical Research Letters*, 27, 405–408, doi:10.1029/1999GL006067, 2000.



- Richardson, C. and Holmlund, P.: Spatial variability at shallow snow-layer depths in central Dronning Maud Land, East Antarctica, *Annals of Glaciology*, 29, 10–16, doi:10.3189/172756499781820905, 1999.
- Rodriguez-Morales, F., Gogineni, S., Leuschen, C. J., Paden, J. D., Li, J., Lewis, C. C., Panzer, B., Gomez-Garcia Alvestegui, D., Patel, A., Byers, K., et al.: Advanced multifrequency radar instrumentation for polar research, *Geoscience and Remote Sensing, IEEE Transactions on*, 52, 2824–2842, doi:10.1109/TGRS.2013.2266415, 2014.
- Sime, L. C., Karlsson, N. B., Paden, J. D., and Prasad Gogineni, S.: Isochronous information in a Greenland ice sheet radio echo sounding data set, *Geophysical Research Letters*, 41, 1593–1599, doi:10.1002/2013GL057928, 2014.
- Steinhage, D., Kipfstuhl, S., Nixdorf, U., and Miller, H.: Internal structure of the ice sheet between Kohnen station and Dome Fuji, Antarctica, revealed by airborne radio-echo sounding, *Annals of Glaciology*, 54, 163–167, doi:10.3189/2013AoG64A113, 2013.
- 10 Urbini, S., Frezzotti, M., Gandolfi, S., Vincent, C., Scarchilli, C., Vittuari, L., and Fily, M.: Historical behaviour of Dome C and Talos Dome (East Antarctica) as investigated by snow accumulation and ice velocity measurements, *global and planetary change*, 60, 576–588, doi:10.1016/j.gloplacha.2007.08.002, 2008.
- Vaughan, D. G., Corr, H. F., Doake, C. S., and Waddington, E. D.: Distortion of isochronous layers in ice revealed by ground-penetrating radar, *Nature*, 398, 323–326, doi:10.1038/18653, 1999.
- 15 Veen, C. and Bolzan, J.: Interannual variability in net accumulation on the Greenland Ice Sheet: Observations and implications for mass balance measurements, *Journal of Geophysical Research: Atmospheres*, 104, 2009–2014, doi:10.1029/1998JD200082, 1999.
- Veres, D., Bazin, L., Landais, A., Toyé Mahamadou Kele, H., Lemieux-Dudon, B., Parrenin, F., Martinerie, P., Blayo, E., Blunier, T., Capron, E., et al.: The Antarctic ice core chronology (AICC2012): an optimized multi-parameter and multi-site dating approach for the last 120 thousand years, *Climate of the Past*, 9, 1733–1748, doi:10.5194/cp-9-1733-2013, 2013.
- 20 Wilhelms, F.: Explaining the dielectric properties of firn as a density-and-conductivity mixed permittivity (DECOMP), *Geophysical Research Letters*, 32, doi:10.1029/2005GL022808, 2005.
- Winter, K., Woodward, J., Ross, N., Dunning, S. A., Bingham, R. G., Corr, H. F., and Siegert, M. J.: Airborne radar evidence for tributary flow switching in Institute Ice Stream, West Antarctica: Implications for ice sheet configuration and dynamics, *Journal of Geophysical Research: Earth Surface*, 120, 1611–1625, doi:10.1002/2015JF003518, 2015.
- 25 Wolff, E., Basile, I., Petit, J.-R., and Schwander, J.: Comparison of Holocene electrical records from Dome C and Vostok, Antarctica, *Annals of Glaciology*, 29, 89–93, doi:10.3189/172756499781820888, 1999.
- Wolff, E. W., Cook, E., Barnes, P. R., and Mulvaney, R.: Signal variability in replicate ice cores, *Journal of Glaciology*, 51, 462–468, doi:10.3189/172756505781829197, 2005.
- Young, D. A., Wright, A. P., Roberts, J. L., Warner, R. C., Young, N. W., Greenbaum, J. S., Schroeder, D. M., Holt, J. W., Sugden, D. E., Blankenship, D. D., et al.: A dynamic early East Antarctic Ice Sheet suggested by ice-covered fjord landscapes, *Nature*, 474, 72–75, doi:10.1038/nature10114, 2011.
- 30



Table 1. Characteristics of the five RES systems. The fourth column gives either the bandwidth in case of the chirp systems, or the pulse length in case of the pulse and burst systems. The last column gives the best vertical resolution due to bandwidth (for distinguishing two reflectors), without taking into account any windowing of signals during processing.

System	aircraft	center freq.	bandwidth/	vertical sampl. freq.	resolution
		MHz	pulse length	MHz	m
AWI	DC-3T	150	60 ns	75	5.0
BAS	Twin Otter	150	10 MHz	22	8.4
CReSIS	Orion P3	195	30 MHz	30	2.8
INGV	ground based	150	200 ns	25	16.8
UTIG	DC-3T	60	15 MHz	50	5.6

Table 2. Identified layers of Fig. 2, their approximate TWTs, depth ranges of their inducing conductivity sections and corresponding age with age uncertainties (average of published AICC2012 age uncertainties of the top and bottom depth) on the AICC2012 timescale (Veres et al., 2013; Bazin et al., 2013).

Horizon	TWT	depth top	depth bottom	age top	age bottom	uncertainty
	μs	m	m	ka	ka	ka
H1	8.0	700.54	702.64	38.17	38.30	0.58
H2	9.5	786.84	808.80	45.49	47.22	0.78
H3	12.5	1078.90	1081.36	73.66	73.96	2.00
H4	13.5	1172.04	1179.06	82.03	82.58	1.53
H5	15.0	1267.34	1271.30	90.04	90.40	1.60
H6	17.5	1447.58	1458.16	106.32	107.49	1.88
H7	20.5	1745.80	1746.02	132.74	132.77	2.13
H8	22.5	1891.54	1892.98	160.96	161.24	3.50
H9	24.5	2060.14	2060.40	197.17	197.23	1.96
H10	30.0	2549.88	2588.34	328.97	337.96	2.74




Figure 1. The deep drill sites in East Antarctica and close-up to Dome C with the RES profiles. The crosses mark each profile's closest trace to the drill site. The location of the EDC drill site is marked by the red hexagon.




Figure 2. RES traces of the five radar systems and synthetic trace. The amplitudes are scaled individually and the exponential trend is removed. The surface reflection of each trace is shifted to time zero (left panel). Some distinct reflections that can be seen in some or all of the traces are gray-shaded. The bottom panel shows the conductivity profile. The conductivity peaks that are plotted in red cause the identified reflections H1–H10 in the synthetic trace.




Figure 3. Z-scope of synthetic and RES data sets of the five radar systems. The surface reflections are shifted to time zero as shown in Fig. 2 and the vertical red lines mark the positions of the traces of Fig. 2. The length of the RES profiles is indicated on the x-axes. For the depth axis we convert TWT to depth with a wave velocity of $c = 168.5 \text{ m } \mu\text{s}^{-1}$ and a firm correction of 10 m. For the bottom UTIG and CReSIS panels an extended focused is applied. The colored arrows and lines mark distinct reflector patterns, closer described in Sect. 5.




Figure 4. Gradient of the age from the AICC2012 age scale with depth (blue, left and bottom axes) and TWT (black, right and top axes) to infer age uncertainties due to reflector width and slope.