Sliding of temperate basal ice on a rough, hard bed: creep mechanisms, pressure melting, and implications for ice streaming

5

Maarten Krabbendam

British Geological Survey, Lyell Centre, Research Avenue South, Edinburgh EH14 4AP, UK

Correspondence to: Maarten Krabbendam (mkrab@bgs.ac.uk)

Abstract

Basal ice motion is crucial to ice dynamics of ice sheets. The classic Weertman sliding model for basal sliding over bedrock obstacles proposes that sliding velocity is controlled by pressure melting and/or ductile flow, whichever is the fastest; it further assumes that stoss-side melting is limited by heat flow through the obstacle and ductile flow is controlled by power-law creep. These last two assumptions, it is argued here, are not applicable if a substantial basal layer of temperate ($T \sim T_{melt}$) ice is present. In that case, frictional melting results in excess basal meltwater and efficient water flow, leading to near-thermal equilibrium. High temperature ice creep experiments have shown a sharp weakening of a factor 5-10 close to T_{melt} , suggesting normal power-law creep does not operate due to a switch to melt-assisted creep with a component of grain boundary melting. Stoss-side melting is controlled by melt water production, heat advection by flowing meltwater to the next obstacle, and heat conduction through ice/rock over half the obstacle height. No heat flow through the obstacle is required. Ice streaming over a rough, hard bed, as possibly in the Northeast Greenland Ice Stream, may be explained by enhanced basal motion in a thick temperate ice layer.

1 Introduction

The manner in which ice deforms within an ice sheet and moves or slides over its base are critical to accurately model the dynamic past, present and future behaviour of such ice bodies (e.g., Marshall, 2005). Internal deformation of cold ice is fairly well understood, and predictions made on the basis of physical laws (e.g., Glen's flow law) are broadly confirmed by observations (e.g., Dahl-Jensen and Gundestrup, 1987; Paterson, 1994; Ryser et al., 2014, but see Paterson (1991) for problems with dusty ice, and Hooke (1981) for a general critique). This is not the case for basal sliding, for which many

parameters are poorly constrained. Instead, many models of modern ice sheets use an empirical drag factor or slip coefficient, derived from observed ice velocity and estimated shear stresses (e.g., MacAyeal et al., 1995; Gudmundsson and Raymond, 2008; Ryser et al., 2014). Using an empirical slip coefficient is reasonable to describe and understand present-day near-instantaneous ice sheet behaviour, but cannot reliably predict or reconstruct ice velocities if parameters such as ice thickness, driving forces and meltwater production change significantly.

5

This problem is particularly acute for ice streams with poor topographic steering. For such ice streams it is commonly assumed that the necessary low drag at their base can be explained by the presence of soft sediment or deformable till (e.g., Alley et al., 1987; Hindmarsh, 1997; Winsborow et al., 2010), which has indeed been shown to occur below some ice streams in West Antarctica (e.g. Alley et al. 1987; King et al. 2009) and also documented in the geomorphological record (e.g. Margold et al. 2015). However, there is increasing geomorphological evidence for palaeo-ice streaming on rough, hard bedrock-dominated beds without clear topographic steering. Hard, rough beds are widespread on the beds of the former Pleistocene ice sheets and also likely beneath large parts of the present-day Greenland and Antarctic ice sheets (e.g., Kleman et al., 2008; Eyles, 2012; Rippin, 2013; Krabbendam and Bradwell, 2014; Krabbendam et al., 2016). Evidence for paleo-ice streaming has been reported from the former Pleistocene Laurentide and British ice sheets and deglaciated parts of West Greenland (Smith, 1948; Stokes and Clark, 2003; Roberts and Long, 2005; Bradwell et al., 2008; Eyles, 2012; Bradwell, 2013; Eyles and Putkinen, 2014; Krabbendam et al., 2016). In these areas, the deforming-bed models cannot apply because little or no soft-sediment is present. These palaeo-ice stream zones are surrounded by areas also subjected to less intense, but still warm-based ice erosion suggesting intermediate ice velocities (e.g., Bradwell, 2013), consistent with ice velocity analysis and borehole observations from the Greenland Ice Sheet that show significant warmbased sliding (10-100 m yr-1) outside ice-streams (Lüthi et al., 2002; Ryser et al., 2014, Joughin et al., 2010). Thus, fast ice flow appears to be possible on hard, rough beds and cannot be explained by a simple cold/warm thermal boundary (cf. Payne and Dongelmans, 1997). In Greenland, the massive Northeast Greenland Ice Stream remains difficult to explain, as current explanations invoke geologically unreasonably high geothermal heat flows (e.g., Fahnenstock et al., 2001) and a deformable bed with an unknown till source (Christianson et al. 2014).

A solution may be presented by the presence of a basal layer of temperate ice (ice at the melting temperature T_m), below cold ice that makes up the remainder of the ice sheet. Drilling in Greenland Ice Sheet adjacent to the Jakobshavn Isbrae has documented a basal layer of temperate ice below cold ice of some 30 m thickness (Lüthi et al., 2002), equal or greater in height than typical bedrock obstacles (roches moutonnées, whalebacks) in most crystalline gneiss terrains (Krabbendam and Bradwell, 2014). Temperate ice has also been modelled to occur beneath other parts of the Greenland Ice Sheet (e.g., Dahl-Jensen, 1989; Calov and Hutter, 1996; Greve, 1997). Two pertinent questions follow from these observations:

1) How does such a temperate layer develop and how is it maintained, given that it is overlain by cold ice? In-situ measurements at a glacier base and experiments have recently shown that warm-based basal sliding occurs under significant friction, caused by basal-debris / bedrock contacts (Iverson et al., 2003; Cohen et al., 2005; Zoet et al., 2013), generating significant frictional heat at the base, which is important for the development of a temperate ice layer.

5

10

15

2) How does basal sliding operate in temperate ice, and how does this differ from classic sliding models? The essence of the classic Weertman (1957) sliding model is that basal ice movement past an obstacle occurs by pressure melting around the obstacle and by ductile flow enhanced by stress concentrations near the obstacle, with ductile flow being more important for larger obstacles. The rheology of enhanced ductile flow is normally described by 'Glen's flow law', whereas pressure melting is regarded to be limited by heat flow *through the obstacle*. Sparse experimental evidence, however, suggests that temperate ice is considerably weaker than cold ice, and that creep may not be modelled reliably according to the standard Glen's flow law (e.g. Colbeck and Evans, 1973; Duval, 1977; Morgan, 1991). Furthermore, in a basal temperate ice layer it maybe that no thermal gradient across an obstacle can be maintained, and that pressure melting at the stoss side has thermal different controls than in the classic model.

Numerous studies have improved upon the Weertman sliding model, focussing on more realistic geometries of the bedrock obstacles, more sophisticated analyses of the stresses near the obstacles, and models that allow for lee-side cavitation, which was not allowed in the original model (e.g., Kamb and La Chapelle, 1964; Kamb, 1970; Nye, 1970, Lliboutry, 1993; Schoof, 2005). Nevertheless, the mechanical behaviour of temperate ice moving over a rough hard bed remains poorly constrained. This paper deals with four issues. Firstly, the problem of how a temperate layer can grow and be maintained below cold ice is discussed. Secondly, it will be shown that the two critical assumptions of classic Weertman sliding (enhanced ductile flow controlled by Glen's flow law and pressure melting controlled by heat flow through an obstacle) cannot be applied to temperate ice, and alternative controlling mechanisms are proposed. Thirdly, the implications of the different behaviour of temperate ice below cold ice for thermo-mechanical modelling of ice sheets are discussed. Finally, it is suggested that the development of a temperate basal ice layer may help to explain the occurrence of ice streaming on rough, hard beds, such as seen on deglaciated terrains and possibly also below the Northeast Greenland Ice Stream.

The paper takes a conceptual approach, focussing on the primary thermodynamic and rheological controls, so to achieve an improved conceptual model of basal ice motion around bedrock obstacles, rather than the exact quantification of geometries and stress distributions around such obstacles.

2 Basal meltwater production by frictional sliding

Consider sliding over a flat area without obstacles, over which debris-laden ice slides under friction. Friction produces drag and heat. Frictional heat production Q_{fr} and geothermal heat flow Q_{geo} together control the heat budget at the base of ice sheets. Frictional heat production is controlled by the friction coefficient μ , the normal vertical stress σ_{nv} and the sliding velocity V_{sl} according to:

(1)
$$Q_{fr} = \mu \, \sigma_v \, V_{sl} \approx \mu (Pi - Pw) \, V_{sl} \quad \text{in [W m}^{-2}].$$

The normal vertical stress σ_v can be taken as the effective pressure, that is ice pressure P_i minus water pressure P_w . (This is the standard friction model, using empirically derived bulk friction coefficients averaged over an areas containing many debris particles (eg Budd et al. 1979; Cohen et al. 2005; Zoet et al. 2014), rather than the theoretical models that consider individual clasts (e.g. Boulton, 1974; Hallet, 1979)). A temperate layer of ice has no significant thermal gradient and cannot conduct heat (see Section 3). Any heat produced at the base therefore causes basal melting, with the resultant melting rate M_{rm} (see Appendix) given by:

(2)
$$M_{rm} = \frac{(Q_{geo} + Q_{fr})}{H_{ice}}$$
 in [kg s⁻¹ m⁻²]

15

where H_{ice} is the heat of fusion of ice. The friction coefficient μ , controlled largely by debris concentration, and water pressure P_w are likely to vary significantly in space and time. Iverson et al. (2003) measured $\mu = 0.05$ in situ below a glacier; Budd et al. (1979) measured $\mu = 0.01$ - 0.4 for experimental sliding over rocks of different micro-roughness and Zoet et al. (2013) reported $\mu = 0.01$ - 0.05 for experimental sliding at the pressure melting point, but much higher values ($\mu = 0.2$ - 0.6) at colder temperatures and also, intriguingly, for warm-based sliding of ice over sandstone, which suggest that different bedrock lithologies can result in very different friction coefficients and hence basal melting rates.

The potential contribution of frictional heat due to basal sliding as a function of μ and P_w is graphically illustrated in Fig. 1. It is clear that under a range of circumstances, frictional heating can be equal or greater than the geothermal heat flow (see also Paterson, 1994; Calov and Hutter, 1994). Even at $\mu = 0.05$ (close to the friction coefficient of Teflon) heat production can be significant. At moderate sliding velocities (<10 m yr⁻¹), heat production at a warm base can be twice the heat production at a cold base, whilst at high sliding velocities typical of ice streams (>50 m yr⁻¹), frictional heating swamps geothermal heat flow. Note that the likely significant spatial variations in friction coefficient and bed roughness at the base of an ice sheet imply that it is not reliable to derive geothermal heat flow on the basis of basal melt rates alone (cf. Fahnestock et al., 2001; Greve, 2005).

The question now becomes: what happens with the water produced by frictional heating? There are two possibilities, not mutually exclusive:

1) The water drains away, initially along a film which may evolve into a dispersed drainage system and further into a channelized drainage system (e.g., Weertman and Birchfield, 1983). Generally water will drain away in the

direction of ice flow and ultimately discharge from the ice sheet, thus representing overall mass loss. Any thermal gradient at the base will be continuously smoothed by the advective heat transport of the flowing water. As a result, the entire basal environment (basal ice, water and top of bedrock) may reach thermal equilibrium at the pressure melting point.

2) If water cannot drain away freely, the water will remain under pressure. Water may move upwards through the temperate ice layer to the cold-temperate-boundary (CTB). Here it will refreeze and release its latent heat; this heat will warm up the cold ice just above the CTB, and thus thicken the temperate layer, as further explained below.

3 Growing and maintaining a temperate ice layer

5

15

20

25

30

The growth and continuance of a temperate ice layer below cold ice is an interesting problem in its own right. The problems associated with this are two-fold (Fig. 2):

- i) because cold ice above the CTB moves (by internal deformation) towards the margin, there is a strong component of horizontal thermal advection, isotherms are compressed and the effective thermal gradient at the base of the cold ice just above the CTB is steep, much steeper than can be maintained by heat conduction alone (Paterson, 1994; Dahl-Jensen, 1989; Funk et al., 1994). In Borehole D north of Jakobshavn Isbrae, this thermal gradient has been measured as $0.05 \, ^{\circ}\text{C m}^{-1}$ (= $50 \, ^{\circ}\text{C km}^{-1}$!) (Lüthi et al., 2002). There is thus the tendency to cool and hence shrink the temperate layer. For a temperate layer to exist and grow, energy must thus be added to the CTB (e.g., Clarke et al., 1977; Blatter and Hutter, 1990);
- ii) a temperate ice layer has no bulk thermal gradient (it has arguably a very small negative gradient, but this is ignored here), so no heat can be conducted through it; it forms a near- ideal thermal barrier (e.g. Aschwanden and Blatter, 2005).

Several mechanisms can be invoked to add energy to the CTB, despite the absence of a thermal gradient (Fig. 2):

- 1) Bedrock highs can conduct heat: if these penetrate the CTB, heat can be conducted into cold ice. This mechanism is limited by the heat conductivity of rock and the height of the obstacle; it cannot explain a CTB above a bedrock high;
- 2) Temperate ice layer may locally thicken by internal deformation, i.e. by folding or thrusting for instance where basal ice flow is heterogeneous near obstacles (e.g. Bell et al. 2014). However, this can only redistribute temperate ice and move it into cold ice, rather than lead to an overall thickening of the temperate layer itself.
- 3) Strain heating within deforming cold ice above the CTB. Given that this zone is subject to high strain this maybe significant (e.g., Clarke et al., 1977; Iken et al., 1993). However, the sharp nick in the temperature profile in Borehole D (Fig. 2) suggests that most heat is transferred across the CTB, rather than generated within the cold ice above the CTB;

4) Transport of water through the temperate layer. If water moves upward through the temperate layer and crosses the CTB, it freezes, releases its latent heat and warms the cold ice just above the CTB. As the ice temperature rises to T_m, the CTB moves upwards and the temperate layer thickens. A water flux through the temperate layer therefore equates with a heat flow. An intergranular vein network of water likely exists along grain boundaries in temperate ice (Nye and Frank, 1973; Mader, 1992). If (locally) $P_w > P_i$ because of a poorly connected subglacial drainage system (high P_w has been observed in drill hole C in Greenland; Iken et al. 1993) then water can migrate upwards against gravity, either by percolation or possibly by hydrauling fracturing. Water may also migrate as bubbles through ductile deformation, as suggested by the experiments of Wilson et al. (1996). Lovell et al. (2015) suggested that the 'dispersed' basal ice facies found close to the base in surge glaciers may form by shear deformation and partial melting along grain boundaries, resulting in an upward flux of liquid and gas along grain boundaries. Although temperate ice has a low permeability (Lliboutry, 1971), even a small water flux is very effective in transporting 'heat' because of the large latent heat of melting compared to the specific heat capacity of ice: 1 kg of freezing water can heat 160 kg of ice by 1 °C (Paterson, 1994). To maintain the CTB with a thermal gradient of 0.05 °C m⁻¹ just above it (e.g., Lüthi et al., 2002), an energy flow of 0.105 W m⁻² is required, about twice the normal geothermal heat flow (see Appendix). This in turn requires a flux of water through the temperate layer of ~23 mm yr⁻¹ (see Appendix), well within the range of water production by frictional melting at moderate to high sliding velocities. This latter mechanism is probably the most important to grow and maintain a temperate layer.

4 The creep component in temperate ice

In Weertman's (1957) model, stress concentrations build up around an obstacle according to:

20 (3)
$$\sigma_{stoss} = \frac{1}{6} \tau \lambda^2 (wh)^{-1}$$

5

10

15

where σ_{stoss} is the normal stress on the stoss side, acting horizontally; τ is the overall shear stress; λ is the spacing between obstacles; and w and h the width and height of the obstacle, respectively (Fig. 5). Weertman (1957) assumed that the creep component of ice flowing around a hard obstacle worked with a rheology according to 'Glen's Flow law', enhanced by stress concentrations around the obstacle. This law concerns the general relation between imposed deviatoric stress and resulting strain rate. The temperature dependence follows the Arrhenius relation, so that the relationship between strain rate $\dot{\varepsilon}$, deviatoric stress σ and temperature is typically described in one dimension as:

$$(4) \dot{\varepsilon} = A \sigma^n e^{\left(-\frac{Q_a}{RT}\right)}$$

where A is a constant, R the gas constant, n the stress component and Q_a the activation energy (Glen, 1955; Paterson, 1994; Alley, 1992). This general power law is applicable at appropriate conditions to many crystalline materials such as quartz, olivine and metals (e.g., Poirier, 1985). For ice, experiments suggest that $n \sim 3$ and $Q_a \sim 80$ -120 kJ mol⁻¹ for T >-10 °C (e.g., Barnes et al., 1971; Duval et al., 1983; Alley, 1992; Paterson, 1994). Comparisons with borehole tilt deformation studies

suggest that this describes the rheology of clean ice reasonably well (e.g., Dahl-Jensen and Gundestrup, 1987; Lüthi et al., 2002). Note that strain rate $\dot{\varepsilon}$ increases exponentially with temperature. The rate-controlling deformation mechanism of power-law creep in ice and other crystalline materials such as quartz and olivine is normally regarded to be intracrystalline creep, mainly by dislocation glide along basal planes (e.g., Duval et al., 1983; Poirier, 1985; Alley, 1992). The question is whether temperate ice behaves according to the same power law, has the same rate-controlling deformation mechanism (e.g., Hooke, 1981; Parizek and Alley, 2004) and is applicable to temperate ice flow around hard obstacles.

Experimental data compiled by Morgan (1991), all performed under constant stress (1 bar = 10^5 Pa), are plotted in Fig. 3 to illustrate the effect of temperature on the strain rate. The natural logarithmic of strain is plotted against the reciprocal of temperature, so that a straight line would confirm the Arrhenius relations within the power law. For temperatures between -5 and -0.5 °C, the data plot on a straight line, the gradient of which equals ($-Q_a/R$), confirming the Arrhenius relation in equation (4) over this temperature interval. However, at about -0.02 °C there is a sharp nick in the trend, with strain rates increasing by up to a factor of ten as the melting temperature is approached. Thus, at constant stress, ice above c. -0.2 °C shows a sudden weakening of a factor 5 to 10, evidently not described by the Arrhenius relation of equation (4) and suggesting that power-law creep is not dominant close to the melting temperature (see also Barnes et al. 1971; Colbeck and Evans, 1973; Morgan, 1991).

10

The stress-strain rate dependency (the value of n in equation (4)) for temperate ice is ambiguous. Experiments at constant temperature but varying stress (T ~ -0.01 °C, σ = 10-100kPa) by Colbeck and Evans (1973) suggest n = 1.3; experiments of creep at the melting temperature past a sphere by Byers et al. (2012) also suggest n < 1.5. By analysing bulk stress and strain rate using borehole tilt measurements in a 3D borehole network in the temperate Worthington Glacier, Marshall et al. (2002) noted n ~ 1 at low stresses, but, interestingly, a change to n ~ 4 at higher stresses (>1.8 kPa). De La Chapelle et al. (1999) noted a similar change from n ~ 1.8 at low stresses to n ~ 3 at high stress (>250 kPa) in experiments of pure ice in the presence of a brine (i.e. not temperate ice *sensu stricto*). Analysis of bulk stress and strain rate of the temperate Glacier de Tsanfleuron, however, suggest n ~ 1 (Chandler et al., 2008). At the base of the same glacier, Tison and Hubbard (2000) documented large grain sizes (5-20 mm) and a well-developed crystallographic fabric in basal deforming ice.

It thus appears that deforming temperate ice behaves fundamentally different from deforming cold ice and cannot be reliably modelled with a standard power law or Glen's flow law. The sharp transition just below the melting temperature suggests that this difference is largely caused by the presence of water. Duval (1977) noted in temperate ice experiments that a rise in water content up to c. 0.8% leads to a 5-8 times strain rate increase. Temperate ice in Alpine glaciers can contain 1-2 % water (Vallon et al., 1976), which has been observed in experiments to gather along grain triple junctions (Barnes and Tabor, 1966; Wilson et al., 1996), so that it is likely that a vein network along triple junctions exists (Nye and Frank, 1973; Mader, 1992). Partial melting of a deforming temperate layer is furthermore suggested by the formation of bubble-free ice, both in experiments (Barnes and Tabor, 1966) as well as in Alpine and surging Syalbard glaciers (Tison and Hubbard, 2000, Lovell

et al. 2015). The dominant deformation mechanism for temperate ice, however, is uncertain and it is possible that different deformation mechanisms operate simultaneously. Possible deformation mechanisms and their potential enhancement by the presence of water are suggested below.

1) Diffusion creep is enhanced by the presence of liquid along grain boundaries, since that liquid functions like a fast diffusion path (Pharr and Ashby, 1983; Raj, 1982; Goldsby and Kohlstedt, 2001).

5

10

15

20

25

- 2) Dislocation creep is also enhanced by liquid (Duval, 1977; De la Chapelle et al. 1995; 1999). Water along grain boundaries decreases the surface area of grain-to-grain contacts and cause an increase in grain-to-grain contact stresses; this will enhance dislocation creep (De La Chapelle et al., 1999) but also other deformation mechanisms. Liquid may also suppress strain hardening and enhance easy intracrystalline basal slip (Duval, 1977; De La Chapelle et al. 1999).
- 3) Dynamic recrystallization and grain growth is rapid in deforming temperate ice (e.g., Duval et al. 1983; Wilson, 1986). Dynamic recrystallization aids dislocation creep as it grows crystals with orientations favourable for easy basal slip and suppresses strain hardening (e.g. Duval et al. 1983). Dynamic recrystallization results in a coarse grain size and should aid development of a crystal fabric.
- 4) Grain boundary sliding is commonly invoked to explain weakening in ductily deforming materials (superplasticity). Superplasticity has been experimentally achieved in ice at very low temperatures (-30 to -80°) and very small (3-40μm) grain sizes (Goldsby and Kohlstedt, 1997, 2001; Goldsby and Swainson, 2005), rather different than the temperate ice under discussion here. Whether grain boundary sliding in ice leads to the formation or destruction of a crystallographic fabric appears debatable (Goldsby and Kohlstedt, 2001; 2002; Duval and Montagnat, 2003; Goldsby and Swainson, 2005).
 - Grain boundary melting (or 'internal pressure melting') has been observed in ice deformation experiments with indentors by Barnes and Tabor (1966), Barnes et al. (1971) and Wilson et al. (1996). The principle is that ice melts at highly stressed grain boundaries, liquid is transported to lesser stressed grain boundaries where it refreezes or water may escape if the intergranular vein network is efficient. Either way, this leads to strain. For ice (in contrast to almost all other materials), it is important to emphasise that grain boundary melting involves a negative volume change upon melting ($\Delta V = -9\%$), which makes grain boundary melting under elevated stresses a thermodynamically favourable mechanism. The distance of heat transport to the stressed grain boundaries necessary to sustain grain boundary melting is half the grain size (Fig. 4), some three orders of magnitude smaller than the size of most bedrock obstacles. It further requires that ice and water are in thermal equilibrium, and might thus not be observed in experiments with cold ice and where the liquid is a brine (cf. De La Chapelle, 1995; 1999). Grain boundary melting is supported by the formation of bubble-poor ice at the base of temperate glaciers: both Tison and Hubbard (2000) and Lovell et al. (2015) show that such ice not formed by direct freeze-on (regelation ice), but by a metamorphic process involving partial melting. Grain boundary melting is loosely analogous to

pressure solution (solution-precipitation creep) observed in salts and limestone, in that material changes from solid to liquid or vice-versa along grain boundaries in different stress states (Pharr and Asby, 1983; McClay, 1977; Rutter, 1983), but differs in that grain boundary melting creates its own liquid.

Which of these deformation mechanisms is dominant is difficult to establish. Given the very different grainsizes and 5 temperatures at which grain boundary sliding has been shown to occur (Goldsby and Kohlstedt, 1997, 2001), and the development of a crystallographic fabric in temperate ice(Tison and Hubbard, 2000), grain boundary sliding is probably not significant. Diffusion creep, grain boundary sliding and grain boundary melting all work on grain boundaries and are grainsize sensitive: they are favoured by a small grain size and the presence of a liquid; these mechanisms normally result in n < 3, and thus could explain the $n \sim 1$ behaviour seen in some experiments and natural glaciers. Considering the near-unique 10 pressure-melting behaviour of H₂O, grain boundary melting is worthy of further study. However, all grain-size sensitive mechanisms are at odds with the large grain sizes observed and can, on their own, not explain well-developed fabrics. Welldeveloped fabrics potentially attests to dislocation creep, but is in turn at odds with the $n \sim 1$ behaviour commonly observed. Altogether there is no clear evidence of a single dominant deformation mechanism, and all deformation mechanisms mentioned above may contribute. The change in the stress-dependency as observed in the Worthington Glacier (Marshall et al. 2002) as well as in some experiments (De La Chapelle et al. 1999) suggests that the dominant deformation mechanism in temperate ice depends on the magnitude of stress. For the moment the rather non-generic term 'melt-assisted creep' is used herein. A strong crystallographic fabric and concentrations of dust or silt particles are known to significantly weaken cold ice in simple shear (e.g., Lile, 1978; Paterson, 1984, 1991; Dahl-Jensen and Gundestrup, 1987; Azuma, 1994), but whether this leads to further weakening of temperate ice is not known. There is still much unknown about creep in temperate ice; regardless of the actual mechanism all experiments show that temperate ice is significantly weaker than, and behaves very differently from, cold ice.

5 The pressure melting component

In the classic Weertman's model, the stress concentration on the stoss side that build up according to equation (3) causes a lowering of the melting temperature ΔT_m according to:

$$\Delta T_m = -C\sigma_{stoss}$$

where C is the pressure melting constant $(7.4 \cdot 10^{-8} \text{ K Pa}^{-1})$. As an example, with w = 1 m, h = 1 m and $\tau = 124 \text{ kPa}$, similar to the parameters used by Weertman, (1957), this would result in a stoss-side normal stress $\sigma_{stoss} = 330 \text{ kPa}$ (see Appendix), causing a lowering of the melting point of $\Delta T_m = -0.025$ °C. Assuming the deviatoric stress on the lee-side is equal but opposite, the melting temperature at the lee side is higher by an equal amount, so that $\Delta T_m = +0.025$ °C. Weertman (1957) envisaged that water freezing on the lee-side released latent heat; this excess heat was regarded to be *transported through the obstacle* towards the stoss side where it caused further melting. The resultant heat flux through the obstacle Q_{ob} is then

controlled by the total temperature difference between the lee and stoss side $(2\Delta T_m = 0.05^{\circ}\text{C})$ in this example), the thermal conductivity of rock K_r and the length l of the obstacle :

$$Q_{ob} = K_r 2\Delta T_m l^{-1}$$

This heat flux was regarded to control the amount of thermal energy available at the stoss side for melting to proceed and hence as controlling the velocity by melting V_{pm} :

$$(7) \hspace{1cm} V_{pm} = Q_{ob} \; H_{ice}^{-1} \; \rho_{ice}^{-1} = K_r \; 2\Delta T_m \; l^{-1} H_{ice}^{-1} \; \rho_{ice}^{-1} \; \propto l^{-1}$$

where ρ_{ice} the density of ice. This model has a number of problems. Firstly, if cavitation occurs it is unclear how heat can be transported to the stoss-side (an issue also addressed by Lliboutry, 1993). Secondly, V_{pm} is inversely proportional to the length of the obstacle, following equation (4). This implies that ice melting around an obstacle that is, say, four times longer than another obstacle (Fig. 5b), would be four times slower, even though this obstacle is more streamlined (having a longer aspect ratio). This result contradicts most observed geomorphology (Stokes and Clark, 1999; Bradwell et al., 2008) and supports the notion that pressure melting is not dominant for large obstacles.

6 Stoss-side pressure melting in temperate ice

What are the rate controlling factors for stoss-side pressure melting in a layer of temperate ice? In the conceptual model here (Fig. 5c), the temperate layer is thicker than the height of the obstacle. Water is continually produced by frictional heating, there is a net-melting environment with an excess of water, and water pressure on the ice-bed contact will be high. Depending on the basal melt rate and the amount of water flowing along the ice-rock interface, heat advection by flowing water may well be more efficient than heat conduction through rock or ice. In that case no significant thermal gradients through bedrock obstacles can build up and the entire basal system (temperate ice, water, and top rock) is kept at thermal equilibrium at T_m . The only exception is the stoss-side of a bedrock obstacle, where the melting temperature is continually depressed as a result of the concentrated deviatoric stress acting onto it (Fig. 5c). Thus, the problem of stoss-side pressure melting is reduced to a single 'cool spot' at the stoss side, with a temperature ΔT_{stoss} below the ambient T_m ($\Delta T_{stoss} = -0.025$ °C in the example, with similar parameter values as Weertman, 1957). To sustain stoss-side pressure melting, heat needs to be transported only a short distance towards this cool spot: anywhere else is at T_m . Although total ΔT is half compared to the Weertman model (there being no 'warm spot' at the lee side), the transport distance is much smaller. Most obstacles will be wider than high, in which case the critical transport distance is 0.5 h. As a consequence the heat flow towards the stoss side will be greater than in Weertman's model, and it is independent of the length of the obstacle. Cavitation may occur, as this system is not dependent on regelation. The process can work without any regelation in an overall melting environment, which is compatible with the observation of continuous net basal melting at the base of ice sheets (e.g., Fahnestock et al., 2001). If regelation occurs on the lee side (because of lower stress) of one obstacle, any excess heat will be advected by flowing water to the stoss-side of the next obstacle. In this process, the rate controlling factors are the height of the obstacle (but not the width or the length) and the efficiency of the heat advection by flowing water. The process is not limited by heat flow through the obstacle (cf. Weertman, 1957; Kamb, 1970), and the length of the obstacle becomes irrelevant. This type of stoss-side melting will be faster than in Weertman's model for all but the shortest obstacles, and certainly so for obstacles with l>h, which is the case for most observed bedrock bedforms in even the roughest of deglaciated terrains (Bradwell, 2013; Roberts and Long, 2005).

5 7 Effect of surface water input on temperate ice on a rough bed

10

20

Influx of surface melt water represent addition of thermal energy and can further aid stoss-side melting and hence basal motion. Consider the dramatic influx of surface melt water by the sudden drainage of supraglacial meltwater lakes in West Greenland (e.g., Das et al., 2008). This water is relatively warm (c. 1° C; Tedesco et al., 2012) and such an influx thus represents a significant addition of thermal energy to the base. Sudden influx of warm melt water may have the following consequences:

- a) Increase of basal water pressure P_w , resulting in a drop in effective pressure P_e , lowering the friction on flat surfaces. Frictional heating and drag on the flats will drop, as long as P_w remains high. On the other hand, because there is less drag on the flat surfaces, the normal stress σ_{stoss} onto the stoss side of obstacles, increases (also temporarily), enhancing stoss-side melting as well as creep.
- b) The basal system is flushed with water that is well above the ambient T_m . Given the very fast recorded flow of large amounts of water (Das et al., 2008), it is assumed here that little heat is lost during englacial transport. Water entering the basal system at 1 °C is 1.5 °C above T_m and 1.525 °C above the stoss-side melting point. There is thus potentially a steeper thermal gradient between the warm water and the cold spot at stoss-side and more thermal energy is available. This may lead to accelerated stoss-side melting, which would continue until all the water temperature has cooled to T_m .
 - c) A more longer-term effect is that if warm water is added to the base and cannot drain away freely, the additional thermal energy will lead to a thickening of the temperate layer (upwards migration of the CTB), in essence cryohydrological warming of the basal system (cf. Phillips et al. 2010).

The rate controlling factors of this enhanced stoss-side melting are (i) the flux of surface melt water; (ii) the temperature of this water, (iii) the dissipation of the extra heat, for instance by further melting of ice above the flat surfaces.

In West Greenland, sudden supraglacial meltwater drainage events are accompanied by (a) an immediate (hour time scale) speeding up of surface velocity, with a total horizontal displacement of < 1 m, and vertical uplift of the ice surface on a centimetre scale, followed by (b) a longer period (days) of decelerating but still above-average ice velocity (e.g., Das et al., 2008; Shepherd et al., 2009; Hoffman et al., 2011). The centimetre-scale ice uplift is clearly insufficient to lift basal ice over 1-10 m high obstacles that are likely to exist at the base of the Greenland ice sheet, given its gneiss-dominated bedrock (Roberts and Long, 2005; Krabbendam and Bradwell, 2014). The sudden, short jump is probably due to true sliding as basal ice is pushed higher onto (but not over) sloping obstacles due to an increase of P_w . However, the longer-term (days) increase

in ice velocity may well be caused by accelerated stoss-side melting as described above. It is remarkable that the dramatic lake drainage events have a rather muted effect on ice velocity, strongly suggesting that the basal ice in West Greenland is 'stuck' on the stoss sides of pronounced bedrock obstacles. The term 'lubrication' (e.g., Parizek and Alley, 2004; Shannon et al. 2013) is inappropriate to describe the latter process: it is enhanced melting-regelation, rather than a lowering of friction, that leads to the speed-up.

8 Critical obstacle size

5

Weertman (1957) introduced the notion of the 'critical obstacle size'. Because pressure melting and enhanced creep have different dependencies on the obstacle size, melting and regelation should be the dominant mechanism for small obstacles, whereas enhanced creep should be dominant for larger obstacles. For his chosen parameters, Weertman arrived at a critical obstacle size of ~ 1 cm (Fig. 6). Replacing the controlling mechanisms with those for temperate ice, but otherwise applying the same parameters, this would result in approximately a 5-10 times increase in creep velocity and a doubling of the pressure melting velocity, because the controlling height is 0.5h. This means that the critical obstacle size becomes even smaller, e.g. c. 0.5 cm (Fig. 6). However, in subglacial observations and experiments Kamb and La Chapelle (1964) noted that melting/regelation was dominant at much larger obstacles and suggested a critical obstacle size of about 1 metre. They suggested that whilst the qualitative idea of a critical obstacle size of Weertman (1957) was correct, the quantification was incorrect. On the scale of typical bedrock obstacles such as roche moutonnées ($l \sim 5$ -50 m, $h \sim 1$ -10 m), enhanced creep will be dominant and, as discussed above, will in temperate ice be controlled by some form of melt-assisted creep. Melting/regelation may not be important for bedrock obstacles on a rough bed, but can be important for ice flow around cobble-sized debris.

20 **9 Discussion**

9.1 Summary of rate-controlling mechanisms

In summary, ice flow around a bedrock obstacle in temperate ice is accommodated by stoss-side pressure melting or by enhanced creep, with creep being more important for larger obstacles. In temperate ice, the enhanced creep component of basal motion operates close to or at the melting temperature, the rheology of this melt-assisted creep is poorly constrained, but does not behave according to standard power-law creep, is up to one magnitude faster than power-law creep in cold ice, and may involve a component of grain boundary melting. The effects of strain softening and dust particles are uncertain; more laboratory experiments on the deformation of temperate ice may help to better understand creep in temperate ice.

If a temperate layer exists that is thicker than the height of bedrock obstacles, it is proposed here that stoss-side pressure melting is constrained by:

- Stress concentration on the stoss-side, which depends on the surface area of the stoss-side with respect to the spacing of obstacles, and also to the slope of the obstacles, something not considered here;
- Height of the obstacle, which is critical to the transport distance of heat transport;
- Frictional heating on the flat surfaces, which causes the production of excess meltwater;
- The efficiency and possible localisation of the local drainage network;
- Input of surface meltwater.

15

30

In contrast to the classic Weertman model, stoss-side pressure melting is *not* constrained by heat flow through the rock obstacle, cavitation is possible, and the length of the obstacle is not relevant.

0 9.2 Basal sliding regimes throughout an ice sheet

The proposed model has implications for ice sheet behaviour and the modelling thereof. Consider a hypothetical half-ice sheet (Fig. 7), based on the thermo-mechanical model by Dahl-Jensen (1989) and with a passing resemblance to the Greenland Ice Sheet. Thermal gradients are strongly affected by horizontal motions as ice velocity exceeds the rate of heat conduction, so that a cold 'tongue' occurs within the ice sheet (e.g., Dahl-Jensen, 1989; Iken et al., 1993). The bed is regarded as rough and hard. In such a model, three thermomechanical basal regimes can occur, with a potential fourth operating seasonally.

- 1) In the cold-based regime, the thermal gradient crosses T_m well into bedrock. All geothermal heat is conducted upwards through the ice. No sliding occurs, and frictional heating is zero. All deformation is internal and can be described by power-law creep.
- 20 2) At some point the thermal gradient crosses T_m at the base of the ice sheet, and the base is at the pressure melting point. Sliding starts and frictional heating kicks in. In this regime, the friction coefficient will be highly variable as some patches will be frozen, with very high static friction coefficient (Barnes et al., 1971; Budd et al., 1979; Zoet et al., 2013) but low sliding velocities, whereas other patches will be wet, with lower friction coefficient but higher sliding velocities. Excess heat may still be conducted away by the overlying cold ice and water may well regelate onto lee-sides and on overlying ice, thus limiting the amount of water present. In this regime, basal sliding by some form of classic Weertman sliding is likely. Almost all creep still occurs in cold ice and can be described by power-law creep.
 - 3) Continuous frictional heating overwhelms the heat conducting capacity of the overlying ice and a thick temperate layer develops. Where or when this happens depends in part on the thermal structure of the ice sheet, and in particular the thermal gradient near the base: a steeper gradient requires more frictional heating to develop a temperate basal layer. Once a thick temperate ice layer has developed, basal motion occurs according to the processes described above: (i) on the flat surfaces frictional sliding occurs; (ii) ductile flow will occur by melt-assisted creep, much faster than power-law creep; (iii) stoss-side melting will be faster than in Weertman Sliding.

4) if large amounts of surface meltwater can drain to the base of the ice sheet, for instance by periodical drainage of supraglacial lakes, a different temporal thermo-mechanical regime develops. Influx of surface meltwater adds thermal energy to the basal environment; this thermal energy is available in part to further accelerate stoss-side pressure melting.

5 9.3 Relevance for ice streaming

The corollary of the processes described herein is that if a thick temperate layer is present, basal motion over a hard bed with bedrock humps provides less drag than ice modelled with cold ice properties. This finding is relevant to ice-sheet modelling. For instance, Peltier et al. (2000) argue that the Laurentide ice Sheet cannot be adequately modelled using a standard 'Glen's flow law' rheology; instead they suggest a different, weaker bulk rheological behaviour. This solution, however, is at odds with findings that the bulk rheology of ice in boreholes can be adequately described as power-law creep. Instead, it may be more realistic to invoke fast, weak basal motion, even on hard beds, in ice-sheet models. How may this relate to ice-streaming mechanisms? A thick temperate layer has been observed in boreholes adjacent to the Jakobshavn Isbrae and inferred within its centre (Lüthi et al., 2002), whereas boreholes in non-ice streaming parts of the Greenland ice sheet show an absence of a temperate layer (Ryser et al., 2014). Ice streams are widespread and their locations appear to be controlled by a range of factors, of which topographic steering and the presence of soft, deforming sediment bed are seen as the most important (e.g., Winsborrow et al., 2010). There are, however, numerous palaeo-ice streams that neither portray strong topographic channelling, nor have soft-sediment (till) at their base (Bradwell et al., 2008; Bradwell, 2013; Eyles, 2012; Krabbendam et al., 2016).

A modern example of such an ice stream maybe the Northeast Greenland Ice Stream (NEGIS) (Joughin et al., 2001; Fahnestock et al., 2001). While there is topographic steering near its outlet glaciers, topographic steering is weak over much of its length (Joughin et al., 2001; Christianson et al. 2014). Seismic and radio-echo-sounding have shown the base of the NEGIS to be rough (e.g. Christianson et al. 2014) and also suggests the possible presence of water-rich till. However, the presence of soft, deformable till below the NEGIS is not proven and, if existent, may not be the rate-controlling factor, as deforming till will not help in moving ice over bedrock humps. The bedrock geology of Greenland is dominated by Precambrian gneisses, and such rocks almost certainly underlie most of the inland track of the NEGIS. Deglaciated areas of Precambrian gneisses in Canada, Scotland, Scandinavia and Greenland generally show a lack of till, extensively exposed bedrock and a rough landscape of rock knolls and rock basins (Roberts and Long, 2005; Krabbendam and Bradwell, 2014). Using high-resolution radar profiles to reconstruct an isochron stratigraphy, Fahnestock et al. (2001) reported large areas of 'missing' basal ice below the NEGIS, and attributed this to very high, long-term basal melt rates (up to c. 100 mm yr⁻¹). These high basal melt rates were thought to be caused by anomalously high (10 times above normal values) geothermal heat flow. The geophysical evidence for such anomalously high geothermal flow, however, is localised and non-unique, and does not cover the track of the NEGIS; moreover, the contribution of frictional heating to high basal melting rates was not taken

into account by Fahnestock et al. (2001). Instead, I suggest here that the NEGIS may possess a substantial basal layer of temperate ice, formed and maintained largely by frictional heating. Basal melting rates of 100 mm yr⁻¹ are possible in areas of high friction and/or high ice velocity (Fig. 1). In the inversion technique employed by Joughin et al. (2001), a weak basal temperate ice layer would potentially give a similarly low basal drag as a soft, deformable bed.

The existence and distribution of a temperate basal layer below cold ice is potentially an important factor controlling ice dynamics and ice streaming. The occurrence of a basal temperate layer and estimates of water content can be detected remotely by using radio-echo sounding at certain frequencies (Björnsson et al., 1996; Murray et al., 2000, 2007). Future challenges to improve dynamic ice sheet modelling include a better knowledge of the rheology of temperate ice, basal friction and frictional heating, basal roughness and distribution and thickness of the basal temperate layer.

10 **10 Conclusions**

5

Basal motion of ice past hard-bed obstacles involves a competition between stoss-side melting and enhanced creep. In a basal layer of temperate ice, stoss-side melting is not controlled by heat flow through the obstacle, but instead by the thickness of the temperate layer, the availability and flux of basal meltwater and the height of the obstacle. Creep in temperate ice is up to ten times faster than in cold ice, suggesting a switch in deformation mechanism to melt-assisted creep. Melt-assisted creep probably comprises several deformation mechanisms triggered or enhanced by the presence of water: grain boundary melting, fast dynamic recrystallisation and enhanced dislocation creep. Together, this suggest that basal motion in temperate ice over a rough, hard bed provides low drag, allowing the possibility of fast ice flow over hard, rough beds. Three different thermo-mechanical regimes control basal sliding: (i) cold-based regime, (ii) warm-based but with a thin temperate layer and (iii) warm-based with a substantial temperate layer. The onset zones of (palaeo)ice streams may coincide with a minimum thickness of the temperate layer, and a thick basal temperate ice layer can explain ice streaming over rough, hard beds, possibly including the Northeast Greenland Ice Stream.

Acknowledgements

Doug Macayeal, Martyn Drury, Roderick van der Wal, Steve Roberts and Phil Sargeant are thanked for encouraging and interesting discussions. Sam Roberson is thanked for comments on a previous version of the manuscript. This paper is published with the permission of the Executive Director, British Geological Survey.

References

- Alley, R. B., Blankenship, D. D., Bentley, C. R., and Rooney, S: Till beneath ice stream B: 3. Till deformation: evidence and implications, Journal of Geophysical Research, 95, 8921-29, doi: 10.1029/JB092iB09p08921, 1987.
- 5 Alley, R B: Flow-law hypotheses for ice-sheet modeling, Journal of Glaciology, 38, 245-56, doi:10.1029/2005JF000320, 1992.
 - Aschwanden, A. and Blatter, H.: Meltwater production due to strain heating in Storglaciären, Sweden, Journal of Geophysical Research, 110, F04024, doi: 10.1029/2005JF000328, 2005.
 - Azuma, N.: A flow law for anisotropic ice and its application to ice sheets, Earth and Planetary Science Letters, 128, 601-14, doi:10.1016/0012-821X(94)90173-2, 1994.
 - Barnes, P. and Tabor, D.: Plastic flow and pressure melting in the deformation of ice I, Nature, 210, 878-82 doi:10.1038/210878a0, 1966.
 - Barnes, P., Tabor, D., and Walker, J. C. F.: The friction and creep of polycrystalline ice, Proceedings of the Royal Society of London. A. Mathematical and Physical Sciences, 324, 127-55, doi: 10.1098/rspa.1971.0132, 1971.
- Bell, R. E., Tinto, K., Das, I., Wolovick, M., Chu, W., Creyts, T. T., Frearson, N., Abdi, A., et al.: Deformation, warming and softening of Greenland's ice by refreezing meltwater, Nature Geoscience, 7, 497-502, doi:10.1038/ngeo2179, 2014.
 - Björnsson, H., Gjessing, Y., Hamran, S. E., Hagen, J. O., Liestøl, O., Pálsson, F., and Erlingsson, B.: The thermal regime of sub-polar glaciers mapped by multi-frequency radio-echo sounding, Journal of Glaciology, 42, 23-32, 1996.
- 20 Blatter, H. and Hutter, K.: Polythermal conditions in Arctic glaciers, Journal of Glaciology, 37, 261-69, 1990.
 - Boulton, G. S.: Processes and patterns of glacial erosion., in D. R. Coates (ed.), Glacial Geomorphology, Binghampton: University of New York, 41-87, 1974.
 - Bradwell, T., Stoker, M.S., and Krabbendam., M.: Megagrooves and streamlined bedrock in NW Scotland: the role of ice streams in landscape evolution, Geomorphology 97 135-56 doi:10.1016/j.geomorph.2007.02.040, 2008.
- Bradwell, T.: Identifying palaeo-ice-stream tributaries on hard beds: Mapping glacial bedforms and erosion zones in NW Scotland, Geomorphology 201, 397-414, doi:10.1016/j.geomorph.2007.02.040, 2013.
 - Budd, W. F., Keage, P. L., and Blundy, N. A.: Empirical studies of ice sliding, Journal of Glaciology, 23, 157-70, 1979.
 - Byers, J., Cohen, D., and Iverson, N. R.: Subglacial clast/bed contact forces, Journal of Glaciology, 58, 89-98, doi: 10.3189/2012JoG11J126, 2012.
- 30 Calov, R. and Hutter, K: The thermomechanical response of the Greenland ice sheet to various climate scenarios, Climate Dynamics, 12, 243-60, doi: 10.1007/BF00219499, 1996.

- Chandler, D., Hubbard, B., Hubbard, A., Murray, T., and Rippin, D.: Optimising ice flow law parameters using borehole deformation measurements and numerical modelling, Geophysical Research Letters, 35, L12502, doi: 10.1029/2008GL033801, 2008.
- Christianson, K., Peters, L. E., Alley, R. B., Anandakrishnan, S., Jacobel, R. W., Riverman, K. L., Muto, A., and Keisling, B. A.: Dilatant till facilitates ice-stream flow in northeast Greenland, Earth and Planetary Science Letters, 401, 57-69, doi: 10.1016/j.epsl.2014.05.060, 2014.
- Clarke, G. K., Nitsan, U., and Paterson, W. S. B.: Strain heating and creep instability in glaciers and ice sheets, Reviews of Geophysics, 15, 235-47, doi: 10.1029/RG015i002p00235, 1977.
- Cohen, D., Iverson, N. R., Hooyer, T. S., Fischer, U. H., Jackson, M., and Moore, P. L.: Debris-bed friction of hard-bedded glaciers, Journal of Geophysical Research: Earth Surface, 110, F02007, doi: 10.1029/2004JF000228, 2005.
- Colbeck, S. C. and Evans, R. J.: A flow law for temperate glacier ice, Journal of Glaciology, 12, 71-86, 1973.

10

15

- Dahl-Jensen, D. and Gundestrup, N. S.: Constitutive properties of ice at Dye 3, Greenland, in E.D. Waddinton and J Walder (eds.), The Physical Basis of Ice Sheet Modelling, 170: IAHS Publications, 31-43, 1987.
- Dahl-Jensen, D: Steady thermomechanical flow along two-dimensional flow lines in large grounded ice sheets, Journal of Geophysical Research, 94, 10355-62, doi: 10.1029/JB094iB08p10355, 1989.
- Das, S. B., Joughin, I., Behn, M. D., Howat, I. M., King, M. A., Lizarralde, D., and Bhatia, M. P: Fracture propagation to the base of the Greenland ice sheet during supraglacial lake drainage., Science, 320 778-81, doi: 10.1126/science.1153360 2008.
- De La Chapelle, S., Duval, P., and Baudelet, B.: Compressive creep of polycrystalline ice containing a liquid phase., 33(3), . Scripta metallurgica et materialia, 33, 447-50, doi:10.1016/0956-716X(95)00207-C, 1995.
- De La Chapelle, S., Milsch, H., Castelnau, O., and Duval, P.: Compressive creep of ice containing a liquid intergranular phase: Rate-controlling processes in the dislocation creep regime, Geophysical Research Letters, 26, 251-54, doi: 10.1029/1998GL900289, 1999.
- Duval, P.: The role of the water content on the creep rate of polycrystalline ice, IAHS Publication, 118, 29-33, 1977.
- Duval, P., Ashby, M. F., and Anderman, I.: Rate-controlling processes in the creep of polycrystalline ice, The Journal of Physical Chemistry, 87, 4066-74, doi: 10.1021/j100244a014, 1983.
 - Eyles, N: Rock drumlins and megaflutes of the Niagara Escarpment, Ontario, Canada: a hard bed landform assemblage cut by the Saginaw–Huron Ice Stream, Quaternary Science Reviews, 55, 34-49, doi:10.1016/j.quascirev.2012.09.001, 2012.
- 30 Eyles, N. and Putkinen, N.: Glacially-megalineated limestone terrain of Anticosti Island, Gulf of St. Lawrence, Canada; onset zone of the Laurentian Channel Ice Stream., Quaternary Science Reviews, 88, 125-34, doi:10.1016/j.quascirev.2014.01.015, 2014.
 - Fahnestock, M., Abdalati, W., Joughin, I., Brozena, J., and Gogineni, P.: High geothermal heat flow, basal melt, and the origin of rapid ice flow in central Greenland., Science, 297, 2338-42, doi: 10.1126/science.1065370, 2001.

- Funk, M, Echelmeyer, K, and Iken, A: Mechanisms of fast flow in Jakobshavns Isbrae, West Greenland: Part II. Modeling of englacial temperatures, Journal of Glaciology, 40, 569585, 1994.
- Glen, J. W.: The creep of polycrystalline ice, Proceedings of the Royal Society of London. Series A. Mathematical and Physical Sciences, 228, 519-38, doi: 10.1098/rspa.1955.0066, 1955.
- 5 Goldsby, D. L. and Kohlstedt, D. L.: Grain boundary sliding in fine-grained ice I, Scripta Materialia, 37, 1399-406, 1997.
 - Goldsby, D. L. and Kohlstedt, D. L.: Superplastic deformation of ice: Experimental observations, Journal of Geophysical Research, 106, 11017-30, doi: 10.1029/2000JB900336, 2001.
 - Goldsby, D. L. and Kohlstedt, D. L.: Reply to comment by P. Duval and M. Montagnat on "Superplastic deformation of ice: Experimental observations", Journal of Geophysical Research: Solid Earth, 107, ECV 17-1–ECV 17-5, doi:10.1029/2001JB000946, 2002.
 - Goldsby, D L and Swainson, I: Development of C-axis fabrics during superplastic flow of ice., Eos, Transactions, American Geophysical Union., 86 2005.
 - Greve, R.: Application of a polythermal three-dimensional ice sheet model to the Greenland ice sheet: response to steady-state and transient climate scenarios, Journal of Climate, 10, 901-18, doi: 10.1175/1520-0442(1997)010<0901:AOAPTD>2.0.CO;2, 1997.
 - Greve, R: Relation of measured basal temperatures and the spatial distribution of the geothermal heat flux for the Greenland ice sheet, Annals of Glaciology, 42, 424-32, doi: 10.3189/172756405781812510, 2005.
 - Gudmundsson, G. H. and Raymond, M.: On the limit to resolution and information on basal properties obtainable from surface data on ice streams. The Cryosphere, 2, 413-45, doi:10.5194/tc-2-167-2008, 2008.
- 20 Hallet, B: A theoretical model of glacial abrasion, Journal of Glaciology, 23, 39-50, 1979.

15

- Hindmarsh, R.C.A.: Deforming beds: viscous and plastic scales of deformation, Quaternary Science Reviews, 16, 1039-56, doi:10.1016/S0277-3791(97)00035-8, 1997.
- Hoffman, M. J., Catania, G. A., Neumann, T. A., Andrews, L. C., and Rumrill, J. A.: Links between acceleration, melting, and supraglacial lake drainage of the western Greenland Ice Sheet Journal of Geophysical Research, 116, F04035, doi: 10.1029/2010JF001934, 2011.
- Hooke, R. L.: Flow law for polycrystalline ice in glaciers' comparison of theoretical predictions, laboratory data, and field, Reviews of Geophysics, 19, 664-72, doi: 10.1029/RG019i004p00664, 1981.
- Iken, A, Echelmeyer, K, Harrions, W, and Funk, M: Mechanisms of fast flow in Jakobshavns Isbrre, West Greenland: Part I. Measurements of temperature and water level in deep boreholes, Journal of Glaciology, 39, 15-25, 1993.
- 30 Iverson, N. R., Cohen, D., Hooyer, T. S., Fischer, U. H., Jackson, M., Moore, P. L., Lappegard, G., and Kohler, J.: Effects of basal debris on glacier flow, Science, 301, 81-84, doi: 10.1126/science.1083086, 2003.
 - Joughin, I., Fahnestock, M., MacAyeal, D., Bamber, J. L., and Gogineni, P.: Observation and analysis of ice flow in the largest Greenland ice stream, Journal of Geophysical Research, 106, 34021-34, doi: 10.1029/2001JD900087, 2001.

- Kamb, B. and LaChapelle, E.: Direct observation of the mechanism of glacier sliding over bedrock, Journal of Glaciology, 5, 159-72, 1964.
- Kamb, B: Sliding motion of glaciers: theory and observation, Reviews of Geophysics, 8, 673-728, doi: 10.1029/RG008i004p00673, 1970.

- 5 King, E C: Flow dynamics of the Rutford Ice Stream ice-drainage basin, West Antarctica, from radar stratigraphy Annals of Glaciology, 50, 42-48, 2009.
 - Kleman, J, Stroeven, A P, and Lundqvist, J: Patterns of Quaternary ice sheet erosion and deposition in Fennoscandia and a theoretical framework for explanation Geomorphology, 97 73-90, doi:10.1016/j.geomorph.2007.02.049, 2008.
 - Krabbendam, M and Bradwell, T: Quaternary evolution of glaciated gneiss terrains: pre-glacial weathering vs. glacial erosion, Quaternary Science Reviews, 95, 20-42, doi: 10.1016/j.quascirev.2014.03.013, 2014.
 - Krabbendam, M, Eyles, N, Putkinen, N, Bradwell, T, and Arbeleaz-Moreno: Streamlined hard beds formed by palaeo-ice streams: A review, Sedimentary Geology, 338, 24-50, doi:10.1016/j.sedgeo.2015.12.007, 2016.
 - Lile, R. C.: The effect of anisotropy on the creep of polycrystalline ice, Journal of Glaciology, 21, 475-83, 1978.
 - Lliboutry, L.: Permeability, brine content and temperature of temperate ice, Journal of Glaciology, 10, 15-29, 1971.
- Lliboutry, L.: Internal melting and ice accretion at the bottom of temperate glaciers, Journal of Glaciology, 39, 50-64, 1993.
 - Lovell, H., Fleming, E. J., Benn, D. I., Hubbard, B., Lukas, S., Rea, B. R., Noormets, R., and Flink, A. E: Debris entrainment and landform genesis during tidewater glacier surges., Journal of Geophysical Research: Earth Surface, 120, 1574-95, doi: 10.1002/2015JF003509, 2015.
- Lüthi, M, Funk, M, Iken, A, Gogineni, S, and Truffer, M: Mechanisms of fast flow in Jakobshavn Isbrae, West Greenland:

 Part III. Measurements of ice deformation, temperature and cross-borehole conductivity in boreholes to the bedrock

 Journal of Glaciology, 48, 369-85, doi: 10.3189/172756502781831322, 2002.
 - Macayeal, D. R., Bindschadler, R. A., and Scambos, T. A.: Basal friction of ice stream E, West Antarctica, Journal of Glaciology, 41, 247-62, 1995.
 - Mader, H. M.: Observations of the water-vein system in polycrystalline ice, Journal of Glaciology, 38, 333-47, 1992.
- Margold, M., Stokes, C. R., and Clark, C. D: Ice streams in the Laurentide Ice Sheet: Identification, characteristics and comparison to modern ice sheets, Earth-Science Reviews, 143, 117-46, doi: 10.1016/j.earscirev.2015.01.011, 2015.
 - Marshall, H. P., Harper, J. T., Pfeffer, W. T., and Humphrey, N. F.: Depth-varying constitutive properties observed in an isothermal glacier., 29(23). Geophysical research letters, 29, 2146, doi:10.1029/2002GL015412, 2002.
 - Marshall, S J: Recent advances in understanding ice sheet dynamics., Earth and Planetary Science Letters, 240 191-204, doi:10.1016/j.epsl.2005.08.016, 2005.
 - McClay, K.R.: Pressure solution and Coble creep in rocks and minerals; a review, Journal of the Geological Society of London, 134, 57-70, doi: 10.1144/gsjgs.134.1.0057 1977.
 - Morgan, V. I.: High-temperature ice creep tests, Cold regions science and technology, 19, 295-300, doi:10.1016/0165-232X(91)90044-H 1991.

- Murray, T., Stuart, G. W., Miller, P. J., Woodward, J., Smith, A. M., Porter, P. R., and Jiskoot, H.: Glacier surge propagation by thermal evolution at the bed, Journal of Geophysical Research, 105(B6), 13491-507, doi: 10.1029/2000JB900066, 2000.
- Murray, T., Booth, A., and Rippin, D. M.: Water-content of glacier-ice: limitations on estimates from velocity analysis of surface ground-penetrating radar surveys, Journal of Environmental & Engineering Geophysics, 12, 87-99, doi: 10.2113/JEEG12.1.87, 2007.
- Nye, J. F.: Glacier sliding without cavitation in a linear viscous approximation., Proceedings of the Royal Society of London, A315, 381-403, doi: 10.1098/rspa.1970.0050 1970.
- Nye, J. F. and Frank, F. C: Hydrology of the intergranular veins in a temperate glacier, Symposium on the Hydrology of Glaciers, 95: International Association of Hydrological Sciences, 157-61, 1973.
- Parizek, B R and Alley, R B: Implications of increased Greenland surface melt under global-warming scenarios: ice-sheet simulations, Quaternary Science Reviews, 23, 1013-27, doi:10.1016/j.quascirev.2003.12.024, 2004.
- Paterson, WSB: Why ice-age ice is sometimes "soft" Cold Regions Science and Technology, 20, 75-98, doi:10.1016/0165-232X(91)90058-O 1991.
- 15 Paterson, W S B: The physics of glaciers, Pergamon, Oxford, 1994.

10

- Payne, A. and Dongelmans, P. W.: Self-organization in the thermomechanical flow of ice sheets, Journal of Geophysical Research, 102, 12219-33, doi: 10.1029/97JB00513, 1997.
- Peltier, R.W., Goldsby, D.L., Kohlstedt, D.L., and Tarasov, L: Ice-age ice-sheet rheology: constraints from the Last Glacial Maximum from of the Laurentide ice sheet., Annals of Glaciology, 30 163-76, doi: 10.3189/172756400781820859, 2000.
- Pharr, G. M. and Ashby, M. F.: On creep enhanced by a liquid phase, Acta Metallurgica, 31, 129-38, doi:10.1016/0001-6160(83)90072-X 1983.
- Phillips, T., Rajaram, H., and Steffen, K.: Cryo-hydrologic warming: A potential mechanism for rapid thermal response of ice sheets, Geophysical Research Letters, 37, L20503, doi: 10.1029/2010GL044397, 2010.
- 25 Poirier, J. P.: Creep of crystals: high-temperature deformation processes in metals, ceramics and minerals, Cambridge University Press, Cambridge, 1985.
 - Roberts, D H and Long, A J: Streamlined bedrock terrain and fast ice flow, Jakobshavns Isbrae, West Greenland; implications for ice stream and ice sheet dynamics, Boreas, 34 25-42, doi: 10.1111/j.1502-3885.2005.tb01002.x, 2005.
- Rutter, E. H.: Pressure solution in nature, theory and experiment, Journal of the Geological Society of London, 140, 725-40, doi: 10.1144/gsjgs.140.5.0725 1983.
 - Ryser, C., Lüthi, M. P., Andrews, L. C., Hoffman, M. J., Catania, G. A., Hawley, R. L., Neumann, T. A., and Kristensen, S. S.: Sustained high basal motion of the Greenland ice sheet revealed by borehole deformation, Journal of Glaciology, 60, 647-60, doi: 10.3189/2014JoG13J196, 2014.

- Schoof, C.: The effect of cavitation on glacier sliding., Proceedings of the Royal Society A: Mathematical, Physical and Engineering Science, 461, 609-27, doi: 10.1098/rspa.2004.1350, 2005.
- Shepherd, A., Hubbard, A., Nienow, P., King, M., McMillan, M., and Joughin, I.: Greenland ice sheet motion coupled with daily melting in late summer, Geophysical Research Letters, 36, L015001, doi: 10.1029/2008GL035758, 2009.
- 5 Smith, H T U: Giant glacial grooves in northwest Canada, American Journal of Science, 246, 503-14, doi: 10.2475/ais.246.8.503 1948.
 - Stokes, C R and Clark, C D: Geomorphological criteria for identifying Pleistocene ice streams Annals of Glaciology, 28 67-74, doi: 10.3189/172756499781821625, 1999.
 - Stokes, C R and Clark, C D:: Laurentide ice streaming on the Canadian Shield: A conflict with the soft-bedded ice stream paradigm?, Geology, 31, 347-50, doi: 10.1130/0091-7613(2003)031<0347:LISOTC>2.0.CO;2 2003.
 - Tedesco, M., Lüthje, M., Steffen, K., Steiner, N., Fettweis, X., Willis, I., Bayou, N., and Banwell, A.: Measurement and modeling of ablation of the bottom of supraglacial lakes in western Greenland, Geophysical Research Letters, 39, doi: 10.1029/2011GL049882, 2012.
 - Tison, J. L. and Hubbard, B.: Ice crystallographic evolution at a temperate glacier: Glacier de Tsanfleuron, Switzerland, Geological Society, London, Special Publications, 176, doi: 10.1144/GSL.SP.2000.176.01.03, 2000.
 - Vallon, M., Petit, J. R., and Fabre, B.: Study of an ice core to the bedrock in the accumulation zone of an alpine glacier, Journal of Glaciology, 17, 13-28, 1976.
 - Weertman, J: On the sliding of glaciers, Journal of Glaciology, 3, 33-38, 1957.

15

- Weertman, J. and Birchfield, G. E.: Stability of sheet water flow under a glacier, Journal of Glaciology, 29, 374-82, 1983.
- Wilson, C. J. L.: Deformation induced recrystallization of ice: the application of in situ experiments, in S.M. Schmid and M. Casey (eds.), Mineral and Rock Deformation: Laboratory Studies: The Paterson Volume: American Geophysical Union, 213-32., 1986.
 - Wilson, C. J. L., Zhang, Y., and Stüwe, K.: The effects of localized deformation on melting processes in ice, Cold Regions Science and Technology, 24, 177-89, doi:10.1016/0165-232X(95)00024-6, 1996.
- Winsborrow, M. C., Clark, C. D., and Stokes, C. R.: What controls the location of ice streams?, Earth-Science Reviews, 103, 45-59, doi:10.1016/j.earscirev.2010.07.003, 2010.
 - Zoet, L. K., Carpenter, B., Scuderi, M., Alley, R. B., Anandakrishnan, S., Marone, C., and Jackson, M.: The effects of entrained debris on the basal sliding stability of a glacier, Journal of Geophysical Research, 118, 656-66, doi:10.1002/jgrf.20052, 2013.

Figures




Figure 1. Basal heat production (left) caused by geothermal heat flux and frictional heating as a function of basal sliding velocity, for different values of friction coefficient μ and water pressure P_w as a percentage of overburden pressure. On the right hand side the rate of melt water production, assuming all heat is taken up by melting. Sliding velocities of Borehole D (adjacent to Jakobshavn Isbrae) after Lüthi et al. (2002); melt rate calculated on basis of thermal gradient – see text. Sliding velocities and basal melt production of Northeast Greenland Ice stream after Joughin et al. (2001) and Fahnestock et al. (2001). GULL, and FOXX show seasonal range of basal ice velocities deduced from borehole data near Swiss Camp, West Greenland (Ryser et al. 2014).




Figure 2. Constraints on the thermal growth of the temperate layer, see text. Schematic thermal gradient of Borehole D is indicated in red line (after Lüthi et al., 2002). CTB = cold-temperate boundary; Q_{geo} = geothermal heat flow; Q_{fr} = heat production by frictional heating.




Figure 3. Strain rate against temperature, for experiments performed at 100 kPa, replotted after Morgan (1991). X-axis: reciprocal of temperature; Y-axis: natural logarithm of strain rate. Points following the Arrhenius relation within the power law should appear on a straight line.




Figure 4. Schematic illustration of grain boundary melting under simple shear. Melting occurs at grain contacts under high stress (compressional deviatoric stress); regelation may occur at grain contacts under low stress (tensional deviatoric stress).

5 Liquid water moves along grain boundaries.




Figure 5. (a) Basic Weertman sliding model, illustrating components of pressure melting. Thermal gradient through bedrock obstacle indicated by red arrow; (b) Weertman sliding pressure melting with an elongate obstacle, all other parameters are the same; (c) Pressure melting, water and heat transport in a temperate basal layer with significant meltwater flow: a thermal equilibrium occurs everywhere by heat advection by flowing water except at the 'cool spot' of the stoss side. CTB = cold-temperate ice boundary. Schematic thermal gradient of Borehole D is indicated (after Lüthi et al., 2002).




Figure 6. Sliding velocity due to pressure melting and enhanced creep (logarithmic scale) as a function of height of obstacle (Weertman, 1957). Intersection represents the critical obstacle size. (W) = velocities following Weertman; (T) = velocities in temperate ice; KC = velocity and critical obstacle size of observations of Kamb and LaChapelle (1964).




Figure 7. Hypothetical half-ice-sheet (e.g., Dahl-Jensen 1989), with different thermal regimes, further explained in the text. CTB = cold-temperate boundary; K = thermal conductivity, in Wm⁻¹K⁻¹, $T_m = \text{melting temperature}$. Numbers correspond to different thermal regimes described in text.

Table 1

Constant	Symbol	Value
Density Ice	$ ho_{ice}$	910 kg m^{-3}
Thermal conductivity ice	K_{ice}	2.10 Wm ⁻¹ K ⁻¹
Thermal conductivity rock	K_r	$3.0~\text{Wm}^{-1}\text{K}^{-1}$
Heat of fusion ice	H_{ice}	$334\cdot10^3~J~kg^{\text{-}1}$
Pressure-melting constant	C	7.4 ·10 ⁻⁸ K Pa ⁻¹

Variable	Symbol	Unit
Overall shear stress near base	τ	Pa
Normal stress on stoss side (horizontal)	σ_{stoss}	Pa
Normal stress on base (vertical)	σ_v	Pa
Heat flow through obstacle	Q_{ob}	$W m^{-2}$
Heat production by frictional heating	Q_{fr}	$W m^{-2}$
Melt rate (by mass)	M_r	$kg s^{-1} m^{-2}$
Melt rate (by volume)	M_r	mm yr ⁻¹
Pure sliding velocity	V_{sl}	m s ⁻¹ or m yr ⁻¹
Velocity component by pressure melting	V_{pm}	m s ⁻¹ or m yr ⁻¹
Velocity component by enhanced creep	V_{cr}	m s ⁻¹ or m yr ⁻¹
Water flow across CTB	F_w	$kg s^{-1} m^{-2}$

Parameter	Symbol	Value
Ice thickness	h_{ice}	800 m
Surface slope	α	1°
Height obstacle (1)	h	1 m
Width obstacle (1)	w	1 m
Spacing obstacles (1)	λ	4m
Geothermal heat flow (2)	Q_{geo}	$0.05~\mathrm{W~m}^{-2}$

⁽¹⁾ same as Weertman (1957)

 Table 1. Constants, variables and parameters with chosen values.

⁽²⁾ typical range: $0.03 - 0.07 \text{ W m}^{-2} = 30 - 70 \text{ mW m}^{-2}$

Appendix

10

25

Frictional heating is in general given by:

(A1)
$$Q_{fr} = \mu \, \sigma_{nv} \, V_{sl} \qquad \text{in [W m}^{-2}]$$

At the base of an ice sheet this can be expressed as:

5 (A2)
$$Q_{fr} = \mu(Pi - Pw) V_{sl}$$
 in [W m⁻²]

Assuming all heat is taken up by melting ice, the melt rate is given by:

(A3)
$$M_{rm} = \frac{(Q_{geo} + Q_{fr})}{H_{ice}}$$
 in [kg s⁻¹ m⁻²]

Recalculated in mm yr⁻¹, the melt rate becomes:

(A4)
$$M_{rv} = \frac{1000}{\rho_{ice}} * 3.15 \cdot 10^7 \frac{(Q_{geo} + Q_{fr})}{H_{ice}}$$
 in [mm yr⁻¹]

To maintain a temperate layer below cold ice with a steep thermal gradient requires a heat flow through the cold-temperate boundary (CTB) of:

(A5)
$$Q_{CTB} = K_{ice}(dT/dz) \text{ in [W m}^{-2}]$$

where K_{ice} is the thermal conductivity of ice and dT/dz the thermal gradient just above the CTB. In the case of borehole D near Jakoshavn Isbrae, the thermal gradient is 0.05 °C m⁻¹ (Lüthi et al., 2002), requiring Q_{CTB} becomes 2.1 * 0.05 = 0.105 W m⁻², about twice the normal geothermal heat flow (compare with Fig. 3).

The transport of energy by water flow through the temperate layer Q_{LAT} that freezes above the CTB is given by:

(A6)
$$Q_{LAT} = F_w H_{ice} \text{ in [W m}^{-2}]$$

where F_w is the mass flux of water across the CTB (in kg m⁻² s⁻¹), and H_{ice} the heat of fusion of ice. A temperate layer will maintain its thickness if $Q_{LAT} = Q_{CTB}$, and will thicken if $Q_{LAT} > Q_{CTB}$. The required mass flux of water thus becomes:

(A7)
$$F_w = K_{ice} (dT/dz) / H_{ice} \text{ in [kg m}^{-2} \text{ s}^{-1}]$$

In the example of Borehole D, the required mass flux $F_{\rm w} = 6.6 \cdot 10^{-7} \, {\rm kg \ m^{-2} \, s^{-1}}$.

Expressed as a melt rate, using equation A4, $M_{rv} = 23$ mm yr⁻¹.

Pressure melting temperature is given by:

(A8)
$$\Delta T_m = -C\Delta P$$

The overall pressure is:

(A9)
$$P_{ice} = \rho_{ice}gh$$

30 With $h_{ice} = 800$ m, it follows that $P_{ice} = 7.13 \cdot 10^6$ Pa, so that $\Delta T_m = -0.52$ °C.

Shear stress is given by:

(A10)
$$\tau = \rho gh \sin \alpha$$

With surface slope $\alpha = 1^{\circ}$ and ice thickness $h_{ice} = 800$ m, the shear stress $\tau = 1.24 \cdot 10^{5}$ Pa or 124 kPa.

The concentration of horizontal normal stress acting onto a vertical stoss side is given by Weertman (1957):

(A11)
$$\sigma_{stoss} = \frac{1}{6} \tau \left(\frac{\lambda^2}{wh} \right)$$
 in [Pa]

Using the same parameters as Weertman (1957): h = 1 m, w = 1 m, $\lambda = 4 \text{ m}$ and the overall shear stress from equation (A10),

5 $\tau = 124$ kPa, it follows that: $\sigma_{stoss} = 330$ kPa.

The pressure melting point at the stoss side is given by:

(A12)
$$\Delta T_{stoss} = -C \sigma_{stoss}^n$$
 in [°C]

Taking the value of σ^n_{stoss} from Eq. (A4) it follows that: $\Delta T_{stoss} = -0.024$ °C. This is the pressure melting point depression below ambient T_m ; so that the $T_{stoss} = -0.544$ °C.

Heat flow through obstacle is given by Weertman (1957):

(A13)
$$Q_{ob} = K_r 2\Delta T_m/l$$
 in [W m⁻²]

For an obstacle 1 m long, and taking the value of ΔT_{stoss} from (A12), $Q_{ob} = 0.15$ W m⁻². For an obstacle 4 m long, but with all other parameters the same, the heat flow becomes: $Q_{ob} = 0.038$ W m⁻²