

**Anonymous Referee #2 (Authors' responses are in green italics)**

**Second review of “Inter-comparison of snow depth retrievals over Arctic sea ice from radar data acquired by Operation IceBridge ” by Kwok et al**

I appreciate the efforts of the author in responding to my earlier comments. I feel some of the replies are unsatisfactory and thus request some more clarification and also clear additions to the manuscript following these responses, before I believe this to be ready for publication.

My new reviewer comments are in red, in response to the response document copied below. I only included comments that required a second response by me.

*Main comments:*

*1. I think you need to discuss more the basin-scale differences between the products. I also think this should be moved further up the paper, as it is what motivates the whole exercise in my opinion, especially as you don't go into huge detail regarding the algorithm differences and echogram interface detection. It is also what most of the readers will be interested in seeing.*

*For example, I think the huge differences in the means across the products for the three ice classes should be its own figure near the start (although I also have issues with the use of age classes, see later main comment, so think this should be by region instead). There are differences of ~100% between some products in the earlier OIB years, while some products show strong regional trends and others don't. It's pretty crazy to me that this is not discussed more as a motivating factor to look more closely at the algorithms, and I feel these differences have been somewhat hidden later in the paper. The more detailed in-situ comparisons could then follow on to help understand why this is.*

We appreciate the broader geophysical perspective although this was not the path taken by the inter-comparison project. Initially, the project was more interested in the quality of different retrieval approaches when assessed with *in situ* snow depth because that allowed for more quantitative evaluations of the procedures at the highest spatial resolution available (i.e., small scale variability). The merits of the basin-scale comparisons were recognized only after the results of the spatial and inter-annual differences were produced. We noted in the text that the robustness and adaptation of the retrieval procedures to changes in radar data quality over the IceBridge Mission are important considerations, in addition to the footprint-scale comparisons, in producing a long-term record. We have added to the text to provide a better description of the evolution of the project (i.e., from the small scale to the large, rather than the motivation suggested above but we prefer to preserve the order of the discussion in the manuscript).

Can you indicate how you have done this please? I.e. what you added and where.

*In the last paragraph of the introduction in our revision, we provided a roadmap of the paper:*

*“...The comparisons with field measurements allow a detailed assessment of the retrievals locally, while the comparisons with climatology and analyzed snowfall provide a large-scale multi-year perspective of their year-to-year retrieval consistency and robustness to changes in radar parameters, and their relative agreements with basin-scale fields.”*

*We do not feel that it adds to the manuscript to describe the detailed evolution of the project.*

2. Any comments on how 'tuned' these data have been, especially to the other snow depth data included in this paper? I believe I'm right in thinking the different groups have all had access to these in-situ data and ERA-I snow depth fields (especially as the lead author has previously produced the ERA-I derived snow depth maps used in the inter- comparison) so is that one reason why some fits are better than others? I understand that tuning happens and is often needed, but I think we need to understand this more to really understand if the differences are due to the choice of algorithm or other factors. Also, I think comments should be made if the individual algorithms were also compared against any other in-situ datasets in their respective papers and how good those fits were. The fact all authors are involved should make this easier. The snow depth retrievals were contributed by different algorithm-developers. Thus, there was no control on the amount of 'tuning'. It was entirely up to the developers of the snow depth data sets. The level of maturity of the algorithms is different and depends on the amount of resources available to the developers. The aim of the work was not to select the best algorithm, but rather to provide results that would serve to inform the development of the next-generation retrieval algorithm.

OK, but as all the developers are part of this paper, it should be possible to provide some factual statements regarding this and to include a discussion in the manuscript regarding the issue. This is a crucial point in terms of reproducibility and understanding how/why better correlations with in-situ/reanalysis data were found, which I feel is still inadequately treated.

*We do not have a fixed set of parameters for each algorithm that one could control because the approaches are very different, and thus it is difficult to comment on the 'tuning' aspects that were undertaken by individual developers. The objective of this work was a broad assessment based on the differences in the localization of the air-snow and snow-ice interfaces without considering the details of the approaches (illustrated in Figure 6). We reiterate that there was NO control over parameters chosen and it was up to the developers on what was delivered for assessment. Yes, the conclusions are rather broad and it remains one of the challenges for the group to harmonize the different approaches. (see also response to next comment)*

3. As all the algorithm developers were part of the paper, I'm surprised a bigger comment was not made of what actually will happen next. Will one/multiple algorithms be scrapped or combined? Are there pros/cons of certain algorithms that will be adopted/used by the Operation IceBridge sea ice group? You do state in the paper that: "The aim of this paper is to examine these algorithms and to use the assessment results to inform the development of the next generation algorithm", but the path forward is unclear to me and I really hope we don't continue with multiple algorithms floating around that different groups/papers use for different reasons. The next step is to develop an improved algorithm, for producing an OIB product, by integrating the experience gained from this work.

It is still not clear to me that this paper has made a significant step towards this other than highlighting the (albeit important) differences between the current algorithms, but it doesn't seem like a more concrete statement will be forthcoming.

*With a group of investigators, because of individual preferences in algorithm development, moving forward involves first building consensus and agreement prior to taking the next steps.*

*We believe that this inter-comparison paper served these goals. The next step is to incorporate the merits of each algorithm in future developments. As mentioned above, it remains one of the challenges for the group to harmonize the different approaches and to provide an improved data product.*

*In the conclusion, we have added: " ... The next step is to harmonize the differences in the present approaches and to provide an improved snow depth product... "*

**5. Why were only these specific field campaigns chosen?**

These were the only field campaigns over fast ice, where we did not have to deal with spatial registration issues related to sea ice motion.

**Can you include this comment in the manuscript?**

*This statement was included in the first paragraph of Section 2.2 in our last revision:*

*"...Coordinated surveys of field measurements and OIB overflights occurred in two years (2012 and 2014) under the auspices of two different programs. Both were located on landfast ice to minimize to the variability introduced by the spatial mismatch of the airborne and ground-based measurements due to ice drift ..."*

**6. Why ERA-Interim for derived snowfall?**

We considered MERRA2 as well but the snowfall from MERRA2 is known to be biased (higher by ~30-40%) compared to climatology and ERA-Interim.

OK but there are other reanalyses available that might not have such a bias. Obviously some also don't provide snowfall which may be an issue? At least a comment on this would be useful (I don't expect you to add in any analysis on this at this stage).

*It is not the intent of this manuscript to provide an exhaustive assessment of all available reanalyses, suffice to say that ERA-Interim is one of the more broadly used reanalysis in climate work and compares reasonably with the modified climatology. We prefer not to comment directly on MERRA2 or some other reanalysis because we are not aware of any published work that addresses this topic of snowfall and snow depth.*

*The first paragraph of Section 2.3 has been modified to read: "Averaged retrievals (25 km × 25 km) from the five algorithms are compared with both snow depths from snowfall in ERA-Interim products and a modification of the W99 climatology. We elected to use the ERA-Interim products here because it is one of the more broadly used reanalysis in climate work and compares reasonably with the modified climatology (see Section 4). Below, the procedures for constructing these daily fields of basin-wide snow depths are described."*

**7. Why were the Wavelet retrievals not available? The Newman et al., (2014) paper shows that data were produced in 2012..? This seems odd.**

We used only those data sets that were available and provided by the algorithm developers at the time of this inter-comparison project. In the case of the Wavelet retrievals, the algorithm developers provided only retrievals from the flight over the Eureka field campaign.

This seems very unusual, although I don't expect you to change this at this stage.

*We had a specific timeframe/schedule for completion of the project and had to set a fixed delivery date for the developers so that the project could proceed. The investigators who were involved in the development of the Wavelet retrievals were not able to provide their dataset during the agreed upon date. We chose to include what was available at the time and that is why we have only a subset of this data set to show. It is unfortunate but it is not fair for the entire group to include the Wavelet retrievals, which to this date have not been delivered.*

*Figure 9 - Confused by the numbers in Figure 9a. There is a lot of information being crammed in and I struggled to understand what it all means.*

*- Why is this saturated at 15 cm? 15 cm was selected because the threshold of detectability of the a-s interface is ~10 cm.*

**So this should be 10 cm then.**

*No, the 15-55 cm range was chosen for best presentation of the datasets in hand. And, it is not just the lower bound physical limit of the retrievals.*

*Multiple figures - The Jet color scale introduces false boundaries, isn't good for people with colorblindness, and should thus not be used in my opinion! Very bad for comparing geospatial data by eye.*

It is somewhat difficult to control the quality of the figures in the pdf files generated by the publisher for review purposes. We have enlarged the tracks in Figure 9 so that they are easier to see. The quality in the final publication should be higher.

This is nothing to do with how the pdf is generated but the use of a bad color scale that makes it harder to interpret the figure data values, no matter how it's generated into the pdf. See e.g. here <https://www.climate-lab-book.ac.uk/2014/end-of-the-rainbow/> for a discussion.

*We take to heart the color-scale issue that the reviewer alluded to and will carefully consider our choice in future publications, but we elect to retain the colors used by our figures at this time.*

# Inter-comparison of snow depth retrievals over Arctic sea ice from radar data acquired by Operation IceBridge

Ron Kwok<sup>1\*</sup>, Nathan T. Kurtz<sup>2</sup>, Ludovic Brucker<sup>2</sup>, Alvaro Ivanoff<sup>3</sup>, Thomas Newman<sup>4</sup>, Sinead L. Farrell<sup>5,6</sup>, Joshua King<sup>7</sup>, Stephen Howell<sup>7</sup>, Melinda A. Webster<sup>2</sup>, John Paden<sup>8</sup>, Carl Leuschen<sup>8</sup>, Joseph A. MacGregor<sup>2</sup>, Jacqueline Richter-Menge<sup>9</sup>, Jeremy Harbeck<sup>3</sup>, Mark Tschudi<sup>10</sup>

<sup>1</sup>Jet Propulsion Laboratory, California Institute of Technology, Pasadena, California, USA

<sup>2</sup>Cryospheric Sciences Laboratory, NASA Goddard Space Flight Center, Greenbelt, Maryland, USA

<sup>3</sup>ADNET Systems Inc., Lanham, MD, USA

<sup>4</sup>University of Toronto, Toronto, Ontario, Canada

<sup>5</sup>Earth System Science Interdisciplinary Center, University of Maryland, College Park, Maryland, USA

<sup>6</sup>Laboratory for Satellite Altimetry, Satellite Oceanography and Climatology Division, NOAA Center for Weather and Climate Prediction, College Park, Maryland, USA

<sup>7</sup>Climate Research Division, Environment and Climate Change Canada, Toronto, Ontario, Canada

<sup>8</sup>Center for Remote Sensing of Ice Sheets, The University of Kansas, Lawrence, Kansas, USA

<sup>9</sup>University of Alaska Fairbanks, Fairbanks, Alaska, USA

<sup>10</sup>University of Colorado, Boulder, Colorado, USA

Correspondence to: Ron Kwok ([ron.kwok@jpl.nasa.gov](mailto:ron.kwok@jpl.nasa.gov))

**Abstract.** Since 2009, the ultra-wideband snow-radar on Operation IceBridge ([a NASA airborne mission to survey the polar ice covers](#)) has acquired data in annual campaigns conducted during the Arctic and Antarctic springs. Progressive improvements in radar hardware and data processing methodologies have led to improved data quality for subsequent retrieval of snow depth. Existing retrieval algorithms differ in the way the air-snow and snow-ice interfaces are detected and localized in the radar returns, and in how the system limitations are addressed (e.g., noise, resolution). In 2014, the Snow Thickness On Sea Ice Working Group (STOSIWG) was formed and tasked with investigating how radar data quality affect snow depth retrievals and how retrievals from the various algorithms differ. The goal is to understand the limitations of the estimates and to produce a well-documented, long-term record that can be used for understanding broader changes in the Arctic climate system. Here, we assess five retrieval algorithms by comparisons with field measurements from two ground-based campaigns, including the BRomine Ozone Mercury EXperiment (BROMEX) at Barrow, Alaska and a field program by Environment and Climate Change Canada (ECCC) at Eureka, Nunavut, available climatology and snowfall from ERA-Interim reanalysis. The aim is to examine available algorithms and to use the assessment results to inform the development of future approaches. We present results from these assessments and highlight key considerations for the production of a long-term, calibrated geophysical record of springtime snow thickness over Arctic sea ice.

## 1 Introduction

The snow layer atop Arctic sea ice modulates the thickness of the underlying ice cover (Maykut and Untersteiner, 1971). In winter, the insulating effects of snow regulate the surface heat balance and hence the rate of ice growth. In spring, the presence of snow shields the ice surface from solar radiation, delaying the onset of surface ice melt. During the melt 5 season, water from snowmelt pools into depressions to form melt ponds, which lower the surface albedo and further enhance the sea ice melt rate. This creates a strong positive feedback between the absorbed downwelling shortwave radiation and melt pond coverage on the ice surface (Kwok and Untersteiner, 2011). Further, available meltwater spreads over larger areas on smoother, seasonal ice compared to rougher, deformed ice (e.g., Fetterer and Untersteiner, 1998; Polashenski et al., 2012; Webster et al., 2015). When this meltwater drains through the ice cover and into the surface ocean (Polashenski et al., 2012), 10 it decreases the salinity and density structure of the ocean, thereby affecting stratification and mixing.

From a remote sensing perspective, estimates of snow loading are required for accurate retrievals of ice thickness from sea ice freeboard (Kwok, 2010). Current and planned satellite altimeters provide only sea ice freeboard (e.g., radar altimeters on CryoSat-2, AltiKa, Sentinel-3) or the combined snow and ice freeboard (lidars on ICESat, ICESat-2), with snow loading (depth and bulk density) left to be measured or modeled by other methods. However, routine measurements of snow depth 15 and density over the Arctic Ocean are not available. Hence, there is extensive interest in the climatology, seasonal and inter-annual variability, and spatial distribution of snow depth for ice thickness retrievals, climate analyses and modeling, and forecast of sea ice behavior.

Previous understanding of snow depth over Arctic sea ice has been derived from various field surveys (e.g., Sturm et al., 2002b; Sturm et al., 2006) and the climatology based on snow data from drifting stations that operated in 1937 and 1954- 20 1991 (Warren et al. (1999), henceforth, *W99*). The *W99* snow climatology is still widely used in ice thickness retrievals.

Because of the wide-ranging importance of snow depth, remote determination of snow depth at almost any spatial scale has long been desired. The sensor suite of Operation IceBridge (OIB) (Koenig et al., 2010) includes an ultra-wideband snow radar that allows estimates of snow depth by resolving the range location of the air-snow and snow-ice interfaces. Early examination shows that snow depth can be estimated to an uncertainty of about several centimeters, and that the mean snow 25 depth is broadly consistent with the *W99* climatology except over seasonal sea ice (e.g., Kurtz and Farrell, 2011; Kwok et al., 2011; Farrell et al., 2012). To date, OIB has acquired eight years (2009–2017) of radar data, including repeat surveys of the early spring snow and ice conditions in different parts of the western Arctic. These snow depth datasets from the OIB snow radar provide an unparalleled opportunity to examine snow depth across the Arctic Ocean and both its recent spatial and interannual variability.

30 Multiple algorithms now exist for the retrieval of snow depth, but they differ in how the air-snow and snow-ice interfaces are detected and localized in the radar returns, and in how the system limitations are addressed (e.g., noise, resolution). In 2014, a working group (STOSIWG) was formed and tasked with investigating how radar data quality affect snow depth retrievals and how retrievals from the various algorithms differ. In this paper, we report on the assessment of retrievals from five algorithms by comparisons of retrieved snow depths with each other, with measurements from two field

surveys, with modified climatology, and with snowfall from ERA-Interim products. The comparisons with field measurements allow a detailed assessment of the retrievals locally, while the comparisons with climatology and analyzed snowfall provide a large-scale multi-year perspective of their year-to-year retrieval consistency and robustness to changes in radar parameters, and their relative agreements with basin-scale fields. The aim of this paper is to examine these algorithms and to use the assessment results to inform the development of the next-generation algorithm. The paper is organized as follows. The next section summarizes the snow radar, the five retrieval algorithms, and the data sets against which we compare the snow radar data. The data sets include snow measurements from the two field campaigns, modified snow climatology, and snow depth estimates based on snowfall from ERA-Interim products. The retrieved snow depths are compared with the field surveys in Section 3, and with the modified climatology and ERA-Interim snowfall in Section 4.

10 The last section concludes the paper with our recommendations for future approaches.

Ronald Kwok 10/3/2017 2:51 PM  
Comment [1]: roadmap

## 2 Data Description

In this section, we describe: (1) the snow radar and the steps followed in producing the echograms from which the air-snow (a-s) and snow-ice (s-i) interfaces are identified; (2) the data from two field programs; (3) the construction of snow depth estimates from climatology and from snowfall; and, (4) the five retrieval algorithms.

15 2.1 Snow radar

In the spring of 2009, an early version of the snow radar was installed and flown on the NASA P-3B to survey Arctic sea and land ice from Alaska and Greenland. This version of the radar employed a fast-tuning, wideband voltage controlled oscillator (VCO) in a phase locked loop (PLL) configuration that used a FMCW chirp signal from a direct digital synthesizer (DDS) as a reference to produce a fast-sweeping, linear, and ultra-wideband chirp capable of collecting high-  
20 resolution sounding measurements from fixed wing aircraft (Panzer et al., 2013). The measurements collected during these initial surveys demonstrated a new capability to routinely measure snow depth over sea ice and annual snow layering over land ice. Since then, the system has been routinely deployed for both Arctic and Antarctic airborne campaigns as part of NASA OIB and to support the University of Kansas' Center for Remote Sensing of Ice Sheets (KU/CReSIS) and other  
25 collaborators' field programs (e.g., Patel et al., 2017; Yan et al., 2017). Below, we describe the system hardware and software processing algorithms used to generate the resulting data products and the changes that have been incorporated throughout the evolution of the system to what is used today.

### 2.1.1 Hardware

Since 2009, the snow radar hardware has been modified to improve system performance in terms of wider bandwidth, improved phase linearity at faster chirp rates, increased data acquisition rates and real-time hardware processing.  
30 Figure 1 shows the system block diagram, although specific values have changed throughout the various OIB deployments. The basic components include a digital system, microwave chirp generator, microwave transmitter and receiver, and intermediate frequency (IF) receiver. The digital system generates a 600-900 MHz reference chirp from the second Nyquist

band of a 1 Giga-sample/s DDS, which is then multiplied by a factor of 20 by the PLL to generate a 12 to 18 GHz Ku-band signal. The 12–18 GHz signal, which is typically used by the CReSIS Ku-band altimeter, is then down-converted using a mixer driven by a 10-GHz phase-locked oscillator to produce the system’s 2-8 GHz transmit waveform. A directional coupler is used to replicate the chirp for the receiver. The receiver filters, amplifies and mixes the received waveform with the replicated chirp to produce an IF signal. This IF signal consists of a collection of near-constant “beat” frequency components in which target delay is expressed by a simple relationship as the ratio of frequency by chirp rate. The spectral purity of each component is related to the frequency linearity of the 2-8 GHz chirp. Deviations from a linear frequency sweep result in reduced resolution and sidelobes. Finally, the sampled IF signal is coherently integrated or stacked 4 to 8 times.

#### 10 2.1.2 Processing

The raw data recorded by the snow radar is a stream of coherently integrated intermediate frequency (IF) signals time tagged with UTC time. In some datasets, an optional digital down converter (DDC) was used. The recorded data are post-processed using the following steps:

1. Locating IF Spectrum: The IF spectrum is found by taking the discrete Fourier transform of the raw data and mapping this result to time delay based on the Nyquist zone and DDC settings. The raw data are windowed to reduce range sidelobes. Additionally, any DDC induced modifications to coherent noise components must be compensated.
- 15 2. Coherent noise removal: There are several unwanted coherent components within the system resulting in noise signals that vary slowly with respect to time. These signals are estimated by analyzing the Doppler components of the data and then removed.
- 20 3. Platform attitude and position corrections: Precision GPS and IMU information is used to position the antennas along the flight track. Relative altitude variations of the antennas within the coherent averaging window are corrected so that the subsequent coherent averaging focuses the along-track beam pattern towards nadir
- 25 4. Windowing/Deconvolution: Phase and amplitude non-linearities of the system are estimated by analyzing data collected over specular returns produced by sea ice leads. A catalog of these responses are saved during a campaign and used to deconvolve non-linearities to produce low sidelobe waveforms. Figure 1 illustrates the effectiveness of the deconvolution process in suppressing sidelobes (noted in Kwok and Haas, 2015) for data collected during the 2012 OIB Arctic campaign.
5. Coherent/Incoherent Integration: Finally, additional coherent and incoherent integrations are used to improve signal-to-noise ratio (SNR), along-track resolution, and to reduce speckle.

## 2.2 Snow depth from field surveys

Coordinated surveys of field measurements and OIB overflights occurred in two years (2012 and 2014) under the auspices of two different programs. Both were located on landfast ice to minimize the variability introduced by the spatial mismatch of the airborne and ground-based measurements due to ice drift. A brief description of these field programs is provided below.

### 2.2.1 BROMEX 2012

In coordination with OIB, *in situ* snow data were collected as part of the 2012 BROMEX near Barrow, Alaska (Nghiem et al., 2013; Webster et al., 2014). Field measurements were conducted on smooth, first-year sea ice on Elson Lagoon, a location where landfast ice undergoes little deformation. Following the OIB pass on 15 March 2012, snow depths were measured every 1–5 m in a two-dimensional layout along two transects using a GPS-enabled Magna-probe units (Sturm and Holmgren, 1999); the probe has an accuracy of 0.3 cm over level sea ice and snow (Sturm et al., 2006). The first transect (used here) consisted of three lines ~1000 m in length, each 5 m apart, for a width of 10 m. Snow density was measured every ~100 m with a Federal Sampler (Marr, 1940); the average density was  $306 \pm 91 \text{ kg m}^{-3}$ . More information about the *in situ* data and field conditions is available in Webster et al. (2014).

### 15 2.2.2 Eureka 2014

During March and April of 2014 coordinated flight and a field-based campaigns (sponsored by ECCC) were carried out near Eureka, Nunavut, Canada to evaluate OIB estimates of snow depth on land-fast first-year ice (FYI). A predetermined set of 11 parallel OIB flight lines were executed within Eureka Sound, a large inlet separating Axel Heiberg and Ellesmere Islands, on 25 March 2014. A spacing of 12 m between OIB flight lines ensured strong coincidence between the narrow swath of the snow-radar and the point-based nature of the planned field measurements. Snow depths within the radar footprints were sampled after the overflights. An extended description of the 2014 Eureka study site and field campaign can be found in (King et al., 2015).

As part of the field campaign, a linear transect was established to characterize local-scale variations in snow depth and density in proximity to the OIB snow radar footprint. Between the dates of 26 March 2015 and 29 March 2015 a total of 37,320 snow depth measurements were made along the transect covering a distance of 46 km. Measurements of snow depth were made also with Magna-probe units (as above), spaced by approximately 2 m between samples. In addition to measurements in the along-track flight direction, orthogonal transects of up to 100 m were completed at random intervals to characterize variation in the radar across-track direction. Snow density was measured along the sampling transect at 174 locations with a coring device commonly referred to as the ESC-30 (Eastern Snow Conference 30 cm cross-section corer). Extracted cores were weighed *in situ* with a hanging scale to estimate bulk snow density and water equivalent.

The observed snow layer along the 2014 Eureka transect was shallow, with a mean snow depth of  $17.8 \pm 9.9 \text{ cm}$ . This general condition corresponded with spatially predominance of large undeformed FYI pans (62% of ice regions under flight

Ronald Kwok 10/3/2017 2:49 PM

Comment [2]: landfast ice

Ronald Kwok 10/3/2017 2:45 PM

Deleted: snow depth

Ronald Kwok 10/3/2017 2:45 PM

Deleted: ;

Ronald Kwok 10/3/2017 2:45 PM

Deleted: GPS-enabled Snow-Hydro Magnaprobe

Ronald Kwok 10/3/2017 2:45 PM

Deleted: (Sturm and Holmgren, 1999; Sturm et al., 2006),

of the Eureka mission). Here, smooth ice topography and sustained Arctic winds allowed rapid redistribution of snow accumulation and limited mean depths to  $16.0 \pm 8.3$  cm. Increased snow depth was associated with local regions of deformed ice where drifted accumulation was found in proximity to convergence features (i.e. rafting, rubble, and pressure ridging). Those areas described as deformed FYI in King et al. (2015) and were shown to have a higher mean depth of  $20.7 \pm 11.4$  cm.

5 Transect variations in density were conservative, with a mean of  $306 \text{ kg m}^{-3}$  and standard deviation of  $50 \text{ kg m}^{-3}$ , comparable to the assumed climatological mean of  $\sim 320 \text{ kg m}^{-3}$  near the end of the winter.

### 2.3 Snow depth from snowfall and climatology

Averaged retrievals ( $25 \text{ km} \times 25 \text{ km}$ ) from the five algorithms are compared with both snow depths from snowfall in ERA-Interim products and a modification of the W99 climatology. [We elected to use the ERA-Interim products here because it is one of the more broadly used reanalysis in climate work and compares reasonably with the modified climatology \(see Section 4\)](#). Below, the procedures for constructing these daily fields of basin-wide snow depths are described.

#### 2.3.1 Snow depth from ERA-Interim snowfall (ERAI-sf)

Fields of snow depth from ERA-Interim snowfall are constructed following Kwok and Cunningham (2008). Daily snowfall on ice parcels ( $100 \text{ km} \times 100 \text{ km}$ ) across the Arctic Ocean is recorded on a daily basis. Ice drift is from optimally interpolated motion fields (described in Kwok et al., 2013). A daily cycle of accumulation and ice advection is carried out for each Lagrangian parcel, which mimics the process of snow accumulation over sea ice in motion. Starting from August 15, the snowfall on each drifting parcel is recorded and accumulated through the end of spring. Surface conditions (air temperature and ice concentration) determine when and where snow is allowed to accumulate. Accumulation is permitted only when the ERA-Interim 2-m air temperature is below freezing and the AMSR-E ice concentration exceeds 50%. When 15 ice concentration drops below 50%, the accumulated snow is removed from that parcel. As ice concentrations rarely drop below 50% within the perennial ice pack, this condition is only relevant to the accumulation process over seasonal ice during the advance of the ice cover in the fall. Typically, the snow is thinner where the ice cover is formed later in the season (W99, Sturm et al., 2002a; Webster et al., 2014). The snow density climatology of Kwok and Cunningham (2008) (a modified version of that used in W99) is used to convert snow water equivalent into snow depth. No initial snow cover, representing 20 snow that survived the melt season, is added to the multiyear ice at the beginning of the accumulation season. Henceforth, we refer to snow depth from this procedure as *ERAII-sf* estimates.

#### 2.3.2 Snow depth from modified climatology (modW99)

In this paper, we compute snow depth ( $h_s$ ) from the climatology (W99) following Kwok and Cunningham (2015) as,

$$h_s(X, t, f_{FY}) = h_s^w(X, t)(1 - f_{FY}) + \alpha h_s^w(X, t)f_{FY} .$$

We use the annual space-varying snow depth and density,  $h_s^w(X,t)$ , from the snow climatology in W99. We note that this W99 climatology is from *in-situ* data collected between 1954 and 1991, and it is considered to be representative of snow depth over multiyear ice, so it does not address the snow depth over the seasonal ice cover of the Arctic Ocean. To account for reduced snow depth over FYI, we follow Laxon et al. (2013), who used a fraction ( $\alpha$ ) of the climatological snow depth 5 to represent the reduced snow accumulation over FYI identified by Kurtz and Farrell (2011). Here  $h_s$  is dependent on the fractional coverage of FYI ( $f_{FY}$ ), derived from ASCAT scatterometer data (following Kwok, 2004). The  $f_{FY}$  retrievals from ASCAT impart time-varying spatial patterns upon these otherwise static climatological fields. While Laxon et al. (2013) used a fixed value of  $\alpha=0.5$ , here we use  $\alpha=0.7$ , based on a subsequent analysis of CryoSat-2 ice thickness (Kwok and Cunningham (2015). Since the above construction represents a modification of the W99 climatology, we henceforth 10 refer to these snow depths as modW99 estimates.

#### 2.4 Retrieval algorithms

Five sets of retrievals from five separate algorithms are considered here. The first algorithm below produced the standard products (2009–2013) that is archived at and distributed by the National Snow and Ice Data Center (NSIDC). The remaining algorithms were developed by members of the Snow Thickness On Sea Ice Working Group (STOSIWG). Only 15 brief summaries of each algorithm are provided here, and the reader is referred to the published literature for details on each of the algorithms. These retrieval algorithms differ in the way the air-snow (a-s) and snow-ice (s-i) interfaces are detected and localized in the radar returns. Figure 2 shows the different range locations of the interfaces in a collection of radar returns from Eureka; these differences are discussed in Section 3.5.

We also note that the following analysis includes only retrieval results contributed by those who elected to participate 20 in STOSIWG at the time of this assessment, therefore it does not include all relevant algorithms (e.g., Holt et al., 2015). Table 2 shows the data sets that were available and used herein.

Ronald Kwok 10/3/2017 2:45 PM  
Deleted: so it

##### 2.4.1 Existing NSIDC product (NSIDC)

This algorithm was used for the Sea Ice Freeboard, Snow Depth, and Thickness data product that is archived at NSIDC with the following designation: IDSI4 (Kurtz et al., 2015). Details of the full algorithm methodology are described in 25 (Kurtz et al., 2013). Briefly, the algorithm is an empirical method that selects the a-s interface using a combined peak and threshold method. The a-s interface is taken to be either the first significant peak above a defined threshold or the first point when the rise in the radar return reaches a specified threshold if no peak is found. The method uses a linear scaling relation to the first version of the snow radar data collected in 2009 to select the thresholds used in the algorithm (as described in Kurtz and Farrell (2011)). The location of the s-i interface is defined as the maxima in the radar signal below the a-s 30 interface.

#### 2.4.2 GSFC-NK

The GSFC-NK algorithm was used for the processing of quick look IceBridge data in 2014–2016 ([https://nsidc.org/data/docs/daac/icebridge/evaluation\\_products/sea-ice-freeboard-snowdepth-thickness-quicklook-index.html](https://nsidc.org/data/docs/daac/icebridge/evaluation_products/sea-ice-freeboard-snowdepth-thickness-quicklook-index.html)). Full details of the algorithm methodology are described in the product documentation at NSIDC. The algorithm is a waveform fitting method that follows the algorithm used for CryoSat-2 surface height retrievals described by Kurtz et al. (2014). A modification to that algorithm accounts for the different instrument characteristics of the snow radar and accounts for coherent scattering of the return using a heterogeneous flat patch surface model (Brown, 1982). The algorithm fits a model waveform to the snow radar data using a bounded trust region method (Coleman and Li, 1996). Both the a-s and s-i interfaces are selected from the model fit results.

This algorithm is highly sensitive to parameters used in the fitting process, and these are selected to provide a balance between the processing time needed and the quality of the fit obtained. The most important of these parameters are the initial guess and model fit bounds for the a-s and s-i interfaces along with the maximum number of iterations used in the fitting process. The initial guesses for the interface locations are taken from the empirical algorithm of the existing NSIDC product, and the bounds for the possible interface locations are restricted to be within  $\pm 1.5$  ns of the initial guesses. The maximum number of fit iterations was set to 300. Due to the large processing time needed for the algorithm, it was run on every other point for this comparison. The model fit quality was determined by calculating the sum of the waveform power divided by the squared norm of the fit residual, and fits with a value less than 0.2 were discarded.

#### 2.4.3 SRLD

The Snow Radar Layer Detection (SRLD) algorithm was first developed for layer detection on land ice, in which the detection of the a-s interface and s-i interface are determined prior to the subsequent detection of deeper layers within the firn (Koenig et al., 2016). Over sea ice, only the a-s and s-i interfaces are returned by the algorithm. The initial application to existing OIB snow radar data from various campaigns (2009 - 2012) and the need for it to be applicable to future campaigns, required a process that would adapt to the data and not be dependent on fixed thresholds in the radar return signal. The SRLD method uses the gradient between the open-air return values and the maximum return value to locate the two interfaces. The a-s interface is taken to be where the presence of snow has caused the radar return level to be elevated above the open-air values, near the beginning of the gradient. The s-i interface is taken to occur where the transition from snow to ice has produced a maximum peak in radar return level, at the end of the gradient. The open-air value is first determined by taking a sample median of the values above the surface for the data frame being analyzed. The median of the peak values is used, along with the open-air value, to define the gradient to which a threshold is then applied for the determination of a-s interface. These gradient endpoints, comprised of the median air value and median peak value, adjust with the data from frame to frame. In the current implementation, the midpoint radar power level is used as the threshold. The point at which this radar power level maps onto each radar return profile determines the a-s interface, while the peak level in the return determines the s-i interface.

#### 2.4.4 Wavelet

The Wavelet algorithm, described by Newman et al. (2014), operates on each trace (column) of an echogram independently and has three components: interface detection through the use of the Haar Wavelet Continuous Wavelet Transform (Haar-CWT), topographic filtering using the  $h_{topo}$  parameter (to mitigate against heavily deformed ice topography on the radar point of closest approach), and the assignment of precision to each derived snow depth using radar system parameters.

The Haar-CWT is optimized for detecting abrupt transitions within a signal, such as those arising from interface returns, with the largest Haar-CWT coefficients localized at the largest magnitude signal transition. To detect the a-s and s-i interfaces, the echograms were preconditioned in different ways. To detect the a-s and s-i interfaces echograms are preconditioned in different ways. To detect the a-s interface the logarithm of the echogram results in the largest magnitude signal transition occurring at the a-s interface. To detect the s-i interface the echogram is left in its original form, wherein the largest magnitude signal transition occurs at the s-i interface. The Haar-CWT is then applied to each echogram trace and the resulting coefficients are summed over a range of different scales: from the broad localization of the interface at large wavelet scales to precise localization at small wavelet scales. The interface location is assigned to the location of the maximum of the summed coefficients. The benefits of this algorithm are that it is (1) robust and does not depend on a set of fixed thresholds and (2) the interface detection process is not affected by changes in transmitted power and receiver noise, which vary both during, and between, different OIB flight campaigns.

Interface picks associated with  $h_{topo}$  values greater than 50 cm are ignored as they are associated with heavily deformed ice topography, such as sea ice pressure ridges, where derived snow depths have been shown to be unreliable due to uncertainty in the radar scattering surface. Interface picks associated with  $h_{topo}$  values of less than 50 cm are deemed valid and converted to snow depth by considering two-way travel time in the snow pack and the permittivity of snow.

Derived snow depths are assigned a precision based upon concurrent snow radar system parameters. Snow depth precision is calculated for each derived snow depth independently with the final precision value the sum of terms relating to the SNR at the a-s interface, the signal-to-clutter ratio at the s-i interface, the fast-time range bin spacing, and the bandwidth-dependent range resolution of the snow radar.

#### 2.4.5 JPL

This is a simplified version of the algorithm by Kwok and Maksym (2014) that deals with residual system sidelobes in the returns. Since a re-processed version of the radar data set with suppressed system sidelobes is now available for all years except 2013, this aspect of the algorithm has been disabled.

In this algorithm, both the s-i and a-s interfaces are detected and localized by determining the significance of each local maximum above the noise floor in individual echo returns. Significance is determined by the strength and width of the local maxima (power) and its associated leading/trailing edges relative to the expected noise power of the system. The system bandwidth controls the width (or sharpness) of a local maximum and the rate of rise of its leading edge. The

algorithm uses these system-dependent parameters to adapt to the changes in the radar system as the bandwidth and noise level of the snow radar have progressively improved over the course of the OIB mission. The highest significant peak in the echo profile is designated as the return from the s-i interface. Returns from a-s interfaces are assumed to be weaker and is the first significant range return, determined using the above criteria, above the s-i interface. Once the interfaces are detected, the radar range ~~to~~ the interface is localized in an oversampled (by 16 times) version of the echo return; this reduces the range error in the identification of the local maxima in the echo return. From a scattering perspective, this restricts the detected returns to a-s interfaces that are more specular and appear as a detectable peak, rather than just ~~the strength of the~~ leading edge.

Ronald Kwok 10/3/2017 2:45 PM

**Deleted:** of

Ronald Kwok 10/3/2017 2:45 PM

**Deleted:** as a strong

### 3 Comparisons with field surveys

In this section, we first describe the comparison approach and the expected variability of the differences given the statistics of the retrievals and field measurements. Next, results from comparisons with measurements from BROMEX and Eureka are discussed. Lastly, we contrast the absolute range locations of the a-s and s-i interfaces from the different algorithms, which provides insights into the preferred location on the echo profile that each algorithm designates as an interface. To account for the reduced propagation speed of the radar wave in the snow layer, all radar measurements below were converted to snow depth assuming an end-of-winter bulk density of  $320 \text{ kg m}^{-3}$  (W99); snow depth estimates are relatively insensitive to uncertainties in bulk density (see error estimates in Kwok et al. (2011)).

#### 3.1 Comparison approach

The spatial correlation length-scales (at  $\rho=0.5$ ) of the point samples from both BROMEX and Eureka are short ( $\sim 5\text{--}7 \text{ m}$ ; Figure 3). Hence, it is essential to select an averaging length scale that is more compatible with the coarser resolution of the snow-radar retrievals ( $5\text{--}10 \text{ m}$ ). We select an averaging radius of  $20 \text{ m}$  to allow for and to reduce the sensitivity of the comparisons to uncertainties in the snow-radar footprint, and to accommodate for uncertainties in the spatial overlap between the snow-radar footprint and the point samples from the field measurements. The number of *in-situ* snow depth measurements in each averaged field sample for BROMEX and Eureka is  $21 \pm 5$  and  $15 \pm 4$ , respectively. And, a  $20\text{-m}$  radius represents an averaging of  $\sim 9$  radar spots along-track, assuming a nominal spacing of  $\sim 5 \text{ m}$ . The pre- and post-averaging spatial statistics of the field data are shown in Figure 3. For both datasets, the correlation length scale becomes broader ( $> 20 \text{ m}$ ) and variability is reduced. The resulting mean standard deviation (i.e., mean of the distribution of  $\sigma_f$ , see Figure 3) of the BROMEX data within a  $20\text{-m}$  circle reduced from  $6.1 \pm 1.5$  to  $2.2 \pm 1.2 \text{ cm}$ , and for the Eureka data from  $7.1 \pm 3.7$  to  $1.9 \pm 1.6 \text{ cm}$ .

To compare the averaged measurements (at a  $40\text{-m}$  spacing), we take the difference between the estimates of from the snow radar ( $d_{sr}$ ) and field ( $d_f$ ) as  $\Delta d = d_{sr} - d_f$ . Assuming that these two estimates are random variables that are uncorrelated and normally distributed, the variance of  $\Delta d$  is expected to be  $\sigma_{\Delta d}^2 = \sigma_{sr}^2 + \sigma_f^2$ . The contribution of  $\sigma_f$  is

expected to be bounded by the values in the distribution shown in Figure 2, and the contribution of  $\sigma_{sr}$  is discussed below.

With the bounds on the two expected variances,  $\sigma_{\Delta d}$  can be estimated for assessment of their differences.

### 3.2 Comparisons with snow depth from BROMEX

Figure 4 shows the comparison between four algorithms (NSIDC, GSFC-NK, SRLD, and JPL) with BROMEX field measurements. These results for the first transect are summarized in Table 4. The Wavelet retrievals were not available for this assessment. The OIB overflight of BROMEX covered a short distance of ~1000 m. Along this track, the field-measured snow depth (averaged) range between 15 and 30 cm. Except for the mean differences, it is apparent that the along-track variability in snow depth is reproduced reasonably well, as measured by the correlations between the radar and field estimates (0.45–0.67). Of note is the lower scatter and reduced sample size in the distributions of  $\sigma_{sr}$  for both the NSIDC and GSFC-NK retrievals prior to averaging (Figure 4). This pattern can be attributed to the fact that both these algorithms used averaged waveforms in their retrievals, rather than raw waveforms provided in the radar data, and thus the data have already been smoothed and subsampled before the retrieval process. The averaging of the SRLD and JPL retrievals, in contrast, reduced  $\sigma_{sr}$  by a factor of ~5. In any case, the standard deviation of the differences of ~3 – 4 cm (Figure 4) is approximately what one would expect when calculating ( $\sigma_{\Delta d}^2 = \sigma_{sr}^2 + \sigma_f^2$ ) using the values of  $\sigma_f$  in Figure 2a and values of  $\sigma_{sr}$  in Figure 4 (center panels). In these comparison, the mean differences vary between a maximum of -5 cm (GSFC-NK) and a minimum of +0.3 cm (NSIDC). These relative differences will be discussed in Section 3.5.

### 3.3 Comparisons with snow depth from Eureka

The comparisons with Eureka field measurements are shown in Figure 5 and the results are summarized in Table 3. This comparison includes many more samples from the multiple OIB tracks and more extensive sampling of the surface compared to the BROMEX survey. Averaged snow depth ranges from ~5 cm to more than 45 cm. This richer dataset tests the skill of five algorithms over a broad range of snow depths. Variability is between 0.29 and 0.72, as measured by the correlations between the radar and field estimates. The NSIDC and GSFC-NK algorithms have lower correlations, as their retrievals tend to underestimate snow depth; these two algorithms seem to be insensitive to snow depths that are more than ~20 cm in this case. The SRLD, Wavelet, and JPL retrievals have comparable correlations (0.66–0.72) with field data. Broadly, these algorithms tend to overestimate snow depths below ~10 cm, and with higher variability in retrievals over thicker snow (Figure 5). Except for the NSIDC retrievals, the standard deviation of the differences of ~4–5 cm is approximately as expected when calculated using the values of  $\sigma_f$  in Figure 2b and values of  $\sigma_{sr}$  ( $\sigma_{\Delta d}^2 = \sigma_{sr}^2 + \sigma_f^2$ ; not shown here). In these comparison, the mean differences vary between a maximum of -6 cm (GSFC-NK) and a minimum of -1 cm (NSIDC).

We also examined the impact of surface roughness on the quality of the retrievals from the different algorithms (Table 3). We define roughness as  $\sigma_f$ , as defined above and as the standard deviation of the snow depth of the field samples used in creating the spatial average. If samples with roughness  $> 10$  cm were not included in the comparisons, there is a consistent decrease in the standard deviation of the differences for all retrievals. This suggests that all the retrievals seem to be affected by surface roughness, consistent with the results reported by King et al. (2015). However, the correlation values did not increase for all algorithms (NSIDC: 0.29 to 0.34, GSFC-NK: 0.45 to 0.61, SRLD: 0.66 to 0.71, Wavelet: 0.72 to 0.67, JPL: 0.63 to 0.60).

### 3.4 Algorithm-dependent filtering strategies: BROMEX and Eureka

For both the BROMEX and Eureka comparisons, the different algorithms do not provide the same number of retrievals (Table 3) because of algorithm-dependent filtering strategies for removing low-quality estimates. More conservative strategies reduce the retrieval rate, which may bias these comparisons. We address this concern by examining the retrieval results for only those samples that are common to a pair of algorithms. Table 4 shows the results from all pairings of the five algorithms. Broadly, the changes in the comparison measures (i.e.,  $\rho$  and  $Diff$ ) did not change significantly for both BROMEX and Eureka. Compared to the diagonal element of the matrices in Table 4, the mean differences and standard deviations (relative to the field data) remain similar even when only the subset of common samples was used. Hence, we conclude that the statistics in Table 3 are fairly robust measures of the retrievals and relatively insensitive to the filtering strategies devised.

### 3.5 Different approaches to localize the air-snow and snow-ice interfaces

As observed earlier, the comparisons show that the biases (or mean differences) for individual algorithms are consistent (similar in magnitude) at both BROMEX and Eureka. For example, the mean differences of the SRLD and JPL retrievals are approximately +2 cm and -2 cm, respectively, at both field sites (see Table 3). Thus, on average, the SRLD snow depth retrievals are 4 cm higher than the JPL retrievals. These patterns suggest that systematic biases exist within individual algorithms due to their range determinations of the a-s and s-i interfaces in the echograms. In each retrieval algorithm, a particular characteristic of a leading edge (see Figure 3b) or return peak is typically used to determine the range point to be the location of an interface. In this case, the same characteristic has to be used consistently for both the a-s and s-i interfaces, otherwise the range distance between the two interfaces will be biased.

Here, we compare the range locations of the two interfaces selected by four of the five algorithms to assess the contribution of algorithm-induced biases seen in the observed mean differences at the Eureka site (Figure 6). The left panel (Figure 6) shows whether there are mean differences in the retrieved range distances (calculated from the range locations of the two identified interfaces) from two algorithms. We first discuss the comparison of the SRLD and JPL retrievals (Figure 6f) since this is the simplest case, where the range distance calculated by the SRLD algorithm is always greater than that obtained by JPL. Here both algorithms use the peak in a given echogram as the location of the s-i interface, so they have a narrow distribution of differences in the range location of that interface (~1 cm). Nearly all of their difference in retrieved

snow depth can be attributed to differences in the location of the a-s interfaces (Figure 6f). The SRLD algorithm locates the a-s interface on the leading edge, while the JPL algorithm located it at the local peak following the leading edge. Relative to the JPL a-s interfaces, the SRLD a-s interfaces are always displaced toward the radar, i.e., in the near range, therefore shorter range. Thus, the range distance to the JPL a-s interface is always higher. The same arguments apply to explaining some of systematic differences in the range location observed in the other comparisons shown in Figure 6. This pattern suggests that systematic choices made in the localization of the interfaces in each algorithm largely explain the consistent mean inter-algorithm differences (Table 3). The related question of where on the echo profile one should pick as the location of an interface will not be addressed here.

#### 4 Basin-scale assessments

We next assess the retrieved OIB snow depths from all Arctic campaigns at a longer averaging length-scale ( $> 10$  km). First, we summarize the overall retrievals from four algorithms available for this analysis (NSIDC, GSFC-NK, SRLD and JPL). Second, the consistency of retrievals at crossovers and repeat tracks (12.5 km) is examined. Last, we compare the averaged retrievals (at 25 km) with the fields of snow depth constructed from ERA-Interim snowfall (ERAI-sf) and modified climatology (modW99). These large-scale comparisons provide a broad assessment of the spatial and interannual variability of the snow radar retrievals, along with their relative agreement with the two reconstructed fields of snow depth.

##### 4.1 Summary of basin-scale snow depths: 2009-2015

Figure 7 shows seven years (2009–2015) of retrievals (25-km averages) from four algorithms NSIDC, GSFC-NK, SRLD, and JPL. These maps show the spatial differences in the retrievals from all the OIB flight tracks for a particular Arctic campaign. Figure 8 shows the associated snow depth distributions in three multiyear/seasonal ice regimes ( $MYf \geq 0.7$ ;  $0.3 < MYf < 0.7$ ;  $MYf \leq 0.3$ ), where  $MYf$  is the fraction of multiyear sea ice MYI) coverage within each 25-km sample. The calculated mean and standard deviation of the sample population of snow depth in each of the three categories are shown on the top left corner of each panel.

As seen in the spatial maps and distributions (Figures 7 and 8), the snow depth within the MYI cover north of Greenland and next to the Canadian Arctic Archipelago is highest in all the retrievals. In general, the average snow depth over the seasonal ice is thinner than those within the MYI cover. Of note is that the snow depth in the southern Beaufort Sea is always the thinnest, especially for those tracks between 2012 and 2015. The differences in retrievals from the four algorithms are examined in more detail in Section 4.3.

##### 4.2 Comparisons at crossovers and repeat tracks

Here we examine the consistency of the snow radar estimates (12.5 km averages) at available crossovers of the OIB flight tracks over the seven years of available data. Figure 9a shows the retrieval crossover differences (up to 164) and the time separation between them. When the time separations are short ( $< 10$  days), the differences are at the centimeter level and quite consistent (high correlation) for all algorithms. Even with the expected spatial variability, these differences remain stable over the seven years and thus indicate the general consistency of individual retrieval algorithms. Crossover

consistency also suggests a relatively long, isotropic spatial correlation length scale for snow depth. That is, at longer length scales snow depth varies slowly spatially and is likely due to synoptic scale patterns. As expected, when the time separation increases, so do the differences. At separations of more than twenty days, the differences are generally higher and positive, which seems consistent with the initial expectation that changes could be attributed to snowfall. However, differences are 5 also likely due to advection of ice parcels with thicker snow covers into the crossover point. As most of the crossovers are located in regions with fairly large spatial gradients in snow depth, attribution of the observed differences is difficult.

Figure 9b compares the snow depth at four available repeat tracks. These near-exact repeat tracks are of outbound and return segments flown during the same flight, so the time separations are typically less than a few hours. Except for ice drift, the snow radar should be acquiring data over similar snow and ice conditions. The difference distributions show that 10 the mean differences are at most ~2–3 cm. The sign and magnitude of the differences are consistent across all the retrievals and suggest that these are valid mean differences in the estimated snow depth. These comparisons also suggest that even though the algorithms produce self-consistent results, the mean snow depth can be quite different between the algorithms, as is evident in the difference in retrieved snow depths from the four algorithms (Figure 9b).

#### 4.3 Comparisons with snow depth from ERA-Interim snowfall (ERA1-sf) and modified climatology (modW99)

15 The snow depth estimates from ERA1-sf, modW99 and their differences along OIB flight tracks are shown in Figure 10a. The large-scale patterns are similar with thinner snow over seasonal ice and thicker snow in regions with higher MYf, especially north of Greenland and the Canadian Arctic Archipelago. Relative to the modW99 estimates, the ERA1-sf snow depths are broadly lower over the entire Arctic Ocean ice cover, except in 2012.

20 Figure 11 shows the relative inter-annual variability (IAV) of the mean snow depth of the two fields over seven years for the same three sea ice categories. As expected, the IAV of modW99 fields are lower than those from ERA1-sf, because the modW99 estimates are a static monthly climatology (W99) and are modulated by only the timing of the OIB flights and spatial variability of MYf derived from satellite data. The largest differences can be seen in the southern Beaufort Sea in 2014 and 2015, where ERA1-sf snow depths are lower than those from modW99. This difference can be largely attributed of 25 the presence of a tongue of MYI that advected into this region, which was used in the construction of the modW99 fields but is absent in the ERA1-sf fields (because the MYf is not used in the estimates). Away from the coastal zones and away from the transition zone between the MYI and seasonal ice cover, these differences are less pronounced.

Figure 11 also shows the IAV in the mean snow depth from the four algorithms. Three of the algorithms (NSIDC, GSFC-NK, and SRLD) have relatively large IAV compared to the two constructed fields. In the mean, the NSIDC snow depths are lower than the constructed fields. The large increase/decrease in the GSFC-NK retrievals in 2012/2013 is much larger than 30 the expected IAV of ~6 cm between March and April (W99). Over the seven years, the SRLD retrievals show significant snow depths trend in all three categories of MYI coverage, which seems unrealistic. The IAV of the JPL retrievals are more similar to those of the constructed fields.

Figures 12 through 15 show the spatial comparisons with the constructed fields. Variability in the differences between the retrievals and ERAI-sf and modW99 is expected. The mean snow depth from the snow radar represents the average of all age types within a track, whereas the ERAI-sf and modW99 estimates represent the accumulated snow depth since the beginning of the season with no consideration of wind-driven redistribution, loss into leads, or the introduction of seasonal ice of variable age (due to deformation of the ice cover). If any of those factors were significant for a given year, it would change the mean snow depth observed by the snow radar. Broadly, the IAV of the retrievals for the different ice categories in Figure 11 is consistent with the variability in the difference maps (Figures 12 through 15).

The contrast in IAV in retrievals from the four algorithms underscores the importance of multi-year assessments. The large IAV of retrievals from a given algorithm suggest issues in algorithmic robustness in adapting to changes in radar data quality. Since the snow radar has changed and improved over time (Table 1), the retrieval algorithms must adapt to changes in data quality. It is important to note that even though the retrievals may be internally consistent for a given algorithm, as suggested in Section 4.2, whether algorithms are sensitive to changes in radar data quality or radar hardware parameters depends on the specific characteristics of each algorithm.

## 5 Conclusions

In this study, we compared the retrievals from five different algorithms with each other and with snow depth measurements from two field surveys, modified climatology, and snow depths derived from ERA-Interim products. The inter-comparisons amongst different retrievals and comparisons with field measurements allow a detailed assessment of the retrievals, while the comparisons with climatology and analysed snowfall provide a broader multi-year perspective of their inter-annual retrieval consistency and robustness to changes in radar parameters, and their relative agreements with basin-scale fields. We reiterate that the aim of the work was not to select the best algorithm, but rather to provide results that would serve to inform the development of the next-generation retrieval algorithm. [The next step is to harmonize the differences in the present approaches and to provide an improved snow depth product](#). Below we highlight the salient points from the above inter-comparisons, and important considerations in the development and assessment of retrieval algorithms:

- When comparing snow-radar retrievals with point snow depth samples, it is essential to select an appropriate length scale such that the differences in the comparisons are not dominated by the geophysical variability. Hence, the fairly large number of point samples within a radar footprint is crucial in generating the averaged field dataset.
- Comparisons with BROMEX and Eureka field data show that, even though there are residual biases, the profile of along-track snow depth can be reproduced and the sensitivity of the snow radar to the a-s and s-i interfaces in the varied conditions at the two field sites can be evaluated.
- Retrieval algorithms differ in the way the a-s and s-i interfaces are detected and localized in the radar returns, and algorithm choices made in the localization of the interfaces by each algorithm mostly explain the consistent mean differences seen in the inter-comparisons and in the comparisons to field data. A related and important question regarding where on the echo profile one should pick as the location of an interface is not addressed here.

- Most of the retrievals were able to reproduce the expected spatial pattern of higher snow depth in MYI regions north of Greenland and near to the Canadian Arctic Archipelago, along with the thinner sea ice cover toward the Beaufort Sea to the southwest.
- The examination of retrievals at cross-overs and repeat tracks shows internal consistency of individual retrieval algorithms. These comparisons also suggest that, even though the algorithms may produce self-consistent results, the mean snow depth may be very different between algorithms, so this metric cannot be used as a measure of the overall performance of a retrieval approach
- Over the seven years, several algorithms have relatively large interannual variability that is higher than expected by climatology (W99). Large interannual variability of retrievals from a given algorithm suggests issues in algorithmic robustness in adapting to changes in radar data quality. The contrast in interannual variability in retrievals from the four algorithms underscores the importance of multi-year assessments, especially when the instrument performance has changed and improved, as is the case here. Of note is that the 2009 snow radar data has lower SNR, and the processed 2013 data had large, persistent sidelobes that affected the retrieval algorithms. To provide a long-term, consistent record of snow depth for understanding changes, algorithms with set thresholds may need to be tuned appropriately for the duration of the record. The new 2-18 GHz system flown this past spring (2017), with the associated large changes in bandwidth and SNR it is likely that the algorithm adaptations to these parameters will be significantly more important in the later years of OIB.

20 *Acknowledgments.* We thank S. S. Pang for her software support during the course of this work. RK carried out this work at the Jet Propulsion Laboratory, California Institute of Technology, under contract with the National Aeronautics and Space Administration. Development and testing of the Wavelet algorithm was supported by Office of Naval Research award N000141210512 and the NOAA Ocean Remote Sensing program.

## References

Brown, G. S.: A Theory for near-Normal Incidence Microwave-Scattering from 1st-Year Sea Ice, *Radio Sci.*, 17, 233-243, 1982.

5 Coleman, T. F. and Li, Y.: An Interior, Trust Region Approach for Nonlinear Minimization Subject to Bounds, *SIAM Journal on Optimization*, 6, 418-445, 1996.

Farrell, S. L., Kurtz, N., Connor, L. N., Elder, B., Leuschen, C., Markus, T., McAdoo, D., and Sonntag, J.: A First Assessment of IceBridge Snow and Ice Thickness Data Over Arctic Sea Ice, *IEEE Trans. on Geosci and Remote Sensing*, 50, 2098-2111, 2012.

10 Fetterer, F. and Untersteiner, N.: Observations of melt ponds on Arctic sea ice, *J. Geophys. Res.*, 103, 24821-24835, 1998.

Holt, B., Johnson, M. P., Perkovic-Martin, D., and Panzer, B.: Snow depth on Arctic sea ice derived from radar: In situ comparisons and time series analysis, *J. Geophys. Res.*, 120, 4260-4287, 2015.

King, J., Howell, S., Derksen, C., Rutter, N., Toose, P., Beckers, J. F., Haas, C., Kurtz, N., and Richter-Menge, J.: Evaluation of Operation IceBridge quick-look snow depth estimates on sea ice, *Geophys. Res. Lett.*, 42, 9302-9310, 2015.

15 Koenig, L. S., Ivanoff, A., Alexander, P. M., MacGregor, J. A., Fettweis, X., Panzer, B., Paden, J. D., Forster, R. R., Das, I., McConnell, J. R., Tedesco, M., Leuschen, C., and Gogineni, P.: Annual Greenland accumulation rates (2009-2012) from airborne snow radar, *Cryosphere*, 10, 1739-1752, 2016.

Koenig, L. S., Martin, S., Studinger, M., and Sonntag, J.: Polar Airborne Observations Fill Gap in Satellite Data, *Eos Trans. AGU*, 91, 2010.

20 Kurtz, N., Studinger, M., Harbeck, J. P., Onana, V. D., and Yi, D.: IceBridge L4 Sea Ice Freeboard, Snow Depth, and Thickness, Version 1, Boulder, Colorado USA., NASA National Snow and Ice Data Center Distributed Active Archive Center, doi: 10.5067/G519SHCKWQV6, 2015. 2015.

Kurtz, N. T. and Farrell, S. L.: Large-scale surveys of snow depth on Arctic sea ice from Operation IceBridge, *Geophys. Res. Lett.*, 38, n/a-n/a, 2011.

25 Kurtz, N. T., Farrell, S. L., Studinger, M., Galin, N., Harbeck, J. P., Lindsay, R., Onana, V. D., Panzer, B., and Sonntag, J. G.: Sea ice thickness, freeboard, and snow depth products from Operation IceBridge airborne data, *Cryosphere*, 7, 1035-1056, 2013.

Kurtz, N. T., Galin, N., and Studinger, M.: An improved CryoSat-2 sea ice freeboard retrieval algorithm through the use of waveform fitting, *Cryosphere*, 8, 1217-1237, 2014.

30 Kwok, R.: Annual cycles of multiyear sea ice coverage of the Arctic Ocean: 1999–2003, *J. Geophys. Res.*, 109, 2004.

Kwok, R.: Satellite remote sensing of sea-ice thickness and kinematics: a review, *J. Glaciol.*, 56, 2010.

Kwok, R. and Cunningham, G. F.: ICESat over Arctic sea ice: Estimation of snow depth and ice thickness, *J. Geophys. Res.*, 113, C08010, 2008.

35 Kwok, R. and Cunningham, G. F.: Variability of Arctic sea ice thickness and volume from CryoSat-2, *Phil. Trans. R. Soc. A*, 373, 2015.

Kwok, R. and Haas, C.: Effects of radar side-lobes on snow depth retrievals from Operation IceBridge, *J. Glaciol.*, 61, 576-584, 2015.

Kwok, R. and Maksym, T.: Snow depth of the Weddell and Bellingshausen sea ice covers from IceBridge surveys in 2010 and 2011: An examination, *J. Geophys. Res.*, 119, 4141-4167, 2014.

Kwok, R., Panzer, B., Leuschen, C., Pang, S., Markus, T., Holt, B., and Gogineni, S.: Airborne surveys of snow depth over Arctic sea ice, *J. Geophys. Res.*, 116, 2011.

Kwok, R., Spreen, G., and Pang, S.: Arctic sea ice circulation and drift speed: Decadal trends and ocean currents, *J. Geophys. Res.*, 118, 2408-2425, 2013.

5 Kwok, R. and Untersteiner, N.: The thinning of Arctic sea ice, *Physics Today*, 64, 36-41, 2011.

Laxon, S. W., Giles, K. A., Ridout, A. L., Wingham, D. J., Willatt, R., Cullen, R., Kwok, R., Schweiger, A., Zhang, J., Haas, C., Hendricks, S., Krishfield, R., Kurtz, N., Farrell, S., and Davidson, M.: CryoSat-2 estimates of Arctic sea ice thickness and volume, *Geophys. Res. Lett.*, 40, 732-737, 2013.

Marr, J. C.: Snow Surveying, U.S. Dept. of Agric., Technol. and Eng., Univ. of Vir., Charlottesville, Va., 1940. 9-11, 1940.

10 Maykut, G. A. and Untersteiner, N.: Some Results from a Time-Dependent Thermodynamic Model of Sea Ice, *J. Geophys. Res.*, 76, 1550-&, 1971.

Newman, T., Farrell, S. L., Richter-Menge, J., Connor, L. N., Kurtz, N. T., Elder, B. C., and McAdoo, D.: Assessment of radar-derived snow depth over Arctic sea ice, *J. Geophys. Res.*, 119, 8578-8602, 2014.

Nghiem, S. V., Clemente-Colón, P., Douglas, T., Moore, C., Obrist, D., Perovich, D. K., Pratt, K. A., Rigor, I. G., Simpson, W., Shepson, P. B., Steffen, A., and Woods, J.: Studying Bromine, Ozone, and Mercury Chemistry in the Arctic, *Eos, Transactions American Geophysical Union*, 94, 289-291, 2013.

Panzer, B., Gomez-Garcia, D., Leuschen, C., Paden, J., Rodriguez-Morales, F., Patel, A., Markus, T., Holt, B., and Gogineni, P.: An ultra-wideband, microwave radar for measuring snow thickness on sea ice and mapping near-surface internal layers in polar firn, *J. Glaciol.*, 59, 244-254, 2013.

20 Patel, A., Paden, J., Leuschen, C., Kwok, R., Gomez-Garcia, D., Panzer, B., Davidson, M. W. J., and Gogineni, S.: Fine-Resolution Radar Altimeter Measurements on Land and Sea Ice (vol 53, pg 2547, 2015), *IEEE Trans. Geosci. Remote Sens.*, 55, 1853-1853, 2017.

Polashenski, C., Perovich, D., and Courville, Z.: The mechanisms of sea ice melt pond formation and evolution, *J. Geophys. Res.*, 117, 2012.

25 Sturm, M. and Holmgren, J.: Self-recording snow depth probe. 871620, U. S. Army Corps of Engineers, Cold Regions Research and Engineering Laboratory, USA, 1999.

Sturm, M., Holmgren, J., and Perovich, D. K.: Winter snow cover on the sea ice of the Arctic Ocean at the Surface Heat Budget of the Arctic Ocean (SHEBA): Temporal evolution and spatial variability, *J. Geophys. Res.*, 107, 2002a.

30 Sturm, M., Holmgren, J., and Perovich, D. K.: Winter snow cover on the sea ice of the Arctic Ocean at the Surface Heat Budget of the Arctic Ocean (SHEBA): Temporal evolution and spatial variability, *J. Geophys. Res.*, 107, 2002b.

Sturm, M., Maslanik, J. A., Perovich, D. K., Stroeve, J. C., Richter-Menge, J., Markus, T., Holmgren, J., Heinrichs, J. F., and Tape, K.: Snow depth and ice thickness measurements from the Beaufort and Chukchi seas collected during the AMSR-Ice03 campaign, *IEEE Trans. Geosci. Remote Sens.*, 44, 3009-3020, 2006.

Warren, S. G., Rigor, I. G., Untersteiner, N., Radionov, V. F., Bryazgin, N. N., Aleksandrov, Y. I., and Colony, R.: Snow depth on Arctic sea ice, *J. Clim.*, 12, 1814-1829, 1999.

35 Webster, M. A., Rigor, I. G., Nghiem, S. V., Kurtz, N. T., Farrell, S. L., Perovich, D. K., and Sturm, M.: Interdecadal changes in snow depth on Arctic sea ice, *J. Geophys. Res.*, 119, 5395-5406, 2014.

Webster, M. A., Rigor, I. G., Perovich, D. K., Richter-Menge, J. A., Polashenski, C. M., and Light, B.: Seasonal evolution of melt ponds on Arctic sea ice, *J. Geophys. Res.*, 120, 5968-5982, 2015.

Yan, J. B., Alvestegui, D. G. G., McDaniel, J. W., Li, Y., Gogineni, S., Rodriguez-Morales, F., Brozena, J., and Leuschen, C. J.: Ultrawideband FMCW Radar for Airborne Measurements of Snow Over Sea Ice and Land, *IEEE Trans. Geosci. Remote Sens.*, 55, 834-843, 2017.

**Table 1**

Radar parameter used in Arctic surveys

Field Season	2009	2010–2011	2012–2015
Frequency Range (GHz)	2.5–7.0	2.0–6.5	2.0–8.0
Pulse Length (μs)	270	250	250
Transmit Power (mW)	10	20–100	100
IF Frequency Range (MHz)	29.2–58.32	31.25–62.50	62.50–125.00
Sampling Rate (Msamples/s)	58.32	62.5	125

5

10 **Table 2**

Availability of retrieval data sets during this study

	BROMEX	Eureka	Arctic campaigns (2009–2015)
NSIDC	✓	✓	✓2009–2013
GSFC-NK	✓	✓	✓2009–2015
SRLD	✓	✓	✓2009–2015
Wavelet		✓	
JPL	✓	✓	✓2009–2015

**Table 3**

5 Comparison of averaged radar snow depth with field measurements at BROMEX and Eureka. The additional comparisons at Eureka are for samples where the standard deviation of the field-measured snow depth within the averaging radius of 20 m is less than 10 cm.

(cm)	NSIDC	GSFC-NK	SRLD	Wavelet	JPL
BROMEX	$\rho$	0.54	0.44	0.66	0.67
	$N$	227	113	227	169
	$Diff$	0.3±4.17	-4.8±4.0	4.2±3.4	-1.8±3.4
Eureka	$\rho$	0.29	0.45	0.66	0.63
	$N$	4666	1746	4479	3042
	$Diff$	-0.8±11.2	-5.7±5.1	1.3±4.5	-2.2±4.6
$\sigma < 10$	$\rho$	0.34	0.61	0.71	0.60
	$N$	3998	1477	3905	2631
	$Diff$	-0.1±9.9	-4.5±2.4	1.8±3.6	-2.3±3.7

**Table 4**

Comparison of radar snow depth with field measurements at BROMEX and Eureka using retrievals at locations that are common to both algorithms. In the matrix presentation below, the snow depth retrieved by the row algorithm (at locations common with the column algorithm) are used in the comparisons with field data. Note that the matrix is not symmetric. Quantities in italics are from Table 3.

(Diff in cm)		NSIDC	GSFCNK	SRLD	Wavelet	JPL
<b>BROMEX</b>						
NSIDC	$\rho$	<i>0.54</i>	0.52	0.54		0.70
	$N$	<i>227</i>	113	227		169
	<i>Diff</i>	<i>0.3±4.2</i>	<i>0.5±4.2</i>	<i>0.3±4.2</i>		<i>0.8±3.0</i>
GSFC-NK	$\rho$	0.44	<i>0.44</i>	0.44		0.39
	$N$	113	<i>113</i>	113		80
	<i>Diff</i>	<i>-4.8±4.0</i>	<i>-4.8±4.0</i>	<i>-4.8±4.4</i>		<i>-4.9±4.5</i>
SRDL	$\rho$	0.67	0.75	<i>0.66</i>		0.68
	$N$	227	113	227		169
	<i>Diff</i>	<i>4.2±3.4</i>	<i>4.6±3.1</i>	<i>4.2±3.4</i>		<i>5.2±3.2</i>
JPL	$\rho$	0.67	0.60	0.67		0.67
	$N$	169	80	169		169
	<i>Diff</i>	<i>-1.8±3.4</i>	<i>-1.2±3.8</i>	<i>-1.8±3.4</i>		<i>-1.8±3.4</i>
<b>Eureka</b>						
NSIDC	$\rho$	<i>0.29</i>	0.45	0.29	0.25	0.28
	$N$	<i>4666</i>	1745	4448	3023	3059
	<i>Diff</i>	<i>-0.8±11.2</i>	<i>-2.2±5.3</i>	<i>-0.7±11.0</i>	<i>-0.3±12.6</i>	<i>-0.9±9.5</i>
GSFC-NK	$\rho$	0.44	<i>0.45</i>	0.48	0.50	0.46
	$N$	1745	<i>1746</i>	1699	1119	820
	<i>Diff</i>	<i>-5.7±5.1</i>	<i>-5.7±5.1</i>	<i>-5.5±4.7</i>	<i>-5.4±4.7</i>	<i>-5.0±4.2</i>
SRDL	$\rho$	0.66	0.64	<i>0.66</i>	0.69	0.59
	$N$	1112	1699	4479	2991	3003
	<i>Diff</i>	<i>1.4±4.4</i>	<i>1.5±4.8</i>	<i>1.3±4.5</i>	<i>1.5±4.3</i>	<i>1.8±4.1</i>
Wavelet	$\rho$	0.72	0.67	0.71	0.72	0.67
	$N$	3032	1119	2991	3042	2016
	<i>Diff</i>	<i>2.0±4.7</i>	<i>2.0±5.1</i>	<i>1.8±4.5</i>	<i>2.0±4.7</i>	<i>2.7±4.4</i>
JPL	$\rho$	0.63	0.58	0.61	0.57	0.63
	$N$	3059	820	3003	2016	3069
	<i>Diff</i>	<i>-2.2±4.6</i>	<i>-2.3±4.3</i>	<i>-2.4±4.4</i>	<i>-2.0±4.4</i>	<i>-2.2±4.6</i>

## Figure Captions

Figure 1. (a) Snow-radar hardware block diagram. Strength and location of sidelobes in the system impulse response (b) before and (c) after deconvolution of the radar data acquired during 2012 OIB Arctic campaign. Family of curves shows dependence on peak-signal-to-noise ratio ( $PSNR$  in dB) and is constructed using all the radar echos ( $\sim 4 \times 10^6$ ) from the campaign. Normalized returns are for every 1-dB increment of  $PSNR$  between 10 and 50 dB.

Figure 2. Location of the air-snow and snow-ice interfaces overlaid on power of return echoes. (a) Examples from four algorithms (black trace – air-snow interface; blue trace – snow/ice). (b) Except for the modeled GSFC-NK algorithm, the variability in the interface locations (e.g., leading edge, peak, etc.) depends on the algorithm.

10 Figure 3. Spatial correlation (left and center) and variability (right panel) of snow depth measurements from (a) BROMEX and (b) Eureka before (black lines) and after (green lines) averaging (diameter of 40 m). Gray bars show the number of measurements used in each correlation calculations.

15 Figure 4. Comparison of four algorithms with field measurements from BROMEX. (a) NSIDC (b) GSFC-NK. (c) SRLD. (d) JPL. (Left panel) Averaged field (black dots) and retrieved (red dots) snow depth with standard deviation at each sample (gray band). (Center) Standard deviation of retrieved snow depth before (black) and after (green) averaging – 40 m along track. (Right) Scatterplot shows correlation ( $R$ ) between the averaged snow depth samples, the number of samples, and the mean/standard deviation of the differences are shown on the top left corner of plot. Error bars show standard deviation of samples in 2-cm bins.

20 Figure 5. Comparison of five algorithms with field measurements from Eureka. (a) NSIDC. (b) GSFC-NK. (c) SRLD. (d) Wavelet. (e) JPL. Scatterplot shows correlation ( $R$ ) between the averaged snow depth samples, the number of samples, and the mean/standard deviation of the differences are show on the top left corner of plot. Error bars show standard deviation of samples in 2-cm bins.

25 Figure 6 Distribution of differences in range locations. (a) GSFC-NK minus Wavelet. (b) GSFC-NK minus JPL. (c) GSFC-NK minus SRLD. (d) Wavelet minus SRLD. (e) Wavelet minus JPL. (f) SRLD minus JPL. (Left panel) differences in the range between the two interfaces, (center panel) differences in range to the snow-ice (s-i) interface, and (right panel) differences in range to the air-snow (a-s) interface.

30 Figure 7. Seven years (2009-2015) of retrieved snow depths from four algorithms. (a) NSIDC. (b) GSFC-NK. (c) SRLD. (d) JPL. Snow depths (top left corner) are averages based on three categories of multiyear-ice fractions (MYf) shown in legend. Background shows multiyear sea ice fraction (dark gray:  $MYf \geq 0.7$ ; light gray:  $0.3 < MYf < 0.7$ ; white:  $MYf \leq 0.3$ ). Corresponding snow depth distributions are shown in Figure 8. The gray shadings represent regions with  $>0.7$  (darker) and  $>0.9$  (lighter) MYf. Repeat tracks are not shown here.

Figure 8. Snow depth distributions in seven years (2009-2015) of retrievals (a) NSIDC. (b) GSFC-NK. (c) SRLD. (d) JPL. Quantities on top right corners are mean, standard deviation, of the sample populations in three multiyear/seasonal ice regimes ( $MYf \geq 0.7$ ;  $0.3 < MYf < 0.7$ ;  $MYf \leq 0.3$ ).

Ronald Kwok 10/3/2017 2:45 PM  
Deleted:  $w$  is the half-width of the mainlobe.

Figure 9. Differences of snow depth retrievals at cross-overs and repeat tracks. (a) Cross-overs with varying time separation. Mean/standard deviation of differences and correlation coefficients (R) are shown on each plot. (b) Repeat tracks: 2 April 2010, 5 April 2010, 17 March 2011, and 22 March 2012. Inset shows the distribution of differences and quantities show mean/standard deviation of differences, correlation, and sample population. Each sample represents the mean snow depth in a 4-km along track segment. (Note: On 21 April 2009, the snow radar was operated with an altitude difference of  $\sim 300$  m in the outbound and return tracks.).

Figure 10. Comparison of snow depth from ERAI-sf and modW99 climatology at the snow radar tracks. (a) ERAI-sf; (b) modW99; and, (c) Difference between (a) and (b). The mean and standard deviation in each of the three categories of MYf are shown on the top left corner of each panel.

10 Figure 11. Comparison of snow depth retrievals from four algorithms (NSIDC, GSFC-NK, SRLD, JPL) with ERAI-sf and modW99 estimates in three multiyear/seasonal ice regimes ( $MYf \geq 0.7$ ;  $0.3 < MYf < 0.7$ ;  $MYf \leq 0.3$ ).

Figure 12. Comparison of NSIDC snow depth retrievals with ERAI-sf and the modW99.

Figure 13. Comparison of GSFC-NK snow depth retrievals with ERA-I snowfall and modW99.

Figure 14. Comparison of SRLD snow depth retrievals with ERA-I snowfall and modW99.

15 Figure 15. Comparison of JPL snow depth retrievals with ERA-I snowfall and modW99.







Figure 1. (a) Snow-radar hardware block diagram. Strength and location of sidelobes in the system impulse response (b) before and (c) after deconvolution of the radar data acquired during 2012 OIB Arctic campaign. Family of curves shows dependence on peak-signal-to-noise ratio ( $PSNR$  in dB) and is constructed using all the radar echos ( $\sim 4 \times 10^6$ ) from the campaign. Normalized returns are for every 1-dB increment of  $PSNR$  between 10 and 50 dB.

Ronald Kwok 10/3/2017 2:45 PM


**Deleted:**  $w$  is the half-width of the mainlobe.




**Figure 2. Location of the air-snow and snow-ice interfaces overlaid on power of return echoes.** (a) Examples from four algorithms (black trace – air-snow interface; blue trace – snow/ice). (b) Except for the modeled GSFC-NK algorithm, the variability in the interface locations (e.g., leading edge, peak, etc.) depends on the algorithm.



**Figure 3.** Spatial correlation (left and center) and variability (right panel) of snow depth measurements from (a) BROMEX and (b) Eureka before (black lines) and after (green lines) averaging (diameter of 40 m). Gray bars show the number of measurements used in each correlation calculations.



**Figure 4. Comparison of four algorithms with field measurements from BROMEX. (a) NSIDC. (b) GSFC-NK. (c) SRLD. (d) JPL. (Left panel) Averaged field (black dots) and retrieved (red dots) snow depth with standard deviation at each sample (gray band). (Center) Standard deviation of retrieved snow depth before (black) and after (green) averaging – 40 m along track. (Right) Scatterplot shows correlation (R) between the averaged snow depth samples, the number of samples, and the mean/standard deviation of the differences are shown on the top left corner of plot. Error bars show standard deviation of samples in 2-cm bins.**



**Figure 5. Comparison of five algorithms with field measurements from Eureka. (a) NSIDC. (b) GSFC-NK. (c) SRLD. (d) WAVELET. (e) JPL.** Scatterplot shows correlation (R) between the averaged snow depth samples, the number of samples, and the mean/standard deviation of the differences are show on the top left corner of plot. Error bars show standard deviation of samples in 2-cm bins.




Figure 6 Distributions of differences in range locations. (a) GSFC-NK minus Wavelet. (b) GSFC-NK minus JPL. (c) GSFC-NK minus SRLD. (d) Wavelet minus SRLD. (e) Wavelet minus JPL. (f) SRLD minus JPL. (Left panel) differences in the range between the two interfaces, (center panel) differences in range to the snow-ice (SI) interface, and (right panel) differences in range to the air-snow (AS) interface.




Figure 7. Seven years (2009-2015) of retrieved snow depths from the four algorithms. (a) NSIDC, (b) GSFC-NK, (c) SRLD, (d) JPL. Snow depths (top left corner) are averages based on three categories of multiyear-ice fractions (MYf) shown in legend. Background shows multiyear sea ice fraction (dark gray:  $\text{MYf} \geq 0.7$ ; light gray:  $0.3 < \text{MYf} < 0.7$ ; white:  $\text{MYf} \leq 0.3$ ). Corresponding snow depth distributions are shown in Figure 8. The gray shadings represent regions with  $>0.7$  (darker) and  $>0.9$  (lighter) MYf. Repeat tracks are not shown here.





Figure 8. Snow depth distributions in seven years (2009-2015) of retrievals (a) NSIDC. (b) GSFC-NK. (c) SRLD. (d) JPL. Quantities on top right corners are mean, standard deviation, of the sample populations in three multiyear/seasonal ice regimes ( $\text{MYf} \geq 0.7$ ;  $0.3 < \text{MYf} \leq 0.7$ ;  $\text{MYf} \leq 0.3$ ).



**Figure 9. Differences of snow depth retrievals at cross-overs and repeat tracks. (a) Cross-overs with varying time separation. Mean/standard deviation of differences and correlation coefficients (R) are shown on each plot. (b) Repeat tracks: 2 April 2010, 5 April 2010, 17 March 2011, and 22 March 2012. Inset shows the distribution of differences and quantities show mean/standard deviation of differences, correlation, and sample population. Each sample represents the mean snow depth in a 4-km along track segment. (Note: On 21 April 2009, the snow radar was operated with an altitude difference of ~300 m in the outbound and return tracks.).**




Figure 10. Comparison of snow depth from ERAI-sf and modW99 climatology at the snow radar tracks. (a) ERAI-sf; (b) modW99; and, (c) Difference between (a) and (b). The mean and standard deviation in each of the three categories of MYf are shown on the top left corner of each panel.




Figure 11. Comparison of snow depth retrievals from four algorithms (NSIDC, GSFC-NK, SRLD, JPL) with ERAI-sf and modW99 estimates in three multiyear/seasonal ice regimes ( $\text{MYf} \geq 0.7$ ;  $0.3 < \text{MYf} < 0.7$ ;  $\text{MYf} \leq 0.3$ ).




Figure 12. Comparison of NSIDC snow depth retrievals with ERAI-sf and modW99.




Figure 13. Comparison of GSFC-NK snow depth retrievals with ERAI-sf and modW99.




Figure 14. Comparison of SRLD snow depth retrievals with ERAI-sf and modW99.




Figure 15. Comparison of JPL snow depth retrievals with ERAI-sf and modW99.