Application of a two-step approach for mapping ice thickness to various glacier types on Svalbard

Johannes Jakob Fürst¹, Fabien Gillet-Chaulet², Toby J. Benham³, Julian A. Dowdeswell³, Mariusz Grabiec⁴, Francisco Navarro⁵, Rickard Pettersson⁶, Geir Moholdt⁷, Christopher Nuth⁸, Björn Sass¹, Kjetil Aas⁸, Xavier Fettweis⁹, Charlotte Lang⁹, Thorsten Seehaus¹, and Matthias Braun¹ ¹Institute of Geography, University of Erlangen-Nuremberg, Wetterkreuz 15, 91058 Erlangen, Germany ²University of Grenoble Alpes, CNRS, IRD, Institut des Géosciences de l'Environnement (IGE), CS 40 700, Grenoble, France ³Scott Polar Research Institute, University of Cambridge, Lensfield Road, Cambridge CB2 1ER, United Kingdom ⁴Faculty of Earth Sciences, University of Silesia in Katowice, ul. Bankowa 12, 40-007 Katowice, Poland ⁵Departamento de Matemática Aplicada a las Tecnologías de la Información y las Comunicaciones, desp. A302-4, ETSI de Telecomunicación. Universidad Politécnica de Madrid, Av. Complutense 30, 28040 Madrid, Spain ⁶Department of Earth Sciences, Uppsala University, Geocentrum, Villav. 16, 752 36 Uppsala, Sweden ⁷Norwegian Polar Institute, Fram Centre, Postbox 6606 Langnes, 9296 Tromsø, Norway ⁸Department of Geosciences, University of Oslo, Postboks 1047, Blindern, 0316 Oslo, Norway ⁹Department of Geography, University of Liège, Quartier Village 4, Clos mercator 3, 4000 Liège, Belgium

Correspondence to: Johannes Fürst (johannes.fuerst@fau.de)

Abstract. The basal topography is largely unknown beneath most glaciers and ice caps and many attempts have been made to estimate a thickness field from other more accessible information at the surface. Here, we present a two-step reconstruction approach for ice thickness that solves mass conservation over single or several connected drainage basins. The approach is applied to a variety of test geometries with abundant thickness measurements including marine- and land-terminating glaciers

- 5 as well as a 2400km² ice cap on Svalbard. Input requirements are kept to a minimum for the first step. In this step, a geometrically controlled, non-local flux solution is converted into thickness values relying on the shallow ice approximation. In a second step, the thickness reconstruction is improved along fast-flowing glacier trunks on the basis of velocity observations. Both steps account for available thickness measurements. Each thickness field is presented together with an error-estimate map based on a formal propagation of input uncertainties. These error estimates point out that the thickness field is least constrained
- 10 near ice divides or in other stagnant areas. Withholding a share of the thickness measurements, error estimates tend to overestimate mismatch values in a median sense. We also have to accept an aggregate uncertainty of at least 25% in the reconstructed thickness field for glaciers with very sparse or no observations. For Vestfonna, a previous ice volume estimate based on the same measurement record as used here has to be corrected upward by 22%. We also find that a 13% area fraction of the ice cap is in fact grounded below sea-level. The former 5% estimate from the direct measurement interpolation exceeds the maximum
- 15 range of 6 23% as inferred from the map of thickness error-estimates.

1 Introduction

For the 210'000 glaciers and ice caps on this planet (Bishop et al., 2004), satellite remote sensing based on optical or radar instruments enables us to monitor glacier surface geometry (e.g. Farr et al., 2007; Tachikawa et al., 2011) and glacier extent variations (e.g. Raup et al., 2007; Rankl et al., 2014). Recent studies have shown that surface elevation changes can be produced

- 5 on a regional basis (e.g. Berthier et al., 2010; Zwally et al., 2011; Gardelle et al., 2013; Paul et al., 2015; Zwally et al., 2015; Rankl and Braun, 2016; Vijay and Braun, 2016). However, for the majority of these ice geometries, there is no information on ice thickness (Gärtner-Roer et al., 2014, 2016). Any attempt to predict the glacier demise under climatic warming and estimate the future contribution to sea-level rise (Radić and Hock, 2011; Radić et al., 2014; Marzeion et al., 2012, 2014; Huss and Hock, 2015) is limited as long as the glacier thickness is not well known. Moreover, the ignorance of the bed topography inhibits
- 10 the applicability of ice-flow models, which could help to understand dominant processes controlling the ice-front evolution of marine-terminating glaciers. This is because the basal topography exerts a major control on the dynamic response of grounded ice (Schoof, 2007, 2010; Favier et al., 2014). A reason for further concern is that grounded parts of the Antarctic Ice Sheet are assumed to respond to climatic warming primarily by outlet glacier acceleration as the floating ice-shelves thin (Paolo et al., 2015) and loose their buttressing ability (Fürst et al., 2016). As it is impractical to measure ice thickness for most
- 15 glaciers, reconstruction approaches have been proposed that can infer thickness fields from available geometric, climatic and ice-velocity information.

In terms of input requirements, reconstruction approaches always need information on the geometric setting. This normally comprises the glacier outline and the surface topography. In the "Ice Thickness Models Intercomparison eXperiment" (ITMIX; Farinotti et al., 2016), two types of reconstruction approaches rely exclusively on this geometric information. The first type

- 20 assumes perfect plasticity, relating ice thickness to a glacier-specific yield stress, which itself is inferred from the elevation range of the glacier (Linsbauer et al., 2012; Frey et al., 2014; Carrivick et al., 2016). The second type assumes that characteristics of the ice-covered bed topography resemble the nearby ice-free landscape (Clarke et al., 2009). Under this premise, an artificial neural network is trained with digital elevation models (DEM) of the surrounding area. Another reconstruction approach (Gantayat et al., 2014) uses additional information on surface velocities and relies on the shallow ice approxima-
- 25 tion (SIA; Hutter, 1983; Morland, 1986). Under this assumption, surface velocities directly translate into ice-thickness values dependent on glacier-surface slopes. Most of the participating approaches rely, however, on mass conservation. This implies that they need information on the difference between the actual surface mass balance (SMB) and the contemporaneous surface elevation changes. This difference is referred to as the "apparent mass balance" (AMB; Farinotti et al., 2009b). A large subset of the mass-conserving approaches assume a generic AMB informed by the geographic location and the continental character
- 30 of the prevailing climate (Farinotti et al., 2009a; Huss and Farinotti, 2012; Clarke et al., 2013). In addition, these approaches rely on the SIA and require an input ice-discharge value for marine-terminating glaciers. As standard procedure, many of the above approaches dissect glacier outlines into a number of centrelines along which the actual reconstruction is performed. Consequently, these approaches are computationally efficient but they require a final interpolation of the thickness values between these centrelines. To avoid such an interpolation, other mass-conservation approaches determine a solution over entire

glacier basins (Morlighem et al., 2011; McNabb et al., 2012; Brinkerhoff et al., 2016) at the expense of computational costs. Two strategies are pursued for these reconstruction types. For the one type, ice-flow models are applied in a pseudo-transient way such that the actual surface elevation remains close to observations optimising the bed topography (van Pelt et al., 2013). For the other type, ice velocities are taken from observations and enter the mass conservation equation, which is then directly solved for ice thickness (Morlighem et al., 2011; McNabb et al., 2012; Mosbeux et al., 2016).

5

From an observational perspective, operational and regular satellite imagery acquisition has become an indispensable and continuously growing source of information. Therefore, automated procedures have been brought in place providing products such as glacier outlines (Bishop et al., 2004; Atwood et al., 2010; Nuth et al., 2013; Rankl et al., 2014; Paul et al., 2015), digital elevation models (ArcticDEM; ASTER GDEM2, Tachikawa et al. (2011); SRTM, Farr et al. (2007), TanDEM-X, Rankl

- and Braun (2016)) and surface velocities (Joughin et al., 2010; Rignot et al., 2011; Rignot and Mouginot, 2012; Rankl et al., 10 2014; Rosenau et al., 2015; Seehaus et al., 2015; Fahnestock et al., 2016; Seehaus et al., 2016). Surface elevation changes can be inferred from DEM differencing. Much development effort is put into reducing uncertainties associated with signal penetration and not well known firn properties (e.g. Gardelle et al., 2012; Berthier et al., 2016). Depending on the mission, surface elevation changes can be generated almost operationally for large areas (Gardelle et al., 2013; Rankl and Braun, 2016).
- Concerning surface velocities from remote sensing, a good coverage is challenging in areas where displacements are small, 15 where the glacier surface is featureless or during periods of rapid changes in surface characteristics. Moreover, associated uncertainties generally exceed 10 m yr⁻¹ (Seehaus et al., 2015; Schwaizer, 2016, e.g.), which limits the reliability in slow moving areas. The SMB field is another prerequisite for mass conservation. It is not directly measurable by remote sensing techniques. Sparse SMB records can be used to determine elevation gradients that are then extrapolated according to a regional
- DEM (Farinotti et al., 2009b). Otherwise, SMB records are exploited to validate parametric SMB approaches (Möller et al., 20 2016) or more physically-based regional climate models (Lang et al., 2015; Aas et al., 2016). For ice-thickness measurements, a standardised, open-access database has recently been launched (Gärtner-Roer et al., 2014) and its gradual growth already justified an updated release (Gärtner-Roer et al., 2016). Despite this international effort, many thickness measurements still remain unpublished.
- 25 In light of this continuously growing body of information, input fields for relatively complex thickness-reconstruction approaches are becoming more available. In this regard, we present a two-step approach that provides, in the first step, a physically based thickness field over entire glacier basins, ice fields or ice caps with few input requirements (Sect. 2.2). In the second step, velocity information is exploited to update and improve the thickness reconstruction in specific areas (Sect. 2.3). A final interpolation of the basal topography is not required. For a set of three test geometries on Svalbard, the necessary input data
- 30 were gathered (Sect. 3) and thickness maps are inferred (Sect. 4). A rich thickness record is available on these test glaciers and serves to constrain both the ice-thickness distribution and the associated map of error estimates.

2 Methods

The thickness reconstruction approach is based on mass conservation and largely originates from ideas presented in Morlighem et al. (2011). We opted for a two-step approach because surface velocity information from satellite remote sensing often fails to cover entire drainage basin. Therefore, the first-step, glacier-wide thickness reconstruction can optionally be updated in areas

5 where velocity measurements are available. In the first step, an ice flux is calculated from the difference between SMB and surface elevation changes. The flux solution is translated into thickness values assuming the SIA (Hutter, 1983). In the second step, the mass conservation equation is directly solved for ice thickness in a sub-domain with reliable velocity information.

2.1 Mass conservation

Over the ice covered domain Ω , the material incompressibility can be written as follows (p. 333 in Cuffey and Paterson, 2010). 10

$$\frac{\partial H}{\partial t} + \boldsymbol{\nabla} \cdot (\boldsymbol{u}H) = \dot{b}_{\rm s} + \dot{b}_{\rm b} \,. \tag{1}$$

Here, ∇ is the divergence operator in two dimensions, H is the ice thickness, $u = (u_1, u_2)$ are the vertically-averaged, horizontal velocity components and $\partial H/\partial t$ are temporal surface elevation changes. Surface and basal mass balance are denoted with \dot{b}_s , \dot{b}_b , respectively. The flux divergence $\nabla \cdot F = \nabla \cdot uH$ is a-priori unknown and we rearrange accordingly.

$$15 \quad \nabla \cdot F = \dot{a}. \tag{2}$$

All source and sink terms are combined in the 'apparent mass balance' (AMB) field $\dot{a} = \dot{b}_s + \dot{b}_b - \partial H/\partial t$. Throughout this manuscript, we assume that the basal mass balance \dot{b}_b is negligible.

2.2 First step: Flux-based solution

In a first step, the mass conservation (Eq. 2) is solved for the ice flux F (Sect. 2.2.2) while prescribing the flux direction
(Sect. 2.2.1). The flux solution is translated into a glacier-wide thickness field relying on the SIA (Sect. 2.2.4). In a last step, the error associated with the thickness reconstruction is estimated (Sect. 2.2.5).

2.2.1 Flux direction

With prior knowledge only on \dot{a} , the single mass conservation equation is insufficient to determine the two unknown flux components. To close the system, ice flux is separated into its magnitude F and its direction vector r.

$$25 \quad F = F \cdot r. \tag{3}$$

The direction is specified following Brinkerhoff and Johnson (2015) as the solution to

$$\boldsymbol{\tau}_s = \boldsymbol{\nabla} \left[(l \cdot H)^2 \nabla \cdot \boldsymbol{\tau}_s \right] + \boldsymbol{\tau}_d \tag{4}$$

Here, τ_s is a smoothed version of the driving stress $\tau_d = (\rho g) \cdot H \cdot \nabla h$. Other parameters needing specification include the ice density $\rho = 917 \text{ kg m}^{-3}$, the gravitational acceleration $g = 9.18 \text{ m s}^{-2}$ and the surface elevation h. The flux direction vector \mathbf{r} is computed by normalising τ_s . Along the lateral glacier margin Γ , the following boundary condition is set:

$$(\boldsymbol{\nabla}\cdot\boldsymbol{\tau}_s)\cdot\boldsymbol{n}_{\Gamma}=0. \tag{5}$$

- 5 Here, n_{Γ} is perpendicular to Γ. The solution to Eq. (4) is equivalent to an averaging of the driving stress using a variable length scale (lH). This scaling stems from theoretical work on the influence of longitudinal stress gradients on glacier flow (Kamb and Echelmeyer, 1986). These stress gradients are comparable to membrane stresses in thin body mechanics (Hindmarsh, 2006). Membrane stresses can instantly transmit perturbations upglacier but this transmission was shown to be a secondary factor in terms of centennial ice-sheet volume evolution (Fürst et al., 2013). The associated scaling length is usually
- 10 expressed as a multiple l of the ice thickness H. For l = 10, we find that resultant flux streamlines are inappropriately averaged over adjacent branches of a single valley glacier. For l = 1 however, the routing remained locally defined. We therefore decided to prescribe l = 3, in agreement with the suggestion by Kamb and Echelmeyer (1986), who expected coupling lengths for valley glaciers between l = 1 and l = 3.

By construction, the ice thickness is a priori unknown and so is the coupling length scale (*lH*). Therefore, we initially
15 assume *H* = 100 m to compute a first flux direction field *r*. Then, a first estimate is available for the thickness field and flux directions are updated accordingly. Thereafter, directions are kept fixed during the optimisation (Sect. 2.2.3). The reasons for fixing the direction are to limit the degrees of freedom during the optimisation and because the first-step thickness field already captures the general magnitude of the observations giving a reasonable (*lH*)-field.

2.2.2 Flux magnitude

- 20 To determine the flux magnitude *F* according to Eqs. (2) and (3), we use the Elmer finite-element software developed at the Center for Science in Finland (CSC-IT, http://www.csc.fi/elmer/) and more specifically the mass conservation solver implemented in its glaciological extension Elmer/Ice (Gagliardini and Zwinger, 2008; Gillet-Chaulet et al., 2012; Gagliardini et al., 2013). For the discretisation of the problem, we select the stabilised streamline upwind Petrov-Galerkin (SUPG) scheme (Brooks and Hughes, 1982). Along all land-terminating segments of the glacier outline, we impose a zero-flux condition. A free
- 25 boundary condition is chosen across marine ice fronts, providing an ice-discharge estimate consistent with the AMB. Inflow boundaries did not occur in our setup. These would require Dirichlet conditions on the ice flux.

2.2.3 Cost function and single-variate optimisation

The direct flux solution to all input fields often shows wide-spread negative values and high spatial variability. Therefore, we chose to iteratively update the AMB-field \dot{a} , as control variable, such that undesired characteristics in the flux field are reduced. We anticipate that the flux magnitude E is positive and smooth. For the purpose of the iterative optimization, we introduce the

30 We anticipate that the flux magnitude F is positive and smooth. For the purpose of the iterative optimisation, we introduce the

following cost function J.

$$J = \lambda_{\text{pos}} \cdot \int_{\Omega} F^2 \cdot \mathbf{H}[-F] \, d\Omega + \lambda_{\text{reg}} \cdot \int_{\Omega} \left(\frac{\partial F}{\partial x}\right)^2 + \left(\frac{\partial F}{\partial y}\right)^2 d\Omega + \lambda_{\dot{a}} \cdot \int_{\Omega} \left(\dot{a} - \dot{a}^{\text{init}}\right)^2 d\Omega \tag{6}$$

Here, H[s] is the Heaviside function, being zero for negative and one for positive $s \in \mathbb{R}$. The first term is thus zero for positive flux values but penalises negative flux solutions. The second term is a regularisation, which favours smooth flux solutions. The last term adds up differences between the iteratively updated \dot{a} and the initial input \dot{a}^{init} . The cost J should primarily be 5 considered as a function of \dot{a} . As the AMB is iteratively updated, the cost should decrease. Multipliers values are $\lambda_{pos} = 10^2$, $\lambda_{\text{reg}} = 10^1$ and $\lambda_{\dot{a}} = 10^{-2}$. For WSB, we chose $\lambda_{\text{reg}} = 10^0$ to compensate for resolution differences. The multiplier choice aimed at a balance between improving the smoothness of the flux field and reducing areas with negative flux values by adapting λ_{pos} and λ_{reg} . The solution showed not much sensitivity to changes in $\lambda_{\dot{a}}$.

10

For the optimisation of the cost function, we rely on the "m1qn3" module (Gilbert and Lemaréchal, 1989) that can solve large-scale unconstrained minimisation problems. It requires first derivatives of the cost with respect to the single control variables \dot{a} . For a precise calculation of these derivatives, we rely on the adjoint system associated with Eq. (2). The stopping criterion for the iterative optimisation is non-dimensional at 10^{-14} and computed as a ratio between the current and the initial norm of the cost derivatives.

15 2.2.4 Inferring ice thickness

Once a flux field is determined over the glacier domain, the ice thickness is inferred in a post-processing step. Flux values are locally translated into thickness values assuming the SIA (Hutter, 1983).

$$F^{\star} = \frac{2}{n+2} B^{-n} \left(\rho g\right)^{n} \left\| \boldsymbol{\nabla} h \right\|^{n} \cdot H^{n+2}$$
(7)

Here, the flow law exponent is n = 3 and the superscript * denotes a flux correction (see below and Appendix C3). Note that in this way, the first-step reconstruction neglects effects from basal sliding, which limits its applicability to areas of slow ice 20 flow. The SIA is typically applied to geometries with small aspect ratios (vertical vs. horizontal scales), which is not necessarily the case for our test geometries. Accounting for the influence of membrane stresses on ice flow, we correct the local surface slope magnitude $\|\nabla h\|$ informed by the smoothed driving stress τ_s (Eq. 4), assuming $\|\nabla t\| = (\rho g)H \cdot \|\nabla h\|$. In areas near the ice divide, surface slopes can locally become very small and thickness values diverge. Therefore, we decided to impose a slope threshold $\alpha_0 = 1^\circ$ as a lower limit on ∇h . The chosen threshold is small as compared to other reconstruction approaches. For 25 a similar reconstruction approach, combining mass conservation with the SIA along glacier flowlines, Farinotti et al. (2009b)

- apply a 5° limit. Assuming perfect plasticity to infer glacier thickness in Patagonia, Carrivick et al. (2016) set a lower limit of 1.7°. Even though our choice for α_0 is somewhat lower, the limit is still applied over a 17% area fraction of the ice-cap test geometry. For the 1.7 and 5° limits, this area fraction increases to 46% and 94%, respectively.
- 30 The ice-viscosity parameter B is a-priori unknown. Yet, where thickness measurements are available, B can be computed from Eq. (7). Thereafter, the scattered information on B is interpolated over the entire glacier domain. To avoid unreliable

extrapolation effects, we prescribe a mean B value from all measurements around the lateral domain margin. If no thickness measurements were available, an a-priori choice of the viscosity parameter B is required.

We apply a correction to the computed flux before computing the ice thickness from Eq. (7). Details of this flux correction and the sensitivity of the results are given in Appendix C3. The reason is that despite the cost term on negative ice flux
5 (Sect. 2.2.3), negative values prevail in limited areas, which transmit into the thickness field. When the input à shows only few source areas with net accumulation, ice flux remains small and negative values were found over as much as 5% of the only land-terminating test glacier. Zero transitions in the flux solution directly transmit into the ice thickness field. To prevent such spurious variations, we correct the flux solution according to Eq. (C1), which guarantees positive values. In areas of more pronounced ice flux, where the correction is a priori not necessary, its effect is inherently compensated by adapting the

10 viscosity parameter B where thickness measurements were collected. If no thickness measurements are available, inferred thickness values are reduced by at most 2% for pronounced ice flow.

2.2.5 Formal error estimate

Together with the thickness map, we present a formal error map. For this purpose, the uncertainty on the input fields, i.e. the SMB and $\partial H/\partial t$, are propagated in two steps. Uncertainties are first transmitted through the mass conservation equation

15 (Eq. 2) and the resulting estimate of the flux error is then scaled by a SIA flux-thickness conversion (Eq. 7). For the first step, we follow the ideas presented in Morlighem et al. (2014), who assume that the inaccurate flux field $F + \delta F$ also satisfies mass conservation.

$$\boldsymbol{\nabla}[(F+\delta F)\cdot(\boldsymbol{n}+\delta\boldsymbol{n})] = \dot{\boldsymbol{a}}+\delta\dot{\boldsymbol{a}}$$
(8)

Here, $\delta \dot{a}$ is the uncertainty of the AMB and δn is the error on the prescribed flux direction. Neglecting second order terms and accounting for the fact that *F* satisfies Eq. (2), the flux error is a solution of:

$$\boldsymbol{\nabla}[\boldsymbol{n}\delta F_1] = \|\delta \dot{\boldsymbol{a}} - \boldsymbol{\nabla}[F\delta \boldsymbol{n}]\| \tag{9}$$

Along the land-terminating domain margin, we assume zero flux and the thickness error estimate implicitly becomes zero. At the thickness measurement locations, we assume that the ice flux is known with a precision that is equivalent to the uncertainty in the thickness measurements δH_{obs} . The thickness-measurement uncertainty is translated into a flux-equivalent value using Eq. (7) without the flux correction, thus $F^* = F$. The solution to Eq. (9) shows a sawtooth pattern along the ice flow, as error estimates increase downglacier until another measurement is reached. There the value drops to a small magnitude and starts again to increase. We however expect that measurements also constrain the ice thickness upglacier. Therefore, we assume that the uncertainty can also decrease at a certain rate along the flow. This generic decrease rate is not known but we assume the same magnitude as for the above error increase rate in Eq. (9).

30
$$\nabla[(n)\delta F_2] = (-1.0) \cdot \|\delta \dot{a} + \nabla[F\delta n]\|$$
 (10)

This equation requires appropriate upstream boundary conditions, such that the error reaches δH_{obs} at the next observation downglacier. Yet this is impractical and we rather restate the problem as an upstream error increase well constrained at the

measurements.

5

$$\boldsymbol{\nabla}[(-\boldsymbol{n})\,\delta F_2] = \qquad \|\delta \dot{\boldsymbol{a}} + \boldsymbol{\nabla}[F\delta\boldsymbol{n}]\| \tag{11}$$

The two problems Eqs. (9) and (11) are structurally identical to Eq. (1) and thus numerically solved as described in Sect. 2.2. The two formal error estimates δF_1 , δF_2 subsequently enter a linear error propagation within the SIA thickness-flux relation (Eq.7). This yields:

$$\delta H_i = \frac{1}{n+2} \left[-\frac{2}{n+2} B^{-1/n} (\rho g)^n \left\| \boldsymbol{\nabla} h \right\|^n \right]^{-1/(n+2)} \cdot \left\| F \right\|^{-(n+1)/(n+2)} \cdot \left\| \delta F_i \right\| \qquad i \in \{1,2\}$$
(12)

In this way, the error analysis is limited by the assumptions inherited from the SIA. Uncertainties in B, ρ, q and ∇h are not accounted for. The final thickness error estimate δH is the minimum of δH_1 and δH_2 .

- Input uncertainties for the test geometries are presented in Sect. 3.9. These uncertainties are chosen constant which is 10 problematic in terms of the control variable a. This variable changes during the optimisation and all uncertainties of other input fields and underlying assumptions of the reconstruction approach are placed into a. Yet, it is not evident how to iteratively update the uncertainty associated with the control parameter and we accept some limitations here. The importance of this assumption can be assessed from a comparison of the initial and the final AMB field (Appendix B). Apart from this limitation, the error analysis accounts for uncertainties in the observational record but does not comprise the error that stems from time-
- averaging of the input and temporal inconsistencies between different fields. A detailed assessment and treatment of various 15 input errors within a Bayesian framework is presented in Brinkerhoff et al. (2016).

2.3 Second step: Velocity-based solution

In a second step, the ice thickness map is updated in areas where reliable surface velocity information is available by solving Eq. (1) directly for the ice thickness. Equation (1) is vertically integrated and the surface velocity information needs to be converted into a vertical mean value. Within the scope of this methodological study, we apply this second step exclusively 20 where velocity magnitudes exceed $100 \,\mathrm{m yr^{-1}}$ (details of the sub-domain delineation in Sect. 2.4). In these sub-domains, basal sliding is assumed to dominate over internal deformation, and therefore vertical mean and surface velocities are set equal. We rely on the same Elmer/Ice routine to discretise and solve the mass conservation problem as above (Sect. 2.2). Previously inferred first-step thickness values are prescribed as Dirichlet conditions around the lateral domain margin, whereas no condition is imposed along marine ice front.

25

2.3.1 Cost function & multi-parameter optimisation

The ice thickness solution is optimised as we cannot anticipate that input fields are consistent in terms of the mass balance equation. Yet in this step, the optimisation makes use of three control variables. The AMB is complemented by both horizontal

velocity components u_i . For this second-step optimisation, a new and more elaborate cost function N is defined.

$$N = \gamma_{\text{pos}} \cdot \int_{\Omega} H^{2} \cdot \mathbf{H}[-H] \, d\Omega + \gamma_{\text{obs}} \cdot \int_{\Omega} (H - H_{\text{obs}})^{2} \, d\Omega + \gamma_{\text{marine}} \cdot \int_{\Gamma_{\text{marine}}} H^{2} \cdot \mathbf{H}[H_{\text{min}} - H] \cdot \mathbf{H}[H - H_{\text{max}}] \, d\Gamma + \gamma_{\text{reg}} \cdot \int_{\Omega} \left(\frac{\partial H}{\partial x}\right)^{2} + \left(\frac{\partial H}{\partial y}\right)^{2} d\Omega + \gamma_{\dot{a}} \cdot \int_{\Omega} \left(\dot{a} - \dot{a}^{\text{init}}\right)^{2} d\Omega + \gamma_{\text{U}} \cdot \sum_{i=1}^{2} \int_{\Omega} \left(u_{i} - u_{i}^{\text{init}}\right)^{2} d\Omega$$
(13)

- Most of the terms have equivalents in Eq. (6). As before, we penalise a negative solution, high variability of the control 5 variables and the control-variable mismatch to initial values. New terms are the penalty for thickness values that differ from the measurements H_{obs} and the line integral along the marine boundary Γ_{marine} . The latter integral penalises thickness values outside a certain range. The lower limit of this range stems from the fact that marine-terminating glacier margins on Svalbard are mostly grounded (Dowdeswell, 1989). Therefore, H_{\min} is given by the flotation criterion $H_{\min} = h \cdot \rho_{water} / (\rho_{water} - \rho_{ice})$. The upper limit is calculated from the IBCAO bathymetry. We assume that the bed topography does not significantly decrease inland
- 10 and thus that the bathymetry along the ice front should be shallower than the maximum depth at all ocean points within a 5-km radius. The multiplier choices are motivated as follows: First, the most decisive multiplier is γ_{reg} . If chosen to high, boundary thickness values and measurements are simply smoothed without much consideration for the ice dynamic influence. If chosen too low, the thickness solution of adjacent flow lines decouples. The choice $\gamma_{reg} = 10^{-2}$ represents a trade-off between the two extremes. Second, we deemed it appropriate to set $\gamma_{\text{pos}} = \gamma_{\text{marine}} = \gamma_{\text{obs}}$. The value was gradually increased until the solution was appropriately affected, giving $\gamma_{\text{pos}} = 10^2$. As before, the remaining two multipliers $\gamma_{\dot{a}} = 10^{-4}$ and $\gamma_{\text{U}} = 10^{-8}$ are not very 15
- decisive and they were mostly added to prevent divergent behaviour.

As above (Sect. 2.2.3), cost derivatives with respect to the control variables \dot{a} and u_i were computed from the adjoint system to Eq. (2). Without further modifications, the iterative optimisation preferentially modifies \dot{a} because the control variables have different magnitudes. To align relative change values, a scaling factor of 0.05 for the velocity derivatives was introduced.

Convergence of this second-step optimisation is reached using the same threshold criterion as above (Sect. 2.2.3). 20

2.3.2 Error estimate

25

Errors are again estimated following the ideas presented in Morlighem et al. (2014). As the ice thickness is calculated directly from mass conservation, errors have only to be propagated through Eq. (1). By analogy with Sect. 2.2.5, two systems of equations limit the error estimate.

$$\nabla [(+\boldsymbol{u}) \,\delta H_1] = \delta \dot{\boldsymbol{a}} + \|\nabla [F \delta \boldsymbol{u}]\|$$

$$\nabla [(-\boldsymbol{u}) \,\delta H_2] = \delta \dot{\boldsymbol{a}} + \|\nabla [F \delta \boldsymbol{u}]\|$$
(14)

The minimum value of the absolute values of these two error estimates gives the actual thickness error $\delta H = \min(||\delta H_1||, ||\delta H_2||)$. Input uncertainties are $\delta u = 20.0 \,\mathrm{m \ yr^{-1}}$ and $\delta \dot{a} = 0.2 \,\mathrm{m \ i.e. \ yr^{-1}}$

2.4 Gridding & Boundary conditions

The individual glacier outlines from Nuth et al. (2013) are first partitioned into marine and land-terminating segments by searching if the surface elevation is zero within 150 m of the outline point. Where the DEM showed more advanced glacier fronts than the glacier inventory, a marine termination is inferred within the same search radius but with 100 m as surface-

5 elevation threshold. Subsequently, nunataks are automatically accounted for in the mesh, if resolved by the target grid spacing. In addition, we added grid points at each location where thickness measurements were available. This was necessary to prescribe internal boundary conditions on the error estimates. High-resoltuion thickness measurements were a-priori subsampled in accordance with the grid resolution. From the outline and measurement locations, a 2D mesh with triangular elements was generated using the open source finite element grid generator Gmsh (Geuzaine and Remacle, 2009). Nodal values for all input

10 fields are determined relying on a standard Natural Neighbours Sibsonsian interpolation procedure (Fan et al., 2005). In the first-step reconstruction, two external boundary conditions are necessary around the glacier domain. At outflow boundaries along marine ice fronts, no conditions are set on either the ice flux or the ice thickness. Where glaciers terminate on land, a zero flux Dirichlet condition is imposed. Internal boundary conditions are applied where measurements were available. There, flux error estimates δF_1 , δF_2 are set in accordance to reported measurement errors (Sect. 3.9). In the second-step, the domain

15 is reduced to sub-domains with reliable velocity information. In each drainage basin, the largest sub-domain is chosen from all areas in which velocity observations exceed 100 m yr⁻¹. At the lateral boundaries of this sub-domain, ice-thickness values as well as thickness error estimates are prescribed from the first-step reconstruction. No boundary conditions are imposed along marine ice fronts. Where thickness measurements were acquired, Dirichlet conditions are imposed on the up- and downstream error propagation. However, the uncertainty δH_{obs} varies with the inferred thickness field. It is chosen as the minimum of the
20 actual mismatch (H - H_{obs}) and the reported measurement error.

3 Test geometries

The two-step reconstruction approach is tested on three ice geometries on Svalbard where an abundant record of thickness observations was available (Fig. 1). The three test geometries are Vestfonna ice cap (VIC) on Nordaustlandet, the land-terminating Werenskioldbreen (WSB) and the glacier complex composed of the marine-terminating Austre Torellbreen, Hansbreen and Paierlbreen (THPB). The latter two geometries are located in Wedel Jarlsberg Land. Input requirements are glacier outline, the surface geometry, the surface mass balance, surface elevation changes as well as surface velocities. Fjord bathymetry information and thickness measurements are used to constrain the inferred thickness values.

3.1 General characteristics

VIC is the second largest ice caps on the Svalbard archipelago (Fig. 1; Dowdeswell, 1986a). According to the 2002-2010
30 glacier inventory, it covers an area of 2366 km² with its summit area lying at 630 m above sea level (a.s.l.). Ice flow is channeled through several elongate outlet glaciers, which drain radially from a central crest and export ice to the surrounding



Figure 1. Overview map of the Svalbard archipelago showing ice coverage (blue shading). The two test sites (red shading and rectangles) are Vestfonna Ice Cap (VIC) on Nordaustlandet and the glacier complex comprising the marine-terminating Austre Torell-, Hans-, Paierlbreen (THPB) and the land-terminating Werenskioldbreen (WSB) in Wedel Jarlsberg Land. Background: grey-scale hill-shaded topography based on a 50 m DEM from the Norwegian Polar Institute (NPI).

ocean (Fig. 2g). Despite the steady retreat of most outlet glaciers since the 1970s (Dowdeswell, 1986b; Braun et al., 2011), Sore and especially Nordre Franklinbreen advanced notably. This re-advance coincided with a strong acceleration reaching far inland. Surface velocities doubled and now exceed 100 m vr^{-1} over a large area (Pohjola et al., 2011). Prior to the speed-up, most of the ice was exported via the northern branch of Nordre Franklinbreen. In the meantime, ice velocities indicate that the

- 5 southern branch is the more prolific export path (Fig. 2g). The bi-modal pattern in ice dynamics is overprinted by cyclic surges with the last active phase reported in 1952 for Søre Franklinbreen (Błaszczyk et al., 2009). Surges are quasi-periodic cycles of an active phase, during which extremely fast flow can transfer an immense ice volume downglacier, followed by a quiescent phase during which the ice cover in the accumulation area gradually regains its former height. Two other surge-type glaciers are known in the eastern part of Vestfonna. Active phases were reported in 1939 and 1992 for Rijpbreen and during the period 1973-1980 for Bodleybreen (Dowdeswell, 1986b; Błaszczyk et al., 2009).
- 10

Austre Torellbreen is a marine-terminating glacier (Fig. 2b) that calves into Skoddebukta and spans altitudes from sea-level to about 900 m a.s.l. The most elevated parts of the accumulation area belong to Amundsenisen (above 700 m a.s.l.). This area is drained by Bøygisen and Løveisen. Before reaching the ocean, Austre Torellbreen is fed by Vrangpeisbreen from the south. Across the divide in the south lies Hansbreen, which has a dominant main branch receiving important lateral inflow from two prominent tributaries in the southwest, i.e. Deileggbreen and Tuvbreen (Grabiec et al., 2012). The glacier shows a somewhat reduced elevation range, only up to 500 m a.s.l. Beyond the mountain range to the east lies Paierlbreen. Both glaciers are well connected via Kvitungisen. Paierlbreeen connects again back to Amundsenisen in the north via Nornebreen. The glacier was not only classified as marine-terminating in the 2002-2010 inventory, but it also exhibited surge behaviour in 1993-1999

5 (Błaszczyk et al., 2009; Nuth et al., 2013). During the surge, the ice front position was, however, not much affected. The reason might be that the surge event was superimposed on the well-documented retreat of all marine-terminating glaciers in the Hornsund area over the last century (Błaszczyk et al., 2013). Austre Torellbreen, Hansbreen and Paierlbreen cover areas of 141, 64 and 99 km², respectively. West of the THPB complex lies Werenskioldbreen (Ignatiuk et al., 2014). It is land-terminating and somewhat smaller with 27 km².

10 3.2 Glacier outlines

Glacier outline information is taken from the 2002-2010 glacier inventory described in Nuth et al. (2013). As THPB is a well-connected glacier complex, adjacent glacier boundaries were removed and joined into one single outline. WSB was not merged with the THPB complex because the shared ice divide is short and shallow (Kosibapasset has only ~ 15 m depth). VIC is treated as a single entity by merging all its individual drainage basins. In this way, we avoid discontinuities in the anticipated thickness solution across ice ridges and divides.

3.3 Surface elevation

15

20

Concerning the Svalbard surface elevation, we rely on a 50 m digital elevation model (DEM) from the 1990s¹ provided by the Norwegian Polar Institute (NPI). This map was produced from areal photos using photogrammetry as well as from contour lines in earlier elevation maps, which were digitised and interpolated. We refrained from using this DEM for VIC where it is based on contour-line information resulting in a characteristic wave pattern in the slope field. Therefore, we use a more recent 10 m DEM inferred from 2010 radar data acquired by the TanDEM-X mission, operated by the German Aerospance Center

(DLR; Krieger et al., 2013). The DEM was processed from bi-static Synthetic Aperture Radar (SAR) data using a differential interferometric approach (Seehaus et al., 2015; Rankl and Braun, 2016; Vijay and Braun, 2016). It was referenced to sea level by laser altimetry measurements with the Ice, Cloud, and Land Elevation Satellite (ICESat) (Schutz et al., 2005).

25 3.4 Thickness measurements

VIC thickness measurements (Fig. 4a) were obtained from 60MHz airborne radio-echo sounding (RES) surveys between 1983 and 1986 (Dowdeswell et al., 1986). Five flightlines run north-south across the ice cap and two from east to west. All profiles follow centrelines of prominent outlet glaciers. Unfortunately, no bed reflector could be identified for a large portion of these airborne data, including most of the ice-divide area. Recently in 2008-2009, ground-based pulsed radar (GPR) data

30 were collected by (Pettersson et al., 2011). Following Pettersson et al. (2011), the early airborne measurements were adjusted

¹Norwegian Polar Institute (2014). Terrengmodell Svalbard (S0 Terrengmodell) [Data set]. Norwegian Polar Institute. doi:10.21334/npolar.2014.dce53a47

assuming a constant thinning rate of $\sim 0.16 \text{m yr}^{-1}$ over the entire ice cap. In addition, they estimate the measurement error for the early airborne surveys from Dowdeswell et al. (1986) to be 23.1 m, whereas the more recent GPR data shows a 9.3 m uncertainty.

In the Hornsund area, Hansbreen is well studied and an ice-core drilling team reached the bed at three locations already in

- 5 1994 (Jania et al., 1996). Between 2004 and 2013, ground-penetrating radar profiles were collected both on THPB and WSB (Navarro et al., 2014). These surveys provide a dense grid over most parts of these glaciers (Fig. 4b). Therefore, the early ice-core information was discarded here because it only gives information at three additional points and because it is not evident how to reliably estimate surface-elevation changes since the early 1990s. For WSB, the GPR measurement error was analysed in depth accounting for positioning-related ice-thickness uncertainty (Lapazaran et al., 2016). Measurement errors fall into a
- 10 range of 3.3 to 6.8 m with an average value of 4.5 m. These error values ignore, however, a known uncertainty term originating from 2D data migration (Moran et al., 2000). This migration is common practice but it ignores transversal bedrock slopes. This processing uncertainty attains up to 14 m for a certain part of a small and shallow Alaskan valley glacier. It is impossible to a-priori determine this uncertainty for each measurement on Svalbard and we therefore ignore this source term here.

3.5 Surface mass balance

- 15 For the SMB information, we rely on the regional climate model MAR (Modèle Atmopshérique Régional; Lang et al., 2015). MAR combines a hydrostatic model for the atmospheric circulation with a physically based model for snow-pack evolution. The MAR-SMB simulations cover the entire archipelago (Fig. 2a,b) and were validated by Lang et al. (2015) against available climatic variables as well as SMB measurements from Pinglot et al. (1999, 2001). The difference between modelled SMB values and 10 used validation sites shows a low bias of -0.03m i.e. yr^{-1} with a standard deviation of 0.14m i.e. yr^{-1} . The
- 20 latter value is considered as an uncertainty estimate for the SMB field. Simulation were conducted on a regular 7.5 km grid but a downscaled output was provided on 200 m spacing using an interpolation strategy that distinguishes the various SMB components (Franco et al., 2012). The components are interpolated according to locally defined, vertical gradients. For the reconstruction, the annual SMB record was averaged over 1979-2015.
- To assess the sensitivity of the thickness reconstruction to the SMB input (Appendix C1), results from the Weather Research and Forecasting (WRF) model were considered (Aas et al., 2016). The WRF-SMB field represents the period 2003-2013 and has a 3 km resolution. The field could not be downscaled as above for the MAR results. Therefore, the SMB sensitivity is only assessed on the large VIC geometry.

3.6 Surface elevation changes

Over VIC, 2003-2007 elevation changes (Fig. 2c) were inferred from ICESat altimetry measurements (Moholdt et al., 2010).
The laser altimetry system has a footprint of 70 m diameter with 170 m along-track spacing. Across-track spacing is irregular and much larger with several kilometres. A Natural-Neighbour Sibsonian interpolation² (Fan et al., 2005) is used to estimate

²source code available at https://github.com/sakov/nn-c/tree/master/nn



Figure 2. Input fields to the ice thickness reconstruction for VIC (a,c,e,g) and THPB/WSB (b,d,f,h). Surface mass balance (SMB) input (a,b) is provided by MAR as an average over the period 1979-2014 (Lang et al., 2015). Elevations changes (c,d) are inferred from 2003-2007 ICESat profiles on VIC and from a 2008 SPOT-HRS DEM in southern Spitsbergen. From this elevation information, we subtracted the 1990 DEM from the Norwegian Polar Institute (NPI). For VIC, line information on elevation changes along the ICESat tracks was linearly interpolated (c). The difference between SMB and surface elevation changes (e,f) is referred to as the AMB. Surface velocity magnitudes (g,h) were inferred from 2015/2016 Sentinel-1 imagery. Background: grey-scale hill-shaded topography based on a NPI 50 m DEM.

elevations changes in between these scattered ICESat measurements. Moholdt et al. (2010) report that the local root-meansquare deviation of several hundred surface-change estimates is 0.3m yr^{-1} .



Figure 2. (continued)

For Wedel Jarlsberg Land, elevation changes were calculated by differencing the NPI 20 m DEM¹ from 1990 with a 40 m DEM inferred from 2008 imagery acquired by the high resolution stereoscopic (HRS) sensor on-board SPOT 5 (Korona et al., 2009). The DEMs were first co-registered (Nuth and Kääb, 2011) before subsequent differencing and re-sampling to 100 m (Fig. 2d). No information on the DEM differencing uncertainty was available.

3.7 Surface velocities

Using satellite imagery acquired between January 2015 and September 2016 by the C-band Synthetic Aperture Radar (SAR) onboard Sentinel-1, we apply intensity offset tracking to consecutive image pairs (Strozzi et al., 2002; Seehaus et al., 2016). The time series of displacement fields is first filtered for obvious outliers within a kernel size scaling with the prevailing flow

5 direction and magnitude (Seehaus et al., 2016). Then, fields are stacked using median-averaging to obtain maximum coverage and to reduce effects from short-term or seasonal fluctuations (Fig. 2g, h). Velocity maps are provided at 100 m resolution. The uncertainty associated to the inferred velocity maps is estimated on 70 stable reference areas without ice cover. We find an average uncertainty of 19m yr⁻¹, which is comparable to independent uncertainty estimates for merged Sentinel-1 imagery with minimum values of ~ 17m yr⁻¹ (Schwaizer, 2016).

10 3.8 Fjord bathymetries

20

Information on the fjord bathymetry is used to further constrain the thickness reconstruction at marine ice fronts. The new International Bathymetric Chart of the Arctic Ocean (IBCAO Version 3.0) holds a wealth of new measurements around the Svalbard archipelago (Jakobsson et al., 2012). It comprises several recent multibeam surveys that entered deep into some major fjords and collected high-resolution seafloor information (Ottesen et al., 2007). Around the archipelago, the new IBCAO map

15 is provided at a spatial resolution of 500 m.

3.9 Grid specifications & Input uncertainties

The target resolution for the meshing is set to 200 m for THPB and VIC and 100 m for WSB. Observations for all test geometries are very densely spaced and we decided to only keep measurements that are more than 50 m apart, which is half of the minimum grid spacing. The initial 20792, 44921 and 21273 measurements collected on VIC, THPB and WSB were thus reduced to 4475, 5945 and 1189 points, respectively.

From the above presentation of the input fields available for the test geometries, we define appropriate input uncertainties for the formal error propagation in Sects. 2.2.5 and 2.3.2. First, the Dirichlet conditions on the error on the WSB and THPB thickness measurement δH is set to 5 m (Lapazaran et al., 2016). For VIC, we prescribe 10 m and 25 m for the ground and airborne RES data, respectively (Pettersson et al., 2011). Second, the AMB uncertainty is estimated to be $\delta \dot{a} = 0.4 \text{m yr}^{-1}$,

which is the sum of the individual error estimate reported for SMB and surface elevation changes (Sects. 3.5 and 3.6). For the first-step reconstruction, we estimate a 20% error in the flux direction δn . Only a scalar estimate is necessary here because of the normalisation of the direction vector n. The surface-velocity uncertainty is directly inferred from ground control points: $\delta u = 20 \text{ m yr}^{-1}$.



Figure 3. Ice-flux solution after cost optimisation for VIC (a), THPB and WSB (b). The ice flux gradually increases and converges into several distinct outlet glaciers. Ice flux converges over major drainage basins and is channeled through several major outlet glaciers. Flux values at marine ice fronts are therefore part of the solution. Background: grey-scale hill-shaded topography based on a NPI 50 m DEM.

4 Results & Discussion

4.1 First-step reconstruction

This section covers the presentation and discussion of the ice-flux solution, the reconstructed thickness and bedrock elevation fields as well as the error estimates. In the error analysis, actual mismatch values from a fraction of withheld measurements are compared to the formal error estimate (Sect. 2.2.5). In the appendix, interested readers find a brief discussion of the viscosity parameter (Appendix A) and a sensitivity assessment with respect to changes in SMB, surface geometry and to a flux correction (Appendix C).

4.1.1 Ice flux

5

For Vestfonna ice cap, the ice-flux field is very instructive (Fig. 3). For many drainage basins, ice flux is small near the
ice divide and gradually increases downglacier. The increase results from ice accumulated along flow lines as well as from flow convergence towards the lateral margin. Often, ice flux is highest near the equilibrium line altitude. For Gimlebreen, Braggebreen, Idunbreen, Aldousbreen and Bodleybreen, ice flux remains elevated up to the marine ice fronts. For Gimlebreen, Braggebreen abd Idunbreen, these high values are explained by an increasingly positive à towards the ice front (Fig. 2e). Also for Aldousbreen, à stays positive near the glacier tongue. Unlike these examples, the AMB turns negative long before

the margin is reached for Nordre Franklinbreen and Frazerbreen. There, elevated ice-flux values are maintained by strong convergence. For Nordre Franklinbreen, the ice flux mainly follows the southern branch.

For WSB and THPB, the ice flux is small all along the land-terminating margin and increases towards centrelines. For Austre Torellbreen, we find strong flux convergence along Bøygisen and Løveisen. Further downstream, ice-flux magnitudes

- 5 remain constant as the AMB is close to zero. Unlike this balanced situation, a large surface lowering signal on Paierlbreen remains unexplained by the SMB, resulting in a positive AMB over the entire catchment area. This imbalance is compensated by extensive downwasting implying a gradual flux increase up to the marine ice front. The imbalance itself might partially reflect the long-term geometric adjustment of Paierlbreen to the surge in 1993-1999. Yet, we cannot exclude that the SMB model underestimates the magnitude of surface melting or that a bias is introduced by the DEM differencing (Sect. 3.6). In any
- 10 case, the Paierlbreen setup is challenging because there is almost no sink in the AMB and ice is primarily lost via the marine ice front. The main branch of WSB shows however very small flux values. The reason is that source areas ($\dot{a} > 0$ in Fig. 2f) are very limited and located on two small glacier branches joining from the north. Though they provide a certain in-flux, values along the main branch remain close to zero. Under the input SMB and elevation-change fields, no important ice-dynamic balancing is required.

15 4.1.2 Ice thickness and bedrock elevation

The first-step thickness map (Fig. 4) depends on surface slopes, thickness measurements and the ice-flux solution. The latter reflects both climatological and geometric information. For VIC, we find a mean thickness of 228 m (Table A1). This value is significantly higher than the previously reported 185 m, which was inferred from a direct kriging interpolation (Pettersson et al., 2011) of the same observations that entered our reconstruction. One reasons for differences is that our reconstruction produces thicker ice along outlet glaciers troughs. Such deep and often over-deepened channels (Frazerbreen and Franklinbreen in Fig. 5) are explained by convergent ice flow draining large zones of the ice-cap accumulation area (Dowdeswell and Collin, 1990). For Braggebreen and Gimlebreen, the reconstruction suggests deep troughs which arise from a very positive AMB. The troughs are absent in the kriging interpolation as no observations were collected in this region. Another reason for differences is that kriging is expected to underestimate the ice thickness along the land-terminating margins away from observations because

- 25 of ice-free conditions outside the domain. For our approach, the margin thickness is affected by physical quantities such as ice flux and surface geometry. An illustrative example for this effect is the dome-like surface topography of Forsiusbreen in the southwest of VIC. This glacier is almost deconnected from the main ice cap and the closest thickness measurements were taken more than 10 km away. As a consequence, Pettersson et al. (2011) generate limited thickness values from kriging. In our reconstruction, a small ice dome is predicted (Fig. 4a) that is even grounded slightly below sea level in its central areas
- 30 (Fig. 5a). In general, the first-step thickness map suggests that more than 13% of the ice-covered area is grounded below sea level. Previously, it was thought that only a 5% area fraction lays below sea-level, due to limited measurements from the outer part of the ice cap. In terms of total ice volume, the first-step thickness map yields 540.2 km³ as compared to the 442 km³ from kriging (Pettersson et al., 2011).



Figure 4. Ice thickness map for VIC (a,c) and THPB/WSB (b,d) as suggested by the first-step reconstruction approach. Thickness values for marine ice fronts are non-zero and a natural outcome of the underlying mass budget calculation. For VIC, thickness measurements (coloured dots) were collected with airborne radio-echo sounding instruments (Dowdeswell et al., 1986) as well as with ground-based pulsed radar systems (Pettersson et al., 2011; Navarro et al., 2014). For THPB/WSB, measurements were collected during several GPR campaigns between 2004-2012 (Navarro et al., 2014). The upper (a,b) and lower (c, d) panels show the respective thickness fields when all or only 1% of all thickness measurements were used in the first-step reconstruction, respectively. For the ice cap, mean thickness values are not very sensitive to the data availability, whereas the not well constrained reconstruction for THPB and WSB produces low biased estimates. Background: grey-scale hill-shaded topography based on a NPI 50 m DEM.



Figure 5. Bedrock topography associated to the thickness field in Fig. 4 for VIC (a,c) and THPB/WSB (b,d). In absence of direct measurements, negative values over larger areas were not anticipated for Gimlebreen and Idunbreen based from a direct interpolation of thickness data (Pettersson et al., 2011). Upper and lower panels reflect the respective amount of considered thickness measurements as in Fig. 4. Ice-free background: grey-scale hill-shaded topography based on a NPI 50 m DEM. Ice-covered background: grey-scale hill-shaded bedrock topography.

For the THPB and WSB systems in southern Spitsbergen (Fig. 4b), an abundant observational record was available. Therefore, we expect that relative differences between thickness maps from a direct interpolation and the first-step reconstruction should be small. From a direct kriging interpolation by Navarro et al. (2014), the mean thickness estimate for the THPB system is 184 m as compared to 176 m, here (Table A1). For the land-terminating WSB, a mean thickness of 119 and 112 m is found, respectively. Relative differences between these values are smaller than 6% for both. The slightly updated volume estimates are then 53.5 km^3 and 3.0 km^3 , respectively. Despite the similarity in these values, we see several systematic differences in the thickness maps from these two approaches. First, the kriging map shows that the measurements were interpolated ignoring

- 5 the presence of some ice-free nunataks (for example above the confluence of Bøygisen and Løveisen in Fig. 4 in Navarro et al., 2014). Similarly, ice thickness does not tend to zero along some land-terminating margins. These positive biases are compensated in other areas, where thickness measurements are not reproduced after kriging. A clear difference is seen along Vrangpeisbreen. In its upper reaches, the direct interpolation shows values below 100 m (Fig. 4 in Navarro et al., 2014), whereas the thickness measurements along the centreline readily exceed 200 m (Fig. 4b). These measurements are by con-
- 10 struction reproduced here. Turning to the basal topography, we find elongate troughs reaching far upglacier from the marine terminus (Fig. 5b). The bedrock elevation is below zero over 12% of the entire THPB area. For Hansbreen, the bed remains below sea-level almost up to Kvitungisen.

For many glaciers, only few or even no thickness measurements are available and, therefore, we want to asses a lack of in situ measurements. For this purpose, we re-computed all thickness fields relying on a random 1%-sample of all thickness

- 15 measurements (Fig. 4c,d). For VIC, we find a slightly larger value for the mean ice thickness of 230 m and the total ice volume of 543.3 km³ (Table A1). Despite this reduction, general characteristics of the basal topography are imprinted in the poorly informed reconstruction (Fig. 5c). For THPB and WSB, the mean ice-thickness values are reduced to 145 and 100 m from previously 176 and 112m, respectively. For THPB, the substantial thickness reduction implies that the area-fraction grounded below sea level falls from 12 to 8%. In many places, the sparsely informed reconstruction underestimates the depth
- 20 of elongate, narrow bed troughs (e.g. Nornebreen, Vrangpeisbreen). The densely spaced GPR grid measured on Hansbreen provides an ideal test case to estimate how well the reconstruction performs without many measurements. Though an elongated bed trough is predicted, thickness values and the slope of lateral valley sides are underestimated. Moreover, the patterns in the bedrock topographies differ (Fig. 5b,d). This implies that some observed features in the bedrock topography are not necessarily imprinted in the glacier surface nor the flux field. Admittedly, a certain degree of details in the slope field is removed by the
- 25 geometric smoothing (Sect. 2.2.1).

4.1.3 Thickness error estimates

The following error analysis is two-fold: we first present and discuss error-estimate maps from the formal error propagation of input uncertainties as described in Sect. 2.2.5. Secondly, we split the abundant thickness measurement record into two subsets. One subset is used in the reconstruction (Sect. 2.2.4), whereas the remainder is withheld for validation. The validation subset is

30 used to infer actual mismatch values at the respective measurement location. Average values for the actual mismatch are then compared with the respective formal error estimates.



Figure 6. Error-estimate map based on the error propagation presented in Sect. (2.2.5) for VIC (a,c) and THPB/WSB (b,d). Values are most elevated in the vicinity of unconstrained ice divides and ridges as well as in other stagnant areas. Error estimates are equal to the measurement uncertainty where observations were collected. Upper and lower panels reflect the amount of considered thickness measurements as in Fig. 4. For panels (c,d), the withheld measurements (dots) are put into three categories. The first category (black dots) comprises all locations where the difference between observed and reconstructed thickness values are within the error bounds. For the other two categories, the difference exceeds these bounds and measured thickness values are either overestimated (green dots) or underestimated (purple dots) by the reconstruction. Background: grey-scale hill-shaded topography based on a NPI 50 m DEM.

4.1.4 Estimates from error propagation

Relying on a formal error propagation (Sect. 2.2.5), it becomes possible to provide an error map (Fig. 6a,b). Using all thickness observations, the survey tracks are visible as small values in all error maps. Away from these measurements, error estimates gradually increase in both direction along streamlines. More abrupt variations are found perpendicular to the inferred flux

- 5 direction. We therefore suggest that future measurement campaigns should give priority to across-flow profiles. Values are highest in areas where ice flux is small as, for example along the southwestern part of the VIC divide and on a large part of the land-terminating WSB. For the latter area, error estimates are largest. These extreme values are caused by negligible ice flux over a major part of the domain (Sect. 4.1.1). The error-estimate map of VIC also highlights that measurements should ideally be acquired on both sides of an ice divide. For Idunbreen, no measurements were obtained (Fig. 4a), which leads to elevated
- 10 error estimates over most of this drainage basin (Fig. 6a). Thickness measurements collected just across the ice divide were not transmitted over the crest to the Idunbreen catchment area.

Considering only 1% of all thickness measurements, the error estimates become larger (Fig. 6c). The ice-cap setup shows largest values along ice divides and ridges where flux values are smallest. On WSB and THPB (Fig. 6d), maximum error estimates are again found in the stagnant areas on WSB but also on Hansbreen and Austre Torellbreen values are elevated. In

15 critical areas on ice caps and glaciers, we confirm that error estimates can readily reach 50% of the inferred ice thickness if thickness measurements are sparse.

4.1.5 Actual thickness mismatch

20

A pressing question is whether the magnitude of these error-estimate maps is reliable and falls into a realistic range. For this purpose, we withheld a random sample of all thickness measurements from the reconstruction and computed an absolute thickness mismatch for comparison. The sample size is defined as a fraction of all measurements and we investigated the range

from 1 to 99%.

In a first attempt, we directly compared the formal error estimates to the in situ absolute mismatch values. Ideally, these two values would show a positive correlation. Yet, no clear dependence was discernible for any of the sample sizes. Both data distributions, for mismatch values and error estimates, are not normal. Being robust to outliers, we decided to quantify these

- 25 distributions in terms of medians and quartiles (Fig. 7). In this aggregate sense, error estimates tend to overestimate the absolute mismatch. For small fractions of withheld measurements, the overestimation is stronger. This bias does not surprise as formal error estimates cannot fall below a preset measurement error (Sect. 3.9), whereas high correlation between thickness values at adjacent location results in very low mismatch values. If only 1% of the measurements is withheld, median mismatch values do not exceed 3 m, which simply reflects spatial data correlation. For this case, median error estimates are about 20 m for VIC
- 30 and THPB. Error estimates are problematic on the stagnant WSB setup, where we find a median of 149 m, which exceeds the mean ice thickness. For a withheld data fraction of 99%, we find mismatch medians of 21 m for VIC, 47 m for THPB and 36 m for WSB. Again these are overestimated by the median error estimates of 102 m, 66 m and 360 m, respectively. Again the



Figure 7. Median values for the absolute thickness mismatches and the error estimates at measurement locations not included during the reconstruction. Marker colours indicate the respective fraction of all measurements withheld from the reconstruction. Dashed crosses span the interquartile range of all mismatch values (horizontal) and all formal error estimates (vertical). For orientation, the grey background shading was added to highlight the identity line.

value on WSB stands out. We conclude that aggregated values of formal error estimates show a tendency to exceed mismatch values. This tendency suggests that error estimates, here, can be interpreted in terms of an upper constraint.

The above aggregate assessment suggested that the error estimates could serve as upper constraints for the actual mismatch. It remains however unclear how reliable this interpretation is at individual measurement locations. We therefore compute the

- 5 data fraction of all withheld measurements for which the actual mismatch is less than the predicted error estimate (Table 1). If only a 1% fraction of the measurements is withheld, more than 90% of the actual mismatch values fall into the error bounds. On VIC, even 100% are reached. As before, these high values simply reflect the strong spatial correlation in the measurements. Withholding gradually more data for validation, the data fraction for which the upper error constraints are valid decrease. The minimum of 64% is reached for THPB. These numbers give a first indication on the spatial reliability of the error-estimate
- 10 map. Looking at the spatial distribution of violated error bounds (Fig. 6c,d), a clustering is visible. For the ice-cap setup, we find violations along the land-terminating margin, where inferred thickness values tend to underestimate the measurements. Concerning violation in the interior, a tendency for overestimating the thickness values is discernible. For the more constrained valley glacier setups (THPB, WSB), these tendencies are not confirmed.

Table 1. Fraction of all validation measurements for which the absolute mismatch is less than the predicted error estimate. Values are given in per cent.

fraction of withheld	test geometries					
measurements [%]	VIC	THPB	WSB			
			I			
99	84.0	63.9	88.7			
95	89.0	80.0	87.0			
90	93.0	79.4	91.1			
80	94.7	82.8	94.1			
70	96.2	86.0	93.4			
60	97.3	88.6	96.1			
50	97.3	88.7	95.6			
40	97.9	89.2	96.8			
30	97.9	89.5	96.9			
20	97.5	89.5	98.0			
10	98.4	91.2	96.6			
1	100.0	93.1	90.9			

We conclude that median error-estimates overestimate the mismatch values and could therefore serve as an upper error constraint. Accepting this interpretation, we can provide an aggregate error range. Mean thickness values for VIC, THPB and WSB fall into a range of 172 - 320 m, 141 - 217 m and 46 - 508 m, respectively. For the area fraction of ice grounded below sea-level, we find ranges of 7 - 23% for VIC and 7 - 22% for THPB. This maximum range on VIC is clearly exceeded by the 5% area fraction inferred by a direct interpolation of measurements. Despite this aggregate assessment, the spatial reliability

5 5% area fraction inferred by a direct interpolation of measurements. Despite this aggregate assessment, the spatial reliability of interpreting the error-estimate map in terms of an upper constraint for local measurements become increasingly difficult the fewer measurements are available.

4.2 Second-step reconstruction

The second step of this reconstruction is applied in one sub-domain for each test geometry, where velocity measurements 10 exceed 100 m yr⁻¹ (Fig. 2g,h). In these sub-domains, mass conservation is directly solved for the unknown ice thickness. As this solution is additionally informed by velocity observations, we expect an improved thickness field.

4.2.1 Ice thickness

On VIC, ice thickness is updated along 8 fast-flowing outlet glaciers (8a,c). In these areas, the new thickness field can differ considerably from the first-step reconstruction (Fig. 4), particularly in areas with sparse observational constraints as for Idunbreen and Riinbreen. The reason is that velocity streamlines deviate from the geometrically prescribed flux direction. Con-



Figure 8. Ice thickness (a,b) as in Fig. 4 and associated bedrock topography (c,d) as in Fig. 5 for VIC (a,c) and THPB (b,d). Along the outlet glaciers (non-transparent lurid colours), the two fields were updated in the second-step accounting for velocity observations in the mass conservation. Partially transparent areas in these maps (unsaturated colours) stem from the first-step reconstruction, for which values are inferred from the flux solution.

sequently, the ice is distributed differently. For Idunbreen and Rijpbreen, deeper troughs are found somewhat away from the ice front and a larger ice volume is inferred. For all other outlet glaciers, the ice volume estimate decreases. In addition, spurious along-flow variations in the geometrically controlled first-step thickness field, for instance on Bodleybreen and Rijpbreen (Fig. 4a), are not visible in the second-step field. Accounting for the second-step reconstruction, both the total ice volume and



Figure 9. Error estimate map as in Fig. 6 for VIC (a) and THPB (b). Partially transparent areas in the thickness maps (unsaturated colours) stem from the first-step reconstruction, for which ice thickness is inferred from the ice-flux solution. Along the outlet glaciers (non-transparent lurid colours), error estimates are updated relying on velocity observations (Fig. 2c, d).

the mean ice thickness slightly decrease to 538.8km³ and 227 m, respectively. This also reduces the area fraction grounded below sea-level to 13.0%.

In Wedel Jarlsberg Land, thickness fields are updated for the three fast-moving frontal areas of the THPB complex. The wealth of thickness observations implies that the first- and second-step reconstructions are very similar (Fig. 8b). This is 5 certainly the case for Paierlbreen. Differences become largest near the calving fronts because of the free boundary condition. For Hansbreen, the bed trough near the ice front becomes both deeper and wider. For Austre Torellbreen, differences are more apparent as only two along-flow measurement profiles constrain the thickness field at low elevations. Along its centreline at the confluence with Vrangpeisbreen, an overdeepened spot in the first-step reconstruction is flattened in the updated basal topography (Fig. 8d). The frontal area is also thinner than in the first-step reconstruction. For the entire THPB complex, we find a small reduction in average thickness to 173 m.

10

4.2.2 **Mismatch & error estimates**

The updated error-estimate map (Fig. 9) is informed by first-step values at lateral boundaries. These estimates are now propagated along velocity streamlines, which themselves are inferred from measurements. On Frazerbreen and Hansbreen, large first-step error estimates near the ice front are reduced because of high velocities. In the sub-domains on VIC, magnitudes of

the updated error estimates tend, however, to increase as compared to the first-step values. A possible reason is the relatively 15 large input velocity uncertainty of 20 m yr⁻¹.



Figure 10. Median values for the absolute thickness mismatches and the error estimates as in Fig. (7). Values are only calculated within the sub-domains. Symbols with black edges represent the results from the first step. Symbols without edge line indicates the second-step results.

We repeat the aggregate error assessment from above (Fig. 10). For VIC and THPB, we find that median mismatch values are higher than in the first step. So despite the additional velocity information, the second-step reconstruction is not necessarily able to produce a more reliable thickness map. Another trend is seen in the interquartile error-estimate range, which is often reduced, certainly for THPB. Yet no trend is visible in the median error estimates, which are smaller for THPB and higher for VIC than in the first step. Following the above interpretation of these aggregated error estimates in terms of a maximum range, we can update the mean thickness ranges to 171 - 320 m and 142 - 212 m for VIC and THPB, respectively. The maximum ranges for the area fraction below sea-level become 6 - 23% and 6 - 18%, respectively.

5 **General Discussion**

5

In this section, we discuss the central assumptions and caveats of the presented reconstruction approach. For the first step, sliding is neglected, assuming that ice motion is an exclusive result from internal deformation. In areas without thickness 10 and velocity information, this assumption is likely the dominant source of uncertainties and biases the results towards higher thickness values. Other reconstruction approaches use an empirical scaling relation (e.g. Farinotti et al., 2009b) or incorporate a transiently resolved relation for basal water availability (van Pelt et al., 2013). In either case, formulations are basic because of our limited knowledge of basal conditions. Although these approaches are valuable attempts to address the issue of unknown

basal conditions, it remains questionable whether uncertainties in the reconstructed thickness field are in fact reduced. Here, we instead address basal sliding by relying on direct measurements of the surface velocities but limited to sub-domains where magnitudes exceed 100 m yr^{-1} . These velocity measurements comprise motion arising from both internal deformation and basal sliding. For THPB and VIC we find reduced values for the mean glacier thickness when using velocities. This concurs with the expected high bias in the first step.

5 with the expected high bias in the first step.

Another caveat in the first-step reconstruction is the assumption that the ice flux follows a smoothed version of the surfaceslope field (Sect. 2.2). The smoothing is spatially variable accounting for non-local flow coupling via membrane stresses. Although the direction choice might be appropriate in slow-moving areas, the actual velocity vector can point elsewhere. The situation becomes even more complex for surging glaciers, for which the surface topography is notably modified during

- 10 these short-term events. An examples is Franklinbreen on VIC, for which velocity information from the early 1990s show main outflow via the northern outlet branch. Using the 1990 DEM (Sect. C2) for the first-step reconstruction, most ice is also exported via the southern branch (not shown). Therefore, the surface topography is not necessarily the best indicator for the flow direction. In the second step, we were able to update the thickness field in consistency with the 2015-2016 velocity fields, with preferential outflow also via the southern branch. Yet even for this reconstruction, it is not evident how to account for
- 15 important, non-regular dynamic changes, such as surging, as for instance on Franklinbreen and Paierlbreen (Błaszczyk et al., 2009).

The provided error-estimate map is shown to be a practical measure for a first error assessment. The underlying error analysis inherits all assumptions made in the mass-conserving reconstruction and thereby accounts for various input uncertainties. A fundamental assumption is that the error estimate is the minimum value of two solutions (Sect. 2.2.5). These two solutions stem from an error increase or an error decrease along the flow, both assumed to change at the same rate. We argue that the

- latter solution is necessary to constrain the error estimate upstream of measurements. The assumed magnitude of the decrease rate is however disputable. Furthermore, the error analysis neglects other sources of uncertainty. First, not all input fields are contemporaneous and therefore an inconsistency is introduced in the mass conservation equation. Second, the control parameters \dot{a} , u_1 and u_2 are updated during the optimisation. These changes are unaccounted for in the constant input uncertainties.
- 25 Third, input fields are time averaged. Such averaging suppresses seasonal signals for instance in the velocity measurements or is simply a necessity to obtain a climatologically meaningful SMB field. Yet, the averaging adds further to the uncertainty. Finally, uncertainties in some SIA parameters and variables remain unconsidered, including surface-slope magnitude and the viscosity parameter. The latter is even unconstrained if no thickness measurement is available. All these unconsidered source terms reduce the reliability of the presented error-estimate map. In a stringent Bayesian framework, Brinkerhoff et al. (2016)
- 30 were able to account for the above terms.

20

Concerning the sensitivity of the thickness map of VIC to changes in the input SMB and the input DEM (Appendix C), we find that integrated values as mean ice thickness and ice volumes are rather insensitive. On VIC, relative differences in our analysis remain within 5% (Table A1). Differences in these integrated values reduce as more and more thickness measurements are available. Locally, differences can however become large. Without thickness measurements for correction, we found that

35 an offset in the specific SMB directly translates into a thickness bias. Concerning the flux correction, we confirm that it is most

influential for stagnating areas. Ice flux values on Werenskioldbreen are very small and the relative volume difference when applying the flux correction reaches 14%. Differences again reduce with increasing availability of thickness measurements. For VIC, ice-volume or mean-thickness estimates change by less than 2.0% after applying the flux correction. For THBP, the relative difference is slightly larger at 5.0%. For VIC and WSB, these relative differences are often smaller than the sensitivity

to measurement availability. Using either all or only 1% of all available measuremetns in the reconstruction results in larger

5

relative changes in the mean ice thickness by 11% for WSB and 17% for THPB.

The central assumption in the second-step reconstruction is that surface velocities equal vertical mean values. This assumption is justified as this step is only applied in areas where surface velocities exceed 100 m vr⁻¹. There, basal sliding is likely dominant. An aggregate assessment of the thickness mismatch indicates that the second-step thickness update is not necessarily

10 more reliable than the first step. Though the updated field is consistent with the actual flow field, mismatch values tend to be larger than in the first-step reconstruction. Reasons for a worse match are that velocity measurements also introduce further uncertainty and that thickness measurements enter a cost term during the second-step optimisation rather than being imposed in the first. In addition, the sub-domain delineation might not be optimal.

6 Conclusions

We present a two-step, mass-conserving reconstruction approach to infer glacier thickness maps with prior knowledge on 15 source and sink terms in the mass budget. The two steps guarantee applicability in absence of velocity measurements. In the first step, a glacier-wide thickness field is inferred from a balance flux calculation on the basis of an input AMB. The second step requires velocity measurements, which are often not reliable all over the glacier. Therefore, the glacier thickness is only updated over a sub-domain. This updated field is consistent with the observed flow field and shows a seamless transition 20 into the glacier-wide first-step map. In both steps, available thickness measurements are readily assimilated to constrain the reconstruction. Moreover, the inferred thickness field is provided together with an error-estimate map, based on a formal propagation of input uncertainties. Here, we present and apply this approach to various glacier geometries on Svalbard where

an abundant thickness record was available.

The approach is found to be most beneficial in areas where thickness observations are sparse or unavailable. There, our 25 reconstruction is informed by glacier geometry and the AMB both constraining the produced thickness values. A direct measurement interpolation ignores such information and fills such gaps according to distant thickness information. The associated error map estimated from our reconstruction additionally highlights areas with least constrained ice thickness, namely away from observations and especially where ice-flow is small or even stagnates. In an aggregate, glacier-wide sense, the actual thickness mismatch is shown to reach 25% for glaciers with only few thickness measurements. In absence of such measurements, the aggregate mismatch freely scales with a-priori choices for not well-constrained parameters.

30

In light of the growing body of information on glacier changes with satellite remote sensing, reconstruction approaches for mapping glacier ice thickness are less and less limited from the input side. Therefore, 2D approaches become increasingly attractive and favourable because a final interpolation, which fills gaps between reconstruction profiles, can be avoided. However, the largest limitation on the applicability of 2D approaches is the availability of regional information on surface elevation changes and surface mass balance. Elevation change maps from stellite remote sensing have already been presented for several regions but further development is necessary to reduce uncertainties associated with signal penetration and firn properties. Concerning regional SMB fields, we can either rely on parametric approaches or on regional climate models. In absence of

5 both SMB and $\partial_t h$, a most basic parametric approach was already forwarded to infer distributed thickness fields world wide (Huss and Farinotti, 2012).

Appendix A: Viscosity parameter

To translate the ice-flux solution into an ice-thickness field, the ice-viscosity parameter B has to be defined (Fig. A1). Parameter values are inferred at locations where thickness measurements are available via Eq. (7). The resultant point information is then interpolated over the entire glacier domain (Sect. 2.2.4). For VIC, we find values covering a spectrum from 0.02 to

- $0.55 \cdot 10^6$ Pa yr^{1/3}, which corresponds to a rate-factor range from $1.90 \cdot 10^{-25}$ to $3.07 \cdot 10^{-21}$ Pa⁻³s⁻¹. For ice temperatures 5 between -20 and 0° C, we would expect rate-factor values between $1.0 \cdot 10^{-25}$ and $2.4 \cdot 10^{-24}$ Pa⁻³s⁻¹ (e.g. p. 75, in Cuffey and Paterson, 2010). The inferred values for VIC clearly exceed this meaningful range and should therefore not be interpreted in terms of a material property. The ice viscosity is a tuning factor, which compensates for any assumptions in the reconstruction or deficiencies and inconsistencies of input fields. The parameter is further aliased by not accounting for basal sliding. The
- 10

highest viscosities are inferred in areas next to land-terminating boundaries. These areas are also characterised by small flux values. As observations show some non-negligible thickness values there, B has to be high. The lowest values are seen in the northern part of the ice cap and along the lower trunk of Aldousbreen. For this glacier, one might interpret these low values in terms of sliding. However, for other outlet glaciers, the viscosity parameter is not necessarily decreased as compared with the surrounding area. This inconsistency also suggests that a physical interpretation of the viscosity parameter is delicate.



Figure A1. The ice-viscosity parameter B for VIC (a) and THPB/WSB (b) is inferred during the first-step of the reconstruction as explained in Sect. 2.2.4. This parameter is used to match observed and reconstructed thickness values. An interpretation in terms of material property is delicate because the parameter compensates for input uncertainties and inconsistencies as well as for assumptions in the first-step reconstruction. Background: grey-scale hill-shaded topography based on a NPI 50 m DEM.

For the THPB and WSB area, the *B*-field also shows strong variations (Fig. A1). Values cover a range from 0.02 to $2.20 \cdot 10^6$ Pa yr^{1/3}, corresponding to a rate factor range between $2.97 \cdot 10^{-27}$ and $2.28 \cdot 10^{-21}$ Pa⁻³s⁻¹. The inferred range is even larger than for VIC and again exceeds the physical range. Yet for these glaciers, a pattern might be discernible. High viscosities are often concentrated along central glacier flowlines. One explanation could be that the flux solution shows a low

5 bias along these trunks as a result of systematic inconsistencies between the input SMB and the surface elevation changes. Such a systematic effect would naturally cumulate as ice flow converges towards centrelines. Lowest viscosity values are concentrated along the ridges and in the flat area between the nunataks separating Paierlbreen and Austre Torellbreen.

In summary, the interpretation of this viscosity field B in terms of ice dynamics is rather limited because values exceed the physical range. The field should rather be seen as a multiplier for tuning purposes as it can compensate for uncertainties in

- 10 and inconsistencies between input fields as well as for assumptions within this first-step reconstruction. *B* is presented here to visualise that a single viscosity parameter might not be sufficient to capture all spatial variations in the thickness field. Initially, a best-fit single viscosity value over entire drainage basins was used, but the thickness pattern could not be explained by variations in ice flux and surface slopes alone (Eq. 7). A single viscosity parameter resulted in underestimated ice thickness for the thick parts of the glacier and overestimated values for shallower parts (not shown). Other comparable state-of-the-art
- 15 approaches often use a constant value for entire glacier basins (Farinotti et al., 2009b; Huss and Farinotti, 2012; van Pelt et al., 2013).

Appendix B: Apparent mass balance

In this section, we will briefly discuss how the AMB-field a is adapted during the first-step optimisation when all thickness measurements are taken into account (Figs. 2e,f and A2). On the ice cap geometry, differences between the initial and the final AMB field are most expressed along the ice divide and ridges but also along some centrelines, as for instance on Frazerbreen.

- 5 The reason for pronounced changes along these features is that they are focal areas in terms of flux convergence or divergence. AMB modifications there can efficiently correct for flux deficiencies (as defined by the cost function) over a large area of influence (either up- or downstream). The initial AMB shows only negative values over the little ice dome feeding Forsiusbreen. Yet after optimisation a small source area was created which explains the presence of ice in this area. Despite these most pronounced changes, the average AMB over the ice cap is initially 0.02 myr⁻¹ while finally we find 0.03 myr⁻¹. This is an
- 10 increase of 35%. For WSB, even the sign of the AMB average changes as initially the main branch of the glacier shows hardly any source region with positive AMB. As ice flux is expected to be positive and as no inflow is possible along the upper landterminated margin, the optimisation guides the system to a more equilibrated AMB state over this glacier. For THPB, the input AMB shows an area average of 4.1 m yr^{-1} , differing by less than one permille from the final average. For THPB, differences between the final and the initial AMB field are again most expressed along certain flowlines.



Figure A2. Apparent mass balance à for VIC (a,c) and THPB/WSB (b,d). Panels (a,b) give the initial input as given by the SMB and the measured surface elevation changes. Panels (c,d) show the final field after adaptation of à during the optimisation in accordance with the cost function. Background: grey-scale hill-shaded topography based on a NPI 50 m DEM.

C1 Surface mass balance

Here, the sensitivity of the first-step reconstruction to the SMB input is briefly discussed for VIC (Fig. 8). For this purpose, we exchange the 1975-2015 MAR-SMB with the 2003-2013 WRF-SMB (Sect. 3.5). A fundamental discrepancy between the

- 5 simulated time periods becomes apparent when integrating the SMB fields over the ice cap. We obtain mean SMB values of -0.08 for MAR and -0.3 m i.e. yr^{-1} per unit area for WRF. For the WRF-SMB, more ice is removed at low elevations consistent with the warmer climatic conditions of the more recent period. When using all thickness measurements, the new thickness field (Fig. A1a) is very similar (Fig. 4a) showing a slightly reduced mean value of 225 m as compared to 228 m (Table A1). Consequently, the new volume estimate is also reduced to 531.9 km³ (about 2%). Reduced thickness values are
- 10 best discernible near the ice fronts of Gimlebreen, Idunbreen and Bodleybreen. Due to a lack of observations in these regions, the reconstruction is not well constrained and as the WRF-SMB removes more ice, glacier thickness estimates become smaller. This reduction is important as the ice cliff height determines the unknown ice discharge. The frontal reduction is less clear for the land-terminating margin because steeper surface slopes limit the ablation-zone extent. The reduction becomes even more evident when only 1% of the thickness measurements is used (Fig. A1b). Thickness values near the ice divide are however
- 15 not necessarily smaller. On average, the ice volume estimate is reduced to 515.9 km³ and a mean thickness value of 218 m is found (as compared to 230 m). In general, the reconstruction is capable of compensating poorly constrained SMB data where the thickness record has good spatial coverage.



Figure A3. Ice thickness map for VIC as in Fig. 4 based on the 2003-2013 WRF-SMB field using all (a) or only 1% (b) of the thickness measurements.

C2 Surface topography

The sensitivity of the first-step thickness field to the DEM choice is smaller as compared to the SMB sensitivity. The exchange of the 2010 DEM (Sect. 3.3) with the NPI 1990 DEM results in relative thickness and ice-volume difference of less than 1.3% (Table A1). Maximum thickness values increase slightly. The new thickness field is comparably smooth because the NPI

5 DEM on VIC was computed from contour line information. As a consequence, some pattern change in the reconstructed ice thickness map (Fig. A4). One more prominent difference is that the lower trunk of Franklinbreen becomes more elongate and deep. Pattern differences are again more expressed in the case when less thickness observations are used. Locally, thickness differences can become very high. Therefore, the DEM choice is important for a reliable reconstruction. However, volume differences are relatively small (<1.3%) as compared to expected mismatch values of more than 25%, if no observations were available.



Figure A4. Ice thickness map for VIC as in Fig. 4. Here, the reconstruction is conducted with the NPI 50 m DEM as surface topography using either all (a) or only 1% (b) of the thickness measurements.

10

Table A1. Reconstruction sensitivity as quantified by the mean and maximum ice thickness, the ice volume and the area fraction grounded below sea-level. The ‡-symbol separates values stemming from a reconstruction using either all or only a 1% fraction of the available thickness measurements.

setting	glacier	mean thickness		maximum thickness		ice volume		area fraction				
	geometry	thickness		thickness				below sea-level				
	abbr.	[m]		[m]		[km ³]		[%]				
reference	VIC	228.3 ‡	229.6	448.5	‡	452.7	540.2	‡	543.3	13.3	‡	13.4
	THPB	175.7 ‡	145.3	611.1	‡	563.6	53.5	‡	44.3	12.2	‡	7.84
	WSB	112.1 ‡	100.3	279.0	‡	210.8	3.00	‡	2.68	0.25	‡	0.08
WRF-SMB	VIC	224.8 ‡	218.0	467.0	‡	424.7	531.9	‡	515.9	12.0	‡	10.2
NPI 50 m DEM	VIC	225.5 ‡	230.5	451.0	‡	475.7	533.6	‡	545.5	12.5	‡	13.0
no flux correction	VIC	226.1 ‡	223.2	451.6	‡	440.2	534.9	‡	528.1	13.2	‡	12.2
	THPB	166.4 ‡	125.6	614.1	‡	567.1	50.7	‡	38.3	10.5	‡	4.56
	WSB	106.0 ‡	87.76	282.2	‡	210.8	2.84	‡	2.35	0.32	‡	0.09

C3 Negative ice flux

values are effectively increased.

5

10

On VIC and THPB, the area fraction with negative ice flux is 1.2 and 3.1%, respectively. On WSB however, the flux solution over the main branch is generally very small and shows many zero transitions. Consequently, the area-fraction is higher at 4.1%. The reason is that the AMB shows no dominant source area in the upper glacier ranges. The zero transitions in the flux solution would directly transmit into the ice thickness field. To avoid such transitions, we correct the flux as follows:

$$F^{\star} = (1 - \kappa) \cdot \|F\| + \kappa \cdot F_{\text{crit}}, \qquad \text{with} \qquad \kappa = 1 - 2/\pi \cdot \operatorname{atan}(F^2/F_{\text{crit}}^2) \tag{C1}$$

The exact functional dependence for κ is not decisive but the choice has to assure a smooth transition. F_{crit} is set to 10% of the average flux magnitude over the domain. This value proved reasonable for the WSB setup. For smaller values, the flux field in the vicinity of negative values is less and less affected resulting in a more abrupt transition. Along the lateral land-terminating domain margin, we keep $F = F^* = 0$. When thickness measurements are available, the effect of this flux correction on the inferred thickness is compensated by the calculation of the ice-viscosity. Without measurements and for $F > F_{\text{crit}}$, the functional dependence implies that the reduction effect on the inferred thickness field remains below 2%. Where flux magnitudes exceed the domain average (10 · F_{crit}), the effect on the ice thickness falls below 0.15%. For $F < F_{\text{crit}}$, thickness

15 The flux correction applied during the first-step reconstruction (Sect. 2.2.4) could be considered an important bias. Note however that the correction is not added to the flux solution itself (Fig. 3) and that it does not enter the error calculations (Sect. 2.2.5). The correction is only applied when inferring ice thickness values for the purpose of avoiding zero transitions in

areas where flux values turn negative. In this way, it only affects the ice thickness and the viscosity parameter. Where negative values occur, the flux solution and the geometrically imposed flux direction cannot be reconciled. The negative values prevail despite the penalty in the cost function during the optimisation (Sect. 2.2.3). An increase of the respective multiplier in the cost function resulted only in a limited improvement on WSB and came at the expense of a more variable flux field on all

- 5 geometries. Therefore we rather decided to introduce a correction term that guarantees positive flux values in the SIA equation (Eq. 7). The correction is primarily required for WSB, for which magnitudes of the flux solution are very small. Anyhow, we applied it to all geometries to keep a uniformity approach. The first-step thickness solution is most sensitive to the flux correction in small areas along divides and ridges (Fig. A5). For VIC, streak features with small thickness values appear for instance on Braggebreen (in the southwest) and northeast of Bodleybreen. Similar features are difficult to discern for THPB.
- 10 More prominent are the effects on WSB. There, a noise pattern of near-zero values appears for the thickness field of the main trunk where flux values are small (Fig. 3). The bogus noise pattern is not acceptable as we expect that the thickness field shows more gradual changes. For all test geometries, differences in mean ice thickness and ice volume reach 5% (Table A1), when all available thickness measurements are considered. Using only 1% of the thickness measurements, relative differences increase to 5% on VIC, 14% on THPB and 13.0% on WSB. In all cases the flux correction results in a reduction of the mean
- 15 ice thickness.

20

In summary, the effect of the flux correction can lead to a considerable difference in ice volume in the case that no thickness measurements are available and that small flux values prevail over a large area. Yet, where measurements are available, a compensation is possible via the ice viscosity parameter *B*. The effect of the flux correction is expected to be largest for stagnating glaciers whereas for dynamically active glaciers, consequences will be negligible. The ice-flux field gives an indication on if consequences are expected to be large and where they will be most expressed. In any case, the error-estimate map will highlight areas where the correction is most important. For the main trunk of WSB, error estimates exceed by far the inferred thickness

values (Fig. 6b).

Author contributions. J.J.F. designed and implemented the reconstruction approach, applied it to the test cases and elaborated the details of the error estimation. The research aims and setup was developed in regular discussion with F.G.-C., T.S., B.S. and M.B. J.J.F. led the writing
of the manuscript, in which he received support from all authors. F.G.-C. developed and provided the initial version of the optimisation routines. Input fields for the reconstruction are Sentinel-1 surface velocities from T.S., ice thickness measurements from T.J.B., J.A.D., R.P., F.N. and M.G., DEMs from C.N. and B.S., surface elevation changes from C.N. and G.M., and surface mass balance fields from X.F., C.L. and K.A.

Competing interests. The authors declare that they have no conflict of interest.

30 Acknowledgements. This study received primary funding from the German Research Foundation (DFG) within the Svalbard - iFLOWbed project, grant number FU1032/1-1. Results presented in this publication are based on numerical simulations conducted at the high performance computing centre of the "Regionales Rechenzentrum Erlangen" (RRZE) of the University of Erlangen-Nuremberg. The reconstruction



Figure A5. Ice thickness for VIC (a,c) and THPB/WSB (b,d) as in Fig. 4. Here, the first-step flux solution is not corrected to avoid negative flux values in the SIA-equation used to infer the ice thickness (Sect. 2.2.4). For WSB, you see that many patches appear with very small thickness values. These bogus variations are a consequence of zero transitions in the flux field. For VIC and THPB such bogus variations are limited to some few small areas.

approach also benefits from co-development work of the Elmer/Ice team at the CSC-IT Center for Science Ltd (Finland). The velocity analysis on Svalbard was funded by DFG within the priority programme 1158 Antarctic Research under contract number BR2105/9-1 and received financial support from the Helmholtz Association of the German Research Centres (HGF) Alliance on Remote Sensing and Earth System Dynamics.Thickness data collection in Wedel Jarlsberg Land was funded by the Spanish R&D projects C11093001 and C150954001, the NCBiR/PolarCLIMATE-2009/2-2/2010 from the Polish National Centre for R&D, by the IPY/269/2006 from the Polish Ministry of Science and Higher Education, by Polish-Norwegian funding through the AWAKE (PNRF-22-AI-1/07) project, by the EU FP7 ice2sea programme (grant number 226375) and by funds of the Leading National Research Centre (KNOW) received by the Centre for Polar Studies of the University of Silesia, Poland. The DEM generation in Wedel Jarlsberg Land received financial support from the European Union/ERC (grant 320816) and from ESA (project Glaciers CCI, 4000109873/14/I-NB). TanDEM-X data was provided under AO XTIGLAC6770. The

5

WRF-SMB field was produced within the PERMANOR project funded by the Norwegian Research Council (255331).

References

- Aas, K., Dunse, T., Collier, E., Schuler, T., Berntsen, T., Kohler, J., and Luks, B.: The climatic mass balance of Svalbard glaciers: a 10-year simulation with a coupled atmosphere–glacier mass balance model, The Cryosphere, 10, 1089–1104, doi:10.5194/tc-10-1089-2016, 2016.
 Atwood, D. K., Meyer, F., and Arendt, A.: Using L-band SAR coherence to delineate glacier extent, Canadian Journal of Remote Sensing,
- Awood, D. K., Weyel, L., and Alendi, A.: Using L-band SAK concrete to define are graciel extent, Canadian Journal of Keniole Sensing
- 5 36, S186–S195, doi:10.5589/m10-014, http://dx.doi.org/10.5589/m10-014, 2010.
- Berthier, E., Cabot, V., Vincent, C., and Six, D.: Decadal Region-Wide and Glacier-Wide Mass Balances Derived from Multi-Temporal ASTER Satellite Digital Elevation Models. Validation over the Mont-Blanc Area, Frontiers in Earth Science, 4, 63, doi:10.3389/feart.2016.00063, http://journal.frontiersin.org/article/10.3389/feart.2016.00063, 2016.
- Berthier, E., Schiefer, E., Clarke, G., and Menounos, B.: Contribution of Alaskan glaciers to sea-level rise derived from satellite imagery,
 Nature Geoscience. 3, 92–95. doi:10.1038/ngeo737. http://www.nature.com/ngeo/iournal/v3/n2/suppinfo/ngeo737 S1.html, 2010.
- Bishop, M., Olsenholler, J., Shroder, J., Barry, R., Raup, B., Bush, A., Copland, L., Dwyer, J., Fountain, A., Haeberli, W., Kääb, A., Paul, F., Hall, D., Kargel, J., Molnia, B., Trabant, D., and Wessels, R.: Global Land Ice Measurements from Space (GLIMS): Remote Sensing and GIS Investigations of the Earth's Cryosphere, Geocarto International, 19, 57–84, doi:10.1080/10106040408542307, http://dx.doi.org/10. 1080/10106040408542307, 2004.
- 15 Błaszczyk, M., Jania, J., and Hagen, J.: Tidewater glaciers of Svalbard: Recent changes and estimates of calving fluxes, Polish Polar Research, 30, 85–142, 2009.
 - Błaszczyk, M., Jania, J., and Kolondra, L.: Fluctuations of tidewater glaciers in Hornsund Fjord (Southern Svalbard) since the beginning of the 20th century, Polish Polar Research, 34, 327–352, doi:10.2478/popore?2013?0024, 2013.
 - Braun, M., Pohjola, V., Pettersson, R., Möller, M., Finkelnburg, R., Falk, U., Scherer, D., and Schneider, C.: Changes of glacier frontal
- 20 positions of Vestfonna (Nordaustlandet, Svalbard), Geografiska Annaler: Series A, Physical Geography, 93, 301–310, doi:10.1111/j.1468-0459.2011.00437.x, http://dx.doi.org/10.1111/j.1468-0459.2011.00437.x, 2011.
 - Brinkerhoff, D. and Johnson, J.: A stabilized finite element method for calculating balance velocities in ice sheets, Geoscientific Model Development, 8, 1275–1283, doi:10.5194/gmd-8-1275-2015, http://www.geosci-model-dev.net/8/1275/2015/, 2015.

Brinkerhoff, D. J., Aschwanden, A., and Truffer, M.: Bayesian Inference of Subglacial Topography Using Mass Conservation, Frontiers in
 Earth Science, 4, 8, doi:10.3389/feart.2016.00008, http://journal.frontiersin.org/article/10.3389/feart.2016.00008, 2016.

Brooks, A. and Hughes, T.: Streamline upwind/Petrov-Galerkin formulations for convection dominated flows with particular emphasis on the incompressible Navier-Stokes equations, Computer Methods in Applied Mechanics and Engineering", 32, 199 – 259, doi:http://dx.doi.org/10.1016/0045-7825(82)90071-8, http://www.sciencedirect.com/science/article/pii/0045782582900718, 1982.

Carrivick, J., Davies, B., James, W., Quincey, D., and Glasser, N.: Distributed ice thickness and glacier volume in southern South Amer-

- 30 ica, Global and Planetary Change, 146, 122–132, doi:http://dx.doi.org/10.1016/j.gloplacha.2016.09.010, http://www.sciencedirect.com/ science/article/pii/S0921818116301515, 2016.
 - Clarke, G., Berthier, E., Schoof, C., and Jarosch, A.: Neural Networks Applied to Estimating Subglacial Topography and Glacier Volume, Journal of Climate, 22, 2146–2160, doi:10.1175/2008JCLI2572.1, http://dx.doi.org/10.1175/2008JCLI2572.1, 2009.
 - Clarke, G., Anslow, F., Jarosch, A., Radić, V., Menounos, B., Bolch, T., and Berthier, E.: Ice Volume and Subglacial Topography for
- 35 Western Canadian Glaciers from Mass Balance Fields, Thinning Rates, and a Bed Stress Model, Journal of Climate, 26, 4282–4303, doi:10.1175/JCLI-D-12-00513.1, http://dx.doi.org/10.1175/JCLI-D-12-00513.1, 2013.

Cuffey, K. and Paterson, W.: The Physics of Glaciers, Butterworth-Heinemann publications, Elsevier, 2010.

Dowdeswell, J.: Drainage-basin characteristics of Nordaustlandet ice caps, Svalbard, Journal of Glaciology, 32, 31–38, 1986a. Dowdeswell, J.: Remote sensing of ice cap outlet glacier fluctuations on Nordaustlandet, Svalbard, Polar Research, 4, 25–32, 1986b. Dowdeswell, J.: On the nature of Svalbard icebergs, Journal of Glaciology, 35, 224–234, 1989. Dowdeswell, J. and Collin, R.: Fast-flowing outlet glaciers on Svalbard ice caps, Geology, 18, 778–781, 1990.

- 5 Dowdeswell, J., Drewry, D., Cooper, A., and Gorman, M.: Digital mapping of the Nordaustlandet ice caps from airborne geophysical investigations, Annals of Glaciology, 8, 51–58, doi:10.1175/2010JCLI3656.1, 1986.
 - Fahnestock, M., Scambos, T., Moon, T., Gardner, A., Haran, T., and Klinger, M.: Rapid large-area mapping of ice flow using Landsat 8, Remote Sensing of Environment, 185, 84–94, doi:http://dx.doi.org/10.1016/j.rse.2015.11.023, http://www.sciencedirect.com/science/article/pii/S003442571530211X, 2016.
- 10 Fan, Q., Efrat, A., Koltun, V., Krishnan, S., and Venkatasubramanian, S.: Hardware-assisted Natural Neighbor Interpolation, In Proc. 7th Workshop on Algorithm Engineering and Experiments (ALENEX), 2005.
 - Farinotti, D., Huss, M., Bauder, A., and Funk, M.: An estimate of the glacier ice volume in the Swiss Alps, Global and Planetary Change, 68, 225–231, doi:10.1016/j.gloplacha.2009.05.004, 2009a.
 - Farinotti, D., Huss, M., Bauder, A., Funk, M., and Truffer, M.: A method to estimate the ice volume and ice-thickness distribution of alpine

15 glaciers, Journal of Glaciology, 55, 422–430, doi:10.3189/002214309788816759, 2009b.

- Farinotti, D., Brinkerhoff, D., Clarke, G., Fürst, J., Frey, H., Gantayat, P., Gillet-Chaulet, F., Girard, C., Huss, M., Leclercq, P., Linsbauer, A., Machguth, H., Martin, C., Maussion, F., Morlighem, M., Mosbeux, C., Pandit, A., Portmann, A., Rabatel, A., Ramsankaran, R., Reerink, T., Sanchez, O., Stentoft, P., Singh Kumari, S., van Pelt, W., Anderson, B., Benham, T., Binder, D., Dowdeswell, J., Fischer, A., Helfricht, K., Kutuzov, S., Lavrentiev, I., McNabb, R., Gudmundsson, G., Li, H., and Andreassen, L.: How accurate are estimates of
- 20 glacier ice thickness? Results from ITMIX, the Ice Thickness Models Intercomparison eXperiment, The Cryosphere Discussions, 2016, 1–34, doi:10.5194/tc-2016-250, http://www.the-cryosphere-discuss.net/tc-2016-250/, 2016.
 - Farr, T., Rosen, P., Caro, E., Crippen, R., Duren, R., Hensley, S., Kobrick, M., Paller, M., Rodriguez, E., Roth, L., Seal, D., Shaffer, S., Shimada, J., Umland, J., Werner, M., Oskin, M., Burbank, D., and Alsdorf, D.: The Shuttle Radar Topography Mission, Reviews of Geophysics, 45, doi:10.1029/2005RG000183, http://dx.doi.org/10.1029/2005RG000183, 2007.
- 25 Favier, L., Durand, G., Cornford, S., Gudmundsson, G., Gagliardini, O., Gillet-Chaulet, F., Zwinger, T., Payne, J., and LeBrocq, A.: Retreat of Pine Island Glacier controlled by marine ice-sheet instability, Nature Climate Change, 4, 117–121, doi:10.1038/nclimate2094, http: //dx.doi.org/10.1038/nclimate2094, 2014.
 - Franco, B., Fettweis, X., Lang, C., and Erpicum, M.: Impact of spatial resolution on the modelling of the Greenland ice sheet surface mass balance between 1990–2010, using the regional climate model MAR, The Cryosphere, 6, 695–711, doi:10.5194/tc-6-695-2012, 2012.
- 30 Frey, H., Machguth, H., Huss, M., Huggel, C., Bajracharya, S., Bolch, T., Kulkarni, A., Linsbauer, A., Salzmann, N., and Stoffel, M.: Estimating the volume of glaciers in the Himalayan-Karakoram region using different methods, The Cryosphere, 8, 2313–2333, doi:10.5194/tc-8-2313-2014, http://www.the-cryosphere.net/8/2313/2014/, 2014.

Fürst, J., Goelzer, H., and Huybrechts, P.: Effect of higher-order stress gradients on the centennial mass evolution of the Greenland ice sheet, The Cryosphere, 7, 183–199, doi:10.5194/tc-7-183-2013, 2013.

- 35 Fürst, J., Durand, G., Gillet-Chaulet, F., Tavard, L., Rankl, M., Braun, M., and Gagliardini, O.: The safety band of Antarctic ice shelves, Nature Climate Change, 6, 479–482, doi:10.1038/nclimate2912, 2016.
 - Gagliardini, O. and Zwinger, T.: The ISMIP-HOM benchmark experiments performed using the Finite-Element code Elmer, The Cryosphere, 2, 67–76, doi:10.5194/tc-2-67-2008, 2008.

Gagliardini, O., Zwinger, T., Gillet-Chaulet, F., Durand, G., Favier, L., de Fleurian, B., Greve, R., Malinen, M., Martín, C., Råback, P., Ruokolainen, J., Sacchettini, M., Schäfer, M., Seddik, H., and Thies, J.: Capabilities and performance of Elmer/Ice, a new-generation ice sheet model, Geophysical Model Development, 6, 1299–1318, doi:10.5194/gmd-6-1299-2013, 2013.

Gantayat, P., Kulkarni, A., and Srinivasan, J.: Estimation of ice thickness using surface velocities and slope: case study at Gangotri

- 5 Glacier, India, Journal of Glaciology, 60, 277–282, doi:doi:10.3189/2014JoG13J078, http://www.ingentaconnect.com/content/igsoc/jog/2014/00000060/00000220/art00007, 2014.
 - Gardelle, J., Berthier, E., and Arnaud, Y.: Impact of resolution and radar penetration on glacier elevation changes computed from DEM differencing, Journal of Glaciology, 58, 419–422, doi:0.3189/2012JoG11J175, 2012.
- Gardelle, J., Berthier, E., Arnaud, Y., and Kääb, A.: Region-wide glacier mass balances over the Pamir-Karakoram-Himalaya during 1999 2011. The Cryosphere. 7, 1263–1286. doi:10.5194/tc-7-1263-2013. http://www.the-cryosphere.net/7/1263/2013/. 2013.
- Gärtner-Roer, I., Naegeli, K., Huss, M., Knecht, T., Machguth, H., and Zemp, M.: A database of worldwide glacier thickness observations, Global and Planetary Change, 122, 330 – 344, doi:10.1016/j.gloplacha.2014.09.003, http://www.sciencedirect.com/science/article/pii/ S0921818114001878, 2014.

Gärtner-Roer, I., Andreassen, L., Bjerre, E., Farinotti, D., Fischer, A., Fischer, M., Helfricht, K., Huss, M., Knecht, T., Landmann, S. K. J., Li,

- 15 I. L. H., Li, Z., Machguth, H., Naegeli, K., Navarro, F., Rabatel, A., Stentoft, P., and Zemp (eds.), M.: WGMS (2016): Glacier Thickness Database 2.0., World Glacier Monitoring Service, Zurich, Switzerland, doi:10.5904/wgms-glathida-2016-07, 2016.
 - Geuzaine, C. and Remacle, J.: Gmsh: a three-dimensional finite element mesh generator with built-in pre- and post-processing facilities, International Journal for Numerical Methods in Engineering, 79, 1309–1331, 2009.
- Gilbert, J. and Lemaréchal, C.: Some numerical experiments with variable-storage quasi-Newton algorithms, Mathematical Programming,
 45, 407–435, 1989.
 - Gillet-Chaulet, F., Gagliardini, O., Seddik, H., Nodet, M., Durand, G., Ritz, C., Zwinger, T., Greve, R., and Vaughan, D.: Greenland ice sheet contribution to sea-level rise from a new-generation ice-sheet model, The Cryosphere, 6, 1561–1576, doi:10.5194/tc-6-1561-2012, 2012.
 - Grabiec, M., Jania, J., Puczko, D., Kolondra, L., and Budzik, T.: Surface and bed morphology of Hansbreen, a tidewater glacier in Spitsbergen, Polish Polar Research, 33, 111–138, doi:10.2478/v10183-012-0010-7, 2012.
- 25 Hindmarsh, R.: The role of membrane-like stresses in determining the stability and sensitivity of the Antarctic ice sheets: back pressure and grounding line motion, Philosophical Transactions of the Royal Society A, 364, 1733–1767, doi:10.1098/rsta.2006.1797, 2006.
 - Huss, M. and Farinotti, D.: Distributed ice thickness and volume of all glaciers around the globe, Journal of Geophysical Research, 117, 10 pp., doi:10.1029/2012JF002523, 2012.
 - Huss, M. and Hock, R.: A new model for global glacier change and sea-level rise, Frontiers of Earth Science, 3, 1261-1273,

doi:10.3389/feart.2015.00054, 2015.

- Hutter, K.: Theoretical glaciology. Material science of ice and the mechanics of glaciers and ice sheets, Publishing Company/Tokyo, Terra Scientific Publishing Company, Dordrecht, Boston, Tokyo, Japan, and Hingham, 1983.
- Ignatiuk, D., Piechota, A., Ciepły, M., and Luks, B.: Changes of altitudinal zones of Werenskioldbreen and Hansbreen in period 1990-2008, Svalbard, AIP Conference Proceedings, 1618, 275–280, doi:10.1063/1.4897727, 2014.
- 35 Jakobsson, M., Mayer, L., Coakley, B., Dowdeswell, J., Forbes, S., Fridman, B., Hodnesdal, H., Noormets, R., Pedersen, R., Rebesco, M., Schenke, H., Zarayskaya, Y., Accettella, D., Armstrong, A., Anderson, R., Bienhoff, P., Camerlenghi, A., Church, I., Edwards, M., Gardner, J., Hall, J., Hell, B., Hestvik, O., Kristoffersen, Y., Marcussen, C., Mohammad, R., Mosher, D., Nghiem, S., Pedrosa, M.,

Travaglini, P., and Weatherall, P.: The International Bathymetric Chart of the Arctic Ocean (IBCAO) Version 3.0, Geophysical Research Letters, 39, doi:10.1029/2012GL052219, http://dx.doi.org/10.1029/2012GL052219, 112609, 2012.

- Jania, J., Mochnacki, D., and Gądek, B.: The thermal structure of Hansbreen, a tidewater glacier in southern Spitsbergen, Svalbard, Polar Research, 15, 53–66, 1996.
- 5 Joughin, I., Smith, B., Howat, I., Scambos, T., and Moon, T.: Greenland flow variability from ice-sheet-wide velocity mapping, Journal of Glaciology, 56, 415–430, doi:10.3189/002214310792447734, 2010.
 - Kamb, B. and Echelmeyer, K.: Stress-Gradient Coupling Glacier Flow. 1. Longitudinal Averaging of the Influence of Ice Thickness and Surface Slope, Journal of Glaciology, 32, 267–284, 1986.

Korona, J., Berthier, E., Bernard, M., Rémy, F., and Thouvenot, E.: SPIRIT. {SPOT} 5 stereoscopic survey of Polar Ice: Reference Images

- and Topographies during the fourth International Polar Year (2007-2009), {ISPRS} Journal of Photogrammetry and Remote Sensing, 64, 204 212, doi:10.1016/j.isprsjprs.2008.10.005, 2009.
 - Krieger, G., Zink, M., Bachmann, M., Bräutigam, B., Schulze, D., Martone, M., Rizzoli, P., Steinbrecher, U., Walter Antony, J., De Zan, F., Hajnsek, I., Papathanassiou, K., Kugler, F., Rodriguez Cassola, M., Younis, M., Baumgartner, S., López-Dekker, P., Prats, P., and Moreira, A.: TanDEM-X: A radar interferometer with two formation-flying satellites, Acta Astronautica, 89, 83–89,
- 15 doi:10.1016/j.actaastro.2013.03.008, 2013.

35

Lang, C., Fettweis, X., and Erpicum, M.: Future climate and surface mass balance of Svalbard glaciers in an RCP8.5 climate scenario: a study with the regional climate model MAR forced by MIROC5, The Cryosphere, 9, 945–956, doi:10.5194/tc-9-945-2015, 2015.

Lapazaran, J., Otero, J., Martín-Español, A., and Navarro, F.: On the errors involved in ice-thickness estimates I: ground-penetrating radar measurement errors, Journal of Glaciology, 62, 1008–1020, doi:10.1017/jog.2016.93, 2016.

20 Linsbauer, A., Paul, F., and Haeberli, W.: Modeling glacier thickness distribution and bed topography over entire mountain ranges with GlabTop: Application of a fast and robust approach, Journal of Geophysical Research, 117, n/a–n/a, doi:10.1029/2011JF002313, http: //dx.doi.org/10.1029/2011JF002313, f03007, 2012.

Marzeion, B., Jarosch, A., and Hofer, M.: Past and future sea-level change from the surface mass balance of glaciers, The Cryosphere, 6, 1295–1322, doi:10.5194/tc-6-1295-2012, http://www.the-cryosphere.net/6/1295/2012/, 2012.

- 25 Marzeion, B., Cogley, J., Richter, K., and Parkes, D.: Attribution of global glacier mass loss to anthropogenic and natural causes, Science, 345, 919–921, doi:10.1126/science.1254702, http://science.sciencemag.org/content/345/6199/919, 2014.
 - McNabb, R., Hock, R., O'Neel, S., Rasmussen, L., Ahn, Y., Braun, M., Conway, H., Herreid, S., Joughin, I., Pfeffer, W., Smith, B., and Truffer, M.: Using surface velocities to calculate ice thickness and bed topography: a case study at Columbia Glacier, Alaska, USA, Journal of Glaciology, 58, 1151–1164, http://www.ingentaconnect.com/content/igsoc/jog/2012/00000058/00000212/art00011, 2012.
- 30 Moholdt, G., Nuth, C., Hagen, J., and Kohler, J.: Recent elevation changes of Svalbard glaciers derived from {ICESat} laser altimetry, Remote Sensing of Environment, 114, 2756–2767, doi:http://dx.doi.org/10.1016/j.rse.2010.06.008, http://www.sciencedirect.com/science/article/ pii/S0034425710001987, 2010.

Möller, M., Obleitner, F., Reijmer, C., Pohjola, V., Głowacki, P., and Kohler, J.: Adjustment of regional climate model output for modeling the climatic mass balance of all glaciers on Svalbard, Journal of Geophysical Research: Atmospheres, 121, 5411–5429, doi:10.1002/2015JD024380, http://dx.doi.org/10.1002/2015JD024380, 2016.

Moran, M., Greenfield, R., Arcone, S., and Delaney, A.: Delineation of a complexly dipping temperate glacier bed using short-pulse radar arrays, Journal of Glaciology, 46, 274–286, doi:doi:10.3189/172756500781832882, http://www.ingentaconnect.com/content/igsoc/jog/ 2000/00000046/00000153/art00012, 2000. Morland, L.: Unconfined ice-shelf flow, in: Dynamics of the West Antarctic ice sheet, Kluwer Academic Publishers, 1986.

Morlighem, M., Rignot, E., H. Seroussi, H., Larour, E., Ben Dhia, H., and Aubry, D.: A mass conservation approach for mapping glacier ice thickness, Geophysical Research Letters, 38, doi:10.1029/2011GL048659, http://dx.doi.org/10.1029/2011GL048659, 2011.

Morlighem, M., Rignot, E., Mouginot, J., Seroussi, H., and Larour, E.: Deeply incised submarine glacial valleys beneath the Greenland ice sheet, Nature Geoscience, 7, 418–422, doi:10.1038/ngeo2167, http://dx.doi.org/10.1038/ngeo2167, 2014.

- Mosbeux, C., Gillet-Chaulet, F., and Gagliardini, O.: Comparison of adjoint and nudging methods to initialise ice sheet model basal conditions, Geoscientific Model Development, 9, 2549–2562, doi:10.5194/gmd-9-2549-2016, http://www.geosci-model-dev.net/9/2549/2016/, 2016.
- Navarro, F., Martín-Español, A., Lapazaran, J., Grabiec, M., Otero, J., Vasilenko, E., and Puczko, D.: Ice Volume Estimates from
 Ground-Penetrating Radar Surveys, Wedel Jarlsberg Land Glaciers, Svalbard, Arctic, Antarctic, and Alpine Research, 46, 394–406, doi:10.1657/1938-4246-46.2.394, 2014.
 - Nuth, C. and Kääb, A.: Co-registration and bias corrections of satellite elevation data sets for quantifying glacier thickness change, The Cryosphere, 5, 271–290, doi:10.5194/tc-5-271-2011, 2011.

Nuth, C., Kohler, J., König, M., von Deschwanden, A., Hagen, J., Kääb, A., Moholdt, G., and Pettersson, R.: Decadal changes from a

15 multi-temporal glacier inventory of Svalbard, The Cryosphere, 7, 1603–1621, doi:10.5194/tc-7-1603-2013, 2013.

Ottesen, D., Dowdeswell, J., Landvik, J., and Mienert, J.: Dynamics of the Late Weichselian ice sheet on Svalbard inferred from high?resolution sea-floor morphology, Boreas, 36, 286–306, doi:10.1111/j.1502-3885.2007.tb01251.x, http:https://dx.doi.org/10.1111/j. 1502-3885.2007.tb01251.x, 2007.

Paolo, F., Fricker, H., and Padman, L.: Volume loss from Antarctic ice shelves is accelerating, Science, doi:10.1126/science.aaa0940, http://science.sciencemag.org/content/early/2015/03/25/science.aaa0940, 2015.

- Paul, F., Bolch, T., Kääb, A., Nagler, T., Nuth, C., Scharrer, K., Shepherd, A., Strozzi, T., Ticconi, F., Bhambri, R., Berthier, E., Bevan, S., Gourmelen, N., Heid, T., Jeong, S., Kunz, M., L., T. R., Luckman, A., Merryman Boncori, J., Moholdt, G., Muir, A., Neelmeijer, J., Rankl, M., VanLooy, J., and Van Niel, T.: The glaciers climate change initiative: Methods for creating glacier area, elevation change and velocity products, Remote Sensing of Environment, 162, 408–426, doi:http://dx.doi.org/10.1016/j.rse.2013.07.043, http://www.sciencedirect.com/
- 25 science/article/pii/S0034425713003532, 2015.

5

- Pettersson, R., Christoffersen, P., Dowdeswell, J., Pohjola, V., Hubbard, A., and Strozzi, T.: Ice thickness and basal conditions of Vestfonna Ice Cap, Eastern Svalbard, Geografiska Annaler: Series A, Physical Geography, 93, 311–322, doi:10.1111/j.1468-0459.2011.00438.x, 2011.
 - Pinglot, J., Pourchet, M., Lefauconnier, B., Hagen, J., Isaksson, E., Vaikmae, R., and Kamiyama, K.: Accumulation in Svalbard
- 30 glaciers deduced from ice cores with nuclear tests and Chernobyl reference layers, Polar Research, 18, 315–321, doi:10.1111/j.1751-8369.1999.tb00309.x, 1999.
 - Pinglot, J., Hagen, J., Melvold, K., Eiken, T., and Vincent, C.: A mean net accumulation pattern derived from radioactive layers and radar soundings on Austfonna, Nordaustlandet, Svalbard, Journal of Glaciology, 47, 555–566, doi:10.3189/172756501781831800, http://www. ingentaconnect.com/content/igsoc/jog/2001/00000047/00000159/art00004, 2001.
- 35 Pohjola, V., Christoffersen, P., Kolondra, L., Moore, J., Pettersson, R., Schäfer, M., Strozzi, T., and Reijmer, C.: Spatial distribution and change in the surface-velocity field of Vestfonna ice cap, Nordaustlandet, Svalbard, 1995-2010 using geodetic and satellite interferometry data, Geografiska Annaler: Series A, Physical Geography, 93, 323–335, doi:10.1111/j.1468-0459.2011.00441.x, http://dx.doi.org/10.1111/ j.1468-0459.2011.00441.x, 2011.

- Radić, V. and Hock, R.: Regionally differentiated contribution of mountain glaciers and ice caps to future sea-level rise, Nature Geoscience, 4, 91–94, doi:10.1038/ngeo1052, 2011.
- Radić, V., Bliss, A., Beedlow, A., Hock, R., and Cogley, E. M. J.: Regional and global projections of twenty-first century glacier mass changes in response to climate scenarios from global climate models, Climate Dynamics, 42, 37–58, doi:10.1007/s00382-013-1719-7, http://dx.doi.org/10.1007/s00382-013-1719-7, 2014.
- Rankl, M. and Braun, M.: Glacier elevation and mass changes over the central Karakoram region estimated from TanDEM-X and SRTM/X-SAR digital elevation models, Annals of Glaciology, 51, 273–281, doi:10.3189/2016AoG71A024, 2016.

Rankl, M., Kienholz, C., and Braun, M.: Glacier changes in the Karakoram region mapped by multimission satellite imagery, The Cryosphere, 8, 977–989, doi:10.5194/tc-8-977-2014, http://www.the-cryosphere.net/8/977/2014/, 2014.

- 10 Raup, B., Racoviteanu, A., Khalsa, S., Helm, C., Armstrong, R., and Arnaud, Y.: The GLIMS Geospatial Glacier Database: a New Tool for Studying Glacier Change, Global and Planetary Change, 56, 101–110, doi:10.1016/j.gloplacha.2006.07.018, 2007.
 - Rignot, E. and Mouginot, J.: Ice flow in Greenland for the International Polar Year 2008-2009, Geophysical Research Letters, 39, 7 pp., doi:10.1029/2012GL051634, 2012.

Rignot, E., Mouginot, J., and Scheuchl, B.: Ice Flow of the Antarctic Ice Sheet, Science, 333, 1427–1430, doi:10.1126/science.1208336,

15 2011.

5

Rosenau, R., Scheinert, M., and Dietrich, R.: A processing system to monitor Greenland outlet glacier velocity variations at decadal and seasonal time scales utilizing the Landsat imagery, Remote Sensing of Environment, 169, 1–19, doi:http://dx.doi.org/10.1016/j.rse.2015.07.012, http://www.sciencedirect.com/science/article/pii/S0034425715300742, 2015.

Schoof, C.: Ice sheet grounding line dynamics: Steady states, stability, and hysteresis, Journal of Geophysical Research, 112, 19 pp.,

20 doi:10.1029/2006JF000664, 2007.

Schoof, C.: Ice-sheet acceleration driven by melt supply variability, Nature, 468, 803–806, doi:10.1038/nature09618, 2010.

Schutz, B., Zwally, H., Shuman, C., Hancock, D., and DiMarzio, J.: Overview of the ICESat Mission, Geophysical Research Letters, 32, doi:10.1029/2005GL024009, 2005.

Schwaizer, G.: Performance assessment of the glacier ice velocity products for Greenland, and description of the evaluation methodology.

- In: Glaciers validation report, Issue 1.0, http://sen3app.fmi.fi/index.php?page=Deliverables_&style=main&p=2, 2016.
 - Seehaus, T., Marinsek, S., Helm, V., Skvarca, P., and Braun, M.: Changes in ice dynamics, elevation and mass discharge of Dinsmoor-Bombardier-Edgeworth glacier system, Antarctic Peninsula, Earth and Planetary Science Letters, 427, 125–135, doi:10.1016/j.epsl.2015.06.047, http://www.sciencedirect.com/science/article/pii/S0012821X15004100, 2015.

Seehaus, T., Marinsek, S., Skvarca, P., van Wessem, J., Reijmer, C., Seco, J., and Braun, M.: Dynamic Response of Sjögren Inlet Glaciers,

- 30 Antarctic Peninsula, to Ice Shelf Breakup Derived from Multi-Mission Remote Sensing Time Series, Frontiers in Earth Science, 4, 66, doi:10.3389/feart.2016.00066, http://journal.frontiersin.org/article/10.3389/feart.2016.00066, 2016.
 - Strozzi, T., Luckman, A., Murray, T., Wegmüller, U., and Werner, C. L.: Glacier motion estimation using SAR offset-tracking procedures, IEEE Transactions on Geoscience and Remote Sensing, 40, 2384–2391, doi:10.1109/TGRS.2002.805079, 2002.

Tachikawa, T., Hato, M., Kaku, M., and Iwasaki, A.: The characteristics of ASTER GDEM version 2, International Geoscience and Remote

- 35 Sensing Symposium Proceedings, 2011.
 - van Pelt, W., Oerlemans, J., Reijmer, C., Pettersson, R., Pohjola, V., Isaksson, E., and D.Divine: An iterative inverse method to estimate basal topography and initialize ice flow models, The Cryosphere, 7, 987–1006, doi:10.5194/tc-7-987-2013, http://www.the-cryosphere.net/7/987/2013/, 2013.

- Vijay, S. and Braun, M.: Elevation Change Rates of Glaciers in the Lahaul-Spiti (Western Himalaya, India) during 2000-2012 and 2012-2013, Remote Sensing, 8, doi:10.3390/rs8121038, http://www.mdpi.com/2072-4292/8/12/1038, 2016.
- Zwally, H., Li, J., Robbins, J., Saba, J., Yi, D., and Brenner, A.: Mass gains of the Antarctic ice sheet exceed losses, Journal of Glaciology, 61, 1019–1036, doi:10.3189/2015JoG15J071, http://www.ingentaconnect.com/content/igsoc/jog/2015/00000061/00000230/art00001, 2015.
- Zwally, H., Li, J., Brenner, A., Beckley, M., Cornejo, H., Dimarzio, J., Giovinetto, M., Neumann, T., Robbins, J., Saba, J., Yi, D., and Wang, W.: Greenland ice sheet mass balance: distribution of increased mass loss with climate warming; 2003-07 versus 1992-2002, Journal of Glaciology, 57, 88–102, doi:10.3189/002214311795306682, 2011.