# Effect of small-scale snow surface roughness on snow albedo and reflectance

Terhikki Manninen<sup>1</sup>, Kati Anttila<sup>1</sup>, Emmihenna Jääskeläinen<sup>1</sup>, Aku Riihelä<sup>1</sup>, Jouni Peltoniemi<sup>2</sup>, Petri Räisänen<sup>1</sup>, Panu Lahtinen<sup>1</sup>, Niilo Siljamo<sup>1</sup>, Laura Thölix<sup>1</sup>, Outi Meinander<sup>1</sup>, Anna Kontu<sup>1</sup>, Hanne Suokanerva<sup>1</sup>, Roberta Pirazzini<sup>1</sup>, Juha Suomalainen<sup>2</sup>, Teemu Hakala<sup>2</sup>, Sanna Kaasalainen<sup>2</sup>, Harri Kaartinen<sup>2, 3</sup>, Antero Kukko<sup>2, 4</sup>, Olivier Hautecoeur<sup>5</sup> and Jean-Louis Roujean<sup>6</sup>

<sup>1</sup>Finnish Meteorological Institute, Helsinki, P.O. Box 503, FI-00101, Finland
 <sup>2</sup>Finnish Geospatial Research Institute/National Land Survey, Geodeetinrinne 2, 02430 Masala, Finland
 <sup>3</sup> University of Turku, Department of Geography and Geology, 20500 Turku, Finland
 <sup>4</sup>Aalto University, Department of Built Environment, 02150 Espoo, Finland
 <sup>5</sup>Météo-France, currently at Exostaff GmbH/EUMETSAT
 <sup>6</sup> Centre d'Etudes Spatiales de la BIOsphère (CESBIO) - UMR 5126 - 31401 Toulouse, France

Correspondence to: Terhikki Manninen (Terhikki.Manninen@fmi.fi)

Abstract. The primary goal of this paper is to present a model of snow surface albedo accounting for small-scale surface roughness effects. The model is based on photon recollision probability and it can be combined with existing bulk volume albedo models, such as TARTES. The model is fed with in situ measurements of surface roughness from plate profile and laser scanner data, and it is evaluated by comparing the computed albedos with observations. It provides closer results to empirical values than volume scattering based albedo simulations alone. The impact of surface roughness on albedo increases with the progress of the melting season and is larger for larger solar zenith angles. In absolute terms, small-scale surface roughness can

20 decrease the total albedo by up to about 0.1. As regards the bidirectional reflectance factor (BRF), it is found that surface roughness increases backward scattering especially for large solar zenith angle values.

#### 1 Introduction

5

The global energy budget is affected by surface albedo, which describes the level of brightness of the surface. Due to its central role for climate, it has been defined as an essential climate variable (ECV) by the Implementation Plan for Global Observing

- 25 System for Climate in support of the United Nations Framework Convention on Climate Change (GCOS Secretariat 2006). The large areal coverage of seasonal snow, together with the high reflectivity of snow, contributes to the relevance of snow albedo on the global energy budget (Flanner et al., 2011; Mialon et al., 2005). Snow component is also important for the liveability of dry and cold areas for both humans and ecosystems by providing a source of melt water in spring and shelter and insulation in winter. Changes in the duration of snow cover and snow type are vital for people and ecology of these areas.
- 30 Accurate large-scale monitoring of snow properties over large areas is only feasible in practice using satellite data-based methods. Prior to that, it is required to obtain a detailed understanding of the reflectivity and scattering properties of snow.

The surface reflectivity of snow depends on grain size, shape and impurity content, which are the basic properties for handling the volume scattering of snow. Traditionally snow grain size is characterized by its largest diameter, whereas it has been

- 35 demonstrated that the specific surface area (SSA) is a more appropriate variable to describe the scattering area per volume (Domine et al., 2012; Leppänen et al., 2015). Light attenuation within the snowpack is related to the density of the scattering elements per unit volume. In addition, layer structure, grain shape, anthropogenic and natural impurities (such as black carbon, dust and algae) and close-packing effects of snow grains affect scattering properties and thus, the albedo of a snowpack (Warren and Wiscombe, 1980; Kokhanovsky and Zege, 2004; Aoki et al., 2011; Kokhanovsky, 2013; Libois et al., 2013;
- 40 Libois et al., 2014; Komuro and Suzuki, 2015; Peltoniemi et al., 2015; Pirazzini et al., 2015; Räisänen et al., 2015; Cook et al., 2017; He et al., 2017, Kokhanovsky et al., 2018). Several models for the coupled mass and energy balances of snow on the ground have also been developed (Flanner and Zender, 2006; Essery, 2015). The decrease of snow albedo due to shadowing effects of larger-scale topography (Picard et al., 2020) and surface features such as sastrugi and crevasses have also been investigated both from the point of view of measurement and modelling (Leroux and Fily, 1998; Warren et al., 1998;
- 45 Zhuravleva and Kokhanovsky, 2011; Lhermitte et al., 2014). But smaller-scale (mm to 10 cm) surface roughness has so far received poor attention in snow albedo modelling. Very recently, a study was published about artificially generated surface roughness in cm scale (Larue et al., 2020).

Snow grain size can also be related to micro-scale surface roughness. Initially snow surface is formed by falling snowflakes, which attach to the surface at first contact instead of being arranged according to the positions of minimum energy (Löwe et al. 2007). Surface crystals are rearranged and shaped by the winds near the surface through saltation, which is the transport of snow in periodic contact with and directly above the snow surface. This process is governed by both the atmospheric shear forces and the moving snow particles (Pomeroy and Gray, 1990). The wind both breaks the particles into smaller pieces and helps the grains grow mass from the air moisture (Armstrong & Brun 2008). These atmosphere-surface interactions create some links between local small-scale surface roughness and the grain size properties of the topmost layers in the snowpack. Moreover, the physical processes governing the snow grain metamorphism (temperature gradient, absorption of solar radiation, water vapor diffusion, liquid water formation) also affect the stickiness and, thus, the aggregation of grains (Löwe et al., 2007), which is associated to the formation of mm-cm-scale surface roughness.

- 60 If the surface were completely isotropic, the surface albedo might in many cases be well explained using only the grain size as a descriptor of the snowpack of sufficient thickness to be semi-infinite from the scattering point of view. But typically, the surface structure slopes and snow properties influenced by wind are not identical in the windward and leeward sides (Sommer et al., 2018). This means that in clear-sky conditions the albedo will not necessarily be the same for azimuthally opposite viewing directions, when the saltation effect is marked. In addition, hoar frost formation depends more on the air temperature
- and humidity than the grain size of the existing snowpack. All in all, despite the dominant character of the snow grain size to

the scattering from a snowpack, the small-scale surface roughness has also a role independent of the snow grain size that should be paid attention to. This study focuses on the effect of surface roughness on snow albedo.

Here, a method taking into account the small-scale surface roughness in addition to the normal bulk volume scattering is
developed for the black-sky (directional-hemispherical reflectance DHR), white-sky (bihemispherical reflectance BHR in isotropic diffuse illumination) and blue-sky albedo (bihemispherical reflectance BHR in ambient illumination) (Lucht et al., 2000; Schaepman-Strub et al., 2006). The main points of the model are described in Section 3.2 and detailed equations are derived in Appendix A. The TARTES snow model is used to simulate the albedo of a smooth snowpack (Warren, 1984; Warren and Brandt, 2008; Kokhanovsky and Zege, 2004; Baldridge et al., 2009; Libois et al., 2013; Libois et al., 2016; Picard et al.,

75 2016).

The rough snowpack albedo model is tested with measurements carried out during the SNOw Reflectance Transition EXperiment (SNORTEX) campaign (Roujean et al., 2010; Manninen and Roujean, 2014) in Sodankylä, Finnish Lapland in March – April, 2009 and in March 2010 augmented with operational albedo measurements that Finnish Meteorological

- 80 Institute (FMI) carries out in The Arctic Space Centre of FMI in Tähtelä, Sodankylä. The physical properties of snow during the campaign were measured from snow pit profiles. The modelled albedo is compared with measured albedo values in diffuse and clear sky cases. The diverse snow measurements are briefly described in Section 2 and more details are available in the given references. The high-resolution surface roughness profiles obtained using a scaled plate (Section 2.1) were also analysed with ray tracing calculations to obtain the directional scattering characteristics related to the small scale surface roughness.
- 85 The BRF thus obtained was compared to empirical BRFs provided by FIGIFIGO measurements (Peltoniemi et al., 2005, 2015, 2014; Section 2.8). The varying role of the small-scale roughness from midwinter conditions throughout the melting season is demonstrated in Section 4.

#### 2 Data

#### 90 **2.1 Test area**

Diverse properties of snow were measured in Sodankylä, northern Finland in March and April, 2009 and in March 2010 in an area of about 10 km x 10 km (Figure 1, Manninen and Roujean, 2014). Every day, measurements were made at about half a dozen test sites in one land cover type (either forest or open areas, the latter being typically aapa mire). The last (first) test site of the day was in 2009 (2010) in the NorSEN mast area (67.3621°N, 26.63445°E), which is located in similar terrain about

95 550 m from the place, where FMI conducts operational surface albedo measurements (67.36664°N, 26.628253°E downward, 67.36695°N, 26.62973°E reflected). Hence, the operational albedo values should be representative for the time series of the snow pit measurements at the NorSEN mast.

#### 2.2 Grain size and density profiles of snowpack

Measurements of snow depth, total density, water equivalent (SWE), humidity profile, temperature profile, grain size profile,

- 100 surface roughness and surface impurity content were carried out at snow pits located in Sodankylä in an area with corner coordinates (67.36°N, 26.63°E; 67.45°N, 26.86°E) in March and April, 2009 and in March 2010 (Manninen and Roujean, 2014). In addition crystal size photos of the snow layers, surface roughness photos and photos of the top surface impurities were taken. In this study we concentrate on the values measured in 2009. The air temperature in March was mostly below 0°C, whereas in April it was almost all the time above 0°C (Table 1). Hence, April represents the melting season and March is still
- 105 midwinter. This is also clear from the increase in median density of the snowpack and the decrease of median snow water equivalent value from March to April. About 40 snow pit measurement points were located in a larger area ( $67.42^{\circ}$ N,  $26.04^{\circ}$ E;  $67.85^{\circ}$ N,  $26.91^{\circ}$ E), where the maximum measured snow depth was 0.92 m in March and 0.76 m in April. The total density varied in the range 180 - 320 kg m<sup>-3</sup> in March and in the range 270 - 570 kg m<sup>-3</sup> in April. The corresponding variation ranges for the snow water equivalent were 0.020 - 0.250 m and 0.034 - 0.239 m, but in April there was plain water in several places
- 110 in the snowpack. Hence, the area covered by the snow pit measurements represents the local variation of snow properties to a large extent.

The traditional snow grain size (the largest dimension of the snow grains, Fierz et al, 2009) was visually estimated using graded plates, collecting the snow crystals from 10 cm-thick snow layers from the bottom to the top of the snowpack. For each analysed

- 115 sample of snow crystals, in addition to the typical value of the largest grain dimension also its minimum and maximum value were provided. The measured snow grain sizes differ from the optically equivalent snow grain size (Mätzler, 1997; Neshyba et al., 2003). To partly compensate for this, the minima of the largest grain diameter were applied in the radiative transfer calculations as the effective diameter. Although this causes some uncertainty in the interpretation of the computed absolute albedo values (particularly for the cases of fresh snow) it has much less impact on the derived effect of small-scale surface
- 120 roughness on snow albedo. The density profile of the snowpack was measured for the same layer structure using the snow fork (Toikka, 1992). The variation range of the grain size and density is shown for the surface layer and for the whole snowpack in Table 2.

#### 2.3 Surface roughness from plate measurements

125 The surface roughness up to 1 m scale was measured in March and April, 2009 and in March 2010 by taking photos of a graded plate placed perpendicularly in the snowpack (Figure 2). The snow surface profiles were automatically calculated from the photos using an image processing technique and the scale at the edge of the plate (Manninen et al., 2012). Control points at the scales were used both for the removal of the barrel distortion of the camera optics and transformation of the pixel coordinates to millimetres with photogrammetric methods. The plate surface roughness measurements were carried out at the 130 same sites as the snow pit measurements (Section 2.2). At each site, profiles were measured in two perpendicular directions with a 1 m interval along 50 m to 100 m distance.

The surface profiles were used to derive the root mean square (rms) height and correlation and their distance dependence (Keller et al., 1987; Church, 1988). Details of the multiscale roughness theory are described by Manninen (2003) and its

application to the snow profiles is presented by Anttila et al. (2014). The snow surface roughness is close to a Brownian fractal surface (Anttila et al., 2014) so that the logarithm of the rms height  $\sigma$  depends linearly on the logarithm of the length x of the analysed profile used for its calculation and the corresponding correlation length L is linearly related to x

$$\log \sigma = a + b \log x \tag{1}$$

$$140 \quad L = k_0 + kx$$

where *a*, *b*,  $k_0$  and *k* are constants and  $k_0 = 0$  for an ideal Brownian surface (Russ, 1994). For each profile the values of the constants were calculated by linear regression using varying sliding window sizes, i.e. varying values of *x* (Anttila et al., 2014).

(2)

In addition, the rms slope angles  $\beta$ , i.e. arcus tangent of the slopes ( $\beta = \arctan(\Delta z/\Delta x)$ ), were calculated for the measured spatial resolution, which was on the average 0.26 mm. The vertical precision was about 0.1 mm and the horizontal precision 0.04 mm (Manninen et al., 2012).

#### 2.4 Surface roughness from laser scanning

- 150 In addition to the plate measurements, laser scanning data for snow roughness was utilized. The laser scanning data used in this study has been acquired using the FGI ROAMER system (Kukko et al. 2007). The system, including a FARO Photon 120 laser scanner, a NovAtel SPAN GPS-IMU system, and data synchronizing and recording devices, was mounted on a sledge, which was towed by a snow mobile. The data acquisition covers a 2.5 kilometres zone at each side of an official snow mobile track (see Kukko et al. 2013 for examples of profiles, the snowmobile track and other details). The landscape covered sparse
- 155 pine forests and open bogs. The absolute precision of these measurements was analysed by Kaasalainen et al. (2011) to be better than 5 cm, while the relative accuracy (which is more relevant for observing the snow roughness) was found to be 0.7 mm 2 mm for a static system, and better than 10 mm when the snowmobile was moving. The best repeatability was achieved at ranges closer to the scanning system, i.e., below 5 m. The data quality and precision were controlled using control points measured with a VRS-GPS (Leica SR530 receiver + AT502 antenna) precision GPS.
- 160

The laser profiles (about 16 profiles per 1m at 3 m/s snow mobile velocity) measured on March 18, 2010 were used to analyse the variation of the slope angles in a larger area than was possible using the plate profiles. The profiles covered an area that

was 2.4 km long and the width extended into 3.2 m at both sides of the snow mobile. The slope angles for successive points were determined for each scan of the whole data set. The slope angles were then binned according to the horizontal distance

165 between the successive points, with a bin width of 10<sup>-5</sup> m. Then the root-mean-square value of the slope angles was determined for each horizontal distance bin and a regression function for the dependence of slope angles on distance between successive points was derived.

#### 2.5 Snow impurity content

170 The snow impurity was measured by filtering a melted sample of snow. The Quartz filters were analysed using NIOSH 5040 protocol. The increase of the median amount of impurities from March to April is obvious from Table 1 (Meinander et al., 2013; Meinander et al., 2014; Meinander et al. 2020). The detection limit of the thermal-optical OCEC method is 0.2 ugC and the uncertainty of the OCEC is estimated to be  $\pm 0.2 \ \mu gC$  ( $\pm 5\%$  relative error for higher loaded samples). The relative portion ( $\pm 5\%$ ) is composed of the instrument variation and slight variations due to sample deposit in-homogeneity and sample 175 handling, as we recently discussed more in detail in Meinander et al. (2020).

#### 2.6 Surface albedo

The surface albedo was operationally measured at Sodankylä (67.36664°N, 26.628253°E downward, 67.36695°N, 26.62973°E reflected) with a one minute interval using Kipp & Zonen CM11 Pyranometers. The site is surrounded by trees and houses, so

- 180 that shadowing takes place in certain azimuth directions, when the solar elevation is very low. Hence, the measured white-sky albedo values are considered more reliable than the blue-sky values. The least shadowed azimuth direction in early March corresponded to the solar zenith angle value of 73° in the afternoon. Thus, the blue-sky albedo values used in the analysis were all taken from the afternoon, when the solar zenith angle equalled 73°. This means that the azimuth direction used increased a bit during the spring, but it did not cause any additional shadowing problem. Yet, the clear-sky albedo of March 12 was
- 185 replaced with the diffuse albedo dominating that day, because the clear-sky albedo value of a narrow time window seemed unrealistically small. Albedo values measured at the NorSEN mast on April 21, 2009 using a portable Kipp & Zonen CM 14 albedometer were used to calibrate the operationally measured albedo data in order to correct for the slight difference in location of the upward and downward looking pyranometer used for operational measurements.
- 190 The portable albedometer was used in April 2009 to measure the snow surface albedo in the same areas where the snow pits were made (Section 2.2). The instrument was installed on a short boom affixed on a lightweight camera tripod for easy transport. The tripod legs affect somewhat the reflected radiation measurements, and therefore a first-order correction, multiplication by 1.055, was applied. It was based on estimation of the solid angle blocked by the tripod legs from fisheye lens photograph with a camera mounted onto the albedometer position on the tripod, assuming a constant albedo of 0.1 for the dark

195 carbon fibre legs. The albedometer was calibrated against a reference pyranometer at FMI-Helsinki prior to each campaign. The albedometer was carefully levelled on the tripod before measurements at each location and the stability of levelling monitored regularly, as melting snow may become unstable during the day.

#### 2.7 Spectral reflectance

- 200 The spectral reflectance of snow was measured using the ASD FieldSpec Pro JR spectrometer on several days, specifically in the perfectly overcast conditions on March 13 and on the perfectly clear-sky day April 22, during the campaign in 2009. The irradiance spectra were measured as well. Every spectrum is an average of 30 individual spectra. The spectrometer was calibrated by the manufacturer prior to the campaigns. The instrument was powered on at least 15-20 minutes before each measurement to ensure an even operating temperature. A Spectralon panel (0.125 x 0.125 m<sup>2</sup>) was used as white reference for
- 205 the reflectance measurements. The spectralon was housed in a container with two orthogonal spirit levels, placed on the snow and leveled. Narrow-view foreoptics were used to ensure that the FOV fits fully onto the spectralon. This was further visually confirmed by looking through the foreoptic before inserting the fiber optic cable. The white reference was measured and then the tripod was carefully rotated so that the foreoptic pointed into pristine snow. Tripod leg shadowing on the measured area was carefully avoided for both white reference and snow measurements. Most measurements took place from a height of 0.5

210 - 0.6 m with an 8-degree foreoptic. The spectrometer was optimized before each measurement.

#### 2.8 BRF

The bidirectional reflectance factor BRF of snow was measured using the Finnish Geodetic Institute's Field Goniospectrometer FIGIFIGO (Peltoniemi et al., 2005, 2015, 2014). FIGIFIGO consists of a motorized arm of length of 2 m, moving the optics head +-90 degree around nadir, and an ASD Field Spec PRO FR spectrometer recording the spectrum in the range of 350 – 2400 nm. The azimuth is turned manually, and all angles and coordinates are recorded automatically, based on inclination, direction, and position sensors. The footprint is around 0.10 m in diameter. FIGIFIGO gives spectrally resolved BRF data, relative to Spectralon reference standard (of the size of 0.25 x 0.25 m<sup>2</sup>, connected to a screw adjustable mount and levelled with a bubble level), from which also spectral albedo can be evaluated by fitting a polynomial function and integrating over

220 the hemisphere. However, as the system is not absolutely calibrated in the field setup, external solar spectrum is needed for deriving real broadband albedos and BRF. In the results shown, a mean solar spectrum is used that may differ several percent from the real time one.

In Mantovaaranaapa, 3 sets of rough snow were measured, and one set of smoother snow formed by a thin layer of windblown grains. Another set of thin and rough snow was measured in Korppiaapa, but were not used in the present study. The sunlight

measurements were complemented by set of artificial light measurements of smoother snow near the NorSEN mast.

#### 3 Methods

#### 3.1 Smooth snowpack albedo modelling

- 230 The TARTES model (available at: <u>https://snowtartes.pythonanywhere.com/</u>) was used to estimate the snowpack white-sky and black-sky albedo values (Warren, 1984; Warren and Brandt, 2008; Kokhanovsky and Zege, 2004; Baldridge et al., 2009; Libois et al., 2013; Libois et al., 2016; Picard et al., 2016). It is a fast and easy-to-use optical radiative transfer model and represents the snowpack as a stack of horizontal homogeneous layers. Each layer is characterized by the snow grain size, snow density, impurities amount and type, and two parameters for the geometric grain shape: the asymmetry factor and the
- 235 absorption enhancement parameter. The albedo of the bottom interface can be prescribed (here 0.13), although the bottom interface only markedly impacts thin snowpacks (<5 cm depth). The model is based on the Kokhanovsky and Zege (2004) formalism. The required input values for the model (density and grain size profile) were provided by the snow pit measurements of the SNORTEX campaign (Manninen and Roujean, 2014; Section 2.2). The amount of impurities was temporally interpolated from the values of measured days. The black-sky albedo values of the bulk snowpack were derived by</p>
- 240 weighting the spectral albedo with the standard top of atmosphere (TOA) spectrum ASTMG173. The white-sky albedo values of the bulk snowpack were derived by weighting the spectral albedo with measured diffuse irradiance spectra of the cloudy day March 13, 2009.

The black-sky albedo values were calculated for three local incidence angle values of each plate surface roughness profile: the mean, mean minus one standard deviation and the mean plus one standard deviation of the individual local incidence angle values determined for each slope of the surface roughness profiles. The nominal incidence angle was set to the solar zenith angle value at the time of the measurements of the plate surface roughness profiles and the density and grain size values of the snowpack layers. The blue-sky albedo values were obtained from the black-sky and white-sky albedo values using the fraction of diffuse irradiance operationally measured at Tähtelä.

250

#### 3.2 Rough snowpack albedo modelling

From the theoretical point of view there is a difference in scattering from a snowpack having an ideally planar surface and a rough surface, because the rough surface may have an incidence angle distribution that markedly differs from the Gaussian distribution of incidence angles produced by a random volume of spherical scatterers partly shading each other. In addition,

the roughness may cause a markedly higher amount of multiple scattering thus reducing the amount of radiation escaping the target.

Scattering from randomly rough continuous surfaces is related to the characteristic size of the surface roughness with respect to the wavelength used (Beckmann and Spizzicchino, 1963; Ulaby et al, 1982; Tsang et al., 1985, Fung, 1994). When the

- surface roughness of a randomly rough continuous surface is large compared to the wavelength of the electromagnetic wave, the scattering of the wave from the surface can be approximated by scattering from random facets (i.e. using the Kirchhoff approximation), whose slopes determine the scattering directions. As the shortwave illumination covers the wavelength range of about 300 nm 2500 nm, all structures in the mm scale (or above) are large compared to the wavelength, so that a facet-based surface scattering calculation is reasonable. Each facet is taken to represent a volume of random scatterers and the local
- 265 incidence angle of the incoming radiation is the angle between the normal of the facet and the solar zenith angle (Figure 3). The surface of a snowpack is not a continuous solid surface, but when the snowpack surface is rough, the incidence angle distributions of the scattering elements may deviate from that of a planar surface with randomly oriented scatterers. In addition, it is possible that a photon escaping one facet hits another facet. The snowpack scattering can then be thought to have elements both of bulk volume scattering and surface scattering. The following 2D analysis demonstrates this idea.
- 270

275

Multiple scattering between facets can be taken into account using the photon recollision probability theory (Knyazikhin et al., 1998; Panferov et al., 2001; Smolander and Stenberg, 2005; Rautiainen and Stenberg, 2005; Stenberg et al., 2008; Stenberg and Manninen, 2015; Stenberg et al., 2016). The formulation is shown in Appendix A separately for diffuse and direct irradiance. The essential equations are repeated here. Firstly, for the diffuse case, the white-sky albedo  $\alpha_w$  (Lucht et al., 2000, Schaepman-Strub et al., 2006) is related to the average number of facet-to-facet scattering events <n>

$$\alpha_w = \alpha_{w0}^{+1} \tag{3}$$

where  $\alpha_{w0}$  is the white-sky albedo of the bulk volume.

280

Second, for direct illumination, the black-sky albedo  $\alpha_b(\theta_i)$  (Lucht et al., 2000, Schaepman-Strub et al., 2006) is approximately related to the  $\alpha_{w0}$ ,  $\langle n \rangle$  and the average number  $\langle m(\theta_i) \rangle$  of facet-to-facet scattering events in direct illumination conditions by

$$\alpha_b = \alpha_{b0} \alpha_{w0}^{} \frac{(1 - \alpha_{w0}^{+1})}{(1 - \alpha_{w0}^{+1})} \tag{4}$$

285

where  $\alpha_{b0}(\theta_i)$  is the black-sky albedo of the bulk part of the snowpack (i.e. the albedo without the surface roughness contribution). In this study the bulk albedo values  $\alpha_{w0}$  are produced using the TARTES model (Section 3.1).

The albedo  $\alpha$  in mixed illumination conditions is typically estimated using the weighted mean approximation of the two extreme values  $\alpha_w$  and  $\alpha_b$  (Lucht et al., 2000, Schaepman-Strub et al., 2006; Román et al., 2010)

$$\alpha = f\alpha_w + (1 - f)\alpha_b$$

(5)

where f is the fraction of diffuse irradiance. According to Eqs. 3 - 5 the blue-sky albedo is then estimated from

295

$$\alpha = \left( f \alpha_{w0}^{+1} + (1-f) \alpha_{b0} \alpha_{w0}^{} \frac{(1-\alpha_{w0}^{+1})}{(1-\alpha_{w0}^{+1})} \right) = \alpha_{w0}^{} \left( f \alpha_{w0} + (1-f) \alpha_{b0} \frac{(1-\alpha_{w0}^{+1})}{(1-\alpha_{w0}^{+1})} \right) \quad . \tag{6}$$

Obviously, surface roughness decreases the white-sky albedo and typically also the black-sky and blue-sky albedo. Only when  $\langle m \rangle$  is larger than  $\langle n \rangle$ , surface roughness can increase the black-sky albedo of bright targets. The effect of surface roughness 300 is non-negligible even when the roughness is not large. On the other hand, the larger the roughness is (i.e. the larger  $\langle n \rangle$  and  $\langle m \rangle$  are), the larger the effect is for darker targets. Hence, for snow the effect is larger in the near-infrared than in the visible wavelengths and in midwinter roughness alters the broadband albedo only slightly, whereas during the melting season, when the snow is darker, the effect of the roughness may be much larger. Thus, the effect of surface roughness would be larger for old snow than for new snow, which may explain part of the quick darkening of snow during the melting season.

305

#### 3.3 Ray tracing analysis of surface roughness

,

Scattering from the snow profiles measured using the plate was analysed by a ray tracing method using 1000 equally spaced rays per profile per direction. The number of hits  $n_s$  on the surface (unity for single reflection and larger for multiple surface scattering) and the direction of the escaping reflected ray was calculated as a function of the zenith angle of the incoming ray

- 310 with an interval of two degrees from 0° to 80°. Scattering from the surfaces was calculated by assuming mirror reflection from smooth facets of continuous material, which has often been also assumed in the computation of ice crystal single-scattering properties in the solar spectral region (Nousiainen and McFarquhar, 2004; Zhang et al., 2004). This approximation neglects the impact on scattering due to snow structures smaller than the measurement resolution (~0.1 mm for plate measurements). For each angle the case was calculated separately for rays coming from the left and from the right and the two results were unified
- 315 to improve statistics. This choice was motivated by the known fact that, even when the snow is highly forward scattering, it is with respect to the direction of the incoming solar radiation, not the wind direction. Thus, the dominant scattering direction moves with the sun during the day. In some cases, the ray was trapped to infinite reflection from facet to facet. But these quite rare (<1 %) cases were excluded from the statistical analysis. Since the surface roughness profiles produce only 2D information and scattering angles differ markedly in 2D and 3D, the calculated ray tracing based 2D BRFs were converted to 3D versions</p>
- assuming that each facet has besides the measured vertical angle also an azimuth angle obeying a random uniform distribution between 0 and 180°. In fact, calculations were made for the range  $0 - 90^\circ$ , assuming the case to be symmetrical with respect

to azimuth angle, like in constructing the FIGIFIGO based BRFs. The 3D conversions make the peaks of the 2D scattering angle distributions slightly less distinct. No atmospheric contribution was included in either data set.

325 Late in spring the scattering from a snowpack often also contains a component that is something between volume and surface scattering, namely deep narrow pits generated by impurities that have sunk downwards in the snowpack due to melting caused by absorption of solar radiation. This kind of an effect is not easy to take into account either in volume scattering or surface scattering, because they don't affect the roughness or density in a random way. Their contribution to albedo is beyond the scope of this study.

330

#### 4 Results

#### 4.1 Surface roughness and inputs for albedo modelling

To start with, we consider the snow surface roughness from the plate measurements. The rms slope angle calculated from the plate roughness measurements had an increasing trend from March to April (Figure 4). The surface height distributions

- 335 developed towards a more Gaussian distribution from March ( $R^2 = 0.97$ ) to April ( $R^2 = 0.99$ ). However, it should be noted that individual profiles could deviate markedly from Gaussianity, as evidenced by the ratio of skewness to standard deviation. The 90% quantile of this ratio for individual profiles was 0.36 in March and 0.13 in April. The ratio was not negligible for the monthly average distributions either (0.17 in March and -0.04 in April). Furthermore, the autocorrelation functions were in most cases not Gaussian (Anttila et al. 2014). The most common (41 %) autocorrelation function (ACF)
- 340 types was multiscale exponential and 66 % of the profiles had multiscale ACF (Anttila et al., 2014).

The mean number of individual reflections  $n_s$  per ray on the surface has an increasing trend during the melting season (Figure 5). It correlates well ( $R^2 = 0.83$ ) with the rms slope angle ( $\beta$ , in radians) of the profile. A good general fit to all measured plate profile data was

345

$$n_s = 1 + 0.355332 \cos \theta_i^4 \beta - 1.08275 \left( 1 - \exp\left( 1.75 \cos \theta_i^{1/4} \beta^4 \right) \right)$$
(7)

where  $\boldsymbol{\theta}_i$  is the solar zenith angle. The mean zenith angle  $\boldsymbol{\theta}_o$  to which the radiation escapes from the surface (when mirror reflection from the facet is assumed) is even more strongly correlated ( $R^2 = 0.93$ ) with  $\beta$  (Figure 6)

$$\theta_o = -0.925239 \left( 1 - \frac{1}{(1 + 0.25 \, \theta_i)^{\frac{3}{2}}} \right) - 1.29982 \left( 1 - \frac{1}{(1 + 0.75 \, \theta_i)^{\frac{3}{2}}} \right) \log(\beta)$$
(8)

All angles ( $\beta$ ,  $\theta_i$ ,  $\theta_o$ ) are given in radians in the above equations, and  $\theta_o > 0$  ( $\theta_o < 0$ ) for forward-scattering (backward scattering). Obviously, the probability for backward scattering increases with increasing incidence angle and increasing  $\beta$ .

355 Since  $\beta$  increases with time, also the probability for stronger backscattering from the snow cover increases with time. Indeed, it is well known that older snow cover is less strongly forward scattering than new midwinter snow (Peltoniemi et al., 2010).

Unfortunately, the  $\beta$  values depend strongly on the scale of the measurements. The laser scanning data is well suited to demonstrate this, because the horizontal distance between successive data points increases from the beginning to the end of the scan line. On March 18, 2010 plate profile measurements and laser scanning were carried out in the same relatively flat wetland area Mantovaaranaapa (67.4°N, 26.7°E). The laser scanning data covered a 2.4 km long and about 3.2 m wide area on each side of the snowmobile route. Altogether 10 plate profile measurements were taken directly after the scanning, at about 100-200 m intervals starting from the western edge of the scan route (Kukko et al. 2013). The average rms slope angle of the 10 plate profiles was  $30.7^{\circ}$  ( $\beta = 0.54$ ) with an 80 % variation range of  $24.7^{\circ} - 34.3^{\circ}$  ( $\beta = 0.43 - 0.60$ ). Consequently,  $n_s$  would then vary in the range 1 - 1.5 (Figure 5). The rms slope angles were calculated also from the laser scanning profiles as a function of horizontal increments, which were within the range 5 mm – 100 mm. The number of points per distance varied between 4 thousand and 2.2 million. Nonlinear regression to the 36 points in the range 5 mm – 100 mm produced an exponential

370

375

As the laser scanner covered a much larger area than the plate profiles, that data gives an estimate of the rms slope angle variation in a larger area and is based on a larger number of individual slope angle values. For the laser data set, the median difference between the 90 % quantile curve of the slope angle values and the rms slope angle value curve was  $6.1^{\circ}$ . The corresponding median difference for the 10 % quantile curve from the rms slope angle curve was  $-5.9^{\circ}$ . For the plate profiles, 90% and 10 % quantile values of the rms slope angle differed from the mean rms slope angle value by  $3.6^{\circ}$  and  $-6.0^{\circ}$ . Thus, the larger area covered by the laser scanner shows a larger variation of the rms slope angle, as one could expect. Obviously,

curve that approaches the mean rms slope angle value obtained from the 10 plate profiles of the same area and (Figure 7).

Shorter increments of the laser data could not be reliably used in the analysis.

the laser scanner data can be extrapolated to estimate  $\beta$  at higher horizontal resolution than the measurements directly enable, but then  $\beta$  has to be analysed as a function of the horizontal distance increment (Figure 7). However, the strong variation of  $\beta$ with spatial resolution suggests that using less scale-dependent surface roughness descriptors would be desirable, if they just can provide the information needed.

The relationship between other surface roughness parameters (such as rms height  $\sigma$  and correlation length *L*) and  $\beta$  is in general not strong even for a Gaussian surface height distribution (Beckmann & Spizzicchino, 1963). For the whole period (March 3 – April 28, 2009) the ratio of  $\sigma/L$  (determined for 0.60 m distance) correlated however relatively well with  $\beta$ , the  $R^2$  values

- 385 being 0.70, 0.62 and 0.67 for the whole data range, March and April, respectively, but the best descriptor of  $\beta$  was found to be  $\sigma/b$  (Eq. 1), its  $R^2$  values for the linear correlation being 0.78, 0.68 and 0.82 for the whole data range, March and April, respectively (data shown in Supplementary material).  $\beta$  tends to increase with the progress of the melting season (0.002 radians per day). Likewise, its correlation with  $\sigma/b$  increases during the melting season. It was therefore examined, whether the measured surface albedo correlates well with the measured surface roughness parameters. Using just the rms height (derived
- for a 0.60 m horizontal scale) as an explanatory variable of the albedo the coefficient of determination was  $R^2 = 0.81$  (data 390 shown in Supplementary material). The relationship between the albedo and surface roughness parameters that are scaleindependent in a large range (Manninen, 2003) was then evaluated. Indeed, a simple linear regression for the data of March and April, 2009 produced a coefficient of determination value as high as  $R^2 = 0.90$ , when the parameters b and  $k_0$  (see Eqs. 1 and 2) were used as explanatory variables (Figure 8). While correlation is not a proof of causality, this result supports the view 395 that surface roughness affects the albedo.

#### 4.2 Snow albedo spectra: measured vs. modelled

Two examples of snow nadir reflectance spectra measured with the ASD spectroradiometer are shown in Figure 9. On March

- 400 13, the sky was completely overcast, whereas on April 22 it was perfectly clear. For comparison, corresponding albedo spectra modelled using TARTES are shown. The ASD reflectance spectra were scaled so that the derived broadband reflectance value matched the calibrated operationally measured broadband albedo value. The scaling factor was 0.994 for the diffuse case of March 13 and 0.937 for the clear-sky case of April 22. No BRF was available for the clear-sky case for the location of ASD, but for old rough snow in the area it was relatively flat (see Section 4.5), so that the comparison of the spectral reflectance and
- 405 albedo values seems reasonable enough to enable the choice of the grain shape to be used in the TARTES model calculations. The spectra modelled with TARTES accounted for the empirical grain size and density values, as well as for black carbon but not for organic carbon (Table 1), which included needles and various tree trash deposited on snow. In March, the impurity content in surface snow was very low, while in April, it was roughly 3 times higher (Table 1). In March a better fit is obtained using fractal grains, which result is also supported by photos taken of snow grains and the fact that the snow was fresh. In
- 410 April the modelled albedo favoured the use of spherical grains rather than fractals in the calculations. The photos taken about the snow grains also supported the use of spherical grains in April. Thus, the TARTES results seem to represent the snowpack in March well, but in April when the melting has been going on for a longer time the modelled albedo values are higher than the empirical reflectance values both in the visible and NIR wavelengths (less than  $\sim 1 \mu m$ ), which dominate the value of the broadband albedo of snow. The grain size estimation uncertainty was not significant in April, because the grains were already
- 415 very rounded, but in March the definition and estimation of the grain size was challenging. However, even if the actual grain size for fractal grains were as much as 1 mm larger than estimated, this would not in all cases provide the measured albedo

value using the TARTES model without contribution of surface roughness. As the median grain size of the top layer was in March 0.5 mm and the corresponding maximum value was 1.5 mm (Table 2), it is in practice highly improbable to make an error of 1 mm or more using a graded plate with 1 mm scale.

420

#### 4.3 Broadband albedo: measured vs. modelled

The evolution of the operationally measured broadband albedo in Tähtelä is shown for the periods March 12 - 19 and April 21 - 28 in Figure 10 together with the corresponding albedo values simulated using the TARTES model assuming a flat surface and the grain size and density measurements of the day in the Sodankylä area. Following the justifications outlined above and

- 425 on the basis of photos taken in every test site, fractal grain shapes were used in March and spheres in April. The simulated values tend to exceed the measured ones, especially in April. In March the grain size estimation was difficult, because of the small dimensions of the very complex grain shapes. Hence, some but not all of the difference between the measured and modelled results may be explained by that. On the contrary, in April the grains were already very large and rounded, so that the difference between the modelled and measured values should not come from grain size uncertainty. Besides, the variation
- 430 range of simulated albedo values is rather small compared to that of the empirical broadband reflectance values. However, it will be demonstrated next that taking into account the surface roughness decreases the difference between simulated and empirical albedo estimates.

The albedo model taking into account both volume and surface scattering (Eqs. 3 – 5) was applied so that  $\alpha_{w0}$  was the value 435 provided by the TARTES model based on the measured density and grain size profile and impurity content. The values for *n* and *m* were derived from the empirical values of  $n_s$ . Namely,  $m = n_s - 1$  for the local solar zenith ( $\theta_{il}$ ) angle range derived using the ray tracing method. And *n* is the weighted mean of  $n_s - 1$ , where the weights are  $\cos(\theta_{il}) \cdot \sin(\theta_{il})$ . The results are shown in Figure 11 and Figure 12.

- 440 First, the ratio  $\alpha_w/\alpha_{w0}$  of the total white-sky albedo and the bulk white-sky albedo provided by the TARTES model is considered in Figure 11. In March, this ratio varies mainly between 0.97 and 0.99, indicating that small-scale surface roughness decreases the snow albedo typically by 1-3%. With the progress of snow melt, the effect of surface roughness increases markedly. On 26-27 April (Julian days 116-117), the median of  $\alpha_w/\alpha_{w0}$  falls below 0.9, indicating an over 10% decrease in snow albedo. The relative difference between the total and bulk albedo values is about the same for the black-sky case as for the white-sky case,
- but the solar zenith angle naturally slightly complicates that relationship (see Eqs. 3 and 4). The larger variation of the  $\alpha_w/\alpha_{w0}$  values in the latter part of April (after Julian day 112) is related to vigorous melting of the snowpack, since then the measured temperatures were about 0°C throughout the snowpack (Manninen and Roujean, 2014).

The modelled albedo values are further compared to observations in Figure 12. The variation range of the simulations shown

- 450 with the background shading is based on the variation of the grain size, density and local incidence angle of the measured profiles. Overall, the inclusion of surface roughness improves significantly the agreement of modelled albedos with the observed ones. A notable overestimation remains, however, on Julian days 77-78, and will be discussed in Section 5. All in all, the model is robust enough to be reasonably applied to empirical data of grain size, density and surface roughness.
- 455 Obviously, taking into account the surface roughness contribution improves the match of empirical and modelled results, but still it is very clear that the grain size, grain shape and SWE (or density) are dominant parameters, because the amount of volume scattering also affects directly the amount of surface scattering. The variation range of the modelled albedo is much larger for clear-sky cases than diffuse cases, which is understandable as some of the variation in clear-sky cases comes from the solar zenith angle variation during the day.

460

#### 4.4 Albedo during snow metamorphosis on April 22

The modelled albedo results were compared with the Kipp & Zonen CM14 albedometer measurements carried out in Mantovaaranaapa on April 22, 2009, which was a perfectly clear day (Figure 13). One snow pit was measured during 9 - 10 UTC at 67.40735°N, 26.72357°E. The albedometer was positioned in its vicinity and it recorded the metamorphosis process shown by the linear ( $R^2 = 0.998$ ) decrease of the albedo with time. Surface roughness of 54 individual profiles were retrieved with the plate method with typically 10 m incremental distance in perpendicular directions covering an area of about 100 m x 100 m (Figure 2). Each position of the plate was photographed three times, so that 18 separate profiles were characterized. Hence, the modelled albedo results were averaged to get one value per surface sample. The light grey band in Figure 13 shows the variation range of the broadband-converted reflectance spectra measured with the ASD spectrometer in the same area at the same time. Obviously, the modelled profile albedos fit in that range. The mean of the empirical albedo values is 0.67 and the modelled mean values are 0.72 and 0.68 for volume scattering only and for both volume and surface scattering, respectively. Taking into account the snow surface roughness thus improved the average modelled albedo estimate.

#### 4.5 BRF

475 Since the contribution of surface roughness to the total albedo is markedly smaller than the contribution of the bulk volume scattering (i.e. scattering of a snowpack with an ideal plane surface), it is clear that the volume scattering dominates also the BRF. However, the contribution of surface roughness is not negligible and the BRF of the surface scattering component may differ markedly from the bulk volume component, resulting in a complex total BRF. The ray tracing based surface BRFs (without any volume scattering contribution) were compared with empirical BRFs measured using FIGIFIGO (Figure 14) in

480 Mantovaaranaapa in April 22, 2009. The area is an aapa mire, which late in spring affects the snow properties markedly (Figure 15). Sporadically the snow had melted and refrozen.

The comparison of the ray tracing and surface roughness based BRFs with the empirical FIGIFIGO-based BRFs were made in the principal plane, since the azimuth information of the former ones was just a statistical assumption to convert the 2D

- 485 principal plane BRF to 3D principal plane BRF. The surface scattering BRFs are typically peaked to the direction  $\theta$  of forward scattering matching mirror reflection of the surface plane of the snowpack. In addition, a backward peak in the direction  $\theta$ -90° is also strong in most cases (Figure 16). The balance between forward and backscattered intensity varies with incidence angle so that large incidence angles favour surface backscattering due to roughness (Figure 17, Table 3). Although mere surface scattering would lead to dominantly backward scattering in Mantovaaranaapa due to the large incidence angle values (55° –
- 490 64° for FIGIFIGO BRFs), the empirical BRFs measured using FIGIFIGO dominated by the volume scattering are still dominantly forward scattering. The balance between forward/backward volume scattering is related to the grain shape (Peltoniemi et al., 2010). But indeed, the smoothest snow sample produced least backscattering, the ratio of the backward to the forward scattered amount of radiation was 0.58, whereas the corresponding ratio was on the average 0.73 for the rough BRFs. This result is quite in line with the general ray tracing analysis results that surface roughness increases the fraction
- 495 scattered backwards (Table 3). Also, in a previous theoretical study of Gaussian surfaces it has been shown that roughness affects the maximum direction of backward scattering (Jämsä et al., 1993). For the profiles measured in Mantovaaranaapa on April 22 the ratio of the backward and forward scattered radiation amounts in the incidence angle range of the FIGIFIGO measurements varied from 1.0 to 1.46. One has to take into account that the plate profiles register roughness in 1 m scale, whereas FIGIFIGO measures samples of 0.10 m diameter. Hence the largest spatial roughness may not necessarily show up
- 500 as strongly in the FIGIFIGO results.

#### 5 Discussion

In this study, the equations combining the volume scattering and surface scattering were derived using the photon recollision theory (Appendix A), because this theory could be extended to include the surface scattering effect. However, to describe properly the volume scattering of real snowpacks, it is essential to pay attention also to layer structure, grain shapes and various types of impurities etc., so that a more complex description is typically needed for realistic volume scattering estimation. In principle, the photon recollision theory could be extended to take the layer structure of the snowpack into account by just letting the photon recollision probability *p* to be a function of the depth, i.e. p = p(z), where *z* would be the distance from the bottom or top surface. However, that is beyond the scope of this study. Hence, the surface scattering part is developed so that in principle it can be combined with any volume scattering method. One just applies the estimates of  $\alpha_{w0}$  and  $\alpha_{b0}$  derived with the chosen volume scattering model in Eqs. 3 - 5. Hence, to obtain more realistic volume scattering estimates for the snowpack, we used the TARTES model for volume scattering in the simulations.

The findings that surface roughness in general decreases albedo and that the effect is larger for larger solar zenith angles are quite in line with the recent results obtained by applying a new rough surface ray-tracing (RSRT) model to artificially generated surface roughness of snow (Larue et al., 2020). This study, however, extends these findings to smaller-scale roughness down to the submillimetre-scale. The discussion about the effect of the varying local incidence angle on a rough surface and shadowing effects has been going on decades, but until recently the emphasis has been on large-scale features (Warren et al., 1998; Kokhanovsky and Zege, 2004; Lhermitte et al., 2014). The essential advantage in studying the roughness from the

- 520 theoretical point of view by generating artificial roughness with known dimensions and orientation is that then one can study the effect of each parameter involved separately (Larue et al., 2020). However, it is not trivial to generalize those results to natural snow, because the deterministic periodic structures may generate scattering features that will not be present for scattering from randomly rough surfaces. The advantage of the statistical approach presented in this study is that it does not make assumptions about the surface roughness characteristics but deals with the surfaces provided by the nature. In addition,
- 525 the derived formulas of the rough surface albedo are mathematically very simple and depend only on very few parameters, which makes their use very easy.

The ray tracing analysis of this study showed that the backward scattering increases with increasing surface roughness and increasing incidence angle of the illumination. However, that analysis concentrates only on surface scattering without any volume scattering contribution. Combining the surface and volume scattering contributions to BRF, perhaps using an adding procedure for radiative transfer, would be an interesting topic for future work.

Although the surface scattering model used here includes multiple scattering from the surface, it may be that a surface layer containing very deep cavities (in the scale of a few centimetres) would benefit from some special attention, like in the case of

- 535 large-scale penitentes (Lhermitte et al., 2014). Namely, surface roughness measurements methods are usually designed for typical roughness of about the same variation range horizontally and vertically, not for extremely deep pits. To some extent the pit structure will be taken into account by the volume scattering models, since they affect the density of the surface layer of the snowpack. However, their very anisotropic (vertical) orientation is not well described by random scattering of a layer with reduced density. The pits act like illumination traps so that a larger part of illumination reaches lower layers of the
- 540 snowpack before it is absorbed or scattered upwards. Therefore, the bulk albedo is smaller than for a completely random volume of the same density.

An example case is offered to illustrate this effect. Slight snow precipitation took place on March 16 so that a very fluffy surface structure of large dendritic snow crystals was formed on the snowpack (Figure 18 and Figure 19). The rms slope angle

- based on the plate method showed an increase with time from about 0.38 to about 0.63 with  $R^2 = 0.68$ . The rms height and correlation length also manifested clear evolution during those days (Figure 20). A related change is obvious also using the roughness parameters *a* and *b* (Anttila et al., 2014). Yet, the surface roughness measurements based on the plate method or laser scanning are not able to catch the deep pit structure of the surface, because of shadowing effects. Therefore, the simulated albedo is higher than the empirical one (Figure 12, Julian days 76-78). However, even if the 2D-surface roughness were
- 550 characterized properly, the surface scattering model based on a statistical approach of random scatterers would not be ideal for a case with a distinct periodic surface structure. For example, one could analyse separately the percentage of illumination that will be completely trapped by the deep cavities and reduce the simulated total albedo with that fraction.

The plate profile method has the advantage of high spatial resolution. Its main drawback is that it can be used only, when the snow is relatively soft. It has been successfully used in Finnish Lapland (Anttila et al., 2014) and at Greenland Summit (Manninen et al., 2016), but Antarctic snow is typically so hard that it is not possible to immerse the plate in it. In addition, icy and crusty snow surface of Finnish Lapland in 2018 and 2019 turned out to be too hard for the plate. For laser scanning, however, the hardness of the snowpack does not cause any problems. Indeed, laser scanning shows great potential for measuring snow surface roughness as it can cover large areas with high point precision accuracy. It is a particularly good method for measuring larger-scale roughness from 0.05 – 0.1 m upwards. The limiting factor in finer scale roughness measurements is the data resolution and footprint size of the laser beam. So far, the scanners with the highest point density, accuracy and smallest spot size are meant for indoors use, but as the technology improves, smaller and smaller features become measurable also outdoors. In addition, the fractal nature of snow surfaces enables extrapolation of surface roughness from cm scale to mm scale (Kukko et al., 2013). Another benefit of using laser scanning for surface roughness measurements is that it

- 565 leaves the surface intact. This enables repeatable measurements of the same surface giving a means to study the evolution of surfaces in time. The backscattering intensity of the laser beam is typically stored for each point measured by laser, and in the most modern scanners also the range deviation is stored. These features have so far not been widely used, but it could potentially be used in the future for surface scattering property measurements and snow surface classifications.
- 570 Finally, considering satellite retrievals, it is expected that for an ideally flat surface, the impact of roughness would be essentially the same at the satellite resolution as that in the scale of in situ measurements. However, the larger the satellite pixel is, the larger spatial scale roughness has to be taken into account. The derived model is applicable to take into account roughness of all relevant scales, but the problem is how to estimate the average multiscale number of facet-to-facet scattering events. It is anticipated that due to the fractal nature of snow the small scale estimate of the average number of facet-to-facet
- 575 scattering events is a reasonable first order estimate for the corresponding multiscale value, but a related detailed analysis is beyond the scope of this study.

#### 6 Conclusions

A method was developed to model the effect of surface roughness on albedo besides the volume scattering. It can be combined

with any volume scattering model. Applying measured surface roughness values to the model produced results closer to measured values than only volume scattering simulations made with the TARTES model. The surface roughness is described by the average number of surface scattering events per ray, which is currently estimated from the rms slope angle values of the measured surface roughness profiles. High empirical correlation ( $R^2 = 0.9$ ) of albedo with just two surface roughness related parameters supports the importance of surface roughness to albedo.

585

590

The albedo modelling results taking into account also the surface roughness indicate that it may decrease the albedo by about 1-3 % in midwinter and even more than 10 % during late melting season. The effect is largest for low solar zenith angle values and lower bulk snow albedo values. Hence, the effect is larger early and late times of day everywhere and it increases during the melting season especially at high latitudes, where the sun elevation is lower. Increasing surface roughness also favours more backwards scattering.

#### Appendix A: Deriving the formulas for surface roughness effect on scattering

#### Scattering of diffuse radiation

595

The scattering of light in canopies has for several years successfully been described with spectral invariants and the so-called photon recollision theory, *p*-theory, (Knyazikhin et al., 1998; Panferov et al., 2001; Smolander and Stenberg, 2005; Rautiainen and Stenberg, 2005; Stenberg et al., 2008; Stenberg and Manninen, 2015; Stenberg et al., 2016). The central parameter, the photon recollision probability *p* is spectrally invariant and depends on the amount of scattering surface in the volume. Canopies don't have distinct upper surfaces, hence the *p*-theory is developed so far only for a scattering volume, but it has already been

600 don't have distinct upper surfaces, hence the *p*-theory is developed so far only for a scattering volume, but it has already been successfully combined with forest floor scattering also for snow covered cases (Manninen and Stenberg, 2009). Here the *p*theory is applied to snowpack scattering taking into account that the snowpack has a distinct surface, which may be rough.

A simple way to take into account the surface roughness effect on scattering is to consider every facet of the snowpack as a separate volume of scatterers. When the irradiance  $i_0 = i_0(\lambda)$  first arrives at the facet, it enters a volume scattering sequence, which can be described with the spectrally invariant photon recollision probability *p* of the bulk part of the snowpack and the single-scattering albedo of the snow grains  $\omega = \omega(\lambda)$  (Knyazikhin et al., 1998; Panferov et al., 2001). The radiation absorbed and scattered by the volume of the facet  $a_0$  and  $s_0$ , respectively, are (Smolander and Stenberg, 2005; Rautiainen and Stenberg, 2005; Stenberg and Manninen, 2015)

610 
$$a_0 = \frac{1-\omega}{1-p\omega} i_0 \tag{A1}$$

$$s_0 = \frac{1}{1 - p\omega} i_0 \tag{A2}$$

For simplicity the dependence of  $\omega$ ,  $i_0$ ,  $a_0$  and  $s_0$  on the wavelength  $\lambda$  is not shown explicitly in the equations. The radiation escaping the volume of the facet either escapes altogether or hits another facet and experiences another volume scattering sequence. The probability of the latter case is defined to be the surface photon recollision probability  $p_s$ . Because the snow

615 grains in the bulk part are completely surrounded by other snow grains while in the surface almost only half of the surrounding volume may contain snow grains, it is essential to assume that p and  $p_s$  are not identical. The radiation escaping the snowpack altogether without hitting another facet,  $r_0$ , is

$$r_0 = (1 - p_s)qs_0 = (1 - p_s)q\frac{\omega - p\omega}{1 - p\omega}i_0 \qquad , \tag{A3}$$

where  $q = q(\lambda)$  is the fraction of the volume scattering escaping upwards. Essentially it corresponds to *Q* defined by Stenberg et al. (2016, Eq. 24), but as it does not contain the fraction scattered upwards by the surface, it is not the total upwards scattered fraction of light. Hence *q* is used here instead of *Q*. Theoretically the values for *q* are in the range 0 – 1 being the larger the thicker and denser the scattering layer is. The radiation hitting another facet is

$$i_1 = p_s q s_0 = p_s q \frac{\omega - p\omega}{1 - p\omega} i_0 \tag{A4}$$

The absorbed  $(a_1)$  and scattered  $(s_1)$  amounts of radiation by the second volume scattering sequence are

625 
$$a_1 = \frac{1-\omega}{1-p\omega} i_1 = p_s q \frac{(1-\omega)(\omega-p\omega)}{(1-p\omega)^2} i_0$$
 (A5)

$$s_1 = \frac{\omega - p\omega}{1 - p\omega} i_1 = p_s q \left(\frac{\omega - p\omega}{1 - p\omega}\right)^2 i_0 \qquad . \tag{A6}$$

The amounts of radiation escaping  $(r_1)$  and entering the following scattering sequence  $(i_2)$  of another facet are

$$r_1 = (1 - p_s)qs_1 = (1 - p_s)p_s q^2 \left(\frac{\omega - p\omega}{1 - p\omega}\right)^2 i_0$$
(A7)

$$i_2 = p_s q s_1 = p_s^2 q^2 \left(\frac{\omega - p\omega}{1 - p\omega}\right)^2 i_0$$
 (A8)

630 Formulas for the corresponding radiation components in the following facet-to-facet scattering round are

$$a_2 = \frac{1-\omega}{1-p\omega} i_2 = p_s^2 q^2 \frac{(1-\omega)(\omega-p\omega)^2}{(1-p\omega)^3} i_0$$
(A9)

$$s_2 = \frac{\omega - p\omega}{1 - p\omega} i_2 = p_s^2 q^2 \left(\frac{\omega - p\omega}{1 - p\omega}\right)^3 i_0 \tag{A10}$$

$$r_2 = (1 - p_s)qs_2 = (1 - p_s)p_s^2 q^3 \left(\frac{\omega - p\omega}{1 - p\omega}\right)^3 i_0$$
(A11)

$$i_3 = p_s q s_2 = p_s^3 q^3 \left(\frac{\omega - p\omega}{1 - p\omega}\right)^3 i_0$$
 (A12)

635 Further on, the components corresponding to the *j*th round are

$$a_{j} = \frac{1-\omega}{1-p\omega}i_{j} = p_{s}{}^{j}q^{j}\frac{(1-\omega)(\omega-p\omega)^{j}}{(1-p\omega)^{j+1}}i_{0}$$
(A13)

$$s_j = \frac{\omega - p\omega}{1 - p\omega} i_j = p_s^{\ j} q^j \left(\frac{\omega - p\omega}{1 - p\omega}\right)^{j+1} i_0 \tag{A14}$$

$$r_{j} = (1 - p_{s})qs_{j} = (1 - p_{s})p_{s}{}^{j}q^{j+1} \left(\frac{\omega - p\omega}{1 - p\omega}\right)^{j+1} i_{0}$$
(A15)

$$i_{j+1} = p_s q s_j = p_s^{j+1} q^{j+1} \left(\frac{\omega - p\omega}{1 - p\omega}\right)^{j+1} i_0 \qquad (A16)$$

640 The amounts absorbed and scattered by the surface and volume, considering up to n facet-to-facet scattering events, are then

$$a = \sum_{j=0}^{n} a_{j} = \sum_{j=0}^{n} p_{s}^{j} q^{j} \frac{(1-\omega)(\omega-p\omega)^{j}}{(1-p\omega)^{j+1}} i_{0} = \frac{(1-\omega)}{(1-p\omega)} i_{0} \sum_{j=0}^{n} \left( p_{s} q \frac{\omega-p\omega}{1-p\omega} \right)^{j}$$
(A17)

$$s = \sum_{j=0}^{n} s_j = \sum_{j=0}^{n} p_s^{\ j} q^j \left(\frac{\omega - p\omega}{1 - p\omega}\right)^{j+1} i_0 = \left(\frac{\omega - p\omega}{1 - p\omega}\right) i_0 \sum_{j=0}^{n} \left(p_s q \frac{\omega - p\omega}{1 - p\omega}\right)^j.$$
(A18)

Correspondingly, the upwards escaping radiation is

$$r = \sum_{j=0}^{n} r_{j} = \sum_{j=0}^{n} (1 - p_{s}) p_{s}^{j} q^{j+1} \left(\frac{\omega - p\omega}{1 - p\omega}\right)^{j+1} i_{0} = (1 - p_{s}) q \left(\frac{\omega - p\omega}{1 - p\omega}\right) i_{0} \sum_{j=0}^{n} \left(p_{s} q \frac{\omega - p\omega}{1 - p\omega}\right)^{j}.$$
(A19)

645

Note, when the number *n* of additional facet scattering sequencies the photon has before it escapes altogether is zero and  $p_s = 0$ , there is no facet-to-facet scattering, i.e. the case is the normal volume scattering case. The total absorbed and upwards escaping radiation of the snowpack are derived as infinite geometrical sums and are

$$a = \frac{(1-\omega)}{(1-p\omega)} \frac{1}{1-(p_s q \frac{\omega-p\omega}{1-p\omega})} i_0 \tag{A20}$$

650 
$$r = (1 - p_s)q\left(\frac{\omega - p\omega}{1 - p\omega}\right)\frac{1}{1 - \left(p_s q\frac{\omega - p\omega}{1 - p\omega}\right)}i_0$$
 (A21)

The total white-sky (diffuse) albedo  $\alpha_w$  of the snowpack is then

$$\alpha_w = \frac{r}{i_0} = (1 - p_s)q\left(\frac{\omega - p\omega}{1 - p\omega}\right)\frac{1}{1 - \left(p_s q\frac{\omega - p\omega}{1 - p\omega}\right)}$$
(A22)

The white-sky (diffuse) albedo of the bulk part of the snowpack (without facet-to-facet scattering)  $\alpha_{w0}$  is

$$\alpha_{w0} = q \frac{s_0}{i_0} = q \frac{\omega - p\omega}{1 - p\omega}$$
 (A23)

655 Hence, the total white-sky albedo is simply

$$\alpha_w = (1 - p_s) \alpha_{w0} \frac{1}{1 - p_s \alpha_{w0}}$$
(A24)

Estimation of the parameter  $p_s$  is not trivial, but when the distribution of n or its average value denoted by  $\langle n \rangle$ , is known from measurements, then a reasonable estimate can be obtained from the total scattered energy s (Eq. A18) as follows. First, s is derived using the finite sum formulation of (A18) with a surface recollision probability of unity, i.e.  $p_s$  set to 1. Second, s is derived using the probabilistic infinite sum formulation of Eq. (A18), i.e., n is set to infinity. These two estimates must equal.

Taking into account Eq. (A23) and the normalized distribution f(n) of the values of n from zero to its maximum value  $n_{max}$ , the following relation is obtained

following relation is obtained

660

$$\sum_{n=0}^{n=n_{max}} \frac{\alpha_{w0}i_0}{q} \frac{1-\alpha_{w0}^{n+1}}{1-\alpha_{w0}} f(n) = \frac{\alpha_{w0}i_0}{q} \frac{1}{1-(p_s \alpha_{w0})}$$
(A25)

which reduces to the following equation

665 
$$\sum_{n=0}^{n=n_{max}} \alpha_{w0}^{n+1} f(n) = 1 - \frac{1 - \alpha_{w0}}{1 - (p_s \alpha_{w0})}$$
 (A26)

The value for  $p_s$  can be solved from the above equation and is

$$p_{s} = \frac{1 - \sum_{n=0}^{n=n} max}{1 - \sum_{n=0}^{n=n} max} \alpha_{w0}^{n+1} f(n)}$$
(A27)

In practice, the number of facet-to-facet scattering sequences *n* is often small, so that f(n) is dominated by values n = 0 and n = 1. When this is the case, the weighted mean of  $\alpha_{w0}^{n+1}$  represented by the left part of Eq. A26 can be approximated with a high precision with  $\alpha_{w0}^{<n>+1}$ . This was indeed the case in the measured profiles. In March the normalized distribution was approximately  $f(n) = 2 \cdot \exp(-2n)$  and in April  $f(n) = 1.5 \cdot \exp(-1.5n)$ . Hence, the albedo estimation using <n> instead of the distribution of *n* caused in March at most an underestimation of the total albedo by 0.004 and in April by 0.014. As reliable estimation of f(n) for singles profile is challenging, it is recommended to simply use the mean value <n>. Then, the value of  $p_s$  can be estimated from

675 
$$p_s = \frac{1 - \alpha_{w0} < n >}{1 - \alpha_{w0} < n > +1}$$
 (A28)

The relationship between the total albedo and the bulk albedo is then

$$\alpha_w = (1 - p_s) \alpha_{w0} \frac{1}{1 - p_s \alpha_{w0}} = \alpha_{w0}^{< n > +1}$$
(A29)

When the surface does not cause additional scattering,  $\langle n \rangle = 0$  and the total albedo equals the bulk albedo. The larger the  $\langle n \rangle$  is the smaller is  $\alpha_w$ .

680 For a single photon the number of facet-to-facet volume scattering rounds is naturally an integer number. For the ensemble of the photons  $\langle n \rangle$  can be estimated to be

$$< n > = \sum_{j=0}^{\infty} p_s \left(\frac{s_j}{i_0}\right) = p_s \left(\frac{\omega - p\omega}{1 - p\omega}\right) \sum_{j=0}^{\infty} \left(p_s q \frac{\omega - p\omega}{1 - p\omega}\right)^j = p_s \left(\frac{\omega - p\omega}{1 - p\omega}\right) \frac{1}{1 - p_s q \frac{\omega - p\omega}{1 - p\omega}} = \frac{p_s \alpha_{w_0}}{q(1 - p_s \alpha_{w_0})}$$
(A30)

Combining Eqs. A28 and A30 it is possible to estimate q for values  $\langle n \rangle$  larger than 0 and it is

$$q = \frac{p_s \alpha_{w_0}}{\langle n \rangle (1 - p_s \alpha_{w_0})} = \frac{\alpha_{w_0} (1 - \alpha_{w_0} \langle n \rangle)}{\langle n \rangle (1 - \alpha_{w_0})}$$
(A31)

For  $\langle n \rangle = 1$ , q equals the bulk white-sky albedo and for larger (smaller) values of  $\langle n \rangle$  it is slightly smaller (larger) for medium albedo values.

#### Scattering of direct radiation

For the direct component of solar illumination one has to take into account that the irradiance depends besides the wavelength also on the solar zenith angle  $\theta_i$ , i.e.  $i_0 = i_0(\lambda, \theta_i)$ . The photon recollision probability in the bulk snowpack will be denoted for the first scattering sequence  $p_1 = p_1(\theta_{il})$  and for latter sequences p, assuming that the incidence angle dependence is lost after the first volume scattering sequence. Here the local incidence angle of the facet is denoted by  $\theta_{il}$ . Then, the absorbed radiation of the volume will be (Stenberg and Manninen, 2015)

695 
$$a_0 = \frac{(1-\omega)(1-\omega(p-p_1))}{1-p\omega}i_0$$
 (A32)

and the radiation scattered by the volume will be

$$s_0 = \frac{\omega(1 - p_1 - \omega(p - p_1))}{1 - p_\omega} i_0 \quad . \tag{A33}$$

When  $p_1 = p$  the above formulas reduce to Eqs. A1 and A2 as they should.

- The first surface scattering sequence shall be treated separately, because the volume scattering depends on the incident solar zenith angle. The surface photon recollision probability is denoted by  $p_{s1} = p_{s1}(\theta_{il})$  for the first facet-to-facet scattering sequence and by  $p_{sr}$  for the latter facet-to-facet scattering sequences. One should notice that  $p_{sr}$  is not necessarily equal to  $p_s$  of the diffuse case, although they certainly approach each other asymptotically. The reason for not taking them to be identical immediately is the typically small number of surface scattering events per ray of relatively smooth midwinter snow surfaces. The radiation
- ros escaping the facet altogether after just volume scattering,  $r_0$ , is

$$r_0 = (1 - p_{s1})q_0 s_0 = (1 - p_{s1})q_0 \frac{\omega(1 - p_1 - \omega(p - p_1))}{1 - p\omega} i_0,$$
(A34)

where  $q_0 = q_0(\lambda, \theta_i)$  denotes the fraction of the scattered radiation escaping upwards from the snowpack during the first volume scattering sequence. The radiation hitting another facet is

$$i_1 = p_{s1}q_0s_0 = p_{s1}q_0\frac{\omega(1-p_1-\omega(p-p_1))}{1-p\omega}i_0 \qquad (A35)$$

710 The further scattering sequencies are assumed to be independent of the solar zenith angle of the original incident radiation. The absorbed  $(a_1)$  and scattered  $(s_1)$  amounts of radiation by the second volume scattering sequence are then

$$a_1 = \frac{1-\omega}{1-p\omega} i_1 = p_{s1} q_0 \frac{\omega(1-\omega)(1-p_1-\omega(p-p_1))}{(1-p\omega)^2} i_0$$
(A36)

$$s_1 = \frac{\omega - p\omega}{1 - p\omega} i_1 = p_{s1} q_0 \frac{\omega(\omega - p\omega) (1 - p_1 - \omega(p - p_1))}{(1 - p\omega)^2} i_0 \qquad (A37)$$

The amounts of radiation escaping  $(r_1)$  and entering the following scattering sequence  $(i_2)$  are

715 
$$r_1 = (1 - p_{sr})qs_1 = (1 - p_{sr})p_{s1}qq_0 \frac{\omega(\omega - p\omega)(1 - p_1 - \omega(p - p_1))}{(1 - p\omega)^2}i_0$$
 (A38)

$$i_2 = p_{sr}qs_1 = p_{sr}p_{s1}qq_0 \frac{\omega(\omega - p\omega)(1 - p_1 - \omega(p - p_1))}{(1 - p\omega)^2}i_0 \quad .$$
(A39)

Formulas for corresponding radiation components in the following round are

$$a_{2} = \frac{1-\omega}{1-p\omega}i_{2} = p_{sr}p_{s1}qq_{0}\frac{\omega(1-\omega)(\omega-p\omega)(1-p_{1}-\omega(p-p_{1}))}{(1-p\omega)^{3}}i_{0}$$
(A40)

$$s_2 = \frac{\omega - p\omega}{1 - p\omega} i_2 = p_{sr} p_{s1} q q_0 \frac{\omega(\omega - p\omega)^2 (1 - p_1 - \omega(p - p_1))}{(1 - p\omega)^3} i_0$$
(A41)

720 
$$r_2 = (1 - p_{sr})qs_2 = (1 - p_{sr})p_{sr}p_{s1}q^2q_0 \frac{\omega(\omega - p\omega)^2(1 - p_1 - \omega(p - p_1))}{(1 - p\omega)^3}i_0$$
 (A42)

$$i_{3} = p_{sr}qs_{2} = p_{sr}^{2}p_{s1}q^{2}q_{0}\frac{\omega(\omega-p\omega)^{2}(1-p_{1}-\omega(p-p_{1}))}{(1-p\omega)^{3}}i_{0}$$
(A43)

The components corresponding to the *j*th round are

$$a_{j} = \frac{1-\omega}{1-p\omega}i_{j} = p_{sr}^{j-1}p_{s1}q^{j-1}q_{0}\frac{\omega(1-\omega)(\omega-p\omega)^{j-1}(1-p_{1}-\omega(p-p_{1}))}{(1-p\omega)^{j+1}}i_{0}$$
(A44)

$$s_j = \frac{\omega - p\omega}{1 - p\omega} i_j = p_{sr}^{j-1} p_{s1} q^{j-1} q_0 \frac{\omega(\omega - p\omega)^j (1 - p_1 - \omega(p - p_1))}{(1 - p\omega)^{j+1}} i_0$$
(A45)

725 
$$r_j = (1 - p_{sr})qs_j = (1 - p_{sr})p_{sr}{}^{j-1}p_{s1}q^jq_0 \frac{\omega(\omega - p\omega)^j(1 - p_1 - \omega(p - p_1))}{(1 - p\omega)^{j+1}}i_0$$
 (A46)

$$i_{j+1} = p_{sr}q_{sj} = p_{sr}^{\ j}p_{s1}q^{j}q_{0}\frac{\omega(\omega-p\omega)^{j}(1-p_{1}-\omega(p-p_{1}))}{(1-p\omega)^{j+1}}i_{0} \qquad (A47)$$

The amounts absorbed and scattered by the surface and volume, considering up to m facet-to-facet scattering events, are then

$$a = \sum_{j=0}^{m} a_j = \frac{p_{s1}q_0}{p_{sr}q} \frac{(1-\omega)(1-p_1-\omega(p-p_1))}{(1-p\omega)(1-p)} i_0 \sum_{j=0}^{m} \left( p_{sr}q \frac{\omega-p\omega}{1-p\omega} \right)^j$$
(A48)

730 
$$s = \sum_{j=0}^{m} s_j = \frac{p_{s1}q_0}{p_{sr}q} \frac{\omega(1-p_1-\omega(p-p_1))}{(1-p\omega)} i_0 \sum_{j=0}^{m} \left( p_{sr}q \frac{\omega-p\omega}{1-p\omega} \right)^j.$$
 (A49)

Correspondingly, the upwards escaping radiation is

$$r = \sum_{j=0}^{m} r_j = (1 - p_{sr}) \frac{p_{s1}q_0}{p_{sr}} \frac{\omega(1 - p_1 - \omega(p - p_1))}{(1 - p\omega)} i_0 \sum_{j=0}^{m} \left( p_{sr} q \frac{\omega - p\omega}{1 - p\omega} \right)^j.$$
(A50)

where m is the number of facet-to-facet scattering events. The total radiation escaping the snowpack upwards is derived again as an infinite geometrical sum

735 
$$r = (1 - p_{sr}) \frac{p_{s1}q_0}{p_{sr}} \frac{\omega(1 - p_1 - \omega(p - p_1))}{(1 - p_{\omega})} \frac{1}{1 - (p_{sr}q\frac{\omega - p_{\omega}}{1 - p_{\omega}})} i_0$$
 (A51)

The total black-sky (direct) albedo  $\alpha_b$  of the snowpack is then

$$\alpha_b = \frac{r}{i_0} = (1 - p_{sr}) \frac{p_{s1}q_0}{p_{sr}} \frac{\omega(1 - p_1 - \omega(p - p_1))}{(1 - p_\omega)} \frac{1}{1 - (p_{sr}q\frac{\omega - p_\omega}{1 - p_\omega})}$$
(A52)

The black-sky (directional) albedo of the bulk snowpack  $\alpha_{b0}$  is

740 
$$\alpha_{b0} = q_0 \frac{s_0}{i_0} = q_0 \frac{\omega(1 - p_1 - \omega(p - p_1))}{1 - p\omega}$$
 (A53)

Taking into account also Eq. (A23) the relationship between the total black-sky albedo and the bulk snowpack black-sky and white-sky albedo is

$$\alpha_b = (1 - p_{sr}) \frac{p_{s1} \alpha_{b0}}{p_{sr}} \frac{1}{1 - p_{sr} \alpha_{w0}}$$
(A54)

Estimating  $p_{s1}$  or  $p_{sr}$  (whether equal to  $p_s$  or not) is not trivial, but like in the case of diffuse irradiance one can benefit from 745 measured average value of *m* denoted by  $\langle m \rangle$  by requiring that the total scattered energy (Eq. A49) is the same, whether it is calculated from the probabilistic infinite sum or a deterministic sum with surface recollision probability of unity, i.e.

$$\frac{p_{s1}}{p_{sr}}\frac{1}{1-p_{sr}\alpha_{W0}} = \left(\frac{1-\alpha_{W0}^{+1}}{1-\alpha_{W0}}\right) \tag{A55}$$

Unfortunately, there are two variables,  $p_{s1}$  and  $p_{sr}$ , to solve, but only one equation. Hence, the theory does not provide an exact solution for both  $p_{s1}$  and  $p_{sr}$ , but only  $p_{sr}$  remains explicitly in the equation of the black-sky albedo

750 
$$\alpha_b = (1 - p_{sr})\alpha_{b0} \left(\frac{1 - \alpha_{w0}^{< m > +1}}{1 - \alpha_{w0}}\right)$$
 (A56)

When the assumption that  $p_{sr} = p_s$  is valid, the following formula is obtained for the black-sky albedo using Eq. (A28)

$$\alpha_b = \alpha_{b0} \alpha_{w0}^{\ n} \left( \frac{1 - \alpha_{w0}^{\ < m > +1}}{1 - \alpha_{w0}^{\ < n > +1}} \right) \tag{A57}$$

When  $\langle m \rangle = \langle n \rangle$ , the black-sky albedo reduces to  $\alpha_{b0} \cdot \alpha_{w0} \langle n \rangle$ . Further on, when  $\alpha_{b0} = \alpha_{w0}$ , the total black-sky and white-sky albedo values are equal as well, if  $\langle m \rangle = \langle n \rangle$ . The above approximation of the black-sky albedo is reasonable only, when the assumption  $p_{sr} = p_s$  is good. Hence, further studies are needed for proper estimation of  $p_{sr}$  and  $p_{s1}$ .

The average number of facet-to-facet scattering rounds  $\langle m \rangle$  is estimated to be

$$< m > = \frac{p_{s1}s_0}{i_0} + \sum_{j=1}^{\infty} p_s \left(\frac{s_j}{i_0}\right) = \frac{p_{s1}\alpha_{b0}}{q_0} - \frac{p_s\alpha_{b0}}{q_0} + \sum_{j=0}^{\infty} p_s \left(\frac{s_j}{i_0}\right) = \frac{(p_{s1}-p_s)\alpha_{b0}}{q_0} + \frac{p_{s1}\alpha_{b0}}{q(1-p_s\alpha_{w0})}$$
(A58)

When  $p_{s1} \rightarrow p_s$ ,  $q_0 \rightarrow q$  and  $\alpha_{b0} \rightarrow \alpha_{w0}$ ,  $\langle m \rangle \rightarrow \langle n \rangle$ , as it should. It should be noticed that the number of facet-to-facet scattering rounds in direct illumination ( $\langle m \rangle$ ) and in diffuse illumination ( $\langle n \rangle$ ) are not necessarily equal, the difference being

related to the difference of  $\alpha_{b0}$  and  $\alpha_{w0}$  and q and  $q_0$ . The estimate for  $q_0$  can now be derived from Eq. (A58).

#### Data availability

Some data of the SNORTEX campaign is directly listed in the report (Manninen and Roujean, 2014). The plate snow profile

765 data and the ASD data are available upon request from Finnish Meteorological Institute. The FIGIFIGO measurements and the laser scanning data are available upon request from Finnish Geospatial Research Institute/National Land Survey.

#### Author contribution

Albedo measurements: TM, AR
Albedo modelling: TM, EJ, AR, JP, RP, J-LR, OH, PR
Plate surface roughness: KA, TM
Laser scanning surface roughness: SK, HK, AKu, KA, TM
FIGIFIGO BRF: JP, JS, TH
Snow density and grain size profiles: PL, NS, LT, AKo
Snow impurities: AKo, HS, OM
ASD snow reflectance spectra: AR, AKo, HS, TM
Ray tracing analysis: TM
Synthesis of analyses: TM, JP, PR, JLR

#### Acknowledgements

Writing of the manuscript: everybody.

780 The co-operation with the operational units of FMI in Helsinki and in Sodankylä and all SNORTEX campaign participants is gratefully acknowledged. The authors are indebted to Mr. Tuure Karjalainen for taking the plate surface roughness related photos in the field in 2009. Panu Lahtinen, Niilo Siljamo and Laura Thölix took the other photos. The authors are also grateful to Mr. Markku Ahponen and Mr. Veikko Mylläri for the snow depth, density and SWE measurements of the remote points outside the intensive test area and to Mr. Markku Ahponen, Mr. Veikko Mylläri and Ms. Anita Sassali for participating in snow impurity sampling. The authors would like to thank Dr. Kokhanovsky, Dr. Picard and an anonymous reviewer for beneficial comments.

**Financial support** 

790

The work was financially supported by Academy of Finland in the projects SnowAPP (315497), OPTICA (295874), Reflectance of Boreal forests (120949), Scattering (260027), Arctic Absorbing Aerosols and Albedo of Snow (A4), (254195), NABCEA (296302) and by EUMETSAT in the projects Satellite Application Facility on Climate Monitoring (CM SAF), Satellite Application Facility on Support to Operational Hydrology and Water Management (H SAF) and Satellite Application Facility on Land Surface Analysis (LSA).

#### References

795 Anttila, K., Manninen, T., Karjalainen, T., Lahtinen, P., Riihelä, A. and Siljamo, N.: The temporal and spatial variability in submeter scale surface roughness of seasonal snow in Sodankylä Finnish Lapland in 2009–2010. J. Geophys. Res. Atmos., 119, 15, 9236-9252, doi:10.1002/2014JD021597, 2014.

Aoki, T., Kuchiki, K., Niwano, M., Kodama, Y., Hosaka, M. and Tanaka, T. : Physically based snow albedo model for
 calculating broadband albedos and the solar heating profile in snowpack for general circulation models, Journal of Geophysical
 Research, 116, D11114, doi:10.1029/2010JD015507, 2011.

Armstrong, R.L. and Brun, E., (Eds.): Snow and climate, Cambridge University Press, New York, 2008.

805 Baldridge, A. M., Hook, S.J., Grove, C.I. and Rivera, G.: The ASTER Spectral Library Version 2.0., Remote Sensing of Environment, 113, 711–715, doi:10.1016/j.rse.2008.11.007, 2009.

Beckmann, P. and Spizzicchino, A.: The Scattering of Electromagnetic Waves from Rough Surfaces, Pergamon Press, Oxford, pp. 497, 1963.

#### 810

Church, E.L., Fractal surface finish, Appl. Opt. 27(8), 1518–1526, 1988.

Cook, J. M., Hodson, A. J., Gardner, A. S., Flanner, M., Tedstone, A. J., Williamson, C., Irvine-Fynn, T. D. L., Nilsson, J., Bryant, R., and Tranter, M.: Quantifying bioalbedo: a new physically based model and discussion of empirical methods for

815 characterising biological influence on ice and snow albedo, The Cryosphere, 11, 2611–2632, https://doi.org/10.5194/tc-11-2611–2017, 2017.

Domine, F., Gallet, J.-C., Bock, J. and Morin, S.: Structure, specific surface area and thermal conductivity of the snowpack around Barrow, Alaska, Journal of Geophysical Research, 117(D00R14), doi:10.1029/2011JD016647, 2012.

820

Essery, R.: A factorial snowpack model (FSM 1.0), Geosci. Model Dev., 8, 3867–3876, doi:10.5194/gmd-8-3867-2015, 2015.

Fierz, C., Armstrong, R.L., Durand, Y., Etchevers, P., Greene, E., McClung, D.M., Nishimura, K., Satyawali, P.K. and Sokratov, S.A.: The International Classification for Seasonal Snow on the Ground, IHP-VII Technical Documents in

825 Hydrology N°83, IACS Contribution N°1, UNESCO-IHP, Paris, 2009.

850

Flanner, M. G., and Zender, C. S.: Linking snowpack microphysics and albedo evolution, J. Geophys. Res., 111, D12208, doi:10.1029/2005JD006834, 2006.

830 Flanner, M.G., Shell, K.M., Barlage, M., Perovich, D.K., and Tschudi, M.A.: Radiative forcing and albedo feedback from the northern hemisphere cryosphere between 1979 and 2008, Nature Geosciences, 4, 151–155. http://dx.doi.org/10.1038/ngeo1062, 2011.

Fung, A.K.: Microwave Scattering and Emission Models and Their Applications, Artech House, Boston, pp. 573, 1994. 835

He, C., Takano, Y. and Liou, K.-N.: Close packing effects on clean and dirty snow albedo and associated climatic implications, Geophys. Res. Lett., 44, 3719–3727, doi:10.1002/2017GL072916, 2017.

Jämsä, S., Peltoniemi, J.I. and Lumme, K.: Thermal emission from a rough surface: ray optics approach, Astron. Astrophys., 840 271, 319–325, 1993.

Kaasalainen, S., Kaartinen, H., Kukko, A., Anttila, K., and Krooks, A.: Brief communication "Application of mobile laser scanning in snow cover profiling", The Cryosphere, 5, 135–138, https://doi.org/10.5194/tc-5-135-2011, 2011.

Keller, J.M., Crownover, R.M. and Chen, R.Y.: Characteristics of natural scenes related to the fractal dimension, IEEE Trans.
 Pattern Anal. Mach. Intell. PAMI, 9, 621–627, 1987.

Knyazikhin, Y., J. V. Martonchik, R. B. Myneni, D. J. Diner, and S. W. Running: Synergistic algorithm for estimating vegetation canopy leaf area index and fraction of absorbed photosynthetically active radiation from MODIS and MISR data, J. Geophys. Res., 103, 32,257–32,276, 1998.

Kokhanovsky, A. A., and Zege, E. P.: Scattering optics of snow, Applied Optics, 43(7), 1589–1602, doi: 10.1364/AO.43.001589, 2004.

855 Kokhanovsky, A. Spectral reflectance of solar light from dirty snow: a simple theoretical model and its validation, The Cryosphere, 7, 1325–1331, doi:10.5194/tc-7-1325-2013, 2013. Kokhanovsky, A., Lamare, M., Di Mauro, B., Picard, G., Arnaud, L., Dumont, M., Tuzet, F., Brockmann, C., and Box, J.E.: On the reflectance spectroscopy of snow, The Cryosphere, 12, 2371–2382, https://doi.org/10.5194/tc-12-2371-2018, 2018.

860

Komuro, Y. and Suzuki, T.: Relationship between the Concentration of Impurity and Albedo in Snow Surface, Atmospheric and Climate Sciences, 5, 426–432, http://dx.doi.org/10.4236/acs.2015.54034, 2015.

Kukko, A., Andrei, C.-O., Salminen, V. M., Kaartinen, H., Chen, Y., Rönnholm, P., Hyyppä, H., Hyyppä J., Chen, R., Haggrén,
H., Kosonen, I. and Čapek, K.: Road environment mapping system of the Finnish Geodetic Institute—FGI Roamer, Int. Arch.
Photogramm. Remote Sens. Spat. Inf. Sci, 36, 241–247, 2007.

Kukko, A., Anttila, K., Manninen, T., Kaartinen, H., and Kaasalainen, S.: Snow surface roughness from mobile laser scanning data, Cold Regions Science and Technology, 96, 23–35, 2013.

870

Larue, F., Picard, G., Arnaud, L., Ollivier, I., Delcourt, C., Lamare, M., Tuzet, F., Revuelto, J., and Dumont, M.: Snow albedo sensitivity to macroscopic surface roughness using a new ray-tracing model, The Cryosphere, 14, 1651–1672, https://doi.org/10.5194/tc-14-1651-2020, 2020.

875 Leppänen, L., Kontu, A., Vehviläinen, J., Lemmetyinen, J. and Pulliainen, J.: Comparison of traditional and optical grain-size field measurements with SNOWPACK simulations in a taiga snowpack, Journal of Glaciology, 61(225), 151–162, doi: 10.3189/2015JoG14J026, 2015.

Leroux, C. and Fily, M.: Modeling the effect of sastrugi on snow reflectance, Journal of Geophysical Research, 103(Ell), 25,779–25,788, 1998.

Lhermitte, S., Abermann, J. and Kinnard, C.: Albedo over rough snow and ice surfaces. The Cryosphere, 8, 1069–1086, doi:10.5194/tc-8-1069–2014, 2014.

Libois, Q., Picard, G., France, J., Arnaud, L., Dumont, M., Carmagnola, C. and King, M. D.: Influence of grain shape on light penetration in snow, The Cryosphere, 7, 1803–1818, doi:10.5194/tc-7-1803-2013, 2013.

Libois, Q., Picard, G., Dumont, M., Arnaud, L., Sergent, C., Pougatch, E., & Vial, D.: Experimental determination of the absorption enhancement parameter of snow, Journal of Glaciology, 60(222), 714–724, doi:10.3189/2014JoG14J015, 2014.

Lucht, W., Schaaf, C.B. and Strahler, A.H.: An Algorithm for the Retrieval of Albedo from Space Using Semiempirical BRDF Models, IEEE Transactions on Geoscience and Remote Sensing, 38(2), 977–998, 2000.

Löwe, H., Egli, S., Bartlett, S., Guala, J.M.M., and Manes, C.: On the evolution of the snow surface during snowfall, 895 Geophysical Research Letters, 34, L21507, 2007.

Manninen, A.T.: Multiscale surface roughness description for scattering modelling of bare soil, Physica A 319, 535–551, 2003.

Manninen, T. and Stenberg, P.: Simulation of the effect of snow covered forest floor on the total forest albedo, Agricultural and Forest Meteorology, 149(2), pp 303–319, 2009.

Manninen, T., Anttila, K., Karjalainen, T. and Lahtinen, P.: Automatic snow surface roughness estimation using digital photos, Journal of Glaciology, 58(211), 993–1007, 2012.

905 Manninen, T. and Roujean, J.-L.,: SNORTEX, Snow Reflectance Transition Experiment. Finnish Meteorological Institute Reports, 2014:7, pp. 68, 2014.

Manninen, T., Lahtinen, P., Anttila, K. and Riihelä, A.: Detection of snow surface roughness and hoar at Summit, Greenland, using RADARSAT data, International Journal of Remote Sensing, 37:12, 2860–2880, DOI: 10.1080/01431161.2015.1131873, 2016.

Meinander, O., Kazadzis, S., Arola, A., Riihelä, A., Räisänen, P., Kivi, R., Kontu, A., Kouznetsov, R., Sofiev, M., Svensson, J., Suokanerva, H., Aaltonen, V., Manninen, T., Roujean, J.-L., and Hautecoeur, O.: Spectral albedo of seasonal snow during intensive melt period at Sodankylä, beyond the Arctic Circle, Atmos. Chem. Phys., 13, 3793–3810, https://doi.org/10.5194/acp-13-3793-2013, 2013.

Meinander, O., Kontu, A., Virkkula, A., Arola, A., Backman, L., Dagsson-Waldhauserová, P., Järvinen, O., Manninen, T., Svensson, J., de Leeuw, G., and Leppäranta, M.: Brief communication: Light-absorbing impurities can reduce the density of melting snow, The Cryosphere, 8, 991–995, https://doi.org/10.5194/tc-8-991-2014, 2014.

Meinander, O., Kontu, A., Kouznetsov R., and Sofiev, M.: Snow samples combined with long-range transport modeling to reveal the origin and temporal variability of black carbon in seasonal snow in Sodankylä (67 °N), Front. Earth Sci.,https://doi: 10.3389/feart.2020.00153, 2020.

<sup>920</sup> 

925 Mialon, A., Fily, M., and Royer, A.: Seasonal snow cover extent from microwave remote sensing data: comparison with existing ground and satellite based measurements. EARSeL eProceeding, 4, 215–225, 2005.

Mätzler, C.: Autocorrelation functions of granular media with free arrangement of spheres, spherical shells or ellipsoids, J. Appl. Phys., 81, 1509–1517, 1997.

930

940

Neshyba, S. P, Grenfell, T. C., and Warren, S. G.: Representation of a nonspherical ice particle by a collection of independent spheres for scattering and absorption of radiation: 2. Hexagonal columns and plates, J. Geophys. Res., 108, 4448, doi:10.1029/2002JD003302, 2003.

935 Nousiainen, T., and McFarquhar, G. M.: Light Scattering by Quasi-Spherical Ice Crystals, J. Atmos. Sci., 61, 2229–2248, https://doi.org/10.1175/1520-0469(2004)061<2229:LSBQIC>2.0.CO;2;, 2004.

Panferov, O., Knyazikhin, Y., Myneni, R. B., Szarzynski, J. Engwald, Schnitzler, K. G., & Gravenhorst, G.: The role of canopy structure in the spectral variation of transmission and absorption of solar radiation in vegetation canopies, IEEE Transactions on Geoscience and Remote Sensing, 39, 241–253, 2001.

Peltoniemi, J., Kaasalainen, S. Näränen, J., Matikainen, L. and Piironen. J: Measurement of directional and spectral signatures of light reflectance by snow, IEEE Trans. Geosci. Remote Sensing, 43(10), 2294–2304, 2005.

- 945 Peltoniemi, J.I., Suomalainen, J., Hakala, T., Puttonen, E., Näränen, J., Kaasalainen, S., Torppa, J. and Hirschmugl. M.: Reflectance of various snow types: measurements, modelling and potential for snow melt monitoring, in Light Scattering Reviews 5: Single Light Scattering and Radiative Transfer, chapter 9, page 393–450, edited by: Alexander A. Kokhanovsky, Springer Praxis Books, Berlin, Heidelberg, 2010.
- Peltoniemi, J. I., Hakala, T., Suomalainen, J., Honkavaara, E., Markelin, L., Gritsevich, M., Eskelinen, J., Jaanson, P., Ikonen,
   E.: A detailed study for the provision of measurement uncertainty and traceability for goniospectrometers, J. Quant. Spectrosc.
   Radiat. Transfer, 146, 376–390, 2014.

Peltoniemi, J. I., Gritsevich, M., Hakala, T., Dagsson-Waldhauserová, P., Arnalds, Ó., Anttila, K., Hannula, H.-R., Kivekäs,

955 N., Lihavainen, H., Meinander, O., Svensson, J., Virkkula, A., and de Leeuw, G.: Soot on Snow experiment: bidirectional reflectance factor measurements of contaminated snow. The Cryosphere, 9, 2323–2337, https://doi.org/10.5194/tc-9-2323-2015, 2015. Picard, G., Libois, Q., and Arnaud, L.: Refinement of the ice absorption spectrum in the visible using radiance profile measurements in Antarctic snow, The Cryosphere, 10, 2655–2672, doi:10.5194/tc-10-2655-2016, 2016.

Picard, G., Dumont, M., Lamare, M., Tuzet, F., Larue, F., Pirazzini, R. and Arnaud, L.: Spectral albedo measurements over snow-covered slopes: theory and slope effect corrections, The Cryosphere, 14, 1497–1517, doi.org/10.5194/tc-14-1497-2020, 2020.

965

Pirazzini, R., Räisänen, P., Vihma, T., Johansson, M., and Tastula, E.-M.: Measurements and modelling of snow particle size and shortwave infrared albedo over a melting Antarctic ice sheet, The Cryosphere, 9, 2357–2381, https://doi.org/10.5194/tc-9-2357-2015, 2015.

970 Pomeroy, J.W. and Gray, D.M.: Saltation of Snow, Water Resources Research, 26(7), 1583-1594, 1990.

Rautiainen, M., and Stenberg, P.: Application of photon recollision probability in coniferous canopy reflectance simulations, Remote Sens. Environ., 96, 98–107, 2005.

- 975 Román, M.O., Schaaf, C.B., Lewis, P., Gao, F., Anderson, G.P., Privette, J.,L., Strahler, A.H., Woodcock, C.E., Barnsley, M.: Assessing the coupling between surface albedo derived from MODIS and the fraction of diffuse skylight over spatiallycharacterized landscapes, Remote Sensing of Environment, 114, 738–760, 2010.
- Roujean, J.-L., Manninen, T., Sukuvaara, T., Peltoniemi, J., Kaasalainen, S., Hautecoeur, O., Lahtinen, P., Riihelä,
  A., Siljamo, N., Lötjönen, M., Karjalainen, T., Kontu, A., Suokanerva, H., Aulamo, O., Lemmetyinen, J., Suomalainen, J.,
  Hakala, T., Kaartinen, H., Thölix, L., Meinander, O. and Karhu, J.: SNORTEX (Snow Reflectance Transition EXperiment):
  Remote sensing measurement of snowmelt in northern boreal forest of Europe. iLEAPS Newsletter, Issue N° 9, Pages : 56-58, 2010.
- 985 Russ, J.C.: Fractal surfaces, Vol. 1., Plenum Press, New York, p. 167, 1994.

Räisänen, P., Kokhanovsky, A., Guyot, G., Jourdan, O. and Nousiainen, T.: Parameterization of single-scattering properties of snow, The Cryosphere, 9, 1277–1301, doi:10.5194/tc-9-1277-2015, 2015.

990 Schaepman-Strub, G., Schaepman, M.E. Painter, T.H., Dangel, S. and Martonchik, J.V.: Reflectance quantities in optical remote sensing—definitions and case studies, Remote Sensing of Environment 103, 27–42, 2006. Smolander. S. and Stenberg, P.: Simple parameterizations of the radiation budget of uniform broadleaved and coniferous canopies, Remote Sensing of Environment, 94, 355–363, 2005.

995

Sommer, C.G., Lehning, M. and Fierz, C.: Wind Tunnel Experiments: Influence of Erosion and Deposition on Wind-Packing of New Snow, Front. Earth Sci. 6:4. doi: 10.3389/feart.2018.00004, 2018.

Stenberg, P., Mõttus, M. and Rautiainen, M.: Modeling the spectral signature of forests: Application of remote sensing models
to coniferous canopies, in Advances in land remote sensing, edited by: S. Liang, Springer Science + Business Media B.V., 147–171, 2008.

Stenberg, P. and Manninen T.: The effect of clumping on canopy scattering and its directional properties: a model simulation using spectral invariants. International Journal of Remote Sensing, 36(19), pp 5178–5191.
1005 https://doi.org/10.1080/01431161.2015.1049383, 2015.

Stenberg, P., Mõttus, M. and Rautiainen, M.: Photon recollision probability in modelling the radiation regime of canopies — A review, Remote Sensing of Environment 183, pp 98–108, 2016.

1010 Toikka, M.: Field tests with the Snow fork in determining the density and wetness profiles of a snow pack, Microwave Signature -92, IGLS-Innsbruck, Austria, 1-3, July 1992. https://toikkaoy.com/snowfork\_brochure\_2018.pdf, 1992.

Tsang, L., Kong., J.A. and Shin, R.T.: Theory of Microwave Remote Sensing, John Wiley & Sons, New York, pp. 613, 1985.

1015 Ulaby, F.T., Moore, R.K. and Fung, A.K.: Microwave Remote Sensing, Active and Passice, Vol. II, Addison-Wesley, London, 457–106, 1982.

Warren, S. G.: Optical constants of ice from the ultraviolet to the microwave, Applied Optics, 23, 8, 1206–1225, doi: 10.1364/AO.23.001206, 1984.

1020

Warren, S.G. and Wiscombe, W.J.: A Model for the Spectral Albedo of Snow. II: Snow Containing Atmospheric Aerosols. Journal of the Atmospheric Sciences, 37(12), 2734–2745, 1980.

Warren, S.G., Brandt., R.E. and O'Rawe Hinton, P.: Effect of surface roughness on bidirectional reflectance of Antarctic snow.
Journal of Geophysical Research, 103(E11), 25,789–25,807, 1998.

Warren, S. G., and R. E. Brandt: Optical constants of ice from the ultraviolet to the microwave: A revised compilation. J. Geophys. Res., 113, D14220, doi:10.1029/2007JD009744, 2008.

1030 Zhang, Z., Yang, P., Kattawar, G., Tsay, S., Baum, B., Hu, Y., Heymsfield, A. and Reichardt, J.: Geometrical-optics solution to light scattering by droxtal ice crystals, Appl. Opt. 43, 2490-2499, 2004.

Zhuravleva, T.B. and Kokhanovsky, A.A.: Influence of surface roughness on the reflective properties of snow. Journal of Quantitative Spectroscopy & Radiative Transfer, 112, 1353–1368, 2011.

Table 1. The variation range and median values of the air temperature and snow surface temperature during the SNORTEX campaign in Sodankylä in March 11 – 19 and April 20 – 27, 2009. The corresponding variation of the snow density and snow water equivalent are given as well. The measurements were carried out during 9 and 17 hours local time (Manninen and Roujean, 2014). The values in brackets are those measured at the reference site NorSEN-mast ( $67.3621^\circ$ N,  $26.63445^\circ$ E) in Tähtelä. The total number of individual measurements was altogether 118 (17) for the reference site. The elemental carbon and organic carbon concentrations measured nearby the NorSEN mast ( $67.364011^\circ$ N,  $26.635891^\circ$ E) in March and April are shown as well (Meinander et al., 2020).

Parameter		Air	Snow surface	Snowpack	Snowpack	Snowpack	Elemental	Organic
		temperature at	temperature	depth	density	water	carbon	carbon
		2 m	··· 1·····		j	equivalent		
			[°C]	[m]	[kg m <sup>-3</sup> ]	equivalent	[10-9	[10-9
		[°C]	[ 0]	[111]	[Kg III ]	[m]	[10	[10
		[ C]				[111]	kg/kg]	kg/kg]
March	Min	-11.0 (-7.3)	-13.3 (-10.7)	0.20 (0.56)	180 (220)	0.051 (0.123)	18.8	483
	Median	-0.4 (0.0)	-2.5 (-4.1)	0.57 (0.59)	230 (230)	0.129 (0.139)	29.4	926
						(0.000)	_,	
	Max	14(12)	0.45(0.45)	0.71 (0.62)	290 (240)	0 225 (0 149)	41.5	1845
	man	1.1 (1.2)	0.15 (0.15)	0.71 (0.02)	200 (210)	0.225 (0.115)	11.5	1015
April	Min	-3.5 (-0.05)	-3.6 (-2.2)	0 (0.36)	250 (220)	0.014 (0.109)	15.7	988
			010 ( 212)	0 (0100)	200 (220)	01011 (01103)	1017	200
	Median	54(54)	0.05 (0.15)	0.37 (0.43)	310 (270)	0.121 (0.130)	85.7	2894
		5.1 (5.1)	0.00 (0.10)	0.07 (0.15)	213 (270)	0.121 (0.150)	00.7	2091
	Max	10.13 (8.9)	0.25 (0.25)	0.76 (0.62)	420 (330)	0.294 (0.145)	106.3	7172
					(000)		10012	

## 1045Table 2. The variation range and median values of snow grain size (defined as the maximum diameter of the smallest snow grain in<br/>each sample) and density of the topmost layer and the snowpack during the SNORTEX campaign in Sodankylä in March 11 – 19<br/>and April 20 – 27, 2009.

Parameter		Grain diameter of top layer [mm]	Grain diameter of snowpack [mm]	Density of top layer [kg m <sup>-3</sup> ]	Density of snowpack [kg m <sup>-3</sup> ]
March	Min	0.25	0.25	110	59
	Median	0.5	1.5	143	173
	Max	1.5	3.25	317	345
April	Min	0.25	0.25	65	11
	Median	2	2	272	259
	Max	3.5	4	433	433

Table 3. The mean values and variation range of the ratio  $r_{fb}$  of backward to forward scattering for diverse solar zenith angle values1050for all profiles measured in March and April, 2009. These values represent the surface scattering contribution only.

Solar zenith angle	Mean <i>r<sub>fb</sub></i>	80% variation range of <i>r<sub>fb</sub></i>
20°	0.35	0.21 – 0.49
40°	0.66	0.36 – 1.02
60°	1.27	0.50 – 2.27
80°	4.05	1.23 - 8.43

Figure captions:

1065

1055 Figure 1. Test area in Sodankylä in northern Finland. The premises of the Arctic Space Centre of FMI are situated in Tähtelä (T). The operational albedo measurements are located in the upper part of that rectangle, the NorSEN mast at the lower part. The aapa mire test site Mantovaaranaapa is marked with M and the forest clearing site Hirviäkuru with H. The corner co-ordinates of the area given in the WGS84 system. CC BY 4.0 National Land Survey of Finland (04/2020).

Figure 2. Examples of surface roughness of snow at Mantovaaranaapa on April 22, 2009. The black background of the plate is 1 m wide.

Figure 3. Facet structure of a randomly rough surface of spherical scatterers. The arrows indicate an example of a possible ray path involving facet-to-facet scattering.

Figure 4. Surface characteristics calculated from the plate measurements in March and April. Left) the relative height distributions and right) the distributions of the slope angles (in degrees) at the average measured spatial resolution of 0.26 mm.

Figure 5. The average number of reflections  $\langle n_s \rangle$  of individual ray hitting the surface as a function of the rms slope angle  $\beta$  (in radians) for two incident solar zenith angle values  $\theta_i$  for the snow profiles measured in the SNORTEX campaign (Manninen and Roujean 2014; Anttila et al. 2014) in March and April 2009.

Figure 6. The average zenith angle  $\theta_0$  of reflected escaping individual ray as a function of the rms slope angle  $\beta$  (in radians) for two irradiance solar zenith angle values  $\theta_i$  for the snow profiles measured in the SNORTEX campaign (Manninen and Roujean 2014; Anttila et al. 2014) in March and April 2009. The sign of the zenith angle is positive for forward reflection and negative for backward reflection.

Figure 7. Relationship between rms slope angle and the horizontal distance between the points used for its determination according to the laser scanning data of March 18, 2010. For comparison the mean value and variation range of the rms slope angle values derived from the 10 plate profiles for horizontal resolution 0.25 mm in the same area in the same day are shown in red. The dashed black curve is the regression to the 36 laser scanning based points (black polyline) and the grey shaded area covers the 80% variation range of rms slope angle at the distance in question.

Figure 8. The relationship between the albedo values corresponding to the solar zenith angle value of  $73^{\circ}$  measured operationally at Sodankylä and the regression (albedo = 0.84 - 0.29 *b* - 0.008 *k*<sub>0</sub>) based on measured surface roughness parameters *b* (Eq. 1) and *k*<sub>0</sub> (Eq. 2) at the NorSEN mast in March and April, 2009. The darkness of the markers is related to the fraction of diffuse irradiance.

Figure 9. Variation range (grey) of the individual snow reflectance spectra measured using the ASD spectrometer in Hirviäkuru (67.38°N, 26.85°E) on March 13 and in Mantovaaranaapa (67.4°N, 26.72°E) on April 22. The albedo simulations using the TARTES model are shown for fractal grains (blue) and spheres (red). The solid lines indicate the mean value and the dotted lines the minimum and maximum curves of the day in question. The ASD measurements were carried out in the same area as the grain size and density measurements, but the impurity measurements were daily values measured at Tähtelä (67.37°N, 26.63°E).

Figure 10. Evolution of measured surface albedo in Tähtelä (67.37°N, 26.63°E) on March 12 - 19 and April 20 – 28, 2009. The corresponding variation range of simulated albedo values based on simultaneous grain size and density
measurements and temporally interpolated impurity content in the same day are shown in grey. The minimum, mean and maximum values are indicated with darker grey curves. The vertical 'error bars' marked for some of the measured albedo values are based on the variation range of the measured ASD spectra based broadband reflectance values during the same day in the larger test area in Sodankylä.

Figure 11. Ratio of simulated total and bulk white-sky albedo values for all 1381 profiles and snow pit and impurity data in Sodankylä in March 11-19 and April 20-28, 2009. The daily mean, minimum and maximum values are indicated by the darker curve and the variation range is shaded.

Figure 12. Simulated albedo values at the NorSEN-mast based on density, grain size and surface roughness measurements of snow in March 12-19, 2009 and in April 20 – 28, 2009 and temporally interpolated impurity content data. The mean values are shown separately for the TARTES model containing only the volume scattering contribution (grey curve) and the TARTES model combined with the surface scattering model of this study (blue or red). The daily variation range based on diverse profiles, grain size and density measured at the site and temporally interpolated impurity content is shown as the area shaded by light blue or light red colour. The darkness of the empirical points indicates the fraction of diffuse irradiance during the measurement.

Figure 13. Measured and modelled blue-sky albedo values at Mantovaaranaapa on April 22, 2009. Each modelled point is an average corresponding to three individual plate profiles taken from the same surface. The empirical albedo values are likewise averages of individual three points recorded using the Kipp & Zonen albedometer CM14 at the time of taking the profile photos. The shaded area shows the variation range of the broadband reflectance values measured using the ASD spectrometer.

Figure 14. Measured principal plane BRFs in Mantovaaranaapa April 22, 2009 of one smooth snow and three rough snow cases, with a few individual profiles each.

Figure 15. Mantovaaranaapa on April 22, 2009.

Figure 16. Calculated average scattering angle distributions for surface scattering (i.e., zenith angles of reflected radiation, positive for forward directions and negative for backward directions) for profiles measured during the SNORTEX campaign in 2009 (blue) and in Mantovaaranaapa in April 22, 2009 (red) for incidence angle values  $20^{\circ}$  and  $60^{\circ}$ .

1115 and 6

Figure 17. Surface roughness parameter *a* as a function of surface roughness parameter *b* (Eq. 1) of the dominantly backscattering and dominantly forward scattering profiles for incidence angles  $20^{\circ}$ ,  $40^{\circ}$  and  $60^{\circ}$ .

Figure 18. Snow surface structure evolution during March 16 - 18, 2009. The cm scale is shown in the right images.

Figure 19. Microscale snow surface structure evolution during March 16 - 18, 2009. In the left images the scale of the grid is 1 mm. In the right images the grids correspond to 1 mm, 2 mm and 3 mm from left to right.

Figure 20. Top) The snow surface rms height and correlation length measured with the plate method during March 16 – 18, 2009. The values correspond to the distance 0.6 m. Bottom) The rms slope angle  $\beta$  (in radians) of individual plate snow profiles during March 16 – 18, 2009. The linear regression for  $\beta$  vs. time is shown for March 16,  $R^2$  value included.



(67.35°N, 26.62°E)

1130 Figure 1. Test area in Sodankylä in northern Finland. The premises of the Arctic Space Centre of FMI are situated in Tähtelä (T). The operational albedo measurements are located in the upper part of that rectangle, the NorSEN mast at the lower part. The aapa mire test site Mantovaaranaapa is marked with M and the forest clearing site Hirviäkuru with H. The corner coordinates of the area given in the WGS84 system. CC BY 4.0 National Land Survey of Finland (04/2020).



Figure 2. Examples of surface roughness of snow at Mantovaaranaapa on April 22, 2009. The black background of the plate is 1 m wide.



Figure 3. Facet structure of a randomly rough surface of spherical scatterers. The arrows indicate an example of a possible ray path involving facet-to-facet scattering.



1180 Figure 4. Surface characteristics calculated from the plate measurements in March and April. Left) the relative height distributions and right) the distributions of the slope angles (in degrees) at the average measured spatial resolution of 0.26 mm.



Figure 5. The average number of reflections  $\langle n_s \rangle$  of individual ray hitting the surface as a function of the rms slope angle  $\beta$ (in radians) for two incident solar zenith angle values  $\theta_i$  for the snow profiles measured in the SNORTEX campaign (Manninen and Roujean 2014; Anttila et al. 2014) in March and April 2009.



Figure 6. The average zenith angle  $\theta_0$  of reflected escaping individual ray as a function of the rms slope angle  $\beta$  (in radians) for two irradiance solar zenith angle values  $\theta_1$  for the snow profiles measured in the SNORTEX campaign (Manninen and Roujean 2014; Anttila et al. 2014) in March and April 2009. The sign of the zenith angle is positive for forward reflection and negative for backward reflection.



Figure 7. Relationship between rms slope angle and the horizontal distance between the points used for its determination according to the laser scanning data of March 18, 2010. For comparison the mean value and variation range of the rms slope angle values derived from the 10 plate profiles for horizontal resolution 0.25 mm in the same area in the same day are shown in red. The dashed black curve is the regression to the 36 laser scanning based points (black polyline) and the grey shaded area covers the 80% variation range of rms slope angle at the distance in question.



Figure 8. The relationship between the albedo values corresponding to the solar zenith angle value of  $73^{\circ}$  measured operationally at Sodankylä and the regression (albedo = 0.84 - 0.29 *b* - 0.008 *k0*) based on measured surface roughness parameters *b* (Eq. 1) and *k0* (Eq. 2) at the NorSEN mast in March and April, 2009. The darkness of the markers is related to the fraction of diffuse irradiance.



Figure 9. Variation range (grey) of the individual snow reflectance spectra measured using the ASD spectrometer in
Hirviäkuru (67.38°N, 26.85°E) on March 13 and in Mantovaaranaapa (67.4°N, 26.72°E) on April 22. The albedo simulations using the TARTES model are shown for fractal grains (blue) and spheres (red). The solid lines indicate the mean value and the dotted lines the minimum and maximum curves of the day in question. The ASD measurements were carried out in the same area as the grain size and density measurements, but the impurity measurements were daily values measured at Tähtelä (67.37°N, 26.63°E).



Figure 10. Evolution of measured surface albedo in Tähtelä ( $67.37^{\circ}$ N,  $26.63^{\circ}$ E) on March 12 - 19 and April 20 – 28, 2009. The corresponding variation range of simulated albedo values based on simultaneous grain size and density measurements and temporally interpolated impurity content in the same day are shown in grey. The minimum, mean and maximum values are indicated with darker grey curves. The vertical 'error bars' marked for some of the measured albedo values are based on the variation range of the measured ASD spectra based broadband reflectance values during the same day in the larger test area in Sodankylä.



Figure 11. Ratio of simulated total and bulk white-sky albedo values for all 1381 profiles and snow pit and impurity data in Sodankylä in March 11-19 and April 20-28, 2009. The daily mean, minimum and maximum values are indicated by the darker curve and the variation range is shaded.



Figure 12. Simulated albedo values at the NorSEN-mast based on density, grain size and surface roughness measurements of snow in March 12-19, 2009 and in April 20 – 28, 2009 and temporally interpolated impurity content data. The mean values are shown separately for the TARTES model containing only the volume scattering contribution (grey curve) and the

1255 TARTES model combined with the surface scattering model of this study (blue or red). The daily variation range based on diverse profiles, grain size and density measured at the site and temporally interpolated impurity content is shown as the area shaded by light blue or light red colour. The darkness of the empirical points indicates the fraction of diffuse irradiance during the measurement.



Figure 13. Measured and modelled blue-sky albedo values at Mantovaaranaapa on April 22, 2009. Each modelled point is an average corresponding to three individual plate profiles taken from the same surface. The empirical albedo values are likewise averages of individual three points recorded using the Kipp & Zonen albedometer CM14 at the time of taking the profile photos. The shaded area shows the variation range of the broadband reflectance values measured using the ASD spectrometer.



Figure 14. Measured principal plane BRFs in Mantovaaranaapa April 22, 2009 of one smooth snow and three rough snow cases, with a few individual profiles each.





Figure 15. Mantovaaranaapa on April 22, 2009.



Figure 16. Calculated average scattering angle distributions for surface scattering (i.e., zenith angles of reflected radiation, positive for forward directions and negative for backward directions) for profiles measured during the SNORTEX campaign in 2009 (blue) and in Mantovaaranaapa in April 22, 2009 (red) for incidence angle values 20° and 60°.



1290 Figure 17. Surface roughness parameter a as a function of surface roughness parameter b (Eq. 1) of the dominantly backscattering and dominantly forward scattering profiles for incidence angles 20°, 40° and 60°.



March 16, 2009



1295

### March 17, 2009





1300 Figure 18. Snow surface structure evolution during March 16 - 18, 2009. The cm scale is shown in the right images.





Figure 19. Microscale snow surface structure evolution during March 16 - 18, 2009. In the left images the scale of the grid is 1 mm. In the right images the grids correspond to 1 mm, 2 mm and 3 mm from left to right.



Figure 20. Top) The snow surface rms height and correlation length measured with the plate method during March 16 – 18, 2009. The values correspond to the distance 0.60 cm. Bottom) The rms slope angle  $\beta$  (in radians) of individual plate snow profiles during March 16 – 18, 2009. The linear regression for  $\beta$  vs. time is shown for March 16,  $R^2$  value included.