

Drainage of an ice-dammed lake through a supraglacial stream: hydraulics and thermodynamics

Christophe Ogier^{1,2}, Mauro A. Werder^{1,2}, Matthias Huss^{1,2,3}, Isabelle Kull⁴, David Hodel⁵, and Daniel Farinotti^{1,2}

¹Laboratory of Hydraulics, Hydrology and Glaciology (VAW), ETH Zurich, Zurich, Switzerland

²Swiss Federal Institute for Forest, Snow and Landscape Research (WSL), Birmensdorf, Switzerland

³Department of Geosciences, University of Fribourg, Fribourg, Switzerland

⁴Geotest AG, Zollikofen, Switzerland

⁵Theiler Ingenieure, Thun, Switzerland

Correspondence: Christophe Ogier (ogier@vaw.baug.ethz.ch)

1 Abstract

The glacier-dammed Lac des Faverges, located on Glacier de la Plaine Morte (Swiss Alps), drained annually as a glacier lake outburst flood since 2011. In 2018, the lake volume reached more than $2 \times 10^6 \text{ m}^3$ and the resulting flood caused damages to the infrastructure downstream. In 2019, a supraglacial channel was dug to artificially initiate a surface lake drainage, thus limiting the lake water volume and the corresponding hazard. The peak in lake discharge was successfully reduced by over 90 % compared to 2018. We conducted extensive field measurements of the lake-channel system during the 48-days drainage event of 2019 to characterize its hydraulics and thermodynamics. The derived Darcy-Weisbach friction factor, which characterizes the water flow resistance in the channel, ranges from 0.17 to 0.48. This broad range emphasizes the factor's variability, and questions the choice of a constant friction factor in glacio-hydrological models. For the Nusselt number, which relates the channel-wall melt to the water temperature, we show that the classic, empirical Dittus-Boelter equation with the standard coefficients is not adequately representing our measurements, and we propose a suitable pair of coefficients to fit our observations. This hints at the need to continue the research into how heat transfer at the ice/water interface is described in the context of glacial hydraulics.

2 Introduction

Glacier-dammed lakes are often unstable as ice dams are prone to rapidly fail which leads to partial or total drainage of the impounded lake through supraglacial, englacial and subglacial conduits (Roberts, 2005). The sudden release of the water impacts glacier dynamics (Röthlisberger, 1972) and may lead to extreme peak discharge at the outlet (Björnsson, 1992). Lake dam failure can occur via three main mechanisms, or a combination thereof, which are the following: (i) high water pressure beneath the dam leads to its flotation (Björnsson, 2010), (ii) the lake water leaks through the dam via e.g. pre-existing **eraeksveins**, channels form and then progressively enlarge (Nye, 1976), or (iii) the lake water overflows the dam and forms a

breach due to ice erosion (Walder and Costa, 1996; Raymond and Nolan, 2000; Mayer and Schuler, 2005). The last process is less well-documented than the former two, and is more common for cold-based glaciers rather than temperate ones (Björnsson, 2010). Enlargement of pre-existing **cracks-veins** and conduits (process ii) is possible due to frictional heating (i.e thermal energy dissipation in the waterflow due to potential energy release) and/or due to sensible heat fluxes (i.e advection of warm water from the lake). In general, both processes (ii) and (iii) lead to progressively rising discharge, whereas process (i) often results in a very fast drainage onset and high discharge. These fast lake drainages, so-called glacial lake outburst floods (GLOFs) or 'jökulhlaups', are a serious threat in populated areas and have caused major destruction in the past (e.g. Haeberli, 1983; Richardson and Reynolds, 2000; Björnsson, 2002; Ancey et al., 2019).

In the frame of hazard mitigation, glacier-dammed lakes have sometimes been drained artificially. In 1892, for example, an outburst event at Glacier de Tête Rousse (France) devastated the village of Saint Gervais les Bains and caused 175 fatalities. To prevent further hazardous events, a tunnel in rock and ice was dug in 1904 to empty the subglacial lake (Vincent et al., 2010b). This tunnel has been maintained until today but water did no longer run through it. In 2010, a subglacial water-filled cavity of 55,000 m³ was discovered at the same glacier through geophysical surveys, and was artificially drained using submersible pumps (Vincent et al., 2012). In some other cases, a channel was dug inside the ice or at the glacier surface to evacuate the lake water. The earliest of such examples, is from Glacier de Giétro (Switzerland) in 1818, when a channel was dug through the ice dam to empty a lake (maximum volume of about 25 × 10⁶ m³) impounded by an advancing glacier. Due to high channel erosion, however, large parts of the ice dam collapsed, releasing the remaining water in very short time, leading to 40 fatalities. The discharge peak reconstructed by Ancey et al. (2019) was about 14,500 m³s⁻¹. In 2005, the 0.7 × 10⁶ m³ ice-dammed lake on Glacier de Rochemelon (French Alps) were also drained artificially. This was done by combining a siphon method and a surface channel of 100 m length (Vincent et al., 2010). The dangerous lake was emptied with success, with a peak discharge of merely 1.5 m³s⁻¹.

In the present paper we focus on glacier lake drainage through a surface channel. When it comes to this sort of intervention for hazard mitigation, it is vital to know whether the drainage will be stable or unstable, i.e. whether the discharge will rise rapidly or not. Raymond and Nolan (2000) introduced the concept of stable and unstable drainage based on observations from Black Rapids Glacier (Alaska) and identified a set of parameters that are of particular interest. In a stable drainage regime, for example, the lowering rate of the lake level is higher or equal to the channel incision rate and, thus, the lake discharge decreases with time. Conversely, in an unstable drainage regime the channel erosion is higher than the lake level lowering. The lake discharge hence increases with time and the lake is emptied completely and rapidly. Vincent et al. (2010) used the Raymond and Nolan (2000) approach to reconstruct the drainage of the ice-marginal Lac de Rochemelon. They based their analysis on extensive field measurements carried out during the artificial drainage. They were able to conduct a sensitivity analysis on the relevant parameters that control the lake discharge, such as water temperature and lake area. However, some of their parameters were only inferred *at post* from the field observations, and the analysis was thus not able to predict the peak discharge in advance.

Since then, other studies have tried to model channelized surface drainage in order to focus on the physical processes at play. Jarosch and Gudmundsson (2012), for example, provided explicit numerical simulations of such drainage by including the

effects of ice dynamics to the pre-existent open-channel flow models. This enabled the shape and evolution of the channel to be purely driven by **physiesice physical and hydraulic processes**, and not to be pre-defined as in earlier studies (e.g. Raymond and Nolan, 2000; Walder and Costa, 1996). Channel slope, water flux and temperature were shown to be the main parameters controlling channel incision, which in turn dictates the discharge at the lake outlet. Kingslake et al. (2015) built upon the work
60 of Raymond and Nolan (2000), and formulated a more generally applicable model by including considerations of sub-critical flow at the lake outlet. Although these studies represent the state-of-the-art in supraglacial lake drainage modelling, they have never been validated against independent field observations (Pitcher and Smith, 2019). This calls for corresponding datasets to be acquired, as the question about whether such models are able to correctly simulate supraglacial lake drainage in the context of hazard mitigation remains open.

65 In this paper, we focus on the collection and interpretation of such a dataset, acquired for the hazardous Lac des Faverges at Glacier de la Plaine Morte (Switzerland). This ice-marginal lake drained subglacially every summer from 2011 to 2018 with increasing volume and peak discharge over time (Huss et al., 2013; Lindner et al., 2020). A monitoring and early warning system was set up in 2012. The drainage event of 2018 caused inundations in the village of Lenk, north of the glacier. Parts of the village needed to be evacuated and damages to houses and infrastructure were substantial. The community thus decided
70 to design measures to artificially lower the lake level to reduce the hazard potential. In 2019, the lake initially drained through an artificial, supraglacial channel (Figure 1). Later during the summer, half of the lake volume drained subglacially again but without causing damage. We took advantage of this particular situation to carry out extensive field measurement during the 48 days of the lake drainage. In particular, we monitored lake level, discharge, water temperature and channel geometry evolution with high spatial and temporal resolution. This allows us to describe the applied flood risk mitigation strategy in detail, and to
75 determine some of the most important physical parameters involved in the supraglacial drainage of an ice-dammed lake. We anticipate that this work will support further modelling studies and, thus, also help in the planning of future hazard mitigation measures.

3 Study area

3.1 Previous GLOFs of Lac des Faverges

80 Glacier de la Plaine Morte is located in the Bernese Alps (46°23'N, 7°30'E), Switzerland. It is the largest plateau glacier in the European Alps (7.1 km² in 2019), with 90% of its surface spanning an elevation range of only 2650–2800 m a.s.l. The ice-marginal Lac des Faverges is located in the upper reaches of the glacier, at its south-eastern margin (Figure 1a). According to aerial imagery of the Swiss Federal Office of Topography, the lake started forming in the 1970s, and now fills annually during the melt season. Because of the rapid ice loss over the last years, the basin enlarged, thus increasing the potential lake volume
85 too (Huss et al., 2013). Simultaneously, the maximum lake level lowered due to a significant reduction in ice surface elevation and since 2012, the lake water no longer overspill a sediment ridge to the south. Instead of draining superficially towards the Rhone basin, the lake water now drains englacially northwards, into the Rhine basin. The glacier lake outburst floods of Lac des Faverges have occurred annually since 2011 (Lindner et al., 2020) and represent a serious concern for Lenk, a 2300-inhabitants

village 10 km downstream of the glacier snout (Bundesamt für Umwelt, 2020) . The lake level and temperature are monitored
90 in detail since 2012 by Geopraevent AG (<https://www.geopraevent.ch/>) for early warning purposes, and daily images from an
automatic camera are also available. An alarm is triggered when the rate of lake-level change reaches a given critical value.
Huss et al. (2013) projected the future evolution of Glacier de la Plaine Morte for the coming century, and also estimated the
changes in the lake basin over the next decades. They concluded that a continuous increase in lake volume is likely, along with
an increase in the potential flood hazard for the village of Lenk. In 2018, the lake discharge reached around $80 \text{ m}^3\text{s}^{-1}$ causing
95 damage to infrastructure for the first time (Gemeinde Lenk, 2019).

3.2 The 2019 GLOF mitigation plan

In spring 2019, local authorities decided to limit the maximum lake volume by constructing a supra- and englacial channel
to artificially drain the lake water in order to face the increasing threat by floods due to sudden lake drainage. This channel
now connects the lake outlet to a permanent large moulin located ~ 1.3 km westward and about 20m lower in altitude (we will
100 refer to this feature as to the "Moulin West" in the following, see Figure 1a). Past observations have shown that this moulin
is in turn connected to the subglacial network, and that this connection often establishes relatively early during the melting
season (Finger et al., 2013). In the middle of the channel there is a ~ 100 m long tunnel (labelled "micro tunnel" in Figure 1c),
which is a remainder of the initial plan to drill a 40 cm-diameter englacial tunnel, instead of a surface channel, for part of the
distance (only a short section of the tunnel was completed, due to technical issues). The supraglacial channel was dug from
105 the beginning of April until early July 2019. In a first stage, the 4-5 m deep snow cover had to be removed by snowcats. In a
second stage, the **solid and impermeable** ice was cut and removed by an excavator. Because of these artificial interventions,
the initial geometry of the channel is well known, with a width of 1 m at the bottom, 4 m to 7 m depth from the ice surface, and
a length of 1.3 km (see Fig. 1d). During this second stage, water from ice- and snow-melt was present in the channel.

The lake is connected via a preexisting ice-surface canyon and a subsequent natural ice cave to the artificial supraglacial
110 channel (figure 1b). At the beginning of the canyon, where it connects to the lake, the water flows through an englacial siphon
for about 30 m.

On 10 July 2019, at 11:00, the channel spillway elevation was lowered by an excavator to match the lake level and to
artificially initiate the lake drainage. At that point, the spillway elevation was 2733.15 m a.s.l., corresponding to a lake volume
of ~~$\sim 1.38 \times 10^6$~~ $1.49 \times 10^6 \text{ m}^3 \pm 0.11 \times 10^6 \text{ m}^3$ and an area of 0.127 km^2 . The lake water ran only into the first, upper part of the
115 channel (Fig. 1c and d), and then infiltrated the glacier through a pre-existing moulin located within the micro-tunnel. A dye
injection in the channel on 26 July 2019 revealed that the lake water exited the glacier outlet after about 2 hours, and that there
was no significant lake water accumulation within the glacier.

In the following, we limit our attention to the upper part of the channel through which the lake water flowed for 36 days in
total (Figure 1c and 1d). This section (termed "channel" henceforth), was located between the cave outlet and the micro-tunnel
120 entrance, was 540 m long and had an average slope of 0.34 %. We designed our field campaign to monitor the hydraulic and
thermodynamic properties of the water flow in the channel, and relate that to lake level and volume evolution.




Figure 1. (a) Map of Glacier de la Plaine Morte where the ice-dammed Lac des Faverges lake is located. The lake area displayed in (b) corresponds to the maximum lake size reached on 10 July 2019 (at a lake level of 2733.15 m a.s.l). The supraglacial channel and the measurement stations P1 to P5 are presented in (c) and (d). The longitudinal profile in (d) was reconstructed from sparse elevation measurements of glacier surface and channel bottom prior to supraglacial lake drainage; the ice cave was not mapped and its representation is indicative only. The digital elevation model used in this figure was created from post-drainage aerial images acquired by the Swiss Federal Office of Topography on 3 September 2019 (see Section 4 for more information).

4 Methods

Two equations are of central importance to characterize the hydraulics and thermodynamics of the lake drainage through a supraglacial channel. The first is the Darcy-Weisbach equation (Incropera et al., 2007) which relates the water flow through a

125 channel to the ~~gradient of the hydraulic potential~~hydraulic slope and to the channel cross-sectional geometry:

$$\theta = \frac{f_D}{2g} \frac{v^2}{D_H}, \quad (1)$$

where g is the gravitational acceleration (m s^{-2}), θ is the hydraulic slope (dimensionless, expressed as ~~meter-water-head-drop-per-meter-channel~~water head drop per horizontal channel length), D_H the hydraulic diameter (m), and v the ~~stream-velocity~~velocity averaged over the cross-section (m s^{-1}). The constant of proportionality is the Darcy-Weisbach friction factor f_D .

130 The second equation characterises the thermodynamics, and relates the channel incision rate m (m s^{-1}) to heat flux q (W m^{-2}), where the latter can be related to the temperature difference between water and ice ΔT ($^{\circ}\text{C}$) via the dimensionless Nusselt number Nu :

$$m = \frac{q}{\rho_i L_f} = \frac{1}{\rho_i L_f} \frac{k_w Nu \Delta T}{\lambda}. \quad (2)$$

Here, k_w is the thermal conductivity of water ($\text{W m}^{-1} \text{ } ^{\circ}\text{C}^{-1}$), ρ_i is the ice density (kg m^{-3}), L_f the latent heat of fusion
135 (J kg^{-1}) and λ (m) is the length scale over which the turbulent heat transfer occurs (Incropera et al., 2007). Note that Nu is not a constant but increases with discharge, and that the equations contain both physical constants (Table 1) and factors (Table 2) depending on the geometry (θ , D_H), the hydraulics (v , D_H , θ), or the thermodynamics (T_w). We will mirror this distinction in the description of the field measurements and the data processing.

In the following, we will describe our approach to obtain all terms of those two equations, in particular by determining their
140 dimensionless parameters f_D and Nu , with our field measurements and their suitable processing steps.

4.1 Field measurements

4.1.1 Topography

Topography of the lake and channel is necessary to characterize the geometry of the channel, to determine the watershed contribution to lake filling, and to obtain the lake bathymetry in order to relate volume changes to lake surface elevation
145 changes. To do so, we use Digital Elevation Models (DEMs) from the Swiss Federal Office of Topography (swisstopo). The latter were derived by using stereophotogrammetry, aerotriangulation, ground control points, and ADS100 Image strips (ground sampling distance of ~ 0.1 m) acquired during flights commissioned by the Swiss Federal Office of the Environment on 28 August 2018 and 3 September 2019 when the lake was empty (see code and data availability section for references). The lake volume for the years 2012 to 2017 were also calculated using swisstopo DEMs. The theoretical nominal error of the swisstopo
150 DEMs is 2 m but is likely to be lower in the present situation with good ground contrast. ~~These uncertainties on DEMs were not taken into account in the following.~~The main uncertainty in our estimate of lake volume is the poorly constrained ice-surface melt occurring in the lake basin between late August 2018 (date of DEM acquisition) and July 2019. This results in bare-ice melting in autumn 2018, and in bare-ice melting due to heat transfer from water to glacier-ice before the lake drainage. Since these melt processes are not quantified in the lake basin, we constrained the lake volume using DEMs from August
155 2018 ($1.38 \times 10^6 \text{ m}^3$) and September 2019 ($1.59 \times 10^6 \text{ m}^3$) as a lower and upper bound, respectively. We determine the

volume to be the average of the two bounds, i.e. $1.49 \times 10^6 \text{ m}^3 \pm 0.11 \times 10^6 \text{ m}^3$. Note, for the subsequent calculation of lake outflow the bathymetry of the lake is required. For this, we use the 2018 DEM because ice-melt between 28 August 2018 to 10 July 2019 is expected to be significantly smaller than between 10 July 2019 to 3 September 2019.

4.1.2 Water pressure, temperature and conductivity in the channel

160 Most measurements were conducted at five locations (called "stations") along the channel, named P1 to P5 (Fig. 1c and 1d). Stations P1 and P2 were marked with ~~a-stake-stakes~~ drilled into the ice at the edge of the channel. At stations P3, P4 and P5 a cross-beam was installed between stakes drilled on either side of the channel. Coordinates and elevation of the stations' stakes were measured by differential Global Positioning System (GPS) with ~~an-~~a vertical accuracy of $\pm 0.02 \text{ m}$.

At four stations (P1,P2,P3 and P5), autonomous and time-synchronized data loggers (DCX-22-CTD by Keller AG für
165 ~~Druckmesstechnik~~) were installed to continuously recorded water pressure, temperature and conductivity. The logging interval was set to 1 s during tracer experiments and to 30 s otherwise. The accuracy of temperature measurements are $\pm 0.1^\circ\text{C}$ at stations P1 and P2, and $\pm 0.05^\circ\text{C}$ at stations P3 and P5. We however note that this is a point measurement of the temperature with the sensor located at the floor of the channel, and that the bulk water temperature is therefore likely higher. The accuracy of the pressure measurements corresponds to a water column uncertainty of ~~0.2~~0.005 m. The accuracy of conductivity
170 measurements is $5 \times 10^{-5} \text{ S m}^{-1}$ over the range 0 S m^{-1} to 0.2 S m^{-1} , which covered all the observations.

4.1.3 Channel geometry

At the stations, channel bottom elevation was measured using measuring tape either by lowering it from the top to the channel bottom, or by abseiling with it into the channel. These measurements provide a longitudinal (i.e along the stream-flow direction) channel-elevation profile and were performed 11 times during the lake drainage. Estimated uncertainties are typically 0.1 m to
175 0.5 m in elevation and 1 m in horizontal position. The best accuracy in elevation was obtained for cross-beam stations (0.1 m). Channel width at the water flow surface was measured only infrequently at P3 and P5 due to complex accessibility, with an ~~error-~~uncertainty of typically 0.1 m.

Higher temporal resolution of channel incision was obtained by measuring the clear diurnal melt-imprints left on the channel walls at P4 and P5 between 16 and 30 July 2019 (Fig. 4). We assume that the difference in elevation between two imprints
180 represents the daily rate of channel floor erosion. This interpretation is supported by the observation that there were 14 marks over the 14-day observation period. We ~~thus-~~suppose that the deeper incised sections of the melt-imprints form during the afternoon, when relatively high water temperature and discharge yield to significant melt on the channel walls. Conversely, decreasing discharge and water stage during the night yields to less side-way melt on the wall section which then emerges from the water, thus producing the less deeply incised sections of the melt-imprints. We thus refer to these marks as daily
185 water level cuts. Note that the channel geometry measurements described above give the temporal evolution of the channel, and thus the incision rates.

4.1.4 Hydraulics

To characterise the hydraulics of the channel we conducted measurements of discharge Q , the flow speed v , the stage h (i.e. water depth) in the channel, and the lake level z_{lake} . In our notation, the variables used for an instantaneous measurement are marked with an index i (e.g. h_i), to emphasize the difference with variables for continuous time series. Physical quantities for a spatial average between two stations are denoted with a bar (e.g. \bar{w}). Channel discharge Q_i was measured using the salt ~~tracer~~-dilution method (Hubbard and Glasser, 2005) at stations P1, P2 and P3. We carried out 33 salt injections at 12 different days during the campaign. Conductivity was measured at the monitored stations downstream of the salt injection location, with stations P3, P2, and P1 situated far enough downstream to ensure the required complete mixing of the tracer. Discharge can then be calculated from the conductivity measurements, as described in Section 4.2.2. The tracer experiments also provide information on travel time of the water between the stations equipped with conductivity sensors, and thus an average flow speed \bar{v}_i between stations can be calculated.

The water stage h is measured via pressure measurements, which were corrected for atmospheric pressure variations. The measurements rely on the pressure transducer sinking to the bottom of the channel, ~~which was~~. This is ensured to be the case for all presented measurements, ~~thanks to repeated visual inspection during field visits and because pressure transducers were weighted. When pressures transducers were not at the bottom of the channel, times series were noisy and close to the atmospheric pressure value, and we discarded the data.~~

The elevation of the lake level z_{lake} was measured by two pressure transducers operated by Geopraevent, with a logging interval of 10 min. The position of the transducers was not always stable, probably due to icebergs shifting them; the resulting obvious shifts in the data were manually corrected, ~~i. e. the data gaps were removed~~. The absolute elevation of the lake level was measured at three instances during the drainage using a differential GPS.

4.2 Data processing

4.2.1 Lake input from precipitation, snow and ice melt

Water input Q_{in} into the lake, by snow- and ice-melt or liquid precipitation, was substantial during the period of lake drainage but could not be directly monitored due to its non-localized nature. Instead, Q_{in} was estimated by using a distributed accumulation and temperature index melt-model driven by daily meteorological data (Hock, 1999; Huss et al., 2015). The model ~~is calibrated with~~ ~~has been calibrated using~~ the seasonal mass balance ~~measurements-carried-out~~ ~~data collected~~ by the programme Glacier Monitoring in Switzerland (GLAMOS). Seasonal mass balance is measured on Glacier de la Plaine Morte since 2009 using the direct glaciological method (GLAMOS, 2020). We applied the model ~~from September 2018 to September 2019~~ with a daily resolution to the watershed of the lake, and used it to estimate Q_{in} consisting of snowmelt from the glacierized and ice-free portion of the basin, bare-ice melt and liquid precipitation. The ~~distributed mass balance model (e.g. Huss et al., 2021) was driven with meteorological observations from Montana (9 km from the study site) and both melt factors as well as a precipitation correction factor have been calibrated to match seasonal mass balance observations on Plaine Morte in 2021.~~ The location of the watershed over the gently-sloping glacier ice is inaccurately known, and was adjusted to match

220 observed total lake volume on 10 July 2019 to the cumulative Q_{in} since the beginning of the melting season. The implicit assumption is, thus, that no water left the lake during that time span.

4.2.2 Hydraulics

The lake outflow Q_{out} , which may consist of both supra- and subglacial runoff, was computed from lake level changes Δz_{lake} with a diurnal resolution (Δt) by considering (1) the lake surface area A_{lake} as a function of z_{lake} according to the DEM
225 available for 28 August 2018, and (2) the recharge from melt Q_{in} at day d :

$$Q_{\text{out},d} = Q_{\text{in},d} - A_{\text{lake},d} \frac{\Delta z_{\text{lake},d}}{\Delta t}. \quad (3)$$

Instantaneous channel discharge Q_i was determined at P3, P2 and P1 was from salt traces using the following steps. First, ~~conductivity readings at those stations~~ the natural background level of conductivity at these stations was removed for each injection, and the conductivity readings were converted into salt concentration using a calibration function derived from measurements
230 conducted in laboratory. The function was derived by least-square regression of conductivity readings to salt concentration, for water temperature at 0°C and for concentration covering the entire range of observations. Second, salt concentrations were integrated over ~~time for each injections~~ the time of the tracer passage, for each injection, and converted to discharge using the tracer dilution method (e.g. Hubbard and Glasser, 2005). We aimed to obtain a continuous discharge time series Q by using the direct measurements Q_i to calibrate a stage-discharge relationship (or rating curve) at one station as follows

$$235 \quad Q = ah^b, \quad (4)$$

where a and b are fitted parameters, and h is the continuous time series of water stage at the selected station. The stage-discharge relation was established at P3 due to the high quality of direct discharge measurements by salt dilution (see Appendix B for values), the most continuous and reliable water stage time series, and the reasonably small geometry changes in the cross-section. Least-square fitting yielded parameters $a = 4.78 \pm 0.95$ and $b = 2.05 \pm 0.25$. The latter is in the range of literature
240 values for natural rivers (Aydin et al., 2002, 2006). The resulting discharge was validated against 19 discharge measurements determined using salt dilution at different times and for stations not used in the calibration. This validation resulted in a root-mean-square-error of $0.11 \text{ m}^3 \text{ s}^{-1}$, which is in line with the uncertainty in Q estimated from the standard error of parameters a and b .

A data gap in the channel's water stage time series between 13 and 24 July 2019 was filled with Q using values based on
245 daily lake discharge calculated according to using Eq. (3). To do so, we make the hypothesis that the channel is the only drainage path existing for the lake water, i.e. that there is no subglacial drainage occurring during that time period.

The average hydraulic slope (or hydraulic gradient) $\bar{\theta}_i$ over a channel segment of length l is

$$\bar{\theta}_i = \frac{\Delta p_i}{l}, \quad (5)$$

where Δp_i is the difference of two hydraulic head measurements (i.e channel bottom elevation z_i plus water stage h_i) at the
250 beginning and at the end of the segment. We calculated $\bar{\theta}_i$, and subsequently derived quantities only for the segment P5-P3 because uncertainties in field measurements were the lowest for this part of the channel.

The hydraulic diameter D_H is given by

$$D_H = \frac{4S}{P_w}, \quad (6)$$

where S (m^2) is the wetted cross-section **area** and P_w (m) is the wetted perimeter. To determine the Darcy-Weisbach friction factor f_D (see Eq. 1), the hydraulic diameter over a channel segment at a given time, $\bar{D}_{H,i}$, needs to be determined. This is obtained by Eq. 6 using \bar{S}_i and $\bar{P}_{w,i}$. \bar{S}_i is given by dividing the discharge \hat{Q}_i by the velocity \bar{v}_i , known at the times of salt dilution experiments. The channel width \bar{w} is assumed to be constant between P3 and P5 as well as constant in time, and we found a value of $\bar{w} = 2 \pm 0.5$ m. In the following, we assume a rectangular cross-section, and define the mean wetted perimeter as $\bar{P}_{w,i} = 2\bar{h}_i + \bar{w}$. This assumption is motivated by the initial channel shape (i.e. the shape prior to drainage) and by visual inspections that revealed a cross-sectional shape which did not evolve substantially over time.

The mean water stage \bar{h}_i is calculated as $\bar{h}_i = \bar{S}_i / \bar{w}$. Alternatively, \bar{h}_i can also be calculated as the mean of the water stage of two stations; both approaches lead to similar hydraulic diameters.

Finally, the friction factor f_D is calculated from Eq. (1) with \bar{S}_i and $\bar{D}_{H,i}$ between P5 and P3. Note that if we would consider the channel cross-section to be a semi-circle, we would write $D_H = 2\sqrt{S_i/\pi}$, and f_D would be on average 11% smaller. As an alternative to the Darcy-Weisbach friction factor, the Manning roughness law can be preferred to characterize the flow resistance (Clarke, 2003). The Manning roughness coefficient n' ($\text{m}^{-1/3} \text{s}$) can be calculated from f_D by $f_D = 8gn'^2/R_H^{1/3}$, where the hydraulic radius R_H is equal to $D_H/4$.

~~To quantify the turbulent flow, the~~ The Reynolds number Re (dimensionless) is **the ratio of inertial forces to viscous forces within a fluid, and quantifies the turbulent flow. It is** calculated at the single cross-section P3 using \bar{w} , and both continuous discharge Q and water stage h :

$$Re = \frac{vD_H}{\nu}. \quad (7)$$

Here, $v = Q/S$, with $S = h\bar{w}$, whilst D_H is calculated at P3 using Eq. (6) and ν is the kinematic viscosity ($\text{m}^2 \text{s}^{-1}$).

4.2.3 Thermodynamics

The Nusselt number Nu , i.e. the unknown parameter in Eq. (2), is defined as the ratio between convective and conductive heat transfer across the water-ice interface:

$$Nu = \frac{h_t \lambda}{k_w}, \quad (8)$$

where λ (m) is the length scale over which the convective heat transfer occurs, h_t is the convective heat transfer coefficient ($\text{W m}^{-2} \text{ }^\circ\text{C}^{-1}$), and k_w is the thermal conductivity of water ($\text{W m}^{-1} \text{ }^\circ\text{C}^{-1}$). For λ we use the typical hydraulic diameter of the channel D_H , which is often used in glaciology (Clarke, 2003; Sommers and Rajaram, 2020) and other fields (Incropera et al., 2007; Shah and London, 1978). Note that this choice of λ is different to P_w , which was used by Walder and Costa (1996) when simulating ice-dam breaches.

Since the hydraulic diameter strongly depends on the channel width in the case of a broad channel, it is relatively poorly constrained in our study. We therefore define λ as the typical, and constant, hydraulic diameter which we calculate using Eq. (6). With \bar{h} the typical water stage observed in the channel ($\bar{h} = 0.5 \pm 0.1$ m) we obtain $P_w = 3 \pm 0.54$ m and $\bar{D}_H = 1.30 \pm 0.22$ m. For comparison, $\bar{D}_{H,i}$ calculated above ranges between 1.0 m to 1.6 m, with a mean value of 1.26 m. We then use $\lambda = \bar{D}_H$ to obtain Nu in Eq. (8).

In glaciological applications and elsewhere, Nu is usually calculated using an empirical relation, often the Dittus-Boelter equation (e.g. Clarke, 2003; Spring and Hutter, 1981; Nye, 1976), or the Gnielinski correlation (e.g. Ancey et al., 2019). These two equations parameterise Nu using the Reynolds (Re) and Prandtl (Pr) numbers, where the latter is the ratio of the dynamic viscosity to the thermal diffusivity of water ($Pr = 13.5$ at 0°C , Clarke (2003)). The Dittus-Boelter equation reads

$$Nu = A Pr^\alpha Re^\beta, \quad (9)$$

where A , α and β are empirical coefficients given in the literature (Incropera et al., 2007). The Gnielinski correlation additionally uses f_D and reads

$$Nu = \frac{\frac{f_D}{8} (Re - 1000) Pr}{1 + 12.7 \left(\frac{f_D}{8}\right)^{\frac{1}{2}} (Pr^{\frac{2}{3}} - 1)}. \quad (10)$$

~~The available measurements allow us to calculate~~ In addition to these two empirical relations, we present below two alternative methods to calculate Nu using two different methods (see below), and thus we can directly from our measurements (i.e. without using a parametrisation). We can thus compare our findings to the above empirical equations. The first method, termed the *melt-rate method*, considers the melt rate and water temperature at one location as a function of time. Nu is then directly derived from Eq. (2) with the vertical melt rate m given by repeated channel floor elevation measurements and with the water temperature given by the continuous monitoring. The water temperature measurements are averaged over the time span between two channel elevation measurements, therefore, Nu obtained by using the melt-rate method is time-averaged as well.

The second method, termed the *spatial-cooling rate method*, considers the water temperature at an instance in time and its decrease as a function of distance along the channel. The water temperature $T_w(x)$ decreases following an exponential law (e.g. Isenko et al., 2005), which can be derived from energy conservation (see Appendix ??A) and can be written as

$$T_w(x) = T_0 e^{-\frac{x}{x_0}}, \quad (11)$$

where x is the distance (m) from the origin (in our case P5, the uppermost monitoring station), T_0 is the temperature at this location ($^\circ\text{C}$), and x_0 is the e-folding length (m). Physically, x_0 is the distance over which the temperature decreases by a factor e and can be expressed in terms of Nu , Q , and the wetted perimeter \bar{P}_w as

$$x_0 = \frac{Q c_w \rho_w \lambda}{Nu k_w \bar{P}_w}, \quad (12)$$

where c_w is the specific heat capacity of water ($\text{J }^\circ\text{C}^{-1} \text{kg}^{-1}$). We obtain x_0 from a least-square fit of Eq. (11) to the hourly-averaged temperature at stations P5, P3, P2 and P1 and, thus, Nu can be calculated.

Table 1. Physical constants used in this work. If not specified, constant refers to the property of water at at 0°C.

Physical constants	Var.	Value	Units
Density of ice	ρ_i	900	kg m^{-3}
Latent heat of fusion	L_f	333×10^3	J kg^{-1}
Density	ρ_w	1000	kg m^{-3}
Specific heat capacity	C_w	4.18×10^3	$\text{J }^\circ\text{C}^{-1} \text{kg}^{-1}$
Thermal conductivity	k_w	0.57	$\text{W m}^{-1} \text{ }^\circ\text{C}^{-1}$
Kinematic viscosity	ν	1.8×10^{-6}	$\text{m}^2 \text{ s}^{-1}$
Prandtl number	Pr	13.5	-

4.2.4 Uncertainty propagation

In this study, uncertainties of field measurements come from the sensors' sensitivity and limitations of the measurement procedures. Both uncertainties are quantified and propagated through the equations by using a Monte-Carlo approach (Carlson, 315 2020). Since this allows us to propagate errors faithfully also through non-linear functions, results are systematically presented with their standard deviation.

Table 2. Table of variable names. *salt dil.* stands for "salt dilution experiment technique", and *a.s.l* stands for "above sea level". Individual quantities might either be available for a point in time (*PT*; the index *i* means that the measurement is instantaneous) or as a time series (*TS*), or might be constant through time (*CT*). A bar over the corresponding symbol indicates that the quantity is averaged over a given channel segment, i.e. between two stations.

Direct field Measurements	Notation			Unit
	PT	CT	TS	
<i>of channel:</i>				
Water stage	h_i		h	m
Channel floor elevation	z_i			m (a.s.l)
Hydraulic head	p_i			m
Hydraulic slope	θ_i			-
Width	w_i			m
Discharge (salt dil.)	Q_i			$\text{m}^3 \text{s}^{-1}$
Stream velocity (salt dil.)	\bar{v}_i			m s^{-1}
Wetted cross-section (salt dil.)	\bar{S}_i			m^2
Water temperature			T_w	$^{\circ}\text{C}$
<i>of lake:</i>				
Lake level			z_{lake}	m
Derived & other variables				
<i>of channel:</i>				
Melt rate	m			m s^{-1}
Discharge			Q	$\text{m}^3 \text{s}^{-1}$
Stream velocity			v	m s^{-1}
Wetted cross-section			S	m^2
Wetted perimeter	$P_{w,i}$		P_w	m
Hydraulic diameter	$D_{H,i}$		D_H	m
Reynolds number			Re	-
Darcy Weisbach friction factor	f_D			-
Manning roughness	n'			$\text{m}^{-1/3} \text{s}$
Convective heat transfer	h_t			$\text{W m}^{-2} \text{ } ^{\circ}\text{C}^{-1}$
Heat flux			q	W m^{-2}
Energy content of water			E	J m^{-1}
Energy source term			M	W m^{-1}
e-folding length of water temperature decrease			x_0	m
Nusselt number			Nu	-
<i>of lake:</i>				
Lake surface area			A_{lake}	m^2
Lake inflow			Q_{in}	$\text{m}^3 \text{s}^{-1}$
Lake outflow			Q_{out}	$\text{m}^3 \text{s}^{-1}$
Time independent variable				
Length between two stations		l		m
Distance in channel from P5		x		m
Time and space independent parameter				
<i>of channel:</i>				
Mean width		\bar{w}		m
Mean water stage		\bar{h}		m
Mean water perimeter		\bar{P}_w		m
Mean hydraulic diameter		\bar{D}_H		m
Nusselt length scale		$\lambda = D_H$		m

5 Results

5.1 Lake drainage hydrographs 2012-2019

Figure 2 shows the temporal evolution of lake-water volumes between 2012 and 2019, and hourly-averaged discharge. The lake water input Q_{in} was only accounted for the year 2019, since it becomes relevant to take it into account in the calculation of Q_{out} , due to much smaller value of the latter ~~than previous year~~ compared to previous years. The increasing trend of both maximum volume and peak discharge from 2012 to 2018 ~~is~~ are clearly visible. The drainage onset time depends, amongst others, on the meteorological conditions during the lake filling phase. ~~With high air temperatures~~ In warmer years, the date of complete filling of the lake basin occurs earlier. Also, an early depletion of the winter snow ~~coverage~~ cover is likely to be linked with an early development of the subglacial drainage system, which in turn favours subglacial lake drainage (GLAMOS, 2018). Since 2014, the lake volume has systematically reached more than $2 \times 10^6 \text{ m}^3$, and the subglacial release of the total lake water occurred within a few days, except for 2015 when the water drained through a supraglacial channel into a nearby moulin for about two weeks.

The 2019 lake drainage pattern is drastically different from previous years due to the artificial intervention. ~~It can be characterized by four distinct~~ We distinguish four different phases. The first phase (Phase I) is from 10 July to 1 August 2019, when approximately half of the lake emptied through the supraglacial channel. Phase II is from 2 to 15 August 2019, when the lake level remains roughly constant but lake water was still running in the channel. Phase III is from 15 to 21 August 2019, when lake water stopped running in the channel and the lake level remained constant or slightly increased. Phase IV is from 22 to 27 August 2019, when the second half of the lake volume emptied subglacially, similar to the natural drainage mechanism of previous years. Note that the discharge peak of $3.5 \text{ m}^3 \text{ s}^{-1}$ was much lower compared to other years, e.g. over 20 times lower than in 2018 (Fig. 2). In this regard, the technical intervention was very successful.

5.2 Channel geometry

The ~~vertical channel incision~~ channel bottom elevation and its evolution with time at five locations along the channel is presented in Fig. 3. ~~This~~ The incision shows a uniform spatial pattern, and is about 8 m during the supraglacial drainage (phase I and II: 10 July - 15 August 2019). Note that the channel slope was not uniform prior to the drainage onset (Fig. 1d), and that it remained relatively constant after natural adjustments during the first days of drainage. The low slope at the channel segment P5–P3 leads to uniform stream flow, that allowed the formation of clear daily water level cuts (Fig. 4). In contrast, the ~~more turbulent water flow~~ higher slope between P2 and P1 (~~higher slope~~ led to the led to more turbulent water flow and subsequent formation of step-pools (e.g. Vatne and Irvine-Fynn, 2016). Note that ~~no~~ meandering (Karlstrom et al., 2013) ~~occurred~~ did not occur and, thus, the channel length stayed constant.

Widening is substantial only at P5 where channel width increased from 1 m on 10 July to $3 \pm 0.1 \text{ m}$ on 8 August 2019. Further downstream, e.g. at P4, the widening is minor (Fig. 4). Overall, the channel geometry was mainly driven by vertical incision rather than lateral melting.




Figure 2. Lake volume (a) and lake discharge (b) during summer from 2012 to 2019. The year 2019 is represented by a black and thicker line. Discharge is shown as hourly averages for 2012 to 2018, and daily averages for 2019. Note that the 2018 discharge peak ($78 \text{ m}^3 \text{ s}^{-1}$) is beyond the plotted range.




Figure 3. Channel bottom elevation at P5, P4, P3, P2 and P1 during the lake drainage (locations are presented in Fig. 1). The color-coded crosses indicate lake level at the corresponding time. Note that the actual lake was located further east than P5. Distance between stations are taken along the channel flow path.



Figure 4. Photo from within the supraglacial channel from P4 towards P3. The dashed line represents the highest water stage in the channel (10 July 2019) prior to the supraglacial lake drainage start and prior to the onset of channel-bottom incision. Daily water level cuts are clearly visible on both sides. The picture was taken on 30 July 2019.

5.3 Channel hydraulics

350 Water stage (Fig. 5) and the hydraulic **gradient-slope** determine the water discharge. Water stage measurements were challenging during the first days of the supra-glacial drainage (i.e. 10 July 2019, beginning of Phase I) since the excavator used to deepen the channel spillway left irregular traces on the channel bottom. Nevertheless, probe measurements (at P5, P4, P3, P2 and P1) together with water pressure sensors (at P5, P3, P2 and P1 only) reveal that water stage on 10 July 2019 was around 1 m at P5, 0.4 m at P4 (which was close to the spillway location), and 0.3-0.5 m for the others stations. Water stage stabilized at 0.6 m
 355 after a few days of drainage (Phase I) at P5, and at around 0.4-0.5 m at the others stations. Daily fluctuation were typically of 0.1 m due to the daily melting cycle influencing the lake input. At P1, measurements were soon no longer feasible because of the formation of step pools. Water stage slowly decreased to a value of 0.1-0.2 m uniformly over the channel during Phase III and Phase IV, when lake water no longer drained through the channel.




Figure 5. Hourly time series of water stage at P5 (dashed black line) and P3 (blue line) from continuous pressure measurements. Direct observations (and associated standard errors) from field visits are marked by black diamonds and blue dots, respectively. Part of the discrepancies between direct field observations and continuous water stage from pressure sensors can be explained by the probing not always being made at the exact location of the sensors.

Figure 6 presents time series of water temperature, channel discharge and channel-bottom elevation at station P3, along with the lake level. Data gaps in discharge and temperature time series are due to disruptions of logging. The daily mean discharge time series between 13 and 24 July 2019 has been calculated using lake level change and modelled lake inflow (see Section 4.4.2.2). The peak in channel discharge was reached on 14 July 2019 (Phase I), with a daily average of $1.7 \text{ m}^3 \text{ s}^{-1}$. The good agreement between the different direct discharge measurements (\hat{Q}_i) and the continuous discharge at P3 indicate that the stage/discharge relationship is valid over the entire drainage duration. The decoupling between Q at P3 and Q_{out} during Phase III and IV (Fig. 6b) is because the lake did no longer drain through the channel at that stage. The temperature and discharge signal of the lake water is clearly visible in the channel until 14 August 2019. This is in contrast with the temperature signal from the glacier's daily melt pattern from 23 August to 4 September 2019 (water temperature close to 0°C at night), when the lake was no longer draining through the channel (beginning of Phase III).

The stable mode of drainage during Phase I is corroborated by the observation that the distance between daily water level cuts in the channel (indicative for channel floor erosion, cf. Sec. 4.1.3) corresponds to the rate at which the lake level lowers (Fig. 6). At P5, this distance varies between 30 cm and 60 cm per day during the second half of July 2019, and drops on average to 12 cm per day for the first half of August 2019.

The stream flow in the channel is highly turbulent during supraglacial drainage. The Reynolds number fluctuates with discharge, and is between 2.5×10^5 and 1.5×10^6 (Phase I and II). Note that the transition between laminar flow in the lake and turbulent flow somewhere at the channel entrance is further upstream than P5 (the location is not known exactly).

The Darcy-Weisbach friction factor was calculated for the channel segment between P5 and P3, where accurate calculation of \bar{D}_H and thus \bar{P}_w , was possible. The time series of the inferred friction factor is presented in Table 3.




Figure 6. (a) Lake level elevation (continuous curve), channel bottom elevation (blue dots) and water level cut elevations (black dots) at P5. (b) Hourly channel discharge at P3 (Q), direct discharge measurement by salt dilution averaged over all stations (\bar{Q}_i), and lake discharge from elevation change (Q_{out}). (c) Water temperature at P3. The four distinct lake drainage phases are delimited by the dashed line and explained in the main text (Sec. 5.1). Standard uncertainties for hourly discharge and temperature are shown with light bands.

5.4 Thermodynamics

Water temperature, measured continuously at P5, P3, P2, and P1, shows an exponential decrease along the channel (Fig. 7), and exhibits daily fluctuations (Fig. 6, e.g. $\pm 0.1^\circ\text{C}$ during Phase I). The relation given in Eq. (11) is fitted to these temperature observations. Note that the pattern is similar whenever lake water was flowing through the channel.

Table 3. Darcy-Weisbach friction factor f_D and Manning roughness n' with associated standard deviation in the channel segment between stations P5 and P3. All measurements were performed during Phase I of the drainage when salt dilution experiments were conducted (see Fig. 6).

Date and time (2019)	f_D (-)	n' ($\text{m}^{-1/3} \text{s}$)
11 July, 09:27	0.41 ± 0.12	0.055 ± 0.009
11 July, 12:51	0.34 ± 0.10	0.051 ± 0.008
16 July, 14:12	0.17 ± 0.02	0.038 ± 0.003
25 July, 08:44	0.17 ± 0.02	0.040 ± 0.003
30 July, 14:47	0.48 ± 0.07	0.068 ± 0.005
30 July, 18:34	0.19 ± 0.03	0.042 ± 0.003
31 July, 09:39	0.35 ± 0.06	0.056 ± 0.005
Mean	0.30 ± 0.12	0.050 ± 0.011




Figure 7. Temperature decrease along the channel-flow path at three different times. Dots are observations, lines correspond to the fitted exponential law according to Eq. (11).

Figure 8 presents time series of the Nusselt number Nu calculated from our measurements according to the melt-rate method (Eq. (2)), the spatial-cooling rate method (Eq. (12)), as well as from the empirical Dittus-Boelter equation (Eq. (9)) and the Gnielinski correlation (Eq. (10)). For the Dittus-Boelter equation we use coefficients A , α and β from previous studies (Table 4); for the Gnielinski correlation, we use the mean friction factor $f_D = 0.3$ (Table 3). The heat transfer is dominated by convection, with typical Nu values in the order of 10^4 . The results from the melt-rate and spatial-cooling rate methods are in good agreement, except for the period 11-16 July 2019 (beginning of Phase I). For this period, the higher Nu values obtained

by the melt rate method compared to the spatial-cooling rate method could be explained by the very high melt rate at P3 (see Fig 3).

390 Our values for Nu are significantly higher than the ones derived from the Dittus-Boelter equation using standard coefficients (e.g. Clarke, 2003). We note, however, that the coefficients used by Lunardini et al. (1986) and Vincent et al. (2010) result in Nu -values that lie at the lower and upper edge, respectively, of the uncertainty range of our Nu -values. Conversely, the Gnielinski correlation produces values of Nu that are significantly higher than our results, as well as the ones obtained by the alternative methods.

Table 4. Dimensionless coefficients of the Dittus-Boelter equation (Eq. (9)) from various studies, including this one (see Section 4.2.3).

Study	A	α	β
Standard (e.g. Clarke, 2003)	0.023	2/5	0.8
Lunardini et al. (1986)	0.0078	1/3	0.927
Vincent et al. (2010b)	0.332	1/3	0.74
This study	1.78	1/3	0.58




Figure 8. Nusselt number Nu at P3 computed using two different approaches and several empirical relations. *MR method* refers to melt-rate method (Eq. (2)) and *SCR method* refers to spatial-cooling rate method (Eq. (12)). The Dittus Boelter equation and the Gnielinski correlation are presented in Eq. (9) and Eq. (10), respectively. For the sake of readability, the standard deviation (band around the mean values) is only displayed for the values derived from our measurements. The vertical dashed line separates Phase I and II of the lake drainage.

395 The Nusselt number Nu is dependent on the Reynolds number Re via turbulent mixing. Figure 9a shows the relation between Nu and Re as determined by our field measurements, along with the previously used parameterisations for Nu . ~~Of note is~~ **It is noteworthy** that our results show a less pronounced dependence of Nu on Re than other assessments. Indeed, fitting the Dittus-Boelter equation (coefficients A and β , Eq. (9)) to our data yields an exponent of $\beta = 0.58$, which is low compared to exponents between 0.75 and 0.93 found by Clarke (2003), Lunardini et al. (1986) and Vincent et al. (2010b) (Table 4).




Figure 9. Nusselt number (a) and friction factor (b) against Reynolds number (Eq. (7)). Note that all quantities are dimensionless. The Nusselt number from our observations is calculated using the *melt-rate method* at P3 (Eq. (2)) and the *spatial-cooling rate method* (Eq. (12)). The band shows the mean relative error of 9%. The Nusselt number is also calculated from the Dittus-Boelter equation Eq. (9) using coefficients (named "D-B coef." in the legend) from other studies (see Table 4) and the Gnielinski correlation (Eq. (10)).

400 6 Discussion

We ~~provided~~ **collected** an extensive data set of a supraglacial lake drainage through a channel, and characterise its hydraulics and thermodynamics. We derive key parameters, namely the factors of hydraulic friction and heat transfer. In the following, we discuss the implications of our findings to future studies and for hazard mitigation measures.

6.1 Reconstruction of the lake drainage during Phase I–IV

405 The four phases of the lake drainage are interpreted as follows: Phase I is characterized by stable supraglacial lake drainage, i.e. the lake draw-down is controlled by the rate of vertical channel incision. There is a significant difference between the computed lake outflow Q_{out} and the channel discharge Q at P3 during the sub-period 26 July to 30 July 2019 (Fig.6b) coinciding with strong rain that ended a heat wave which started on 20 July 2019.

During Phase II, the lake level remained constant (Fig.6a), but the lake water was still running in the channel as evidenced
410 by the relatively warm water (Fig.6c). This is indicative for the outflow of the lake-channel system behaving like a non-erosive spillway: the channel only received the water from snow and ice melt, which spilled above a constant elevation. The exact location of the spillway is unknown: it could either be located in the englacial siphon between the main lake and the canyon, or in the ice cave (Fig. 1) although visual inspection gave no evidence for the latter. Phase III is characterized by the stop of the supraglacial drainage around 15 August 2019. It is likely that lake surface became too small, such that the lake draw-down
415 became higher than the channel incision. This is especially likely if the channel was disconnected from the main lake by the spillway between the canyon and the main lake, or in the case of subglacial leaks. Although no sensors were installed in the channel from 19 to 23 August 2019, the channel incision between 14 to 23 August 2019 was negligible (Fig. 3). This indicates that the peak in Q_{out} on 19 August 2019 was due to subglacial rather than supraglacial drainage.

During Phase IV, the lake emptied subglacially, with no influence from the supraglacial channel. The triggering mechanism
420 is presumably similar to previous years. Lindner et al. (2020) showed, for example, that the drainage in 2016 was initiated by hydrofracturing.

6.2 Hydraulics

We calculated the hydraulic friction factor f_D of the channel at several instances during Phase I (Table 3), when the necessary salt-dilution measurements are available. Values for f_D range from 0.17 to 0.48, corresponding to a Manning roughness n'
425 of 0.038 to 0.068 $\text{m}^{-1/3}$ s. These values are similar to the ones of Mernild et al. (2006), who inferred n' between 0.036 and 0.058 $\text{m}^{-1/3}$ s in supraglacial streams on the Greenland Ice Sheet. Similar observations of Gleason et al. (2016) revealed strong variability of n' in time and space, ranging from 0.009 to 0.154 $\text{m}^{-1/3}$ s with a mean value of 0.035 ± 0.027 $\text{m}^{-1/3}$ s, similar to ours. The lower end of their range corresponds to a smooth channel, whereas the upper end cannot be explained by ice-channel roughness alone and is ~~indicative for, e.g., suspended~~ **an indication for** slush-ice being present in the channel, **but also for the**
430 **influence of form friction (as opposed to skin friction) in a complex three dimensional channel geometry.**

Why the friction factors vary so much is unclear from our observations. For instance, there is no correlation with the Reynolds number (Fig. 9b). Previous studies already highlighted the need to better quantify hydraulics of englacial channels (e.g. Clarke, 2003; Gleason et al., 2016), and the need for additional in situ observations to better constrain the parameters that control discharge (e.g. Kingslake et al., 2015; Smith et al., 2015). Our work provides a range of accurate, field-based friction factors
435 for a supraglacial stream at different times during a lake drainage, and shows its variability. However, the large range of friction factor values reported here and in other studies suggests that using a constant value in modelling studies could be inappropriate.

Instead, we suggest that modelling studies should treat f_D as a stochastic variable (e.g. Brinkerhoff et al., 2021; Irrazaval et al., 2021), i.e. that they should use a range of values as opposed to a single one.

6.3 Thermodynamics

440 In general, the supraglacial drainage of an ice-dammed lake progresses via the incision of the channel by melt. The incision rate determines whether the lake drains gradually, i.e. with an approximately constant discharge over time, or unstably, i.e. with a progressively increasing discharge (Raymond and Nolan, 2000).

To characterise channel incision, the heat transfer between the advected lake water and the ice channel walls needs to be quantified. This heat transfer is captured by the Nusselt number Nu , which was derived from measurements in this study. Our
445 results (Fig. 8 and 9) are in-between the predictions of the Dittus-Boelter equation (Eq. (9)) using the parameters from Vincent et al. (2010), which are higher than our values ~~and, and those of Lunardini et al. (1986) with lower values than our results, which are lower than our values.~~ This suggests that using the parameterisations of ~~those~~ ~~these~~ two studies, that have a cryospheric context as well, gives an interval of Nusselt numbers to consider. Again, as for the hydraulic friction factor, the large range of plausible Nusselt numbers means that it should be a stochastic parameter in modelling studies.

450 The cause of the discrepancy between the exponent of Reynolds number in the Dittus-Boelter equation determined in our study ($\beta = 0.58$) and others (β between 0.75 and 0.93, Table 4, Fig. 9a) is not clear. Our water temperature measurements were conducted using CTD sensors which sunk to the channel bottom. Their close proximity to the ice means that they might have measured a temperature below the bulk water temperature, which would lead to an overestimation of Nu using the melt-rate method. Conversely, the results of the spatial-cooling rate method would likely be less impacted as the temperature e-folding
455 length should not depend on the location of the sensors. Future studies should put an emphasis on accurate water temperature measurements, for instance by using fiber optics methods as in Karlstrom et al. (2014), paying attention to accurately estimate the bulk water temperature.

Longitudinal temperature profiles of supraglacial channels have been studied in both the field and in the laboratory, but only by one study so far (Isenko et al., 2005). Water temperature decreases exponentially with distance, which is the basis
460 of estimating Nu ~~though in~~ our spatial-cooling rate method (Eq. (12)). This method is useful because it is easier to implement and allows a higher sampling rate than the melt-rate method (Eq. (2)) because it only requires temperature measurements and not the more challenging channel-incision rate measurements, as were used in other studies (e.g. Vincent et al., 2010). If the melt-rate method is chosen, direct measurements of channel incision are needed and we support the idea of Raymond and Nolan (2000) that daily water level cuts can be used to conduct those measurements a posteriori (Fig. 4).

465 Besides the incision rate, the channel aspect-ratio plays a major role in the drainage stability of a supraglacial lake: for a given stage, a wider channel has a bigger discharge capacity than a narrower channel, and will consequently contribute to stabilize the drainage by accelerating the lake-level draw-down (Raymond and Nolan (2000), their Eq. (8)). Channel width was considered constant in the present field study and was used to calculate the hydraulic diameter and consequently all parameters which are derived from it. The large uncertainties we put on the width take into account a potential change in width, and the

470 estimated parameters take this fully into account. Moreover, our stage/discharge relation at P3 seems to work well despite of a slight widening at that location.

The channel aspect-ratio was considered ~~in the model of~~ by Jarosch and Gudmundsson (2012) ~~which suggests~~ who suggest that this ratio is determined by melt rate dependence on water depth: if the melt rate is independent of water depth, a very broad channel forms, whereas if it scales linearly, a nearly semi-circular channel forms. To our knowledge, there is no theoretical
475 work available for how melt rates distribute over the channel perimeter, but ~~an extension~~ extending the study of Sommers and Rajaram (2020) could ~~potentially be applied to~~ shed light on this issue. Future field-based studies could try to quantify the channel aspect-ratio, as it would give indications on both lake drainage stability as well as melt-rate distribution along the channel perimeter.

6.4 Hazard mitigation

480 The maximum lake volume of $1.49 \times 10^6 \text{ m}^3 \pm 0.11 \times 10^6 \text{ m}^3$ reached in 2019 was limited by the constructed supraglacial channel to about two thirds of its potential volume, and half of the lake water ($\sim 0.7 \times 10^6 \text{ m}^3$) drained, stably, through the channel once the lake overspilled into it. In this sense, the hazard mitigation of Lac des Faverges was very successful; however construction costs were considerable at 1.7 million CHF. ~~Furthermore~~ Still, construction costs ~~are relatively low compared to~~ were lower
485 than the damage costs of 2.5 million CHF only in 2018. The relatively small volume of remaining water later then drained subglacially during an outburst event (Fig. 2). The peak discharge was only $\sim 3.5 \text{ m}^3 \text{ s}^{-1}$, and thus far lower than the $\sim 80 \text{ m}^3 \text{ s}^{-1}$ recorded in 2018.

The intervention at Lac des Faverges thus indicates that a channel dug at the glacier surface prior to the lake filling can successfully limit the maximum lake volume and thus the hazard potential. Indeed, partially or fully-filled lakes have been successfully drained in the past via such channels (e.g. Vincent et al., 2010), however not at the scale of the present artificial
490 intervention. Nonetheless, surface lake drainages also have considerable hazard potential (e.g. Ancey et al., 2019; Walder and Costa, 1996) and therefore the prediction of whether a surface drainage proceeds stably or unstably is critical for hazard assessments. Raymond and Nolan (2000) proposed a criterion based on lake area and temperature (their Eq. (8)). The area and temperature of Lac des Faverges respected this stability criterion when the drainage initiated in 2019, but only barely. However,
495 the past surface drainage of 2015 (Fig. 2), which drained stably through a shorter channel (about 400 m), suggests that the 2019 drainage was well in the stable regime; refining this criterion would help improve future hazard assessments.

The artificial channel remained active throughout the summer of 2020 and it was effective in limiting the lake volume and thus the hazard emerging from it. In terms of operations, the substantial amounts of winter snow blown into the channel proved to be challenging, as they formed an intermediate blockage. In early August 2020, the winter-snow was partially removed by an excavator, and the remaining snow blockage was eroded in a slush-flow like event, after which the lake
500 drained partially through the supraglacial channel (i.e. corresponding to Phase I in Figure 6), and partially subglacially (i.e. corresponding to Phase IV in Figure 6). Since the slush-flow like event was relatively difficult to control, additional artificial measures were taken for 2021. These aimed at activating the channel's water flow underneath the extensive snow cover that rebuilds during winter. However, in 2021 the lake drained subglacially when only half full and before lake

water could flow through the channel; the lake outlet was situated in the “canyon” region (Fig. 1b). The drainage occurred
505 in late July 2021 which was early relative to the still extensive snow cover and to the low filling level.

7 Conclusions

In 2019, the ice-dammed Lac des Faverges, located on Glacier de la Plaine Morte in the Swiss Alps, partially drained through
an artificial supraglacial channel, constructed in order to mitigate the hazard posed by this lake. This unique setting was used
to acquire a comprehensive dataset describing the evolution of the lake level, channel discharge, channel incision, and channel-
510 water temperature during drainage. It is probably one of the most comprehensive such datasets currently available.

The field measurements were used to characterize the hydraulics and thermodynamics of the supraglacial channel, quantify-
ing, among other parameters, the friction factor and the Nusselt number. The observed Darcy-Weisbach friction factors range
between 0.17 and 0.48, with a mean value of 0.30 which is close to what other studies found and to what modelling studies
used so far. However, the large spread ~~is indicative for the importance of~~ found in our study suggests considering the friction factor
515 as a stochastic variable, instead of as a constant.

The heat transfer between water and channel wall, responsible for channel incision and quantified by the Nusselt number,
was determined using two distinct methods: the *melt rate method* and the *spatial cooling-rate method*. The results of the two
methods agree, but as for the hydraulic friction factor, a large spread is found, indicating that the Nusselt number should also be
treated as a stochastic variable in modelling studies. The Nusselt numbers derived from the often-used empirical Dittus-Boelter
520 equation are significantly different to ours. More precisely, the dependence of the Nusselt number on the Reynolds number is
less pronounced than previously reported (e.g. Clarke, 2003; Lunardini et al., 1986; Vincent et al., 2010) or in the commonly
used empirical Gnielinski correlation. We identify the heat-transfer rate as one of the key processes to be investigated by future
studies, since it defines the supraglacial channel incision rate and thus the discharge and lake drainage stability. For this to be
successful, an increase in the representativeness and accuracy of water temperature measurements would be needed.

525 The modelling of supraglacial lake drainages will likely remain afflicted ~~by~~ with large uncertainties. In line with previous
work, our study shows that some key hydraulic and thermodynamic parameters are only weakly constrained. This translates
into large model uncertainties which, in turn means that model-based hazard assessments will ~~need to continue allowing for large~~
~~margins of errors~~ have to allow for large uncertainties.

Appendix A: Calculation of Nu as a function of the e-folding length x_0

530 We derive the spatial temperature profile along the channel (Eq. (11) and Eq. (12)) using the energy conservation equation

$$\frac{\partial E}{\partial t} + \frac{\partial vE}{\partial x} = M, \quad (\text{A1})$$

where ~~$E = \rho_w c_w T_w A$~~ $E = \rho_w c_w T_w S$ is the energy density of the water per unit channel length (J m^{-1}), x the distance (m) along
channel-flow path, v the stream flow velocity (m s^{-1}), and M is a source term (W m^{-1}). The source is expressed in terms of q ,

the heat flux (Wm^{-2}) from the water into the ice

$$535 \quad M = qP_w. \quad (\text{A2})$$

We thus assume that the only relevant heat source ~~stems from~~ is negative and stems from the consumption of energy related to ice melt at the channel wall and that both heat exchange at the ice-air interface and heat production due to potential energy dissipation can be neglected. This ~~is justified as the those two heat sources can be justified, as these two sources are~~ on the order of 100 Wm^{-1} , which is two orders of magnitude smaller than M . We write q as

$$540 \quad q = h_t \Delta T, \quad (\text{A3})$$

where h_t is the convective heat transfer coefficient (the conductive heat transfer can be neglected) and ΔT is the temperature difference between water and ice. Note that since the ice temperature is 0°C , $\Delta T = T_w$. Assuming a steady state, i.e. $\frac{\partial E}{\partial t} = 0$, using Eq. (A3), and expressing E in terms of T_w , the Eq. (A1) becomes

$$Q c_w \rho_w \frac{\partial T_w}{\partial x} = h_t T_w P_w, \quad (\text{A4})$$

545 which uses the ~~approximation~~ $\frac{\partial Q}{\partial x} \approx 0$ ~~assumption~~ $\frac{\partial Q}{\partial x} = 0$. This equation can be integrated to give

$$T_w = T_0 e^{-\frac{x}{x_0}}, \quad (\text{A5})$$

with

$$x_0 = c_w \rho_w \frac{Q}{h_t P_w} = \frac{c_w \rho_w \lambda}{k_w} \frac{Q}{Nu P_w}, \quad (\text{A6})$$

where the second equality follows from Eq. (8).

550 **Appendix B:** Salt dilution experiments in the supraglacial channel

Table B1 presents the salt dilution experiments conducted to determine the discharge Q_i at station P3, and the velocity \bar{v}_i and the wetted cross section \bar{S}_i averaged between stations P5 and P3. These quantities are in turn used to characterise the hydraulics (calculation of Reynolds number Re and the Darcy Weisbach friction factor f_D) and the thermodynamics (calculation of the Nusselt number Nu) of the supraglacial channel. Other salt dilution experiments conducted at stations
555 P2 and P1 were used to validate the rating curve (Eq. (4)) and are presented in Code and data availability Section.

Table B1. Table of salt dilution experiments conducted to determine Q_i at station P3, and to obtain \bar{v}_i and \bar{S}_i averaged between stations P5 and P3. Salt dilution experiments at P3 were used for the rating curve (Equation (4)) when water stage h_i was available at the same moment and at the same location. The accuracy for Q_i and \bar{S}_i is typically 4%. The accuracy for h_i is 0.005 m.

Salt injection	Date	Time	Q_i ($\text{m}^3 \text{s}^{-1}$)	\bar{v}_i (m s^{-1})	\bar{S}_i (m^2)	h_i (m)	Used for rating curve
1	2019-07-08	13:16	0.016	-	-	-	no
2	2019-07-08	14:45	0.017	-	-	-	no
3	2019-07-09	10:50	0.016	0.073	0.219	0.126	yes
4	2019-07-10	10:01	0.021	0.098	0.214	0.192	yes
5	2019-07-10	14:44	0.115	0.288	0.399	0.165	yes
6	2019-07-10	15:13	0.116	0.202	0.574	0.174	yes
7	2019-07-11	09:11	0.206	0.387	0.532	0.239	yes
8	2019-07-11	12:27	0.252	0.585	0.431	0.300	yes
9	2019-07-11	12:42	0.262	0.437	0.600	-	no
10	2019-07-15	16:26	1.020	1.103	0.925	-	no
11	2019-07-16	14:07	0.811	1.057	0.767	0.350	yes
12	2019-07-24	16:57	1.300	0.890	1.461	0.552	yes
13	2019-07-25	08:41	1.140	1.015	1.123	0.478	yes
14	2019-07-30	14:40	0.923	0.583	1.583	0.446	yes
15	2019-07-30	18:29	0.942	0.832	1.132	0.441	yes
16	2019-07-31	09:32	0.619	0.564	1.098	0.382	yes

Code and data availability. The raw data, the code to process the raw data, and the results are available at <https://www.research-collection.ethz.ch/> with the DOI: 10.3929/ethz-b-000504956. (**This DOI-link will only be available once the data/code is finalised, which will happen if the manuscript is accepted. Until then it can be found at <https://people.ee.ethz.ch/~werderm/pm-data/>. TODO: remove in production.**)

560 *Author contributions.* CO conducted the field campaign, did the data analysis, produced the figures, and wrote the paper. MW designed the field campaign, participated in it, developed the general methodological aspect of the study, and co-wrote the paper. MH provided inputs on the Methods, helped with fieldwork, and gave feedback on the paper. IK and DH provided information on the channel construction, measured and provided data, and gave feedback on the paper. DF did the overall supervision, gave feedback on the paper, and acquired funding. We thank two anonymous reviewers for their helpful comments.

565 *Competing interests.* The authors declare that they have no conflict of interest.

Acknowledgements. The field campaign was partly funded by the WSL internal project *Glacier lake outburst floods – a full-scale experiment (GLOFFEE)*. The additional support by La Prairie and the ETH Zurich Foundation are kindly acknowledged. The authors thanks all the helpers who took part in the field campaigns: L. Geibel, E. Hodel, J. Klahold, S. Förster, F. Lindner, A. Sergent, and F. Walter. We appreciated the collaboration with Geotest AG for field logistics.

570 References

- Ancey, C., Bardou, E., Funk, M., Huss, M., Werder, M. A., and Trehwela, T.: Hydraulic Reconstruction of the 1818 Giétro Glacial Lake Outburst Flood, *Water Resources Research*, 55, 8840–8863, <https://doi.org/10.1029/2019WR025274>, 2019.
- Aydin, I., Ger, A. M., and Hincal, O.: Measurement of small discharges in open channels by slit weir, *Journal of Hydraulic Engineering*, 128, 234–237, [https://doi.org/10.1061/\(ASCE\)0733-9429\(2002\)128:2\(234\)](https://doi.org/10.1061/(ASCE)0733-9429(2002)128:2(234)), 2002.
- 575 Aydin, I., Altan-Sakarya, A. B., and Ger, A. M.: Performance of slit weir, *Journal of Hydraulic Engineering*, 132, 987–989, [https://doi.org/10.1061/\(ASCE\)0733-9429\(2006\)132:9\(987\)](https://doi.org/10.1061/(ASCE)0733-9429(2006)132:9(987)), 2006.
- Björnsson, H.: Jökulhlaups in Iceland: prediction, characteristics and simulation, *Annals of Glaciology*, 16, 95–106, <https://doi.org/10.3189/1992AoG16-1-95-106>, 1992.
- Björnsson, H.: Subglacial lakes and jökulhlaups in Iceland, *Global and Planetary Change*, 35, 255–271, [https://doi.org/10.1016/S0921-](https://doi.org/10.1016/S0921-8181(02)00130-3)
580 8181(02)00130-3, 2002.
- Björnsson, H.: Understanding jökulhlaups: from tale to theory, *Journal of Glaciology*, 56, 1002–1010, <https://doi.org/10.3189/002214311796406086>, 2010.
- Brinkerhoff, D., Aschwanden, A., and Fahnestock, M.: Constraining subglacial processes from surface velocity observations using surrogate-based Bayesian inference, *Journal of Glaciology*, pp. 1–19, <https://doi.org/10.1017/jog.2020.112>, 2021.
- 585 Bundesamt für Umwelt: Hydrologisches Jahrbuch der Schweiz 2019, Tech. rep., Bundesamt für Umwelt, Bern, <https://www.bafu.admin.ch/uz-2019-d>, 2020.
- Carlson, F. B.: MonteCarloMeasurements.jl: Nonlinear Propagation of Arbitrary Multivariate Distributions by means of Method Overloading, <https://github.com/bagepinnen/MonteCarloMeasurements.jl>, 2020.
- Clarke, G. K.: Hydraulics of subglacial outburst floods: new insights from the Spring–Hutter formulation, *Journal of Glaciology*, 49, 299–313, <https://doi.org/10.3189/172756503781830728>, 2003.
- 590 Finger, D., Hugentobler, A., Huss, M., Voinesco, A., Wernli, H., Fischer, D., Weber, E., Jeannin, P.-Y., Kauzlaric, M., Wirz, A., et al.: Identification of glacial meltwater runoff in a karstic environment and its implication for present and future water availability, *Hydrology and earth system sciences*, 17, 3261–3277, <https://doi.org/10.5194/hess-17-3261-2013>, 2013.
- Gemeinde Lenk: Informationsveranstaltung Hochwasserschutz Gletschersee und Simme, https://web.archive.org/web/20210517092845/http://www.lenkgemeinde.ch/dl.php/de/5c423874232b9/Informationsanlass_HWS_2019-01-18.pdf, 2019.
- 595 GLAMOS: The Swiss Glaciers 2015/16 and 2016/17, Bauder, A., Huss, M., Linsbauer, A. (eds.), Glaciological Report No. 137/138 of the Cryospheric Commission (EKK) of the Swiss Academy of Sciences (SCNAT) published by VAW / ETH Zürich, Tech. rep., https://doi.org/10.18752/glrep_137-138, 2018.
- GLAMOS: The Swiss Glaciers 2017/18 and 2018/19, Bauder, A., Huss, M., Linsbauer, A. (eds.), Glaciological Report No. 139/140 of the Cryospheric Commission (EKK) of the Swiss Academy of Sciences (SCNAT) published by VAW / ETH Zürich, Tech. rep., https://doi.org/10.18752/glrep_139-140, 2020.
- 600 Gleason, C. J., Smith, L. C., Chu, V. W., Legleiter, C. J., Pitcher, L. H., Overstreet, B. T., Rennermalm, A. K., Forster, R. R., and Yang, K.: Characterizing supraglacial meltwater channel hydraulics on the Greenland Ice Sheet from in situ observations, *Earth Surface Processes and Landforms*, 41, 2111–2122, [https://doi.org/DOI: 10.1002/esp.3977](https://doi.org/DOI:10.1002/esp.3977), 2016.
- 605 Haeberli, W.: Frequency and characteristics of glacier floods in the Swiss Alps, *Annals of Glaciology*, 4, 85–90, <https://doi.org/10.3189/S0260305500005280>, 1983.

- Hock, R.: A distributed temperature-index ice-and snowmelt model including potential direct solar radiation, *Journal of glaciology*, 45, 101–111, <https://doi.org/10.3189/S0022143000003087>, 1999.
- Hubbard, B. and Glasser, N. F.: *Field techniques in glaciology and glacial geomorphology*, John Wiley & Sons, 2005.
- 610 Huss, M., Voinesco, A., and Hoelzle, M.: Implications of climate change on Glacier de la Plaine Morte, Switzerland, *Geographica Helvetica*, 68, 227–237, <https://doi.org/10.5194/gh-68-227-2013>, 2013.
- Huss, M., Dhulst, L., and Bauder, A.: New long-term mass-balance series for the Swiss Alps, *Journal of Glaciology*, 61, 551–562, <https://doi.org/10.3189/2015JoG15J015>, 2015.
- Huss, M., Bauder, A., Linsbauer, A., Gabbi, J., Kappenberger, G., Steinegger, U., and Farinotti, D.: More than a century of direct glacier
615 mass-balance observations on Claridenfirn, Switzerland, *Journal of Glaciology*, pp. 1–17, <https://doi.org/10.1017/jog.2021.22>, 2021.
- Incropera, F. P., Lavine, A. S., Bergman, T. L., and DeWitt, D. P.: *Fundamentals of heat and mass transfer*, Wiley, 2007.
- Irrazaval, I., Werder, M. A., Huss, M., Herman, F., and Mariethoz, G.: Determining the evolution of an alpine glacier drainage system by solving inverse problems, *Journal of Glaciology*, pp. 1–14, <https://doi.org/10.1017/jog.2020.116>, 2021.
- Isenko, E., Naruse, R., and Mavlyudov, B.: Water temperature in englacial and supraglacial channels: Change along the flow and contribution
620 to ice melting on the channel wall, *Cold Regions Science and Technology*, 42, 53–62, <https://doi.org/10.1016/j.coldregions.2004.12.003>, 2005.
- Jarosch, A. H. and Gudmundsson, M. T.: A numerical model for meltwater channel evolution in glaciers, *The Cryosphere*, 6, 493–503, <https://doi.org/10.3189/2015JoG14J158>, 2012.
- Karlstrom, L., Gajjar, P., and Manga, M.: Meander formation in supraglacial streams, *Journal of Geophysical Research: Earth Surface*, 118,
625 1897–1907, <https://doi.org/10.1002/jgrf.20135>, 2013.
- Karlstrom, L., Zok, A., and Manga, M.: Near-surface permeability in a supraglacial drainage basin on the Llewellyn Glacier, Juneau Icefield, British Columbia, *The Cryosphere*, 8, 537–546, <https://doi.org/10.5194/tc-8-537-2014>, 2014.
- Kingslake, J., Ng, F., and Sole, A.: Modelling channelized surface drainage of supraglacial lakes, *Journal of Glaciology*, 61, 185–199, <https://doi.org/10.5194/tc-6-493-2012>, 2015.
- 630 Lindner, F., Walter, F., Laske, G., and Gimbert, F.: Glaciohydraulic seismic tremors on an Alpine glacier, *The Cryosphere*, 14, 287–308, <https://doi.org/10.5194/tc-14-287-2020>, 2020.
- Lunardini, V., J.R. Z., and Yen, Y.: Experimental determination of heat transfer coefficients in water flowing over a horizontal ice sheet, Tech. Rep. 3, US Army Corps of Engineers, Cold Regions Research & Engineering Laboratory, 1986.
- Mayer, C. and Schuler, T. V.: Breaching of an ice dam at Qorlortossup tasia, south Greenland, *Annals of Glaciology*, 42, 297–302,
635 <https://doi.org/10.3189/172756405781812989>, 2005.
- Mernild, S. H., Hasholt, B., and Liston, G. E.: Water flow through Mittivakkat Glacier, Ammassalik Island, SE Greenland, *Geografisk Tidsskrift-Danish Journal of Geography*, 106, 25–43, <https://doi.org/10.1080/00167223.2006.10649543>, 2006.
- Nye, J. F.: Water flow in glaciers: jökulhlaups, tunnels and veins, *Journal of Glaciology*, 17, 181–207, <https://doi.org/10.3189/S002214300001354X>, 1976.
- 640 Pitcher, L. H. and Smith, L. C.: Supraglacial Streams and Rivers, *Ann. Rev. Earth Planet. Sci.*, 47, 421–452, <https://doi.org/10.1146/annurev-earth-053018-060212>, 2019.
- Raymond, C. F. and Nolan, M.: Drainage of a glacial lake through an ice spillway, IAHS publication, pp. 199–210, 2000.
- Richardson, S. D. and Reynolds, J. M.: An overview of glacial hazards in the Himalayas, *Quaternary International*, 65, 31–47, [https://doi.org/10.1016/S1040-6182\(99\)00035-X](https://doi.org/10.1016/S1040-6182(99)00035-X), 2000.

- 645 Roberts, M. J.: Jökulhlaups: a reassessment of floodwater flow through glaciers, *Review of Geophysics*, 43, <https://doi.org/10.1029/2003RG000147>, 2005.
- Röthlisberger, H.: Water pressure in intra- and subglacial channels, *Journal of Glaciology*, 11, 177–203, <https://doi.org/10.3189/S0022143000022188>, 1972.
- Shah, R. K. and London, A. L.: *Laminar Flow Forced Convection in Ducts*, *Advances in Heat Transfer*, Academic Press, Inc., New York, 650 1978.
- Smith, L. C., Chu, V. W., Yang, K., Gleason, C. J., Pitcher, L. H., Rennermalm, A. K., Legleiter, C. J., Behar, A. E., Overstreet, B. T., Moustafa, S. E., et al.: Efficient meltwater drainage through supraglacial streams and rivers on the southwest Greenland ice sheet, *Proceedings of the National Academy of Sciences*, 112, 1001–1006, <https://doi.org/10.1073/pnas.1413024112>, 2015.
- Sommers, A. N. and Rajaram, H.: Energy Transfer by Turbulent Dissipation in Glacial Conduits, *Journal of Geophysical Research: Earth* 655 *Surface*, 125, <https://doi.org/10.1029/2019JF005502>, 2020.
- Spring, U. and Hutter, K.: Numerical studies of jökulhlaups, *Cold Regions Science and Technology*, 4, 227–244, [https://doi.org/10.1016/0165-232X\(81\)90006-9](https://doi.org/10.1016/0165-232X(81)90006-9), 1981.
- Vatne, G. and Irvine-Fynn, T.: Morphological dynamics of an englacial channel, *Hydrology and Earth System Sciences*, 20, 2947–2964, <https://doi.org/10.5194/hessd-12-7615-2015>, 2016.
- 660 Vincent, C., Auclair, S., and Le Meur, E.: Outburst flood hazard for glacier-dammed Lac de Rochemelon, France, *Journal of Glaciology*, 56, 91–100, <https://doi.org/doi.org/10.3189/002214310791190857>, 2010.
- Vincent, C., Garambois, S., Thibert, E., Lefebvre, E., Le Meur, E., and Six, D.: Origin of the outburst flood from Glacier de Tête Rousse in 1892 (Mont Blanc area, France), *Journal of Glaciology*, 56, 688–698, <https://doi.org/10.3189/002214310793146188>, 2010b.
- Vincent, C., Descloitres, M., Garambois, S., Legchenko, A., Guyard, H., and Gilbert, A.: Detection of a subglacial lake in Glacier de Tête 665 *Rousse* (Mont Blanc area, France), *Journal of Glaciology*, 58, 866–878, <https://doi.org/10.3189/2012JoG11J179>, 2012.
- Walder, J. S. and Costa, J. E.: Outburst floods from glacier-dammed lakes: The effect of mode of lake drainage on flood magnitude, *Earth Surface Processes and Landforms*, 21, 701–723, [https://doi.org/10.1002/\(SICI\)1096-9837\(199608\)21:8<701::AID-ESP615>3.0.CO;2-2](https://doi.org/10.1002/(SICI)1096-9837(199608)21:8<701::AID-ESP615>3.0.CO;2-2), 1996.