



Towards accurate quantification of ice content in permafrost of the Central Andes, part I: geophysics-based estimates from three different regions

Christin Hilbich¹, Christian Hauck¹, Coline Mollaret¹, Pablo Wainstein², Lukas U. Arenson³

¹Department of Geosciences, University of Fribourg, Fribourg, 1700, Switzerland
 ²BGC Engineering Inc., Calgary, AB, Canada
 ³BGC Engineering Inc., Vancouver, BC, Canada

Correspondence to: Christin Hilbich (christin.hilbich@unifr.ch)

Abstract. In view of the increasing water scarcity in the Central Andes in response to ongoing climate change, the significance

- 10 of permafrost occurrences for the hydrological cycle is currently controversial. The lack of comprehensive field measurements and quantitative data on the local variability of internal structure and ground ice content further enhances the situation. We present field-based data from six extensive geophysical campaigns completed since 2016 in three different high-altitude regions of the Central Andes of Chile and Argentina (28 to 32° S). Our data cover various permafrost landforms ranging from ice-poor bedrock to ice-rich rock glaciers and are complemented by ground truthing information from boreholes and numerous
- 15 test pits near the geophysical profiles. In addition to determining the thickness of the potential ice-rich layers from the individual profiles, we also use a quantitative 4-phase model to estimate the volumetric ground ice content in representative zones of the geophysical profiles.

The analysis of 52 geoelectrical and 24 refraction seismic profiles within this study confirmed that ice-rich permafrost is not restricted to rock glaciers, but is also observed in non-rock-glacier permafrost slopes in the form of interstitial ice as well as

20 layers with excess ice, resulting in substantial ice contents. Consequently, non-rock glacier permafrost landforms, whose role for local hydrology has so far not been considered in remote-sensing based approaches, may be similarly relevant in terms of ground ice content on a catchment scale and should not be ignored when quantifying the potential hydrological significance of permafrost.

We state that geophysics-based estimates on ground ice content allow for more accurate assessments than purely remote-

25 sensing-based approaches. The geophysical data can then be further used in upscaling studies to the catchment scale in order to reliably estimate the hydrological significance of permafrost within a catchment.





30 1 Introduction

Permafrost covers about 15 to 20 % of the Northern hemisphere global land-surface (Obu, 2021; Obu et al., 2019). Most permafrost studies address permafrost occurrences either in the Arctic, Antarctica, or mountain ranges of the Northern Hemisphere. However, in the mid-latitudes of the Southern Hemisphere the presence of permafrost is also widespread at high elevation in the Central Andes of South America, where only few studies and even less borehole data (e.g., within the global

- 35 permafrost data base GTN-P, Biskaborn et al., 2019) currently exist. Continued climate change is projected to cause significant temperature increase for the Subtropical Central Andes, yielding significant water shortage especially in the arid mountain regions (Hock et al., 2019). In this context, the significance of permafrost occurrences in the Central Andes for the hydrological cycle is currently controversial (e.g., Arenson and Jakob, 2010; Azócar and Brenning, 2010; Brenning, 2008; Duguay et al., 2015; Jones et al., 2019). On the one hand, permafrost in general, and especially rock glaciers (which are conspicuous and
- 40 often ice-rich permafrost landforms) are considered key stores of frozen water and alternative future water resources in view of the ongoing recession of glaciers in the dry Andes (e.g., García et al., 2017; Masiokas et al., 2020; Rangecroft et al., 2015). Consequently, degrading permafrost is speculated to partly compensate the strongly decreasing glacial discharge in the future, and aid the strong demand for fresh water from the Andean Cordillera for the growing population and economy in the Central and dry Andes (Bradley et al., 2006; Schaffer et al., 2019).
- 45 On the other hand, the significance of permafrost for the hydrological cycle and regional hydrology is disputed (Arenson et al., 2013; Duguay et al., 2015), due to (1) the methodology to quantify ground ice resources in Andean permafrost regions, (2) the time scales involved for significant discharge from permafrost bodies, and also (3) unknowns on evaporation and sublimation processes under intense solar radiation. A large part of the current debate focusses on rock glaciers as the most prominent, ice-rich permafrost landforms, which can easily be identified by remote sensing (e.g., Azócar et al., 2017; Janke et
- 50 al., 2017; Rangecroft et al., 2014; Villarroel et al., 2018). Remote-sensing based rock glacier inventories have been used to estimate the total ice volume in rock glaciers from rough estimates of rock glacier thickness (e.g., Rangecroft et al., 2015) or empirical volume-area correlations (Brenning, 2005; Jones et al., 2018b, 2018a, 2019), with the aim to compare the ice content stored in rock glaciers to the total ice content of glaciers per region. However, these estimates have been conducted without any ground truthing or other means of validation, and volume-area correlations for rock glaciers have significant uncertainty
- 55 as local topography, geology and geomorphic processes are ignored. In addition, permafrost occurrences other than rock glaciers have rarely been considered due to the difficulty of detecting them from space. This focus on rock glaciers and remote-sensing-derived estimates points to the problem of a general lack of ground-based data in the high Andes, with only very few exceptions (e.g., Arenson et al., 2010; Croce and Milana, 2002; Halla et al., 2021;
- 60 thickness, internal structure, and ground ice content of permafrost, and especially rock glaciers, to evaluate the role of ground ice within the hydrological cycle (Arenson et al., 2010; Azócar et al., 2017; Azócar and Brenning, 2010; Croce and Milana, 2002; Duguay et al., 2015; Jones et al., 2018a, 2019; Perucca and Angillieri, 2011; Rangecroft et al., 2015). Duguay et al.,

Monnier and Kinnard, 2013; de Pasquale et al., 2020). Numerous authors highlight the need for field observations regarding





(2015) emphasise in this context that practically no quantitative data on the hydrology of rock glaciers are available, but that most studies are qualitative instead.

- 65 To estimate the ground ice content of permafrost landforms such as a rock glacier, both the total volume of the landform, i.e., horizontal <u>and</u> vertical extent, as well as the spatial variability of its ground ice content needs to be known. Both parameters can be derived from geophysical data. Compared to direct methods (core drillings or excavations/test pits), which are very costly and mostly restricted to point information or shallow depths, geophysical surveying can cover larger areas and depths, is cost-effective and comparatively easy to apply, and can be applied non-invasively, also in fragile and remote polar and high
- 70 mountain terrain (e.g., Kneisel et al., 2008). Recent developments in the application of geophysical techniques to permafrost problems have focused on quantitative estimates of volumetric ground ice content from electric, electromagnetic, seismic and gravimetric techniques, mostly applied in combination (Duvillard et al., 2018; Hauck et al., 2011; Hausmann et al., 2007; Mollaret et al., 2020; Oldenborger and LeBlanc, 2018; Wagner et al., 2019). Hauck et al. (2011), Wagner et al. (2019) and Mollaret et al. (2020) showed that the spatial distribution of the subsurface composition (ice, water, air and rock/soil content)
- 75 can be derived from linking the measured electrical and seismic properties through petrophysical models and validated their approach using borehole (core) data. In the Andes, such quantitative geophysical studies are still very rare and focused on individual rock glaciers (e.g., Halla et al., 2021; Monnier and Kinnard, 2013; de Pasquale et al., 2020). To reduce the lack of comprehensive and quantitative field data on the local variability of ground ice content within rock

glaciers but also on other ice-rich and ice-poor permafrost occurrences in the Central Andes, we conducted extensive

- 80 geophysical measurement campaigns in different high-altitude regions of Chile and Argentina. We here present a large number of geoelectric (Electrical Resistivity Tomography, ERT, 52 surveys) and seismic (Refraction Seismic Tomography, RST, 24 surveys) data sets from several permafrost sites with different geomorphologic settings, including numerous ice-rich and icepoor permafrost occurrences (Table 1, Table 2). Borehole and test pit data are available for some of the sites, which are used to validate the quantitative estimates of ground ice contents by the 4-phase model (Hauck et al., 2011). The surveys were
- 85 conducted during the years 2016 2019 in four different regions between 28 and 32° S (Figure 1) in the framework of several Environmental Impact Assessment studies.

With these data, we want to address the following objectives: (1) Demonstrate the potential and feasibility of geophysical surveys for the quantification of ground ice content of different permafrost landforms in the Central Andes; (2) compare the ground ice content in different rock glaciers with non-rock glacier permafrost occurrences; and (3) analyse the uncertainties

90 of ground ice content estimates in the context of future studies of water availability from thawing permafrost under climate change.

In the following, we will introduce our methodology to estimate the thickness of ice-rich permafrost layers and quantify ground ice contents from geophysical surveys, present the compiled data set, and comment on the implications of the results regarding potential water storage within permafrost systems in high mountain regions.

95





Table 1: Overview over main characteristics of the field locations and number and type of geophysical profiles (Abbreviations: RG = rock glacier, PR = protalus rampart, TS = talus slope, SED = sediment slopes (including gelifluction slopes, colluvial slopes, debriscovered bedrock, moraines, landslides).

			Elevation	nr. of p	nr. of profiles		Landforms		
Date	Location	Province	range [m]	ERT	RST	RG/PR	TS	SED	
Feb 2016	А	Choapa Province (CL)	3500 - 3900	15	13	7	2	1	
Mar 2017	В	Choapa Province (CL)	3600- 3900	3	3	3	-	-	
Mar 2017	С	Elqui Province (CL)	4900 - 5100	8	2	-	-	8	
Fab 2019		Copiapó Province (CL)		10	2			10	
Feb 2018	D	San Juan Province (AR)	5000 - 5200	10	3	-	-	10	
Feb 2019 E		San Juan Province (AR)	4200 - 4800	15	2	2	1	8	
Feb 2018 F		San Juan Province (AR)	4300 - 4500	1	1	1	-	-	





Figure 1: Map of the Central Andes with the study sites A - F, and detailed images for each of the study sites, showing the geophysical lines completed (Map data: © Google Earth 2021).





2 Methods

With respect to the conducted ERT (Electrical Resistivity Tomography) and RST (Refraction Seismic Tomography) surveys,
we follow the well-established methodology described in Halla et al. (2021), Mewes et al. (2017), and Mollaret et al. (2019).
This methodology includes the conduction of the surveys, data processing with filtering of measured apparent resistivities (ERT), first break picking (RST), data inversion using the software RES2DINV (Aarhus Geosoftware) and Reflex-W (Sandmeier Geophysical Research) and, where applicable, running the 4-phase model (Hauck et al., 2011).

ERT data were obtained in the field using a SYSCAL multi-electrode instrument (Iris Instruments) with 48 electrodes. As ERT

- 110 data acquisition quality often suffers from low signal-to-noise ratios, induced by the high contact resistances of galvanically coupled electrodes in dry and coarse-blocky substrates, all measurements were performed in the Wenner configuration to ensure maximum signal strength. The spacing between the electrodes for the individual profiles varied between 1 and 8 m depending on the desired survey geometry and penetration depth. The obtained apparent resistivity data sets were filtered following the procedure described in Mollaret et al. (2019). Data inversion was conducted using the Software RES2DINV
- 115 (Loke, 2020) and typical inversion parameters used for heterogeneous and highly resistive terrain (Hilbich et al., 2009; Mollaret et al., 2019). Inversions with other schemes such as the open-source library pyGIMLi (Rücker et al., 2017) gave comparable results (Mollaret et al., 2020).

Table 2: Overview over all ERT and RST profiles in all regions, including classification into landform types, availability of ground
truthing data and indication of permafrost presence or absence, where possible. Abbreviations: RG = rock glacier, TS = talus slope,SED = sediment slopes (including gelifluction slopes, colluvial slopes, debris-covered bedrock, moraines, landslides).





												-	_															
	Profile	10 4	A02	A03	A04	A05	A06	A07	A08	A09	A15	A16a	A16b	A17	A24	A25	B 01	B 02	B 03		707	C03	C04	C06	C07	C08	C09	C10
-	location	А	Α	А	А	Α	А	А	А	Α	Α	А	Α	Α	Α	А	В	В	В	C	2	С	С	С	С	С	С	С
Meta	landform	RG	RG	RG	RG	TS	PR/RG	RG	RG	RG	RG	PR	RG	RG	SED	TS/PR	RG	RG	RG	SE	D	SED	SED	SED	SED	SED	SED	SED
_	altitude	3762	3730	3742	3840	3850	3810	3830	3775	3785	3730	3708	3740	3650	3710	3695	3680	3800	3850	50	85	5065	5005	5110	4910	4975	5080	4995
ERT	length [m]	144	595	144	235	213	213	188	380	94	141	94	188	285	213	141	355	213	285	14	12	94	69.5	94	142	94	94	141
÷.	spacing [m]	3	5	3	5	3	3	4	4	2	3	2	4/2	3	3	3	5	3	3	2	2	2	1.5	2	2	2	2	3
RST	length [m]	69	164	69	-	180	164	164	164	69	69	82	164	-	-	46	123	177	123	46	46				103			
2	spacing [m]	3	4	3	-	3	4	4	4	3	3	2	4	-	-	2	3	3	3	2	2				2.5			
Ξ.	borehole		x		×		x	×	xx				x	x														
ground truth	test pit		x	x					xxx	x		x	x												x	x	x	
50 T	other																							×				
	permafrost	у	у	у	у	?	у	у	у	у	у	?	у	n	n	?	?	у	у	у	?	n	у	у	у	у	у	у
													<	>	т					-	۵,							l
	Profile	10 Q	D02	D03	D04	D 05	D 06	D 06b	D07	D08	000	F01	Г EO3	EO3_BV	E03_BH	E 04	EOS	E08	E09	E11_H	E11_I	E12	E13	E14	E15	E16	E17	
	location	D	D	D	D	D	D	D	D	D	D	F	Е	Е	E	E	E	Е	Е	Е	Е	E	E	Е	Е	Е	Е	
Meta	landform	SED	SED	SED	SED	SED	SED	SED	SED	SED	SED	RG	SED	SED	SED	SED	SED	RG	RG	SED	SED	SED	SED	SED	SED	TS/PR	PR	
_	altitude	5080	5135	5160	5105	5100	5025	5025	5030	5085	5108	4408	4520	4520	4520	4815	4815	4620	4640	4615	4615	4830	4545	4415	4400	4210	4210	
н	length [m]	70.5	104	94	94	188	142	47	328	188	70.5	235	94	47	141	142	70.5	470	235	235	235	70.5	235	94	94	142	235	
ERT	spacing [m]	1.5	1.5	2	2	2	2	1	2	2	1.5	5	2	1	1.5	2	1.5	5	5	5	5	1.5	5	2	2	2	5	
	length [m]				82					46	46	69						123		69								
RST	spacing [m]				2					2	2	3						3		3								
	borehole				-					-	-	~						~										
ground truth	test pit								×				xx	x		×	×					x			×			
gro tri	other				×	×			^		×		~~	^		^	^					^			^			
	permafrost	v	N.				v	V		v		v	n	n.		?	?	X	v	?	?	N			n		v	
	permatrost	У	У	У	У	y .	У	У	У	У	У	У	n	n	n		1 (L	У	У	1	1	У	n	n	n	У	y	i i

Refraction seismic data were recorded through a Geode system (Geometrics) with 24 geophones and a sledgehammer as source. First breaks were picked manually and afterwards inverted within the software REFLEXW (Sandmeier, 2020) to yield

- 125 tomograms of P-wave velocity on co-located lines of specific ERT profiles. The resolution and data quality differ for each profile and method; in general, the resulting root-mean-square errors of the ERT profiles were below 10 % (except for E17 with 22 %) and below 3 ms for the RST inversion (Table A1). See Table 2 for details on the individual profiles. Regarding quantification of the volumetric ground ice content (ice content), Hauck et al. (2011) introduced a petrophysical
- approach by way of the so-called 4-phase model (4PM) using the obtained specific resistivity and P-wave velocity distributions
 as input variables. The 4PM consists of a combination of two basic mixing rules for electrical resistivity (Archie's Law, Archie, 1942) and seismic P-wave velocities (a modified Wyllie equation, see Timur, 1968), and the condition that the volumetric contents of ice, water, air and rock sum up to 1 for each model cell. Under the assumption of a site-specific porosity distribution, the 4PM estimates the ice-, water and air content for each model cell. Wagner et al. (2019) extended the approach to a petrophysical joint inversion (PJI) model, which yields physically consistent estimates of all 4 phases, i.e. without the necessity
- of prescribing porosity. Both model approaches were successfully applied to various permafrost occurrences (Halla et al., 2021; Mollaret et al., 2020; de Pasquale et al., 2020; Pellet et al., 2016; Schneider et al., 2013). However, the PJI still faces convergence problems in the absence of a priori knowledge, and its application to a large number of geologically and





geomorphologically different profiles is therefore challenging. Therefore, we opted here for the application of the 4PM, which allows consistent ice content modelling for a large number of profiles.

- 140 In the 4PM, the largest uncertainties in absolute ground ice content values are due to the absence of reliable porosity information and extreme values of pore water resistivities. The later are a factor in Archie's Law that must be prescribed (Hauck et al., 2011). Halla et al. (2021) established a procedure using ranges of porosity and pore water resistivity values to quantify the uncertainty in absolute volumetric ice content estimates of a rock glacier in the Argentinian Andes.
- Within this study, we used ERT surveys to detect ground ice occurrences and delineate their vertical extent. As seismic surveys are much more time-consuming, they were conducted only at specific ERT profiles to get quantitative ice content estimates at representative locations. As co-located ERT and RST profiles are necessary to provide input data for the 4PM, these model results are only available for 22 profiles (see Table 2). Ice content estimates and ground ice extent were estimated from ERT data alone for all other profiles. Hereby, resistivity averages and maxima were evaluated within so-called zones-of-interest (ZOI), i.e. the profile region, which is assumed to be representative for the landform and permafrost occurrence (Etzelmüller
- 150 et al., 2020). Validation data are available for several profiles and ZOI's through drill cores, borehole temperature information and test pits (see next section).

3 Study sites and data set

Between 2016 and 2019, five extensive geophysical campaigns were completed in three different regions of the Central Andes on both sides of the border between Chile and Argentina. In total 52 ERT and 24 RST profiles were acquired to characterize
permafrost conditions regarding extent, active layer thickness and ground ice content. All field data were acquired in the austral summer as part of characterising the periglacial environment. Profile locations were chosen according to the probable presence of frozen ground, but also according to easy access and safety. Apart from the fact that some of the considered permafrost landforms had surface disturbances (e.g., access roads or drilling platforms), the context of the projects has no further relevance for the scientific content of this paper. The available infrastructure, however, enabled access to high-altitude permafrost environments and made possible the collection of a large and unique data set, including in-situ validation data.







Figure 2: Photographs of typical landforms with survey lines.





Due to the different locations (cf. Figure 1), a large variety of ground conditions ranging from sediment slopes (including gelifluction slopes, colluvial slopes, debris-covered bedrock, moraines, landslides) over talus slopes, protalus ramparts (also called protalus rock glaciers, or embryonic rock glaciers, cf. Barsch, 1996; Hedding, 2011) to rock glaciers is covered by geophysical profiles. Table 1 summarises the main characteristics of the different study sites and geophysical profiles, and Figure 2 shows some typical examples of the considered landforms with the geophysical profile lines indicated. Many of the rock glaciers in the different investigation areas show initial or advanced signs of degradation (e.g., inactive front slopes, thermokarst depressions), but in the absence of kinematic data for most of the observed rock glaciers a reliable determination

- of their activity state according to the guidelines of the IPA action group on rock glacier inventory and kinematics (RGIK, 2020) remains challenging. As the activity of a rock glacier is not directly linked to its ice content, which is the focus of this paper, we avoid any pre-classification of the rock glacier activity here, even if geomorphological indications and kinematic data are available in some cases.
- 175 In total 24 coinciding ERT and RST profiles were subsequently used for the estimation of the ground ice content and its spatial variability based on the 4PM. The availability of undisturbed core drillings, borehole temperature measurements and numerous test pits enabled the validation of the methodological approach at 24 of the profile lines (availability of ground truthing data indicated in Table 2).

180 4 Results

All available data (ERT/RST) have been quality-checked, processed and interpreted. An overview about data quality (filter statistics, RMS error) and a reference plot with all available ERT and RST tomograms is provided in the Appendix (cf. Table A1, Figures A1 and A2). In the following, we will present exemplary results regarding different landforms characteristics.

4.1 Rock Glaciers and Protalus Ramparts

185

4.1.1 General characteristics

In total, 19 ERT profiles were measured on ice-rich permafrost landforms, including rock glaciers (16) and protalus ramparts (3). These are shown in Figure 3 with the same dimensions and colour scales for all tomograms. All profiles have been analysed and interpreted independently (Hauck et al., 2017; Hilbich et al., 2018; Hilbich and Hauck, 2018a, 2018b, 2019); here, we focus on a general and comparative analysis of all profiles, as a detailed discussion of each case study is beyond the scope of

190 this paper.

Among our data, the resistivities of rock glaciers can be grouped into two parts: rock glaciers with resistivity maxima of the permafrost body below the active layer well above 100 k Ω m, partly reaching 1 M Ω m or more (RG I, Figure 3a), and rock glaciers with resistivity maxima mostly < 100 k Ω m and/or shallower and more patchy resistive zones (RG II, Figure 3b). Rock





glaciers of group RG II often show visible degradation expressions, such as inactive front slopes or thermokarst depressions. 195 Protalus ramparts show similar resistivity values as rock glaciers (Figure 3c).



B) Rock Glaciers II - resistivity maxima < 100 kΩm









Figure 3: Inverted ERT tomograms for all rock glacier and protalus rampart profiles of the study. Zones of the tomograms not related to a rock glacier or protalus rampart are indicated by diagonal lines. The dashed rectangles mark the so-called zone-ofinterest (ZOI) used for the resistivity averaging and comparison. Data misfit (absolute error in %) is indicated for each profile.

Note, that rock glaciers with a very coarse-blocky and dry active layer (with air-filled voids) typically can have similarly high resistivities in the active layer as in the ice-rich permafrost layer, as both air and massive ice are electrical isolators (e.g., profiles A04, A15). However, at the bottom of the active layer, more fine-grained material typically accumulates, and moisture from snowmelt and seasonal active layer thawing may be retained on top of the impermeable frozen layer, often resulting in a more conductive intermediate layer (e.g., visible in A01, A03, A08, A09, cf. Figure 3a).

A high-resistive zone indicating ice-rich permafrost can usually be observed throughout the entire landform for rock glaciers of group RG I, but with varying thicknesses and specific resistivity values. We estimate the thickness of the ice-rich permafrost body of the rock glaciers from the thickness of this high-resistive zone. As the resolution of geophysical methods generally decreases with depth, the determination of the upper boundary is more reliable than its vertical extent. The resolution of the

- 210 lower boundary depends on several factors:
 - a) survey geometry, defining the spatial resolution and the depth of investigation;
 - b) the depth of the lower boundary in relation to the investigation depth (the shallower the boundary, the better its resolution); and
 - c) the resistivity contrast between ice-rich permafrost layer and underlying layer (e.g., bedrock, the higher the contrast,

215

205

the better the resolution).

We therefore use the onset of a decreasing resistivity gradient (below the maximum) as a conservative indicator for the lower limit of ice-rich permafrost.



Figure 4: Overview over minimum and maximum thickness of ice-rich permafrost in all protalus ramparts (PR), and rock glaciers (RG) of group I and II, determined from the high-resistive zone in the ERT tomograms. Profile A17 is from a relict rock glacier with little probability for ground ice.





The investigation depth was sufficient to identify the bottom of the ice-rich permafrost layer for most rock glacier profiles. Due to the spatial heterogeneity within the observed profiles, the thickness of the ice-rich permafrost layer cannot reliably be determined everywhere along the profile and remains an estimate. Figure 4 indicates the ERT-based minimum and maximum

- thickness of the ice-rich layer in all ice-rich permafrost profiles (i.e. rock glaciers and protalus ramparts). Note, that the minimum thickness refers to the ice-rich zones within the tomograms, and that most profiles also contain zones without permafrost or ice-rich layers. The determined thicknesses mainly range between a few meters and do not exceed 25 m for all considered landforms. No clear difference is observed for the different categories (and was not expected).
- As an overall observation, it can be noted that data quality is often worse on the coarse-blocky parts of the rock glaciers because of challenging conditions for sufficient galvanic coupling at the surface (Hilbich et al., 2009; Mollaret et al., 2019) than for the generally more fine-grained surface material and lower resistivities of rock glaciers with advanced degradation (RG II). This clearly affected the data quality in the first half of profile E17 (22 % data error, cf. Figure 3c), but had no severe impact on most other profiles (a few more profiles with insufficient data quality exist, but were not considered for this study).

4.1.2 Example data set: Rock glacier A16B

- As an example, Figure 5 shows the geophysical results for profile A16B, which crosses two neighbouring rock glacier lobes, with a borehole drilled in one of the lobes marked by the black vertical line. The active layer was largely removed through the construction of the borehole platform. Maximum resistivities of up to 1 M Ω m are observed in two distinct anomalies corresponding to the two different lobes, and indicate high ground ice content occurrences of 5-18 m thickness, which is confirmed by the drilling results (cf. Figure 5a, Figure 6, Table 3).
- 240 The corresponding seismic results (Figure 5b) confirm ice-rich permafrost with P-wave velocities of 3000-4000 m/s within the zone of the high resistivity anomalies. Below this zone, P-wave velocities of up to 6000 m/s indicate the bedrock at around 20 m depth. The profile clearly illustrates coinciding characteristic resistivity/velocity values for pure ice ($\rho > 1 \text{ M}\Omega\text{m} \& v_p = 3500 \text{ m/s}$) and bedrock ($\rho \sim 1 \text{ k}\Omega\text{m} \& v_p = 6000 \text{ m/s}$, cf. Hauck et al., 2011).

Based on the co-located ERT and seismic profiles, the volumetric fractions of the four phases rock, ice, water and air have

been modelled using the 4PM (cf. section 2). Figure 5c shows the modelled ice content for profile A16B, with two anomalies of > 60 % ground ice content, which is in good agreement with the previous interpretation and the results from the borehole stratigraphy. The thaw depth is around 3-5 m in both lobes (except for the disturbed area of the drilling platform).







Figure 5: Geophysical results of A16B (rock glacier): a) section of the ERT profile covered by the RST profile (see Figure 3a for full profile), b) RST profile, and c) volumetric ice content modelled by the 4PM. The borehole position is indicated, with the light blue part indicating the frozen part. The data misfit of both inversion models is indicated in the upper right corner. The cross-hatched zone marks the area detected as bedrock in the 4PM. Labels denote the interpretation.







Figure 6: Example of a frozen core extracted from a rock glacier at 11 – 14 m depth (ERT profile A16b). The upper half of the core run shows massive ground ice and the lower half frozen gravel and sand with a very low ground ice content.

Table 3: Overview over available ground truthing data with the most important permafrost-relevant information. Abbreviations: BH = borehole; TP = test pit; PF = permafrost; AL = active layer. The presence of one or more boreholes or test pits is indicated with one or more 'x', similarly one or more 'y' or 'n' indicate, if permafrost was confirmed or not. The ice content range represents the observed minimum and maximum values throughout the entire depth column.

	type of ground truthing data				type of v	alidation			
			natural	max.	PF	AL	PF		
Profile	BH	ТР	outcrop	depth	confirmed	thickness	thickness	ice content	comments
A02	х	xxx		28 m	ууу	3.2 m	25 m	45 - 90 %	
A04	x			32 m	У	2 m	21 m	25 - 75 <mark>%</mark>	
A06	x			31 m	У	8 m	12 m	0 - 95 %	
A07	x			29 m	У	unknown	25 m	40 - 85 %	
A08	xx	xx		25 m	У	2 m	> 15 m	10 - 100 %	Monnier & Kinnard (2013)
A16a		x		5.1 m	n				minimum 5.1 m unfrozen, TP infront of the protalus rampart
A16b	x	x		15.4 m	У	unknown	13 m	70 - 100 %	AL removed during drilling
A17	x			37 m	n				minimum 37 m unfrozen
C06			x	2 m	У	~0.5 m		unknown	nearby test pits indicate shallow PF (< 0.5 m) with 60 - 75 % ice content
C07		×		1.3 m	У	1.2 m		40 %	ice-rich sediment
C08		x		1.3 m	у	1.2 m		100 %	> 10 cm thick ice lens
C09		x		0.9 m	у	0.8 m		70 %	10 cm thick ice lens with 70 % ice content
D05			x	1.5 m	у	~0.5 m		unknown	variable ice content, incl. ice lenses with 100 %
D07		×		5 m	y	~0.5 m	> 5 m 10 - 50 %		variable ice content, incl. ice lenses with 100 %; liquid water flow observed within the PF layer at 3-4 m depth
D09			x	5 m	У	unknown		60 - 70 %	ice-rich bedrock
E03_A		xx		6.5 m	nn				minimum 6.5 m unfrozen
E03_BV		xx		7.3 m	nn				minimum 7.3 m unfrozen
E04		×		2.2 m	unclear	~2.1 m		0 %	potentially frozen at >2.1 m depth, no ice visible
E05		×		4.3 m	у	~0.4 m		0 %	negative temperature, no ice visible
E12		×		4.6 m	У	~0.25 m		< 5 %	frozen layer with ice-coated rocks (ice-poor)
E15		x		8 m	n				minimum 8 m unfrozen

260





4.2 Talus slopes

4.2.1 General characteristics

- ERT profiles were collected on three talus slopes, and all of them show a similar resistivity pattern: a layer of increased resistivity (~10 k Ω m) within the talus material having a bulk resistivity of only a few k Ω m (Figure 7). The resistive layer is located at depths > 3 m, i.e. below a potential active layer, and has a maximum thickness of 10 m for the four measured profiles. The resistivities are sufficiently high to support the hypothesis of frozen conditions within the talus slope (Hauck and Kneisel, 2008), even if the expected ground ice content would be low. The resistive zone could also be explained by purely air-filled voids within the porous coarse-blocky substrate, similar to the resistive anomalies visible directly at the surface in most
- 270 profiles. This ambiguity can, in general, be addressed through coinciding seismic profiles (available for A05, A16a, and A25) and will be shown exemplary in section 4.2.2. Unfortunately, no ground truthing information is available for any of the talus slopes.

4.2.2 Example data set: Talus slope A05

Profile A05 is a longitudinal profile within a talus slope, located on an east-facing slope in the western part of a valley with

- 275 numerous rock glaciers at its south- and west-facing slopes. The ERT results in Figure 8a show comparatively low resistivities of < 10 k Ω m in most parts of the profile, indicating no or very small ground ice content. A localised anomaly with higher resistivities ($\rho \ge 10 \text{ k}\Omega\text{m}$) exists between 80 - 140 m horizontal distance and suggests a small possibility for potential ground ice at approximately 5 - 12 m depth. Seismic velocities of $v_p < 1500$ m/s in the same region point to loose blocks and debris with air-filled voids (Fig. 8c), rather than a layer with massive ground ice, except at larger depths (~25 m), where higher P-
- wave velocities ($v_p \sim 2000-3000 \text{ m/s}$) and coinciding low resistivities ($\rho < 5 \text{ k}\Omega \text{m}$) strongly indicate the bedrock. No ground truthing data are available for this profile. The anomaly with slightly larger resistivity values around 10 k Ω m between distances 80 - 140 m could indeed indicate frozen conditions, but with volumetric ice contents, which are too small to be detected by our seismic survey set-up. Consequently, the 4PM-estimated ice content is close to zero within the whole model domain (Fig. 8d).









285

Figure 7: Inverted ERT tomograms for all talus slope profiles of the study. Zones of the tomograms not related to the talus slope are indicated by diagonal lines. The dashed rectangles mark the so-called zone-of-interest (ZOI) used for the resistivity averaging and comparison. Data misfit (absolute error in %) is indicated for each profile.







290 Figure 8: Geophysical results of A05 (talus slope): a) section of the ERT profile covered by the RST profile (see Figure 7 for full profile), b) RST profile, and c) volumetric ice content modelled by the 4PM. The data misfit of both inversion models is indicated in the upper right corner. Labels denote the interpretation.

295





4.3 Sediment slopes

4.3.1 General characteristics

In addition to the 22 profiles on pebbly and coarse-blocky substrates of rock glaciers, protalus ramparts and talus slopes, 30 additional ERT profiles were measured in more fine-grained sedimentary substrate, including colluvial slopes (17 profiles), 300 gelifluction slopes (4 profiles), and weathered bedrock covered with a shallow debris layer (9 profiles, cf. Figure A2). Some of these ERT profiles on sediment slopes do not contain permafrost (e.g., E03, E13, E14, E15, cf. Table 2). However, all profiles on sediment slopes show significantly lower resistivities (mostly well below 1 kΩm) compared to rock glaciers, protalus ramparts and talus slopes (cf. Figure A1), including those, where ground ice was confirmed by test pits or outcrops (e.g., D07, D09, C06, C08). The reduced resistivity values are a result of the fine-grained and partly humid substrate and/or

305 the weathered bedrock, as well as the generally lower volumetric ice content in sediment slopes in the form of interstitial ice (i.e. << 50 %, except for excess ice in mostly thin ice lenses). In addition, many of these profiles contain prominent conductive layers of < 100 Ω m (Figure A2). We speculate that this is

mainly caused by (a) conductive sediments stemming from eroded hydrothermally altered bedrock, which was transported downslope (in case of the colluvial slopes), (b) the altered/conductive bedrock itself, or partly also (c) liquid (supercooled)

- 310 water due to freezing point depression by increased ion content related to hydrothermal alteration (Hauck et al., 2017; Hilbich and Hauck, 2018a). Significant water flow was for example observed above an ice-rich layer in a 4-5 m deep test pit close to profile D07 and below a frozen layer in profile C08 (cf. Figure A2a). It is important to note that these conductive layers are with high probability features strongly amplified by the inversion process caused by preferential current flow through conductive layers, which strongly biases the inversion result towards this conductive layer. Various synthetic modelling studies
- 315 (e.g., Hilbich et al., 2009; Mewes et al., 2017) have shown that the real thickness of such conductive layers may be more than an order of magnitude smaller than illustrated in the resulting tomograms. In this case, the resistivity of layers below will be biased towards lower values (i.e. ice contents may well be higher than expected from the inverted values), while the depth of the deeper layers could be strongly overestimated.

The detection of permafrost occurrences is further complicated by the often thin or patchy ice-lenses, which cannot be detected

- 320 with confidence because of the trade-off in the electrode spacing between reasonable large investigation depth/profile length and the resulting reduced spatial resolution capacity. A reliable interpretation of these tomograms is therefore not straightforward, but experience from the synthetic modelling studies mentioned above and comparison with ground truthing information allows resistive anomalies caused by small ice lenses to be identified, even if absolute resistivity values are lower than commonly known to indicate frozen conditions. Similar cases are known from the European Alps, where the combination
- of low-resistive geologic host material, increased water content and temperatures close to the freezing point leads to similarly low permafrost resistivities (Hilbich et al., 2008; Mollaret et al., 2019; Noetzli et al., 2019).
 Permafrost was clearly detected in profiles C07, D04, D05 and D09, where a prominent resistive layer (> 10 kΩm) is observed. Similar values but within much smaller and thinner anomalies were found in profiles D06, D07, D08. Test pits and natural outcrops within incised channels confirm the presence of permafrost for profiles D04 D07 and D09 (cf. Figure A2).





330

4.3.2 Example data set: Colluvial Slope D04

Figure 9 shows the results of profile D04 located within an east-facing slope, and consisting of mainly fine-grained colluvial sediments, cut by incised channels, which are active during snow melt (cf. Figure 2e). The slope shows a slightly convex form, indicating the potential for ice-rich conditions. The ERT tomogram in Figure 9a shows a high-resistive layer with values up to

- 335 10 kΩm indicating ice-rich permafrost between approximately 2 8 m depth, with a maximum around 3 m depth. Maximum resistivity values are similar to the maximum values in profile D09, where ground truthing from a test pit confirmed ice contents ≥ 50 %. We therefore expect significant ice-rich layer(s) in this profile with a possibly supersaturated zone around the resistivity maximum. The presence of ice-rich sediments is further confirmed by a natural outcrop formed by an incised channel close to profile D04, which exposed ice-rich and partly supersaturated sediments at about 1 m depth (thickness of this layer
- 340 unknown).







Figure 9: Geophysical results of D04 (colluvial sediments): a) section of the ERT profile covered by the RST profile (see A2a for full profile), b) RST profile, and c) volumetric ice content modelled by the 4PM. The data misfit of both inversion models is indicated in the upper right corner. The cross-hatched zone marks the area detected as bedrock in the 4PM. Labels denote the interpretation.

345

Below this ice-rich layer, resistivities $< 500 \ \Omega m$ prove ice-poor conditions, while a reliable differentiation between sediment or bedrock is not possible without further information. Seismic P-wave velocities increase to > 5000 m/s at $\sim 10 \text{ m}$ depth and indicate a transition to more competent frozen rock at this depth (Figure 9b).





Figure 9c shows the modelled ground ice content with maximum values around 60 %, which confirms the expected high 350 ground ice contents in this profile. Highest values are observed between 30 - 70 m horizontal distance with decreasing values in upslope direction (40 - 50 %) and an abrupt change to values < 30 % near the road in the lower part of the profile.

4.4 Joint analysis

4.4.1 Mean resistivity and P-wave velocity

- Comparing mean resistivity and P-wave velocities of the various profiles is a delicate task due to their dependence on 355 (potentially very different) local geologic conditions, which may give rise to substrate-dependent resistivity/velocity variations that may be misinterpreted as differences in ground ice content. Besides, uncertainties due to different measurement configurations and inversion errors may further impact a joint comparison. On the other hand, the dependence of resistivity and P-wave velocity on ice content is very strong, and its signal should be clearly detectable in such a large and comparatively homogeneous dataset presented in this study.
- 360 For a joint analysis of the representativeness of the measured geophysical parameters for the considered landforms, we selected all profiles where the presence of permafrost a) has been identified, or b) is considered possible but not confirmed (e.g. in talus slopes, cf. Table 2). We defined a rectangular zone either within the presumed permafrost occurrence (representative permafrost zone), or within the zone most probable/indicative for permafrost in case of ambiguous interpretation and call this zone hereafter the zone of interest (ZOI). The ZOI was chosen to be representative for the confirmed (or unconfirmed possible)
- 365 permafrost occurrence within the respective landform with minimal bias from potential inversion artefacts, thus resulting in various sizes and positions of the ZOI for different profiles.

Mean and maximum resistivities/velocities within the ZOIs were then extracted, and they clearly show different resistivity and velocity regimes for different landforms and substrates (see Figure 10a,b). Figure 10c analyses the relationship between mean specific resistivity and P-wave velocity within the ZOI of co-located ERT and seismic profiles, and reveals a landform-specific

- 370 clustering of resistivity-velocity pairs. Hereby, the resistivity/velocity pairs of rock glaciers cluster in two parts (green and purple in Fig. 10c). The purple cluster (lower resistivity and P-wave velocity) is consistent with the rock glaciers of group RG II (see section 4.1.1), showing visible signs of advanced degradation and lower ground ice contents than the ones in the green cluster (RG I). Similarly, lower velocity mean values are present for protalus ramparts (PR) and talus slopes (TS), with the exception that TS show lower maximum resistivities than PR and RG II; probably due to their lesser ground ice contents.
- 375 While the two rock glacier groups clearly differ in their mean resistivities and velocities, their maximum values overlap probably because most degrading rock glaciers still contain ice-rich zones with similar values as in intact rock glaciers (Figure 10a,b). Sediment slopes (often reaching bedrock at shallow depths) have clearly differing characteristics from coarse-blocky sites, which is attributed to their lower porosity (higher velocity) and lower ground ice content (lower resistivity). Note, however, that Figure 10c only provides an incomplete picture biased towards ice-rich landforms, as seismic surveys have
- 380 mainly been conducted on ERT profiles indicating ice-rich permafrost (cf. Table 2).







Figure 10: Landform-specific distribution of mean (black) and maximum (blue) values of inverted a) resistivity and b) velocity within the ZOIs of the respective ERT and RST tomograms. c) Scatter plot of mean resistivity and velocity for all co-located ERT and RST profiles, classified after landforms. Unfilled symbols in a) denote ERT profiles without co-located RST profiles. Unfilled symbols in a) denote ERT profiles without co-located RST profiles. Unfilled symbols in c) denote ZOIs with only possible permafrost occurrence. Abbreviations: SED = sediment slopes (including debris-covered bedrock, colluvial slopes, gelifluction slopes, etc.); TS = talus slopes; RG = rock glaciers (groups I and II described in section 4.1.1).

The striking pattern in Figure 10c, with clustered and high resistivities for intermediate velocities (RG I), and low-intermediate resistivities for similarly high or even higher P-wave velocities (bedrock) is apparent and has already been noted by Hauck et al. (2007) for geophysical surveys on several permafrost landforms in the South Shetland Islands/Maritime Antarctica. Rock glaciers with massive ice cause maximum resistivities, but P-wave velocities around 3500 m/s, close to the literature value for ice. Sites with v_p > 4000 m/s usually indicate the presence of (unfrozen or frozen) bedrock, coinciding with lower resistivities due to the lower ice content. Mean seismic velocities in Figure 10b are all < 3000 m/s, which is certainly influenced by the limited investigation depth on some rock glaciers (bedrock not reached), but also represents the generally lower P-wave

395 velocities of hydrothermally altered bedrock in some cases.

The systematic pattern observed in Figure 10 with a high consistency in the resistivity values over so many different surveys justifies the applicability of the geophysical approach to characterise different permafrost landforms, even in the absence of ground truthing. The seismic results further support and confirm the interpretation of the ERT data, but with a reduced overall representativeness due to a biased profile selection, fewer profiles and smaller profile dimension.

400





4.4.2 Volumetric ground ice contents

Similarly to Figure 4 (section 4.1.1), Figure 11a shows the estimated minimum (dark grey) and maximum (light grey) thicknesses of the ground ice layer for all profiles, where permafrost is a) confirmed or probable (indicated by blue frames), or b) unconfirmed and uncertain, but possible. The permafrost base for non-rock glacier sites could not always be detected, in 405 these cases the base of the surficial ice-rich layer was determined and is plotted instead. It is clear that ice-rich layers in sediments are much thinner than in coarse-blocky substrates. Further, most ice-rich layers within our study are thinner than 25 m, including all rock glacier profiles. Quantitative model results for volumetric ice content (as presented exemplarily above) are available for a total of 21 profiles with co-located ERT and seismic surveys, including 12 rock glaciers, 2 protalus ramparts, 1 talus slope, and 6 sediment slopes. Figure 11b shows the modelled mean (dark grey) and maximum (light grey) volumetric 410 ground ice contents within the defined ZOIs for all these profiles. The error bars give the uncertainty resulting from different 4PM runs spanning over the most probable porosity range for the respective landforms (SED: 30-45-60 %; TS: 40-50-60 %; RG: 40-60-80 %). The results indicate that maximum ice contents within the considered ZOIs are 51 - 56 % (+- 20 %), highest for rock glaciers of group RG I, and between 25 - 49 % (+- 20 %) for all other profiles. Note that anomalies with even higher ice contents can be present, but cannot explicitly be delineated if their size is smaller than detectable by the measurement 415 configuration. More representative for the landform scale is, however, the mean ground ice content within the considered

ZOIs, which spans in the same order of magnitude for most considered profiles (11 - 40 %) and shows that the ice content in the ice-rich layers of sediment slopes can be comparable to those of rock glaciers, even if the overall dimension of the ice-rich layer is very different.







Figure 11: Landform-specific distribution of a) minimum and maximum thickness of the ground ice layer, and b) the mean and maximum volumetric ground ice content within the ZOIs defined before, as derived from the 4PM. The bars and error bars in b) are based on landform-specific porosity ranges indicated in the text. Abbreviations: SED = sediment slopes (including debris-covered bedrock, colluvial slopes, gelifluction slopes, etc.); TS = talus slopes; PR = protalus ramparts; RG = rock glaciers. Profiles with confirmed or probable permafrost occurrence are highlighted in light blue, while the other values are only based on zones
 with possible permafrost occurrence.

5 Discussion

The uncertainty of the ice content estimation presented above depends first of all on the standard uncertainties of the geophysical data such as measurement data quality, resolution capacity, investigation depth, potential inversion artefacts, and representativeness of the geophysical profile for the whole landform. In addition, the uncertainties of the 4PM approach (rock-

- 430 ice ambiguity, porosity range, Archie parameter and estimate of rock P-wave velocity) have to be taken into account. In the context of mountain permafrost studies, 4PM-related uncertainties have already been addressed by Mewes et al. (2017) and Halla et al. (2021). In this study, we make additional use of the opportunity to compare our estimates with available ground truthing information, wherever possible, which when used as calibration reduces the uncertainty considerably. However, a large uncertainty remains regarding the representativeness of the individual profiles for a given landform. Depending on the
- 435 local geomorphological setting, ground ice contents can vary strongly, especially in case of very large landforms (e.g., Halla et al., 2021).

5.1 Comparison of results with ground truthing information

Since permafrost is thermally and temporally defined (Muller, 1943) and can be present in different substrates under various porosity and saturation conditions, it can exhibit a wide range of possible values in the geophysical parameters. Attribution of absolute electrical resistivity and P-wave velocity values to permafrost presence and specific ice contents can therefore be ambiguous without additional information. Further, the inverted geophysical parameters within a tomogram are influenced by the resolution capacity of the survey geometry in relation to the observed structure, the data quality and the material contrasts, which may all lead to inversion artefacts (Day-Lewis et al., 2005; Hilbich et al., 2009; Mewes et al., 2017). Small-scale anomalies and thin ice layers may not become visible in the comparatively coarse survey geometries utilised in the majority of the profiles of our study.

445 of the profiles of our study.

Table 3 gives an overview over the different types of available ground truthing data (boreholes, test pits, natural outcrops), the respective depth range covered, and the type of validation provided by the different data.

In general, the interpretation of the tomograms (regarding presence/absence of ice-rich permafrost, cf. profiles highlighted in blue in Figure 11a) as well as the overall dimension of the active layer thickness (cf. ERT tomograms in Figure A1, A2) is

450 confirmed by the ground truthing data, thus enabling the spatial analysis of ground ice occurrence and its quantification. For some rock glaciers (A02, A06, A07, A08, A16b), borehole-derived ice content values (representing minimum and maximum values observed throughout the borehole) can be compared to 4PM-derived min/max ice contents within the pre-





defined ZOIs (Figure 12). As thin ice-rich layers can be resolved by direct observations from boreholes or test pits but not necessarily by the relatively coarse survey geometries of the geophysical profiles, maximum ice content values observed in
the drill cores are generally higher. In addition, the 4PM cannot model super-saturated conditions (i.e. ice contents exceeding the assumed porosity), which further implies a bias towards underestimated maximum ice contents for the applied porosity ranges (cf. section 4.2.2). It is therefore not surprising, that the borehole-derived ice contents are mostly higher than the 4PM-derived values. Where quantitative ground truthing information is available, the 4PM can be calibrated by minimising the difference between the estimate and the ground truth, resulting in more consistent ice content values, as illustrated exemplarily

- 460 in Figure 13 for a profile with intermediate ice content (A02) and one with high ice content (A16b). Figure 13 further shows, that the porosity models of 60 or 80 % lead to more realistic ice content values than the lower-bound porosity model of 40 %. However, borehole validation provides highly valuable information on the point scale, but a direct comparison of borehole-and 4PM-derived ground ice contents remains challenging due to the different resolution capacities, dimensions (1-D vs. 2-D) and 4PM-related limitations. In the absence of such calibration data, ice content estimates of ice-rich permafrost layers may
- be underestimated (as a consequence of underestimated porosity ranges) and rather represent lower-bound estimates. This bias is, however, also a direct consequence of the spatially averaging ZOIs, which also include zones with higher spatial variability and therefore smaller ice contents. On the contrary, boreholes represent single-point information and are usually placed where the maximum ground ice content is assumed.



470 Figure 12: Comparison of borehole-derived with 4PM-derived min/max ice contents within the pre-defined ZOIs. Here, only borehole values for the depth range covered by the ZOIs are considered.







Figure 13: Comparison of ground truthing information from a drill core (black line) with 4PM-derived ground ice volumes at the borehole position of profiles A02 (A) and A16b (B). The blue lines correspond to 4PM runs based on homogeneous porosity models with 40, 60, and 80 % (as used for the ZOIs), and the orange line shows the 4PM result after calibration with ground truthing data.

5.2 Ice content of rock glaciers

Ground ice is present in the majority of all profiles, with ice contents ranging from a few percent by volume to clearly supersaturated conditions within various rock glaciers (Figure 3, Table 3). At sites with shallow sediment cover, small ice lenses are frequently present, which appear in the tomograms in the form of local resistive anomalies (cf. Table 3 and Fig. A2),

- 480 and could be validated through various test pits and natural outcrops. Based on the estimates drawn from the 4PM simulations (considering the 60 % and 80 % porosity models), the rock glaciers with resistivity maxima > 100 k Ω m (RG I) within our study areas show on average ground ice contents between 35 and 55 % by volume and thicknesses of the ice-rich layer of 3 to 25 m, but with a considerable spatial heterogeneity (cf. min/max estimates for the thickness of the ice-rich layer in Figure 11a, or the example in Figure 5). Our results further suggest, that the detected <u>maximum ice contents</u> within the ZOIs (35 - 75 %)
- 485 roughly correspond to the general assumption on average ice contents within active rock glaciers found in the literature (40 –





60 %, cf. Arenson and Springman, 2005; Barsch, 1996), which implies, however, that this assumption may tend to overestimate mean ground ice contents on a landform scale. Care has therefore to be taken regarding general up-scaling approaches for quantitative estimates of the total ground ice content within a rock glacier. Several studies of the hydrologic role of rock glaciers in the Andes used an estimate of 50 % volumetric ice content as mean value for rock glacier bodies (e.g., Brenning, 2005; Perucca and Angillieri, 2011; Rangecroft et al., 2015). This commonly used estimate is often justified by borehole core data from rock glaciers elsewhere (e.g., Haeberli et al., 1988; Mühll and Holub, 1992). However, boreholes are usually drilled at promising locations for massive ground ice occurrences and the recovery of undisturbed samples with high ice contents is easier than sampling ice-poor samples. Therefore, results from boreholes are often biased towards ice-rich conditions, hence, do not represent mean conditions for the entire landform. Estimates of volumetric ice content using a homogeneous value of

495 50 % can therefore easily lead to over-estimations.

In addition, published estimates of total ground ice volumes within rock glaciers have been based on simplified relations between the surface area and average rock glacier thickness (i.e. area-thickness relations introduced by Brenning, 2005). Figure 14 compares the area-thickness estimates according to the approach by Brenning (2005) with our geophysics-based estimates for the rock glaciers of our study. This comparison suggests that the thickness of the ice-rich permafrost layer as inferred from

500 geophysical data is in most cases considerably smaller than the one approximated from commonly applied area-thicknessrelations (cf. Azócar and Brenning, 2010; Janke et al., 2017; Rangecroft et al., 2015). Only for few of the very ice-rich landforms (e.g. E17 or A16b) the two approaches show comparable results. In addition, areal extents of rock glaciers are often not clear and very difficult to determine (Brardinoni et al., 2019; RGIK, 2020), especially in the case of complex landforms combining multiple rock glacier generations, resulting in a significant source of error when applying any rock glacier areatick.



505 thickness correlation.

Figure 14: Comparison of the minimum/maximum (black/grey) thickness of the ice-rich layer of rock glaciers (as in Figure 4) with the estimated rock glacier thickness according the area-thickness relation after Brenning 2005 (orange) for selected rock glaciers and protalus ramparts. Brennings approach has not been applied to A17 and B01, which are strongly degraded or relict rock glaciers. For E17, the area-thickness relation revealed a slightly smaller thickness (dashed orange line) than the geophysical maximum value. Black vertical lines illustrate the permafrost thickness revealed from borehole evidence, where available.



515



Although previous assumptions of ground ice content within rock glaciers (40 - 60 %, e.g., Brenning, 2005) roughly correspond to our field-based results, this is only true for their ice-rich zone. As rock glacier bodies also consist of zones with considerably smaller ice contents (cf. Fig. A1), large-scale model studies using the above-mentioned area-thickness relations will introduce a bias towards overestimation of total ice content with respect to total area. In the companion paper in part II, Mathys et al. (n.d.) propose a new upscaling approach of geophysically-based estimates of the ice volume per landform, which is compared

to standard approaches using area-thickness scaling and constant ground ice contents per rock glacier. Similar to our results presented in Figure 14 they find lower total ground ice volumes in rock glaciers when estimates are based on geophysical data in the field compared to simplified rock glacier – ice content relations.

520 5.3 Ice content of other landforms

In contrast to remote-sensing-based approaches, which can only delineate rock glaciers as indirect representations of permafrost bodies with unknown relevance for the hydrological cycle (Azócar and Brenning, 2010), the geophysically-based approach presented in this study is not restricted to rock glaciers, but allows the estimation of ground ice content in a variety of landforms that constitute the periglacial belt. Examples are given in sections 4.2 and 4.3. Neglecting landforms other than

- 525 rock glaciers in most studies is due to the invisibility of their ground ice content from space (and during site visits) and the corresponding difficulties in obtaining field data from remote areas. Rough approximations indicate that even thin ice-rich layers in permafrost slopes at high elevations (e.g. Figure 9) may add up to similar ice volumes per catchment as present in catchments in zones where individual rock glaciers are present and only a medium probability of permafrost exists. To investigate this hypothesis, we exemplarily upscaled the geophysics-based ice content estimates to the landform scale for
- 530 two sites, where ground truthing data is available. Based on geophysical results from six different profiles on a sediment slope (D03, D04, D05, D06, D07, D08), and three different profiles from a rock glacier (A01, A02, A03), the average thickness and ice content of the ice-rich layer of both landforms was approximated in terms of a lower-bound and an upper-bound estimate. Figure 15 shows the two landforms, the lower- and upper-bound estimates of the thickness of the ice-rich layer, as well as the estimated total ground ice volumes for the sediment slope and the rock glacier. The area of the rock glacier is approximately
- 535 0.11 km^2 , which is about ten times smaller than the considered area of the colluvial slope (~1 km²), but the rock glacier is expected to have a substantially thicker ice-rich layer of 10 - 15 m, compared to 0.5 - 1.5 m for the sediment slope. Assuming an average volumetric ice content of 50 % for the ice-rich layer at both sites leads to an approximated lower-bound estimate of the total ice volume of 250 000 m³ for the sediment slope and 550 000 m³ for the rock glacier. Considering the upper-bound estimate, i.e. the upper-bound average value for the thickness of the ice-rich layer (as opposed to its maximum within the
- 540 landform), estimated volumes range with 750 000 m³ for the sediment slope and 825 000 m³ for the rock glacier in the same order of magnitude. This indicates that even thin ice layers in sediment slopes can contain similar dimensions of ice volume per catchment as rock-glacier-dominated catchments. A more detailed analysis of this hypothesis using a newly developed upscaling approach is presented and discussed in the companion paper, part II (Mathys et al., n.d.).







b) Rock glacier Considered area (landform scale): 0.11 km²



1 k	m ²	area	0.11 km ²					
lower-bound estimate	upper-bound estimate		lower-bound estimate	upper-bound estimate				
~50 %	~50 %	mean ice content	~50 %	~50 %				
~0.5 m	~1.5 m	thickness ice-rich layer	~10 m	~15 m				
250.000 m ³	750.000 m ³	total ground ice volume	550.000 m ³	825.000 m ³				

545 Figure 15: Estimated total ice content of a) a colluvial slope area containing profiles D03 - D08 versus b) a rock glacier area (profiles A01 - A03).

6 Conclusion and Outlook

Based on more than 50 geophysical surveys from various regions in the Central Andes, this study demonstrates the value of geophysical surveys to a) detect ice-rich permafrost occurrences in various landforms (also beyond prominent forms such as
rock glaciers); and b) to estimate ground ice volumes in permafrost regions. The added value of combined ERT and RST surveys lies in an increased reliability of the interpretation (e.g., regarding the identification of bedrock), and the potential for ice content quantification through coupled petrophysical relationships such as within the 4-phase model.

The availability of various ground truthing data (cores from boreholes, test pits, natural outcrops) in this study allows the validation of the geophysical results for many cases. The good agreement between independent validation data and interpreted

- 555 geophysical profiles confirms the detection of ice-rich layers in various non-rock-glacier permafrost landforms, emphasizing the value of geophysical data in the scientific debate on the role of ice-rich permafrost in the hydrological cycle. Further, we observe a substantial intra- and inter-site heterogeneity of the thickness of the ice-rich layer(s) and ice volumes, which is often wrongly inferred from visual inspections alone. Geophysics-based estimates on ground ice content therefore allow for more accurate assessments than purely remote-sensing-based approaches without a solid data basis. The data set presented in this
- 560 paper is therefore one of the first available extensive set of field-based and validated data regarding the presence and total quantities of ground ice in the Central Andes.





The analysis of 52 ERT and 24 RST profiles within this study confirmed that ice-rich permafrost is not restricted to rock glaciers, but is also observed in non-rock-glacier permafrost slopes in the form of interstitial ice as well as layers with excess ice, resulting in substantial ice contents (e.g. D09, D04, C07), which can be close to the volumes observed in rock glaciers (D09). Consequently, non-rock glacier permafrost landforms, whose role for local hydrology has so far not been considered in remote-sensing based approaches, may, depending on the catchment size of the watershed, be similarly relevant in terms of ground ice content on a catchment scale and should not be ignored when quantifying the potential hydrological significance of permafrost.

- On the other hand, a realistic estimate of ground ice volume is only the first step towards the evaluation of the hydrological importance of permafrost within a catchment. Further factors, such as a) different response times of permafrost landforms to observed and projected atmospheric changes in the Central Andes, and b) the dominance of the relevant hydrological processes (e.g. melting vs. sublimation, and discharge vs. evaporation), play a decisive role in the annual contribution to total runoff to downstream water resources from degrading permafrost (or to evaporation and sublimation) (e.g., Rivera et al., 2017). According to Duguay et al. (2015) the contribution of degrading permafrost to the total runoff of a catchment is difficult to
- 575 measure, hence quantify, and therefore remains basically unknown. Without a reliable determination of these factors (e.g., by measuring or modelling the full energy balance over permafrost areas, cf. e.g., Harrington et al., 2018), the relevance of permafrost for the hydrological cycle remains strongly speculative. Preliminary modelling approaches suggest that this is negligible and would be non-measurable in the arid Andes (Arenson et al., 2013), and a recent analysis of mass-balance rates of ice masses in the Argentinian Central Andes confirms that rock glaciers showed almost zero mass balance rates from 2000
- 580 2018 (Ferri et al., 2020). However, no publications exist so far, that have specifically calculated the contribution of rock glaciers to streamflow in the semiarid Andes of Chile (Schaffer et al., 2019). Studies from other mountain environments (e.g., the European Alps, Marmy et al., 2016; Scherler et al., 2013) have shown that, depending on the snow cover and surface characteristics, the degradation of rock glaciers can be a very slow process because of the extremely efficient insulating effect of the active layer (coarse blocks) and the latent heat effect. Haeberli (1985) approximated the time needed for the complete
- 585 decay of ice-rich permafrost in rock glaciers under a warming climate to be in the order of centuries to millennia, and Krainer et al. (2015) showed that ~10.000 years old permafrost ice persisted until today even during warm periods of the Holocene. The quantitative contribution of melting ground ice of degrading permafrost in rock glaciers to the annual discharge from the catchment can therefore be very small (Harrington et al., 2018; Krainer et al., 2015; Pruessner et al., 2021) and the relative contributions from other ice-poor permafrost landforms without blocky surfaces and thin but widespread ground ice layers still
- 590 remain unknown. The geophysical data set presented in this study may therefore serve as input for modelling studies on the overall amount of ground ice present within the periglacial belt and estimates regarding the relative contributions of rock glacier and non-rock glacier ground ice to runoff in the semi-arid regions of the Central Andes.





Acknowledgements

The acquisition of this comprehensive data set would not have been possible without the valuable support and hard work of numerous field helpers from Chile, Argentina and Switzerland. Therefore, we sincerely thank all field helpers for their efforts in the field. The authors also would like to acknowledge the support from various private companies that agreed for having their data published, provided additional information, and logistically supported the various field campaigns.

Code/Data availability

600 The data that support the findings of this study are available from the corresponding author upon request and will be provided through an online data repository after acceptance of the manuscript.

Author contribution

CHi planned, coordinated and participated at the geophysical campaigns, processed the geophysical data, conducted the 4phase modelling, wrote the major part of the text, and made all figures. CHa had the overall lead of the geophysical campaigns,

605 and contributed to the study design. CM coordinated and participated at two of the geophysical field campaigns, and helped with data processing. PW and LA coordinated the environmental impact assessment studies, which included the geophysical campaigns, but also borehole drilling, excavation of test pits and collection of other data. They planned and coordinated the field logistics of the geophysical campaigns together with CHi, and provided further background information. All authors contributed actively to the discussion and interpretation of all data sets, and the intermediate and final version of the manuscript.

610 Competing interests

The authors declare that they have no conflict of interest.

7 References

Archie, G. E.: The Electrical Resistivity Log as an Aid in Determining Some Reservoir Characteristics., Pet. Trans. AIME, 146, 54–62 [online] Available from: http://www.sciepub.com/reference/194490 (Accessed 10 June 2021), 1942.

615 Arenson, L. U. and Jakob, M.: The significance of rock glaciers in the dry Andes - A discussion of Azócar and Brenning (2010) and Brenning and Azócar (2010), Permafr. Periglac. Process., 21(3), 282–285, doi:10.1002/ppp.693, 2010.

Arenson, L. U. and Springman, S. M.: Triaxial constant stress and constant strain rate tests on ice-rich permafrost samples,





Can. Geotech. J., 42(2), 412-430, doi:10.1139/t04-111, 2005.

Arenson, L. U., Pastore, S., Trombotto Liaudat, D., Bolling, S., Quiroz, M. A. and Ochoa, X. L.: Characteristics of two Rock

620 Glaciers in the Dry Argentinean Andes Based on Initial Surface Investigations, Geo 2010-Proceedings 62nd Can. Geotech. Conf., (1996), 1501–1508, 2010.

Arenson, L. U., Jakob, M. and Wainstein, P. A.: Hydrological contribution from degrading permafrost and rock glaciers in the northern Argentinian Andes, Mine Water Solut. Extrem. Environ., 171–181, 2013.

Azócar, G. F. and Brenning, A.: Hydrological and geomorphological significance of rock glaciers in the dry Andes, Chile (27°-33°s), Permafr. Periglac. Process., 21(1), 42–53, doi:10.1002/ppp.669, 2010.

Azócar, G. F., Brenning, A. and Bodin, X.: Permafrost distribution modelling in the semi-arid Chilean Andes, Cryosphere, 11(2), 877–890, doi:10.5194/tc-11-877-2017, 2017.

Barsch, D.: Rockglaciers, Springer Berlin Heidelberg, Berlin, Heidelberg., 1996.

Biskaborn, B. K., Smith, S. L., Noetzli, J., Matthes, H., Vieira, G., Streletskiy, D. A., Schoeneich, P., Romanovsky, V. E.,
Lewkowicz, A. G., Abramov, A., Allard, M., Boike, J., Cable, W. L., Christiansen, H. H., Delaloye, R., Diekmann, B.,
Drozdov, D., Etzelmüller, B., Grosse, G., Guglielmin, M., Ingeman-Nielsen, T., Isaksen, K., Ishikawa, M., Johansson, M.,
Johannsson, H., Joo, A., Kaverin, D., Kholodov, A., Konstantinov, P., Kröger, T., Lambiel, C., Lanckman, J. P., Luo, D.,
Malkova, G., Meiklejohn, I., Moskalenko, N., Oliva, M., Phillips, M., Ramos, M., Sannel, A. B. K., Sergeev, D., Seybold, C.,
Skryabin, P., Vasiliev, A., Wu, Q., Yoshikawa, K., Zheleznyak, M. and Lantuit, H.: Permafrost is warming at a global scale,
Nat. Commun., 10(1), 1–11, doi:10.1038/s41467-018-08240-4, 2019.

Bradley, R. S., Vuille, M., Diaz, H. F. and Vergara, W.: Threads to water supplies in the tropical Andes, , 312(June), 1755–1757, 2006.

Brardinoni, F., Scotti, R., Sailer, R. and Mair, V.: Evaluating sources of uncertainty and variability in rock glacier inventories, Earth Surf. Process. Landforms, 44(12), 2450–2466, doi:10.1002/esp.4674, 2019.

 640
 Brenning, A.: Climatic and geomorphological controls of rock glaciers in the Andes of Central Chile | Request PDF, Humboldt-Universität

 Universität
 zu
 Berlin.
 [online]
 Available
 from: https://www.researchgate.net/publication/279829240_Climatic_and_geomorphological_controls_of_rock_glaciers_in_the_A ndes_of_Central_Chile (Accessed 9 June 2021), 2005.

Brenning, A.: The Impact of Mining on Rock Glaciers and Glaciers, Darkening peaks glacier retreat, Sci. Soc., 196-205, 2008.

645 Croce, F. A. and Milana, J. P.: Internal structure and behaviour of a rock glacier in the arid Andes of Argentina, Permafr. Periglac. Process., 13(4), 289–299, doi:10.1002/ppp.431, 2002.

Day-Lewis, F. D., Singha, K. and Binley, A. M.: Applying petrophysical models to radar travel time and electrical resistivity



660



tomograms: Resolution-dependent limitations, J. Geophys. Res. Solid Earth, 110(8), 1–17, doi:10.1029/2004JB003569, 2005.

Duguay, M. A., Edmunds, A., Arenson, L. U. and Wainstein, P. A.: Quantifying the significance of the hydrological
 contribution of a rock glacier – A review, GEOQuébec 2015. 68th Can. Geotech. Conf. 7th Can. Permafr. Conf., (October),
 CD-Rom, 2015.

Duvillard, P. A., Revil, A., Qi, Y., Soueid Ahmed, A., Coperey, A. and Ravanel, L.: Three-Dimensional Electrical Conductivity and Induced Polarization Tomography of a Rock Glacier, J. Geophys. Res. Solid Earth, 123(11), 9528–9554, doi:10.1029/2018JB015965, 2018.

655 Etzelmüller, B., Guglielmin, M., Hauck, C., Hilbich, C., Hoelzle, M., Isaksen, K., Noetzli, J., Oliva, M. and Ramos, M.: Twenty years of European mountain permafrost dynamics-the PACE legacy, Environ. Res. Lett., 15(10), doi:10.1088/1748-9326/abae9d, 2020.

Ferri, L., Dussaillant, I., Zalazar, L., Masiokas, M. H., Ruiz, L., Pitte, P., Gargantini, H., Castro, M., Berthier, E. and Villalba, R.: Ice Mass Loss in the Central Andes of Argentina Between 2000 and 2018 Derived From a New Glacier Inventory and Satellite Stereo-Imagery, Front. Earth Sci., 8(December), doi:10.3389/feart.2020.530997, 2020.

García, A., Ulloa, C., Amigo, G., Milana, J. P. and Medina, C.: An inventory of cryospheric landforms in the arid diagonal of South America (high Central Andes, Atacama region, Chile), Quat. Int., 438, 4–19, doi:10.1016/j.quaint.2017.04.033, 2017.

Haeberli, W.: Creep of Mountain Permafrost: Internal Structure and Flow of Alpine Rock Glaciers., Mitteilungen der Versuchsanstalt fur Wasserbau, Hydrol. und Glaziologie an der Eidgenoss. Tech. Hochschule Zurich, (77), 1985.

665 Haeberli, W., Huder, J., Keusen, H., Pika, J. and Röthlisberger, H.: Core drilling through rock glacier permafrost, in Proceedings of the Fifth International Conference on Permafrost, pp. 937–944, Tapir Publishers, Trondheim. [online] Available from: https://www.researchgate.net/publication/245800726_Core_drilling_through_rock_glacier_permafrost (Accessed 11 June 2021), 1988.

Halla, C., Henrik Blöthe, J., Tapia Baldis, C., Trombotto Liaudat, D., Hilbich, C., Hauck, C. and Schrott, L.: Ice content and
interannual water storage changes of an active rock glacier in the dry Andes of Argentina, Cryosphere, 15(2), 1187–1213,
doi:10.5194/tc-15-1187-2021, 2021.

Harrington, J. S., Mozil, A., Hayashi, M. and Bentley, L. R.: Groundwater flow and storage processes in an inactive rock glacier, Hydrol. Process., 32(20), 3070–3088, doi:10.1002/hyp.13248, 2018.

Hauck, C. and Kneisel, C.: Applied geophysics in periglacial environments, Cambridge University Press., 2008.

675 Hauck, C., Vieira, G., Gruber, S., Blanco, J. and Ramos, M.: Geophysical identification of permafrost in Livingston Island, Maritime Antarctica, J. Geophys. Res. Earth Surf., 112(2), doi:10.1029/2006JF000544, 2007.

Hauck, C., Böttcher, M. and Maurer, H.: A new model for estimating subsurface ice content based on combined electrical and





seismic data sets, Cryosphere, 5(2), 453–468, doi:10.5194/tc-5-453-2011, 2011.

Hauck, C., Hilbich, C. and Mollaret, C.: Geophysical Surveys Alturas, Chile, 2017, Fribourg., 2017.

Hausmann, H., Krainer, K., Brückl, E. and Mostler, W.: Internal structure and ice content of Reichenkar rock glacier (Stubai Alps, Austria) assessed by geophysical investigations, Permafr. Periglac. Process., 18(4), 351–367, doi:10.1002/ppp.601, 2007.

Hedding, D. W.: Pronival rampart and protalus rampart: A review of terminology, J. Glaciol., 57(206), 1179–1180, doi:10.3189/002214311798843241, 2011.

685 Hilbich, C. and Hauck, C.: Geophysical Surveys in Filo Del Sol, Fribourg., 2018a.

Hilbich, C. and Hauck, C.: Geophysical Surveys on Barriales Rock Glacier, Argentina, Fribourg., 2018b.

Hilbich, C. and Hauck, C.: Geophysical Surveys in Josemaria, Argentina, Fribourg., 2019.

Hilbich, C., Hauck, C., Hoelzle, M., Scherler, M., Schudel, L., Völksch, I., Vonder Mühll, D. and Mäusbacher, R.: Monitoring mountain permafrost evolution using electrical resistivity tomography: A 7-year study of seasonal, annual, and long-term variations at Schilthorn, Swiss Alps, J. Geophys. Res. Earth Surf., 113(1), 1–12, doi:10.1029/2007JF000799, 2008.

Hilbich, C., Marescot, L., Hauck, C., Loke, M. H. and Mäusbacher, R.: Applicability of electrical resistivity tomography monitoring to coarse blocky and ice-rich permafrost landforms, Permafr. Periglac. Process., 20(3), 269–284, doi:10.1002/ppp.652, 2009.

Hilbich, C., Mollaret, C. and Hauck, C.: Geophysical Surveys Mineras Los Pelambres (2016) and Rio Blanco (2017), Chile, 695 Fribourg., 2018.

Hock, R., Rasul, G., Adler, C., Cáceres, B., Gruber, S., Hirabayashi, Y., Jackson, M., Kääb, A., Kang, S., Kutuzov, S., Milner, A., Molau, U., Morin, S., Orlove, B. and Steltzer, H. I.: Chapter 2: High Mountain Areas. IPCC Special Report on the Ocean and Cryosphere in a Changing Climate, IPCC Spec. Rep. Ocean Cryosph. a Chang. Clim., 131–202, 2019.

Janke, J. R., Ng, S. and Bellisario, A.: An inventory and estimate of water stored in firn fields, glaciers, debris-covered glaciers, and rock glaciers in the Aconcagua River Basin, Chile, Geomorphology, 296, 142–152, doi:10.1016/j.geomorph.2017.09.002, 2017.

Jones, D. B., Harrison, S., Anderson, K. and Betts, R. A.: Mountain rock glaciers contain globally significant water stores, Sci. Rep., 8(1), 1–10, doi:10.1038/s41598-018-21244-w, 2018a.

Jones, D. B., Harrison, S., Anderson, K., Selley, H. L., Wood, J. L. and Betts, R. A.: The distribution and hydrological significance of rock glaciers in the Nepalese Himalaya, Glob. Planet. Change, 160(November 2017), 123–142, doi:10.1016/j.gloplacha.2017.11.005, 2018b.





Jones, D. B., Harrison, S., Anderson, K. and Whalley, W. B.: Rock glaciers and mountain hydrology: A review, Earth-Science Rev., 193(April), 66–90, doi:10.1016/j.earscirev.2019.04.001, 2019.

Kneisel, C., Hauck, C., Fortier, R. and Moorman, B.: Advances in geophysical methods for permafrost investigations, Permafr.
Periglac. Process., 19(2), 157–178, doi:10.1002/ppp.616, 2008.

Krainer, K., Bressan, D., Dietre, B., Haas, J. N., Hajdas, I., Lang, K., Mair, V., Nickus, U., Reidl, D., Thies, H. and Tonidandel, D.: A 10,300-year-old permafrost core from the active rock glacier Lazaun, southern Ötztal Alps (South Tyrol, northern Italy), Quat. Res. (United States), 83(2), 324–335, doi:10.1016/j.yqres.2014.12.005, 2015.

Loke, M. H.: RES2DINVx64 ver. 4.10.3 Rapid 2-D Resistivity and IP inversion using the least squares method, 2020.

715 Marmy, A., Rajczak, J., Delaloye, R., Hilbich, C., Hoelzle, M., Kotlarski, S., Lambiel, C., Noetzli, J., Phillips, M., Salzmann, N., Staub, B. and Hauck, C.: Semi-automated calibration method for modelling of mountain permafrost evolution in Switzerland, Cryosphere, 10(6), 2693–2719, doi:10.5194/tc-10-2693-2016, 2016.

Masiokas, M. H., Rabatel, A., Rivera, A., Ruiz, L., Pitte, P., Ceballos, J. L., Barcaza, G., Soruco, A., Bown, F., Berthier, E., Dussaillant, I. and MacDonell, S.: A Review of the Current State and Recent Changes of the Andean Cryosphere, Front. Earth Sci., 8, 99, doi:10.3389/feart.2020.00099, 2020.

Mathys, T., Hilbich, C., Arenson, L. U., Wainstein, P. A. and Hauck, C.: Towards accurate quantification of ice content in permafrost of theCentral Andes - Part II: an upscaling strategy of geophysicalmeasurements to the catchment scale at two study sites, n.d.

Mewes, B., Hilbich, C., Delaloye, R. and Hauck, C.: Resolution capacity of geophysical monitoring regarding permafrost degradation induced by hydrological processes, Cryosphere, 11(6), 2957–2974, doi:10.5194/tc-11-2957-2017, 2017.

Mollaret, C., Hilbich, C., Pellet, C., Flores-Orozco, A., Delaloye, R. and Hauck, C.: Mountain permafrost degradation documented through a network of permanent electrical resistivity tomography sites, Cryosphere, 13(10), 2557–2578, doi:10.5194/tc-13-2557-2019, 2019.

Mollaret, C., Wagner, F. M., Hilbich, C., Scapozza, C. and Hauck, C.: Petrophysical Joint Inversion Applied to Alpine
Permafrost Field Sites to Image Subsurface Ice, Water, Air, and Rock Contents, Front. Earth Sci., 8(April), doi:10.3389/feart.2020.00085, 2020.

Monnier, S. and Kinnard, C.: Internal structure and composition of a rock glacier in the Andes (upper Choapa valley, Chile) using borehole information and ground-penetrating radar, Ann. Glaciol., 54(64), 61–72, doi:10.3189/2013AoG64A107, 2013.

Mühll, D. S. V. and Holub, P.: Borehole logging in alpine permafrost, upper Engadin, Swiss Alps, Permafr. Periglac. Process., 3(2), 125–132, doi:10.1002/ppp.3430030209, 1992.

Muller, S. W., French, H. M. and Nelson, F. E.: Frozen in time: Permafrost and engineering problems, American Society of



745

750

755



Civil Engineers (ASCE)., 2008.

Noetzli, J., Pellet, C. and Staub, B.: Permafrost in Switzerland 2014/2015 to 2017/2018. Glaciological Report (Permafrost) No. 16–19 of the Cryospheric Commission of the Swiss Academy of Sciences., 2019.

740 Obu, J.: How Much of the Earth's Surface is Underlain by Permafrost?, J. Geophys. Res. Earth Surf., 126(5), doi:10.1029/2021jf006123, 2021.

Obu, J., Westermann, S., Bartsch, A., Berdnikov, N., Christiansen, H. H., Dashtseren, A., Delaloye, R., Elberling, B., Etzelmüller, B., Kholodov, A., Khomutov, A., Kääb, A., Leibman, M. O., Lewkowicz, A. G., Panda, S. K., Romanovsky, V., Way, R. G., Westergaard-Nielsen, A., Wu, T., Yamkhin, J. and Zou, D.: Northern Hemisphere permafrost map based on TTOP

Oldenborger, G. A. and LeBlanc, A. M.: Monitoring changes in unfrozen water content with electrical resistivity surveys in cold continuous permafrost, Geophys. J. Int., 215(2), 965–977, doi:10.1093/GJI/GGY321, 2018.

modelling for 2000–2016 at 1 km2 scale, Earth-Science Rev., 193, 299–316, doi:10.1016/j.earscirev.2019.04.023, 2019.

de Pasquale, G., Valois, R., Schaffer, N. and MacDonell, S.: Active and inactive Andean rock glacier geophysical signatures by comparing 2D joint inversion routines of electrical resistivity and refraction seismic tomography, Cryosph. Discuss., (November), 1–33, doi:10.5194/tc-2020-306, 2020.

Pellet, C., Hilbich, C., Marmy, A. and Hauck, C.: Soil moisture data for the validation of permafrost models using direct and indirect measurement approaches at three alpine sites, Front. Earth Sci., 3, doi:10.3389/feart.2015.00091, 2016.

Perucca, L. and Angillieri, M. Y. E.: Glaciers and rock glaciers' distribution at 28° SL, Dry Andes of Argentina, and some considerations about their hydrological significance, Environ. Earth Sci., 64(8), 2079–2089, doi:10.1007/s12665-011-1030-z, 2011.

Pruessner, L., Huss, M., Phillips, M. and Farinotti, D.: A Framework for Modeling Rock Glaciers and Permafrost at the Basin-Scale in High Alpine Catchments, J. Adv. Model. Earth Syst., 13(4), doi:10.1029/2020ms002361, 2021.

Rangecroft, S., Harrison, S., Anderson, K., Magrath, J., Castel, A. P. and Pacheco, P.: A first rock glacier inventory for the Bolivian Andes, Permafr. Periglac. Process., 25(4), 333–343, doi:10.1002/ppp.1816, 2014.

760 Rangecroft, S., Harrison, S. and Anderson, K.: Rock glaciers as water stores in the Bolivian Andes: An assessment of their hydrological importance, Arctic, Antarct. Alp. Res., 47(1), 89–98, doi:10.1657/AAAR0014-029, 2015.

RGIK: Towards standard guidelines for inventorying rock glaciers: baseline concepts (v. 4.1), edited by R. Delaloye and T. Echelard. [online] Available from: https://www3.unifr.ch/geo/geomorphology/en/research/ipa-action-group-rock-glacier (Accessed 11 June 2021), 2020.

765 Rivera, J. A., Penalba, O. C., Villalba, R. and Araneo, D. C.: Spatio-temporal patterns of the 2010-2015 extreme hydrological drought across the Central Andes, Argentina, Water (Switzerland), 9(9), doi:10.3390/w9090652, 2017.





Rücker, C., Günther, T. and Wagner, F. M.: pyGIMLi: An open-source library for modelling and inversion in geophysics, Comput. Geosci., 109(July), 106–123, doi:10.1016/j.cageo.2017.07.011, 2017.

Sandmeier, K.-J.: REFLEXW Version 9.1.3. Windows[™] XP/7/8/10-program for the processing of seismic, acoustic or electromagnetic reflection, refraction and transmission data, 2020.

Schaffer, N., MacDonell, S., Réveillet, M., Yáñez, E. and Valois, R.: Rock glaciers as a water resource in a changing climate in the semiarid Chilean Andes, Reg. Environ. Chang., 19(5), 1263–1279, doi:10.1007/s10113-018-01459-3, 2019.

Scherler, M., Hauck, C., Hoelzle, M. and Salzmann, N.: Modeled sensitivity of two alpine permafrost sites to RCM-based climate scenarios, J. Geophys. Res. Earth Surf., 118(2), 780–794, doi:10.1002/jgrf.20069, 2013.

575 Schneider, S., Daengeli, S., Hauck, C. and Hoelzle, M.: A spatial and temporal analysis of different periglacial materials by using geoelectrical, seismic and borehole temperature data at murtel-corvatsch, upper engadin, swiss alps, Geogr. Helv., 68(4), 265–280, doi:10.5194/gh-68-265-2013, 2013.

Timur, A.: Velocity of Compressional Waves in Porous Media At Permafrost Temperatures, Geophysics, 33(4), 584–595, doi:10.1190/1.1439954, 1968.

780 Villarroel, C. D., Beliveau, G. T., Forte, A. P., Monserrat, O. and Morvillo, M.: DInSAR for a regional inventory of active rock glaciers in the Dry Andes Mountains of Argentina and Chile with sentinel-1 data, Remote Sens., 10(10), doi:10.3390/rs10101588, 2018.

Wagner, F. M., Mollaret, C., Günther, T., Kemna, A. and Hauck, C.: Quantitative imaging of water, ice and air in permafrost systems through petrophysical joint inversion of seismic refraction and electrical resistivity data, Geophys. J. Int., 219(3), 1866–1875, doi:10.1093/gji/ggz402, 2019.





790 Appendix:

Table A1: Overview about the data quality of the geophysical data. Abbreviations: n = number of quadrupoles, $n_{filtered} =$ remaining quadrupoles after filtering, RMS = root mean square error.

		ERT		RST
Profile	n	n_filtered (%)	RMS [%]	RMS [ms]
A01	360	92	7.7	2.9
A02	1188	81	9.6	2.6
A03	360	89	6.0	2.5
A04	360	85	7.9	
A05	636	100	1.8	2.7
A06	636	91	3.6	2.6
A07	360	99	7.0	1.7
80A	912	96	3.0	1.7
A09	360	99	2.6	2.0
A15	360	100	9.0	
A16a	360	100	2.4	1.9
A16b	360	100	9.8	1.8
A17	912	100	4.0	
A24	636	95	2.1	
A25	360	100	2.3	1.4
B01	636	100	4.0	2.3
BO2	636	100	2.5	2.5
B03	912	100	5.8	
C02	636	100	4.3	1.2
	000		4.3	1.0
C03	360	100	6.7	
C04	360	100	1.3	
C06	360	100	4.1	
C07	912	100	3.0	1.2
C08	360	100	3.2	
C09	360	100	1.2	
C10	360	100	1.5	
D01	360	100	1.3	
D02	636	100	1.1	
D03	360	100	2.5	
D04	360	100	6.1	1.3
D05	912	100	2.3	
D06	636	100	2.3	
D06b	360	99	2.0	
D07	1740	99	2.4	
D08	912	99	4.6	
D09	360	99	2.8	1.1
F10	360	99	2.9	1.6
E03_A	360	81	5.9	
E03_BV E03_BH	636 360	100 100	2.7	
E05_BH	636	99	3.8	
E04 E05	360	100	2.2	
E08	912	99	5.0	2.0
E09	360	94	6.6	2.0
E11 H	360	100	2.5	2.1
E11_D	360	100	2.8	
E12	360	100	3.4	
E13	360	100	2.2	
E14	360	97	1.6	
E15	360	100	2.1	
E16	636	97	4.8	
E17	360	72	22.1	
	000	16	<u></u>	





A) Rock Glaciers I - resistivity maxima > 100 kΩm COARSE-BLOCKY SITES A02 | abs. error 9.6 % A01 | abs. error 7.7 % Ωm -10 -50 100000 50 0 100 depth [m] -100 A03 | abs. error 6.0 % 0 -10 -20 10000 50 150 100 1000 -150 A09 abs. error 2.6 % -10 100 50 100 150 200 250 300 350 400 450 500 550 0 100 B03 | abs. error 5.8 % 50 B02 | abs. error 2.5 % 3880-10 3820-A07 | abs. error 7.0 % 3860-E 3800 Ξ 3780 -3840 depth 3820 50 150 200 0 200 250 200 50 100 50 100 150 50 100 150 A04 | abs. error 7.9 % A08 | abs. error 3.0 % 0 A16b | abs. error 9.8 % -20 -20 depth [m] -40 -20 -40 -60 -40 -60 -80 -60 50 100 150 200 100 150 0 50 100 150 200 250 300 350 0 50 distance [m] distance [m] distance [m]

795 Figure A1: inverted tomograms of all ERT profiles from coarse-blocky sites (same spatial and colour scales), sorted by landforms

B) Rock Glaciers II - resistivity maxima < 100 kΩm









Figure A2: inverted tomograms of all ERT profiles from sediment and bedrock sites (same spatial and colour scales), sorted by landforms



B) Gelifluction Slopes

4620

E 4600

4580

4560-







-20





800 A3: inverted tomograms of all RST profiles from coarse-blocky sites (same scales and colour scales), sorted by landforms

41

-80





A4: inverted tomograms of all RST profiles from sediment and bedrock sites (same scales and colour scales), sorted by landforms



