

The effects of surface roughness on the calculated, spectral (300 – 1400 nm), conical-conical reflectance factor (CCRF) as an alternative to bidirectional reflectance distribution function (BRDF) of bare sea ice

Maxim L. Lamare¹, John D. Hedley², and Martin D. King¹

¹Department of Earth Sciences, Royal Holloway University of London, Egham, Surrey, TW20 0EX, UK

²Numerical Optics Ltd, Witheridge, Tiverton, Devon, EX16 8AA, UK

Correspondence: M.D. King (m.king@rhul.ac.uk)

Abstract. The Conical-Conical Reflectance Factor (CCRF) has been calculated, as an alternative to, the Bidirectional Reflectance Distribution Function (BRDF)~~has been calculated~~, for three types of bare sea ice with varying surface roughness ($\sigma = 0.1\text{--}10\text{m}$) and ice thicknesses (50–2000 cm) over an incident solar irradiance wavelength range of 300–1400 nm. The comprehensive study of the BRDF-CCRF of sea ice presented here is paramount for interpreting sea ice measurements from satellite imagery and inter-calibrating spaceborne-space-borne sensors that derive albedo from multiple multi-angular measurements. The calculations performed by a radiative-transfer-radiative-transfer code (PlanarRad) show that the BRDF-CCRF of sea ice is sensitive to realistic values of surface roughness. The results presented here show that surface roughness cannot be considered independently of sea ice thickness, solar zenith angle and wavelength. A typical BRDF-CCRF of sea ice has a quasi-isotropic reflectance over the hemisphere, associated with a strong forward scattering peak of lightphotons. Surface roughness is crucial for the location, size and intensity of the forward scattering peak. As the surface roughness increases, a spreading of the BRF-CCRF peak is observed. The hemisphere was split in to 216 quadrangular regions or quads. The peak remains specular for the smaller surface roughnesses ($\sigma = 0.001\text{ m}$ to $\sigma = 0.01\text{ m}$), whereas for larger surface roughness features (above $\sigma = 0.05\text{m}$), the peak spreads out over multiple quads with a lower intensity than for smaller roughness features, and the highest value is displaced further out on the solar principal plane. Different types of sea ice have a similar pattern with wavelength, the BRF increases by 29.5% CCRF increases by 30% from first-year sea ice to multi-year sea ice at 400 nm and up to 630.7631% at 1100 nm, 31.532% from melting sea ice to multi-year sea ice at 400 nm and a maximum of 97.798% at 900 nm, and 11.311% from melting sea ice to first-year sea ice at 400 nm and up to 86.286% at 800 nm. As a specific example, for first-year sea ice at $\lambda = 500\text{ nm}$ and $\theta_r = 60^\circ$, the BRF of an optically thick layer with surface roughness of $\sigma = 0.001\text{ m}$ is 0.543 at nadir. The forward scattering peak is spread over a single quad located at $\phi_r = 0^\circ$, $\theta_r = 60^\circ$, that has a BRF of 9.748. For the same configuration with surface roughness of $\sigma = 0.1\text{ m}$, the nadir has a BRF of 0.549 and the forward scattering peak is spread over 18 quads, located between $\phi_r = 345^\circ$ and $\phi_r = 15^\circ$, $\theta_r = 40^\circ$ and $\theta_r = 87.5^\circ$ with values between 0.776 and 5.089. The BRDF The CCRF calculations presented in this study form the first set of complete BRDF values-CCRF values as an approximation of the BRDF for bare sea ice with a wide range of configurations.

1 Introduction

25 Knowledge of the surface albedo of sea ice and its temporal variability is essential to understand the energy budget of polar regions, that strongly affects the Earth's climate system (e.g. Curry et al., 1995; Qu and Hall, 2005; Flanner et al., 2011). Sensors aboard Earth Observing satellites allow the synoptic observation of expansive areas with regular repeat coverage, providing an ideal tool for the monitoring of albedo at high latitudes (e.g. Bacour et al., 2020; Qu et al., 2015). However, the scattering of light-solar photons from the surface of sea ice is not isotropic (e.g. Buckley and Trodahl, 1987) and therefore calculations

30 of spectral albedo rely on the knowledge of viewing and illumination angles. Most satellite sensors are only able to measure reflected energy over a small number of viewing angles and spectral bands. Indeed, only a limited number of satellite systems currently provide near-simultaneous multi-angular measurements (Gatebe and King, 2016) and satellite sensors commonly used to derive surface albedo such as MODIS (Moderate Resolution Imaging Spectroradiometer), are constrained to collecting multi-angular measurements over several orbits. Therefore, knowledge of the angular distribution of the reflected radiation of

35 sea ice is necessary to accurately derive surface albedo and provide climate models ~~rwith-with~~ reliable inputs. The Bidirectional ~~Reflectance Distribution Function~~ reflectance Distribution Functions (BRDF) is a ~~directional description of albedo, describing the relationship between illumination and viewing angles (Nicodemus et al., 1977). Previous studies have characterised BRDF of snow, either with field measurements of the Hemispherical Directional Reflectance Function (HDRF) as an approximation of BRDF(e.g. Middleton and Mungall, 1952; Dirmhirn and Eaton, 1975; Dozier et al., 1988; Bourgeois et al., 2006; Malinka et al., 2016)~~

40 ~~, focussing on roughness(e.g. Manninen, 1997), polarization(e.g. Leroux et al., 1998; Peltoniemi et al., 2005a, 2009), physical properties like grain size and sastrugi(e.g. Aoki et al., 2000; Stanton et al., 2016; Kuchiki et al., 2011; Sun and Zhao, 2011), wavelength(e.g. , impurities(e.g. Peltoniemi et al., 2015), fine angular resolution(e.g. Goyens et al., 2018) or specific places like Antarctica(e.g. Hudson et al., , Arctic(e.g. Ball et al., 2015; Hakala et al., 2014), glacial(e.g. Joerg et al., 2015)or specifically snow on sea sea ice(e.g. Heygster et al., 2017)~~. There have also been studies modelling BRDF or the Bidirectional Reflection Function (BRF) as an derivative distribution

45 function that maps its contribution of incident irradiance from a direction to the reflected radiance in another direction (Nicodemus et al., 1977). Strictly the quantity, BRDF, cannot be measured and often other directional reflectance measurements are undertaken as an alternative or approximation of BRDF (e.g. Leroux et al., 1999; Mishchenko et al., 1999; Dumont et al., 2010; Heygst

50 ~~. The BRDF of glacial ice has been reported by (e.g. Ren et al., 2021) and lake ice by (e.g. Miao et al., 2020). BRDF models of snow are found concentrating on mountain snow (e.g. Dozier and Painter, 2004; Painter et al., 2013; Wang et al., 2017), snow kernals(e.g. Ding et al., 2019b, a; Jiao et al., 2019; Qu et al., 2016c), snow grain size(e.g. Zege et al., 2011), polarization(e.g. Yang et al., 2 , sastrugi(e.g. Corbett and Su, 2015), remote sensing(e.g. Pope et al., 2016; Wu et al., 2012, 2011; Jin and Simpson, 2001) and models (e.g. Kokhanovsky and Breon, 2012a; Hudson et al., 2010). BRDF models also exists (Schaepman-Strub et al., 2006). There is a large of terms in the literature for quantities that are measurable alternatives to BRDF that may not have been used uniformly and will be described herein as directional reflectance. Directional reflectance models exist for seaice (e.g. Qu et al.,~~

55 2016b; Mishchenko et al., 1999)~~The effect of light absorbing impurities on HDRF (e.g. Khan et al., 2017; Li and Zhou, 2002) and angular reflectivity of snow(e.g. Lv et al., 2018) have also been reported. The BRDF. The directional reflectance~~ of snow covered sea ice has also been measured or modelled (e.g. Arnold et al., 2002; Li and Zhou, 2004b), but the characterisation

of the BRDF-directional reflectance of bare sea ice in the literature remains scarce. Jin and Simpson (1999) calculated the Anisotropy Reflectance Factor (ARF) for bare sea ice. The ARF is equivalent to the ratio of the isotropic-isotropic albedo to measured albedo and is a measure of the similarity (or not) to an isotropic reflected radiation field (Jin and Simpson, 1999). Jin and Simpson (1999) showed that sea ice has a larger reflectance anisotropy in the forward observation direction and presents a high-sensitivity-is sensitive to solar elevation and surface roughness. However the study was limited to 2 spectral bands at 580–680 nm and 725–1000 nm and a single type of multi-year sea ice with parameters obtained from Weeks and Ackley (1994). Schlosser (1988) measured the angular reflected radiance of laboratory grown sea ice for varying ice thicknesses between 6 mm and 11 cm, showing a strong dependance-of-BRDF-dependence of directional reflectance on ice thickness and structure. Arnold et al. (2002) and Gatebe and King (2016) described airborne BRDF-directional reflectance measurements acquired for a variety of natural surfaces over 13 wavelength bands from 502 nm to 2289 nm, including polar snow and sea ice. The BRDF-directional reflection of snow-covered sea ice, melt-season sea ice and snow-covered tundra were reported for a limited number of solar zenith angles, showing quasi-isotropic reflectance outside an enhanced forward scattering peak. Stamnes et al. (2011) modelled the BRDF-directional reflection of snow covered and bare sea ice, using a coupled atmosphere-snow-ice-ocean radiative-transfer model. Using sea ice inherent optical properties (IOPs), Stamnes et al. (2011) computed the BRDF-directional reflectance for a range of sea ice types between the wavelengths of 300 and 4000 nm. The theoretical computations relied on a smooth interface between the media however, and to represent surface roughness, the authors used a fixed 10° Gaussian beam, that did not take in account varying surface roughness effects which have been shown to significantly affect BRDF (Jin and Simpson, 1999)-directional reflectance (Jin and Simpson, 1999). Owing to its complex nature, the optical and physical properties of sea ice vary spatially and temporally, altering the solar radiation reflected from the surface (Perovich, 1996). Previous studies have demonstrated a strong dependence of albedo on the type of sea ice (e.g. Perovich et al., 2002; Marks et al., 2015). Light-reflection-Reflection and transmission are sensitive to changes in the thickness of the sea ice (Perovich, 1996), and surface roughness has been shown to significantly affect the angular pattern of reflectance at larger viewing angles for snow (Warren et al., 1998; Ball et al., 2015) and sea ice (Jin and Simpson, 1999). Yet, to the authors' knowledge, no-modelling studies comprehensively characterising the-BRDF-of bare sea ice have been carried out previously. Thus, a systematic study of the dependance-of-the-BRDF-dependence of the directional reflectance of multiple types of bare sea ice to changing surface roughness conditions and varying thickness is requireduseful.

In this work, the radiative-transfer model PlanarRad (Hedley, 2008, 2015) was used to model the BRDF-CCRF (conical-conical reflectance factor) of three different types of sea ice from 300 to 1400 nm with varying thicknesses as a function of surface roughness in two steps. Firstly, the BRDF of three different types of sea ice with a thickness large enough to be optically thick was modelled with an increasing surface roughness. Secondly, the calculations performed in the first step were repeated, but the optically thick thicknesses were replaced with fixed thicknesses of 50 cm and 100 cm for each type of sea ice. The optical properties of the three types of bare sea ice are chosen to represent multiyear sea ice, first year sea ice and melting sea ice and will be described in detail in the methodology .

2 Methods

2.1 Definitions

BRDF is commonly used to represent the reflective properties of a surface by describing the angular distribution of the scattering of light incident radiation from the surface (Nicodemus et al., 1977). The spectral BRDF describes the relationship
95 between the irradiance incident from a given direction relative to its contribution to the reflected radiance in another direction (Nicodemus et al., 1977), which can be expressed mathematically by:

$$BRDF(\lambda) = f_{r}(\theta_i, \phi_i; \theta_r, \phi_r; \lambda) = \frac{dL_r(\theta_i, \phi_i; \theta_r, \phi_r; \lambda)}{dE_i(\theta_i, \phi_i; \lambda)}, \quad (1)$$

where θ and ϕ are the zenith and azimuth angles respectively in a spherical coordinate system, λ is the wavelength of light
radiation, L is radiance, E is irradiance, i refers to incident directions and r to reflected directions (Nicodemus et al., 1977;
100 Schaepman-Strub et al., 2006). The angles used to define BRDF are shown in Figure A1a. BRDF requires the irradiance to be in the form of a collimated beam and the radiance to be measured with an infinitesimal solid angle. Thus, BRDF cannot be measured directly (Schaepman-Strub et al., 2006). In order to facilitate comparison with the literature and field studies, the BRDF computed in this study was may be converted to the unitless Bidirectional Reflectance Factor (BRF). BRF is defined by the ratio of the reflected radiant flux, $d\Phi_r$ from a surface area to the reflected radiant flux, $d\Phi_r^{lamb}$ from an idea-ideal Lambertian
105 reflector under identical viewing angles and single direction illumination (Schaepman-Strub et al., 2006). Therefore, BRF is expressed as:

$$BRF(\lambda) = \frac{d\Phi_r(\theta_i, \phi_i; \theta_r, \phi_r; \lambda)}{d\Phi_r^{lamb}(\theta_i, \phi_i; \lambda)} = \pi BRDF(\lambda) \quad (2)$$

The BRDF of an ideal Lambertian reflector is $\frac{1}{\pi}$ (Nicodemus et al., 1977; Schaepman-Strub et al., 2006). Hence, the BRDF
calculated by PlanarRad a BRDF may be converted to BRF by multiplying by π .

110 2.2 Model description

The calculations of the BRDF-CCRF, as an alternative to BRDF, of sea ice were performed using PlanarRad (Hedley, 2015), a radiative-transfer model that computes the radiance distributions and derived quantities for homogeneous scattering and absorbing media (Hedley, 2008). The model is an open-source implementation of the invariant imbedded numerical integration technique for radiative-transfer, based on the algorithm described by Mobley (1994). PlanarRad has previously been used for
115 reflectance computations in marine environments (Lim et al., 2009; Hedley et al., 2012) and is functionally similar to the commercial software Hydrolight (Mobley, 1989).

In PlanarRad, radiance is calculated as the average radiance over finite solid angles, defined by a discretisation of the surface of a sphere divided into two hemispheres (Figure A1b). The lower hemisphere corresponds to the upwelling radiance (exiting the surface), whereas the upper hemisphere corresponds to the downwelling direct sky radiance. The discretisation is determined
120 by bounding lines of constant zenith (θ) and azimuth (ϕ) angle, forming quadrangular regions, commonly called "quads". The two hemispheres are divided into 9 by 24 segments each, forming a total of 432 quads over the whole sphere. The directionally

averaged radiance is computed by PlanarRad within each quad. The input irradiance is set to a single quad with a fixed azimuth, ϕ_i and a variable zenith, θ_i , the model being rotationally invariant. Radiance is constant over the solid angle subtended by each segment of the angular discretisation, both for upwelling and downwelling radiation and the directional reflectance is evaluated as conical-conical or biconical (geometry equivalent to case 5 in Table 2 of Schaepman-Strub et al. (2006)). For the rough surface constructed from randomly oriented surfaces used in this study, only the relative azimuth angle between ϕ_i and ϕ_r is required. The incident irradiance was fixed at a constant value for the purpose of this study. The azimuth angles corresponding to the quad centres are located every 15° from $\phi = 0^\circ$ to $\phi = 345^\circ$ and the zenith angles corresponding to the quad centres are located at $\theta = 0, 10, 20, 30, 40, 50, 60, 70, 80$ and 87.5° . Out of convention, the incident azimuth angle, ϕ_i was set to 180° , the quarter-sphere from 270 to 90° azimuth representing the forward scattering of light photons and the quarter-sphere from 90 to 270° azimuth representing the backward scattering. Thus, the solar principal plane is defined as $\phi = 180-0^\circ$. Figure A2 shows a typical 2D polar plot of a PlanarRad output for optically thick (as described in Sect. 2.3) first-year sea ice, with a solar zenith angle, $\theta_i = 60^\circ$ and a roughness parameter of $\sigma = 0.01$ m (described below).

The absorption coefficient, a , attenuation coefficient, α , scattering phase function, complex refractive index of sea ice, complex refractive index outside the sea ice, surface roughness and thickness of the sea ice were used in the radiative-transfer calculations. The parameters are presented in Sect. 2.3. The calculations presented here assume that no atmosphere is present and that the sea ice is floating on an optically thick body of sea water that has a wavelength independent diffuse reflectance of 0.1.

A roughness parameter effecting the statistical distribution of surface slope was implemented in a similar way to that described in Mobley (1994). The roughness parameter, σ , describes the standard deviation of the height relative to the horizontal distance, and is therefore unitless. For example, if $\sigma = 1$, the slope between points located 1 mm apart has a $\sigma = 0.5$, two points located 2 mm apart would have their heights drawn from a normal distribution of mean zero and standard deviation of 1 mm. As the system is considered spatially consistent, the overall BRDF-CCRF and the effect of σ is scale invariant. The surface was modelled as a grid of equilateral triangles and the height of the vertices was set randomly using σ . The procedure is the same as the one applied to water surfaces in Mobley (1994), except there σ is derived from windspeed and the triangles are not equilateral to account for directional dependency of water waves. The light transfer-transfer of photons across the realised surfaces was modelled using Monte Carlo ray tracing, over the discretised sphere described previously. In the work presented here, 5 modelled surfaces were generated with an elevation standard deviation, $\sigma = 0.001, 0.005, 0.01, 0.05$ and 0.1 (Figure A3) and visualised in Figure A3. The surfaces were generated using 10 rays per quad (4320 rays in total) with results averaged over 2000 surfaces. The roughness model being scale invariant, and the relative amplitude defined as 1 meter, the scale height of the roughness is 0.1, 0.5, 1, 5 and 10 cm.

Sea ice roughness shows significant spatial variability, with vertical features ranging from the millimetre-scale to the meter-scale (e.g. Manninen, 1997; Peterson et al., 2008). The larger surface roughness features are generally caused by the deformation of the sea ice, forming rubble fields and pressure ridges that can reach 10 to 20 m in height (Tucker et al., 2013). At a smaller scale, brash ice, ridged blocks or frost flowers can create roughness with a standard deviation of a few millimetres to centimetres. To cover a wide range of conditions, a selection of five surface roughness parameters, defined by the standard deviation of the height of the surface were picked, with a standard deviation of 1 mm to 10 cm relative to two surface points

1m horizontally apart. The range of surface roughness is in agreement with observations reported in the literature for small scale roughnesses (e.g. Tucker et al., 2013).

160 Random surface realisations were generated to calculate the surface roughness in the model, which is rotationally invariant, figure A3. Therefore, Planarrad produces a random surface roughness, that has no specific structure or pattern. Specific complicated shapes present in sea ice, such as pressure ridges were not modelled.

2.3 Calculation of the **BRDF-CCRF** of 3 types of sea ice with different roughness parameters

The **BRDF-CCRF** of three types of sea ice were modelled: first-year ice, multi-year ice and melting ice. The selected optical and physical parameters were based on field studies and cover a wide range of observed values (Lamare et al., 2016; Marks and King, 2014, 2016). A base amount of black carbon was added to the model to be more representative of natural sea ice, as small quantities of black carbon deposited from the atmosphere in polar regions (e.g Doherty et al., 2010) are likely to be found in sea ice. The mass absorption coefficient of black carbon was calculated using Mie theory, using refractive indices from Chang and Charalampopoulos (1990), and following the method described by Flanner et al. (2007). A mass-ratio of 1 ng g^{-1} of black carbon was added to the sea ice, by combining the mass absorption coefficients of sea ice and black carbon. The attenuation coefficient of sea ice was calculated using the scattering cross-sections and densities described by Lamare et al. (2016) and Marks and King (2014), as:

$$\alpha(\lambda) = a(\lambda) + s(\lambda); \quad s(\lambda) = \phi_s \sigma_s, \quad (3)$$

175 where α is the attenuation coefficient of sea ice, a is the absorption coefficient of sea ice with an added mass-ratio of 1 ng g^{-1} of black carbon, s is the scattering coefficient of sea ice, ϕ_s is the scattering cross-section and σ_s is the density. According to Light et al. (2004), the fractional volume of ice is larger than the fractional volume of brine, and the absorption coefficient of ice is similar to the absorption coefficient of brine, hence the absorption coefficient of sea ice may be set equivalent to pure ice. Therefore, the refractive index of pure ice (Warren and Brandt, 2008) was used for sea ice and a refractive index value of 1.0 was used above sea ice. To describe the directionality of the scattering of the sea ice, the Henyey-Greenstein phase function (Henyey and Greenstein, 1941) was used, with a fixed, wavelength independent asymmetry factor g of 0.98 (Lamare et al., 2016). In this work, the asymmetry parameter, g , and the attenuation coefficient, a were held constant, and the scattering coefficient, s was varied to simulate different sea ice configurations, according to the methods outlined in Lee-Taylor and Madronich (2002). The optical and physical parameters of the selected sea ice types are summarised in Table A1A1. The scattering coefficient was fixed with wavelength (Malinka et al., 2018; Lamare et al., 2016).

185 The **BRDF-CCRF** of the three different types of sea ice were subjected to solar radiation with a wavelength from 300 to 1400 nm with a 100 nm interval, as a function of surface roughness and ice thickness. The solar zenith angle was varied in 10 steps corresponding to the centre of the quads, from $\theta_i = 0^\circ$ to $\theta_i = 87.5^\circ$, and the surface roughness parameterisations described in section 2.2 were used, providing a wide range of configurations.

In some of the experiments described here, the sea ice was defined as optically thick, to allow for a direct comparison be-

tween the different types of ice and with studies present in the literature. An optically thick sea ice as defined in this study
190 as a sea ice with a thickness for which the underlying medium (i.e. seawater) does not affect the surface reflectance. ~~The~~
~~Previously~~ sea ice was considered to be optically thick ~~between at 3 to 5 e-folding depths, i.e. where over 95% of the~~
~~incident light diffuse incident radiation~~ is attenuated (France et al., 2011). ~~in the work described here 5 e-folding depths~~
~~i.e. where over 99% of diffuse incident radiation is attenuated, was used as an over cautious approach because unlike previous~~
195 ~~using direct, not diffuse radiation. King et al. (2005) demonstrate that the decay of direct illumination in the near surface region~~
~~of sea ice is not asymptotic.~~ An optically deep thickness of 1.85 m for first-year sea ice, 3.75 m for multi-year sea ice and 20
m for melting sea ice were picked, based on values compiled by Lamare et al. (2016). In a second step, sea ice thicknesses
of 50 cm and 100 cm were selected for the three different types of sea ice. The two thicknesses were chosen to examine and
inter-compare the effect of the sea ice thickness and roughness on the ~~BRDF-CCRF~~ of different sea ice types rather than model
200 representative values. Nevertheless, the model can produce results for a range of thicknesses, from the centimetre scale to
optically thick thicknesses.

3 Results

3.1 ~~Nadir BRF~~ ~~The variation of CCRF with roughness and sea ice and forward scattering peak thickness~~

The nadir ~~BRF of the three types of sea ice was computed with varying thicknesses from 300 nm to 1400 nm and for a fixed~~
205 ~~solar zenith angle of $\theta_i = 60^\circ$. In a second step, the forward principal plane of optically thick first-year sea ice was plotted as a~~
~~function of solar zenith angle for a range of surface roughness values.~~

3.1.1 ~~Nadir BRF of sea ice for varying sea ice thicknesses and surface roughness~~

~~The nadir BRF of CCRF of~~ first-year sea ice, multi-year sea ice and melting sea ice with thicknesses 50 cm, 100 cm and
the optically thick thicknesses are shown in Figure A4. The plotted data were obtained from the nadir quad of PlanarRad,
210 with a surface roughness of $\sigma = 0.01\text{m}$, and a solar zenith angle $\theta_i = 60^\circ$. ~~For the three types of sea ice, the BRF is strongly~~
~~wavelength dependent due to the large absorption in the ice dominating the signal beyond 700 nm, and significantly lowering~~
~~the BRF. Although the different types of sea ice have a similar pattern with wavelength, the BRF increases by 29.5% from~~
~~first-year sea ice to multi-year sea ice at 400 nm and up to 630.7% at 1100 nm, 31.5% from melting sea ice to multi-year sea~~
~~ice at 400 nm and a maximum of 97.7% at 900 nm, and 11.3% from melting sea ice to first-year sea ice at 400 nm and up to~~
215 ~~86.2% at 800 nm.~~ The effect of the thickness of the sea ice on the ~~BRF nadir CCRF~~ varies according to the type of sea ice.
The ~~BRF decreases by 20.6% nadir CCRF decreases by 21%~~ when going from an optically thick first-year sea ice to a 100 cm
thick first-year sea ice and ~~47.447%~~ from optically thick to 50 cm. For multi-year ice the decrease in ~~BRF-CCRF~~ is 3% from
optically thick to 100 cm and ~~12.813%~~ from an optically thick thickness to 50 cm. Melting sea ice shows the largest change in
~~BRF nadir CCRF~~ relative to thickness with a decrease in ~~BRF of 72.9% nadir CCRF of 73%~~ between an optically thick thickness

220 and 100 cm and 83.684% between an optically thick thickness and 50 cm. Melting sea ice is more translucent than first-year or multi-year sea ice, therefore more ~~light penetrates~~ photons penetrate the sea ice deeper and ~~is-are~~ absorbed by the underlying seawater, explaining the larger reduction in ~~BRF-CCRF~~ at nadir. On the contrary, with sea ice types that scatter ~~light photons~~ more efficiently, less ~~light penetrates the ice~~ photons penetrate the ice deeply and the proportion absorbed by the seawater under the ice is less.

225

3.1.1 The effects of roughness on the forward scattering peak of the BRF

To investigate the influence of surface roughness on the location of the dominant directional scattering of ~~light photons~~, hereafter referred to as forward scattering peak, the BRF along the solar principal plane is presented. Knowledge of the intensity and size of the forward scattering peak are essential to reliably calculate the energy budget of the sea ice, and correct for the fluctuations
230 in temporal remote sensing data (e.g. Leroy and Roujean, 1994; Li et al., 1996)(e.g. Leroy and Roujean, 1994; Li et al., 1996; Qu et al., 2000). Figure A5 shows the effects of surface roughness on the forward scattering peak of the ~~BRF-CCRF~~ of optically thick, first-year, sea ice with a solar zenith angle, $\theta_i = 60^\circ$. The results are also representative of multi-year and melting sea ice. Figure A5a displays the intensity, shape and position of the ~~BRF-CCRF~~ peak on the forward solar principal plane ($\phi_r = 0^\circ$). As the surface roughness increases, a spreading of the ~~BRF-CCRF~~ peak is observed. Indeed, the peak remains specular for the smaller
235 surface roughnesses ($\sigma = 0.001$ m to $\sigma = 0.01$ m), whereas for larger surface roughness features (above $\sigma = 0.05$ m), the peak spreads out over multiple quads with a lower intensity than for smaller roughness features, and the highest value is displaced further out on the solar principal plane. ~~Figure A5b shows the effect of surface roughness on the position of the BRF peak on the solar principal plane under different illumination conditions ($\theta_i = 0$ to 87.5°). For the smaller roughness features ($\sigma = 0.001$ m to $\sigma = 0.01$ m), the position of the peak on the solar principal plane is specular and therefore matches the solar zenith angle.~~
240 ~~A roughness of $\sigma = 0.05$ m affects the position of the BRF peak at low sun angles ($\theta_i = 60$ to 87.5°), moving the peak to a lower position on the hemisphere and therefore to a higher viewing zenith angle. For a solar zenith angle $\theta_i = 60^\circ$, the viewing zenith angle is $\theta_r = 70^\circ$, for $\theta_i = 70^\circ$, $\theta_r = 80^\circ$ and for $\theta_i = 80^\circ$ and 87.5° , $\theta_r = 87.5^\circ$. With a surface roughness of $\sigma = 0.1$ m, the forward scattering peak is located at higher viewing zenith angles than the solar zenith angles, except for $\theta_i = 10$ and 20° , where the angle of the forward scattering peak equals the angle of incident illumination.~~

245

3.2 The BRF of sea ice with varying surface roughness

3.1.1 BRF and thickness

Figure A6 shows the ~~BRF-CCRF~~ of first-year, multi-year and melting sea ice with a solar zenith angle, $\theta_i = 60^\circ$ and at a wavelength, $\lambda = 500$ nm. The ~~BRF-CCRF~~ was modelled for three thicknesses as a function of surface roughness: 50 cm, 100
250 cm and an optically thick layer. The modelled ~~BRF-CCRF~~ pattern is similar to snow (e.g. Dumont et al., 2010) and consistent with the literature for sea ice (e.g. Arnold et al., 2002), showing a quasi-isotropic reflectance apart from a strong forward

scattering peak. The surface roughness plays an essential role in the BRF-CCRF of sea ice, by controlling the location and size of the forward scattering peak, as shown previously in Figure A5. Indeed, the peak is mostly specular and located in a single quad for a surface roughness of $\sigma = 0.001 \text{ m}$ and spreads out over multiple quads and moves lower on the hemisphere to larger
 255 viewing zenith angle with a larger surface roughness. As a specific example, for first-year sea ice at $\lambda = 500 \text{ nm}$ and $\theta_i = 60^\circ$, the BRF-CCRF of an optically thick layer with surface roughness of $\sigma = 0.001 \text{ m}$ is 0.543 at nadir. The forward scattering peak is spread over a single quad located at $\phi_r = 0^\circ$, $\theta_r = 60^\circ$, that has a BRF-CCRF of 9.748. For the same configuration with surface roughness of $\sigma = 0.1 \text{ m}$, the nadir has a BRF-CCRF of 0.549 and the forward scattering peak is spread over 18 quads, located between $\phi_r = 345^\circ$ and $\phi_r = 15^\circ$, $\theta_r = 40^\circ$ and $\theta_r = 87.5^\circ$ with values between 0.776 and 5.0895.09. Furthermore,
 260 the effects of thickness and surface roughness on the BRF-CCRF of sea ice are inter-dependantinter-dependent. For smaller surface roughness parameters, an increase in the thickness of the sea ice mainly changes the intensity of the quasi-isotropic part of the BRF-CCRF, affecting the forward scattering peak much less. For the first-year sea ice with the configuration described above and a roughness parameter of $\sigma = 0.001 \text{ m}$, the BRF, the CCRF of the quad with the highest value in the specular peak increases by 2.422% from a 50 cm layer to an optically thick layer whereas the BRF-CCRF at nadir increases by 45.5746%. For
 265 larger surface roughnesses, a change in sea ice thickness affects the specular peak strongly, as well as the quasi-isotropic part of the BRF. The BRF-CCRF. The CCRF of the first-year sea ice described previously with a surface roughness of $\sigma = 0.1 \text{ m}$ changes by 81.66changes by 82% at nadir and between 3.27% and 69.073% and 69% in the forward scattering peak between a layer of 50 cm and an optically thick layer. Thus, the distribution and values of the BRF-CCRF over the azimuth, ϕ and zenith, θ are sensitive to the thickness and the roughness. For small roughnesses ($\sigma < 0.01$) the quasi-isotropic part of the CCRF is
 270 affected by a changing thickness and for large roughnesses ($\sigma \geq 0.01$) the forward scattering peak is also affected.

3.1.1 BRF and solar zenith angle

3.2 The variation of CCRF with roughness and solar zenith angle

Figure A5b shows the effect of surface roughness on the position of the CCRF peak on the solar principal plane under different illumination conditions ($\theta_i = 0$ to 87.5°). For the smaller roughness features ($\sigma = 0.001$ to $\sigma = 0.01$), the position of the peak
 275 on the solar principal plane is specular and therefore matches the solar zenith angle. A roughness of $\sigma = 0.05$ affects the position of the CCRF peak at low sun angles ($\theta_i = 60$ to 87.5°), moving the peak to a lower position on the hemisphere and therefore to a higher viewing zenith angle. For a solar zenith angle $\theta_i = 60^\circ$, the viewing zenith angle is $\theta_r = 70^\circ$, for $\theta_i = 70^\circ$, $\theta_r = 80^\circ$ and for $\theta_i = 80^\circ$ and 87.5° , $\theta_r = 87.5^\circ$. With a surface roughness of $\sigma = 0.1$, the forward scattering peak is located at higher viewing zenith angles than the solar zenith angles, except for $\theta_i = 10$ and 20° , where the angle of the forward scattering
 280 peak equals the angle of incident illumination.

Figure A7 shows the BRF-CCRF of optically thick first-year, multi-year and melting sea ice at $\lambda = 500 \text{ nm}$, with an increasing surface roughness for three solar zenith angles, $\theta_i = 50^\circ$, $\theta_i = 70^\circ$ and $\theta_i = 80^\circ$. Note that the scale of the colour bar varies for the different illumination angles in order to visualise clearly the BRF pattern in figure A7. The results for $\theta_i = 60^\circ$ can be found in Figure A6 for comparison. Low illumination angles (large solar zenith angles) are presented in this study, as

285 they are representative of conditions observable in polar regions. The location and intensity of the forward scattering peak are strongly influenced by the incident zenith angle, whose effects are ~~inter-dependant~~inter-dependent of surface roughness. For a small surface roughness of $\sigma = 0.001\text{m}$, the highest value of the forward scattering peak is equal to the incident illumination angle over the range of solar zenith angles, however the intensity of peak increases with θ_i . For first-year sea ice, the peak ~~BRF-CCRF~~ increases from 5.01 for $\theta_i = 50^\circ$ to ~~28.92~~28.9 for $\theta_i = 70^\circ$ and to ~~143.16~~143 for $\theta_i = 80^\circ$. The forward scattering
290 peak diffuses with larger solar zenith angles, from 1 quad at $\theta_i = 50^\circ$ to 3 quads at $\theta_i = 80^\circ$ for all three types of sea ice. With surface roughnesses of $\sigma = 0.005\text{ m}$ and $\sigma = 0.01\text{ m}$, the forward scattering peak increases in intensity with increasing solar zenith angles, however the peak remains spread over a similar number of quads between $\theta_i = 50^\circ$ and $\theta_i = 80^\circ$. For larger surface roughnesses of $\sigma = 0.05\text{ m}$ and $\sigma = 0.1\text{m}$, although the intensity of the wide forward scattering peak increases with larger solar zenith angles, the intensity is lower than for small roughness parameters. For first-year sea ice with a surface
295 roughness of $\sigma = 0.1\text{m}$, the highest ~~BRF-value is 1.360~~CCRF value is 1.36 for $\theta_i = 50^\circ$ and ~~54.271~~54.3 for $\theta_i = 80^\circ$. Moreover, the forward scattering peak is distributed over a larger number of quads for higher incident illumination angles. At large solar zenith angles, typical of polar latitudes, the isotropic part of the ~~BRF-CCRF~~ remains similar with an increasing surface roughness, whilst the forward scattering peak diffuses and moves to larger viewing zenith angles than the incident illumination angles.

300 3.2.1 ~~BRF and wavelength~~

3.3 The variation of CCRF with roughness and wavelength

~~The BRF~~For the three types of sea ice, the nadir value of the CCRF is strongly wavelength dependent due to the value of the absorption coefficient of ice increasing rapidly with wavelength and starting to change the interplay between scattering and absorption beyond 700 nm, and significantly lowering the CCRF. Although the different types of sea ice have a similar pattern
305 with wavelength, the CCRF increases by 30% from first-year sea ice to multi-year sea ice at 400 nm and up to 631% at 1100 nm, 32% from melting sea ice to multi-year sea ice at 400 nm and a maximum of 98% at 900 nm, and 11% from melting sea ice to first-year sea ice at 400 nm and up to 86% at 800 nm.

However, the CCRF does not decrease uniformly over the hemisphere with an increasing wavelength. The CCRF of optically thick first-year sea ice, multi-year sea ice and melting sea ice with increasing surface roughness, for a solar zenith angle
310 $\theta_i = 60^\circ$ and for wavelengths of $\lambda = 400\text{ nm}$, 800 nm and 1300 nm is shown in Figure A8. The results for $\lambda = 500\text{ nm}$ can be found in Figure A6 for direct comparison. As partly shown in Figure A4, the ~~BRF-CCRF~~ of sea ice is strongly wavelength dependent. At nadir, the highest ~~BRF-CCRF~~ values are found in the near ultra violet and visible wavelengths, decreasing rapidly between 500 and 900 nm. Beyond 900 nm for first-year and melting sea ice and 1000 nm for multi-year sea ice, the ~~BRF-CCRF~~ tends to zero, owing to the absorption by the sea ice. ~~However, the BRF does not decrease uniformly over the~~
315 ~~hemisphere with an increasing wavelength.~~The quasi-isotropic part of the hemisphere follows the same trend as the nadir, whereas the forward scattering peak conserves high ~~BRF-CCRF~~ values, independently of the wavelength. The behaviour is valid for the entire range of roughness parameters. For optically thick first-year sea ice with a solar zenith angle, $\theta_i = 60^\circ$,

the nadir BRF-CCRF decreases by 99.92% from 400 nm to 1300 nm for a surface roughness of $\sigma = 0.001\text{m}$, and by 99.90% for a surface roughness of $\sigma = 0.1\text{m}$. However, the change within the forward scattering peak with wavelength differs for different amounts of surface roughness. ~~The forward scattering peak located at $\phi_r = 0^\circ, \theta_r = 60^\circ$ for first-year sea ice with a surface roughness of $\sigma = 0.001\text{m}$, decreases by 13.94%.~~ For the same configuration with a surface roughness of $\sigma = 0.1\text{m}$, the wider forward scattering peak decreases non-uniformly and reduces in size. Within the 18 quads of the forward scattering peak located between $\phi_r = 345^\circ$ and $\phi_r = 15^\circ$, $\theta_r = 40^\circ$ and $\theta_r = 87.5^\circ$, the highest BRF-CCRF value ($\phi_r = 0^\circ, \theta_r = 87.5^\circ$) decreases by 14.9215%, but the lowest BRF-CCRF value ($\phi_r = 15^\circ, \theta_r = 40^\circ$) decreases by 83.0583% between 400 and 1300 nm. The same behaviour is observable for multi-year and melting sea ice. For small roughnesses ($\sigma \leq 0.01\text{m}$) the intensity of the forward scattering peak that does not change in size varies little with wavelength compared to the quasi-isotropic part of the BRF-CCRF. For large roughnesses ($\sigma > 0.01\text{m}$) the forward scattering peak decreases strongly around the edges with wavelength, whereas the centre quads vary by a small amount as with smaller roughnesses. Furthermore, the quasi-isotropic part of the BRF-CCRF behaves in the same manner than for smaller surface roughnesses.

330 4 Discussion

4.1 The effects of surface roughness on the BRF-CCRF of sea ice

As shown in Sect. 3, surface roughness plays a paramount role in the BRF-CCRF of bare sea ice. Not only does surface roughness have an effect on the reflected radiance, particularly in the forward scattering peak, it also modifies the behaviour of the BRF-CCRF with other controlling parameters such as thickness, solar zenith angle or wavelength. Surface roughness alone principally changes the specular forward scattering peak by diffusing it around the specular point and outwards to a larger viewing zenith angle. Indeed, a smooth surface reflects the incident light photons specularly, whereas reflection from a roughened surface is composed of the specular reflection of the angled facets in multiple directions as well as a diffuse component from the multiple reflections among the facets (Torranca and Sparrow, 1967). A reduction in thickness of a sea ice layer with a small amount of surface roughness mainly decreases the BRF-CCRF in the quasi-isotropic part, having little effect on the specular peak (Figure A6). Indeed, with a thinner sea ice layer, a number of the scattered photons are absorbed by the strongly absorbing underlying layer (reflectance of 0.1) instead of exiting the medium upwards. Most of the ~~light-scattered forwards-exits photons scattered forwards exit~~ the sea ice in the same manner as for an optically thick layer, explaining the smaller reduction in BRF-CCRF for the forward scattering peak. When surface roughness is included, the forward scattering peak is more sensitive to a changing thickness. With an increasing solar zenith angle, the BRF-CCRF with a smaller roughness parameter shows a decrease in intensity of the BRF-CCRF over the whole hemisphere apart from the specular peak that increases and moves in a specular manner relative to the solar zenith angle. With a higher solar zenith angle (lower sun on the horizon), the photons travel less deep into the sea ice than for a lower solar zenith angle and go through fewer scattering events due to the shorter path length and the relative angle between the incident light-path and the surface. Therefore, the ~~light-is photons are~~ less scattered in multiple directions (lower BRF-CCRF over the hemisphere) and more ~~light-is photons are~~ scattered forwards (stronger specular peak). However increasing the surface roughness introduces more scattering events, as

the ~~light is photons are~~ reflected at different angles off the features. Less photons travel directly in a specular manner, reducing the increase in the forward scattering peak with an increasing solar zenith angle, and the larger number of scattering events lead to a smaller reduction in the ~~BRF-CCRF~~ of the remaining hemisphere.

355 Miao et al. (2020) also noted forward scattering of ~~light photons~~ was strongly affected by “ice surface condition”. The ~~BRF~~
~~directional reflectance~~ of sea ice is strongly wavelength dependent owing to the ~~light photons~~ scattering and absorption by the
ice. At shorter wavelengths (~~300—900~~ ~~300–900~~ nm), sea ice is highly scattering, whereas from ~~900—1400~~ ~~900–1400~~ nm the
absorption by the ice dominates, with a nadir ~~BRF-CCRF~~ close to zero (Figure A4). For a small amount of surface roughness,
the ~~BRF-CCRF~~ exhibits the same wavelength dependence over the hemisphere, bar the specular peak (Figure A8). Indeed,
360 at longer wavelengths, the photons that are scattered in the sea ice are more likely to be absorbed than the photons quickly
exiting the medium in a specular direction, creating a strong anisotropy. With increased surface roughness, a similar trend to
the smaller surface roughness is observable, however the size of the forward scattering peak decreases with wavelength. The
reduction may be caused by the absorption of photons at larger wavelengths that would otherwise have exited the ice in a
forward direction after a low number of scattering events within the roughness features at lower wavelengths.

In the literature, a similar behaviour of the response of ~~BRF-CCRF~~ to an increasing roughness was observed by Jin and
365 Simpson (1999), when modelling the anisotropic reflectance factor of sea ice with three different roughnesses. Jin and Simpson
(1999) also modelled the effects of a varying solar zenith angle on the anisotropic reflectance factor of sea ice for a fixed
roughness, showing that the reflectance anisotropy is much larger for a solar zenith angle of 60° than for 45° . The effect of
the solar zenith angle on the angular reflectance of sea ice was confirmed in the work presented here, additionally showing
that surface roughness modulates the intensity and width of the forward scattering peak. Arnold et al. (2002) presented ~~a an~~
370 airborne case measurement of BRF for melt-season ice with a solar zenith angle $\theta_i = 55^\circ$. Their measurement of BRF shows
no significant departure from uniformity across the hemisphere, apart from a forward scattering peak spread widely forward
of the specular peak, suggesting large surface roughness. The BRF pattern ~~, as well as the BRF~~ reported in the principal
plane for melt-season sea ice are in agreement with the modelled ~~BRF pattern of the CCRF~~ presented here. However, the
results from Arnold et al. (2002) are not directly comparable with the modelled ~~BRF-CCRF~~, as the irradiance for the BRF
375 measured with the Cloud Absorption Radiometer instrument is composed of a direct and a diffuse component, whereas the
illumination in the modelling conducted here is direct only. Although not bare sea ice, ~~Manninen et al. (2021) noted there is~~
~~some benefit in the comparison with the effect of surface roughness on the~~ BRF of snow. ~~Manninen et al. (2021) modelled~~
~~the BRF of snow~~ and found surface roughness ~~increased of snow increased the~~ back scattering at large solar zenith ~~angles~~
~~and Carlsen et al. (2020) found MODIS MCD43 underestimate anisotropy of surface reflection. angle. Carlsen et al. (2020)~~
380 ~~measured the HDRF of Antarctic snow surfaces in the wavelength band 490–585 nm using a 180 degree fish-eye camera in~~
~~an airborne platform whilst retrieving the surface roughness using an airborne laser scanner and found that the backscatter~~
~~is enhanced over rougher surfaces concluding that shadows and changing the effective angle of incidence were responsible.~~
~~Accepting that snow and sea ice are different materials with some similar optical similarities the findings presented here are~~
~~consistent with the works of Manninen et al. (2021) and Carlsen et al. (2020)~~

385 4.2 Defining the roughness parameter

Sea ice roughness shows significant spatial variability, with vertical features ranging from the millimetre-scale to the meter-scale (e.g. Manninen, 1997; Peterson et al., 2008). The larger surface roughness features are generally caused by the deformation of the sea ice, forming rubble fields and pressure ridges that can reach 10 to 20 m in height (Tucker et al., 2013). At a smaller scale, brush ice, ridged blocks or frost flowers can create roughness with a standard deviation of a few millimetres to centimetres. As shown in the results (Sect. 3), surface roughness strongly influences the BRDF of sea ice. To cover a wide range of conditions, a selection of five surface roughness parameters, defined by the standard deviation of the height of the surface were picked, with a standard deviation of 1 mm to 10 cm. The range of surface roughness is in agreement with observations reported in the literature for small scale roughnesses (e.g. Tucker et al., 2013). Random surface realisations were generated to calculate the surface roughness in the model, which is rotationally invariant. Therefore, Planarrad produces a random surface roughness, that has no specific structure or pattern. Specific complicated shapes present in sea ice, such as pressure ridges were not modelled.

4.2 Model limitations

As described in Sect. 2.2, Planarrad computes the BRDF-CCRF over a hemisphere discretised into quads, and the calculated radiance leaving the surface is averaged over each quad. The input irradiance was set to a single quad in this study. Therefore the angular resolution of the model is limited to the quad size. Any differences in radiance within a single quad cannot be resolved, which results in a loss of definition for features smaller than the size of a single quad. Furthermore, in this configuration, the radiance for a quad containing the forward scattering maxima is lower than the radiance of a specular peak if it is smaller than a quad. Ideally the solid angle of the illumination source, as well as the solid angle of the quads should tend to zero. However, increasing the discretisation necessitates a considerable computational effort, which led the authors to the current choice of angular resolution representing a balance between resolution and computational resources. Computational time scales roughly as f^3 , where f is the angular resolution.

The radiative-transfer equation was computed without an atmosphere, providing a surface BRDF-CCRF product, whereas the radiance measured by satellite sensors at the Top-Of-Atmosphere (TOA) is a function of the properties of the surface and the atmospheric conditions at the time of the measurement. The purpose of the study was to characterise and quantify the intrinsic BRDF-CCRF of sea ice as a function of roughness and thickness that can be incorporated in radiative transfer models by the community. Therefore, to obtain a direct comparison with remote sensing products that have not been corrected for atmospheric effects, the results of this study have to be propagated to the TOA using an additional radiative-transfer model considering direct and diffuse illumination (e.g. Kotchenova et al., 2008).

In this study, the sea ice was modelled as a single homogeneous slab with defined optical properties. The model does not presently allow for the study of multiple layers with different optical properties. However, PlanarRad allows the input of a BRDF as a lower boundary condition, therefore calculations for a layer of snow on the sea ice are possible. The work presented

here focusses on a comprehensive characterisation of the BRDF-CCRF of bare sea ice which is lacking in the literature, and adding a layer of snow on the sea ice would have added too much complexity. Thus snow was not considered in this study.

420 For the BRDF-CCRF calculations described here, black carbon was assumed to be the only external absorber present in the ice. As described in Sect. 2.3, a base mass-ratio of 1 ng g^{-1} was added to the modelled sea ice. Although organic debris, algae, soot, HULIS-HUmic-Like Substances (HULIS) (Beine et al., 2012; France et al., 2012; Voisin et al., 2012) or mineral dust have an effect of the radiative forcing of sea ice, other light-absorbing impurities other than black carbon were not examined in this study. Additionally, further investigation related to the effects of a varying mass-ratio of light-absorbing light-absorbing impurities on the BRF-CCRF of sea ice is required.

425 5 Conclusions

~~This study~~ The study presented here provides a large dataset parameterising the BRDF-CCRF of bare sea ice, accounting for varying surface roughnesses. The BRDF/BRF-CCRF of three different types of sea ice was modelled, for a wavelength range of ~~300–1400~~ 300–1400 nm. The effects of surface roughness were investigated as a function of thickness, solar zenith angle and wavelength. Radiative-transfer calculations show that surface roughness has a significant effect on the BRDF-CCRF of sea ice, controlling the anisotropy through the forward scattering peak. Furthermore, the surface roughness is inter-dependent of other parameters that determine the BRDF-CCRF pattern of sea ice, such as thickness, solar zenith angle and wavelength. As predicted by the model, the BRDF-CCRF of sea ice exhibits a strong forward scattering peak surrounded by a quasi-isotropic response. For small amounts of surface roughness, a reduction in sea ice thickness decreases the quasi-isotropic part of the BRDF-CCRF, affecting the forward scattering peak very little, ~~the~~ The forward scattering peak changes consistently in a specular manner with a varying solar zenith angle while the intensity of the peak increases, ~~and the~~ The forward scattering peak is much less wavelength ~~dependant~~ dependent than the surrounding quasi-isotropic part of the hemisphere. For larger amounts of surface roughness, a decrease in ice thickness affects strongly the entire BRDF-CCRF, including the forward scattering peak, ~~the~~ The intensity of the forward scattering peak increases and moves to larger viewing zenith angles than the solar zenith angles as the latter increase but remains overall lower than for smaller amounts of surface roughness, ~~and the~~ The size of forward scattering peak is strongly wavelength dependent. ~~Because~~ As the surface roughness is inter-dependent of other physical parameters, it is essential to account for roughness in the theoretical calculations of the radiation budget of sea ice.

440 The study provides a wide range of BRDF-CCRF for sea ice that cover a diversity of conditions encountered in nature. The data generated here is expected to facilitate the development of more accurate radiative-transfer models used to derive albedo products by the remote sensing community, ~~as well as reduce uncertainties in global climate models.~~

445 *Author contributions.* M. L. Lamare performed the modelling, including the data analysis and result preparation, and authored the paper. J. Hedley designed the model, wrote the roughness code, and edited the paper. M. D. King conceived and oversaw the study, and edited the paper.

Competing interests. The authors declare that they have no conflict of interest

450 *Acknowledgements.* The output data from this modelling study are stored on the open repository Zenodo, run by the CERN data centre,
under a Creative Commons license. The data can be found at DOI 10.5281/zenodo.5733402. MDK and MLL thank NERC for support under
~~Grant~~ Grants [NE/K000770X/1](#) and [NE/T00732X/1](#).

Copyright statement. TEXT

Code availability. TEXT

Data availability. The data can be found at DOI 10.5281/zenodo.5733402.

455 *Code and data availability.* The code is available at <http://www.planarrad.com>

Sample availability. TEXT

Video supplement. TEXT

Appendix A

A1

460 *Author contributions.* TEXT

Competing interests. TEXT




Figure A1. **a)** Diagram of the incident and viewing configuration defining $BRDF_{CCR}$. E_i is the irradiance from the azimuth angle ϕ_i and the zenith angle θ_i . L_r is the radiance in the azimuth angle ϕ_r and zenith angle θ_r . In this study, ϕ_i was fixed to 180° , the model being rotationally invariant. **b)** Diagram of the directional surface discretisation scheme used by PlanarRad to compute $BRDF_{CCR}$. Adapted from Hedley (2008).

Disclaimer. TEXT

Acknowledgements. [TEXT](#)

465 **The effects of roughness on the forward scattering peak of the BRF. (a) BRF in the forward solar principle plane ($\phi_r = 0^\circ$) of optically thick first-year sea ice, modelled with a solar zenith angle $\theta_i = 60^\circ$ as a function of surface roughness. (b) Location**




Figure A2. Polar plot of the BRF-CCRF of optically thick first-year sea ice, with a solar zenith angle, $\theta = 60^\circ$ and a roughness parameter of $\sigma = 0.01\text{m}$. The solar azimuth angle ϕ_i is located at 180° , consequently the left half of the hemisphere between $\phi = 90^\circ$ and $\phi = 270^\circ$ represents the backward scattering component and the right half of the hemisphere between $\phi = 270^\circ$ and $\phi = 90^\circ$ represents the forward scattering component. In this case, a strong specular forward scattering peak can be observed centred over the quad located at $\phi_r = 0^\circ$ and $\theta_r = 60^\circ$. A nonlinear colour bar was used to capture the large values around the scattering peak whilst showing the pattern in the quasi-isotropic part of the BRF-CCRF .

of the BRF peak of optically thick first-year sea ice on the forward solar principle plane ($\phi_r = 0^\circ$) as a function of solar zenith angle, θ_i for different surface roughness parameters.




Figure A3. Visualisation of example random surface roughness input parameters, controlled by the standard deviation (σ) of the elevation of the surface. In this study, 5 surface roughnesses of **a)** $\sigma = 0.001$, **b)** $\sigma = 0.005$, **c)** $\sigma = 0.01$, **d)** $\sigma = 0.05$ and **e)** $\sigma = 0.1$ meters were generated.




Figure A4. Nadir BRF-CCRF for first-year, multi-year and melting sea ice, from 300 to 1400 nm in 100 nm steps with a solar zenith angle, $\theta = 60^\circ$ and a roughness parameter of $\sigma = 0.01$ m. The BRF-CCRF of the different types of sea ice is plotted for an optically thick layer (185, 375 and 2000 cm), 100 cm and 50 cm. For each optically thick layer of sea ice, the nadir BRF-CCRF is plotted for surface roughnesses of $\sigma = 0.001$ m and of $\sigma = 0.1$ m. The different sea ice parameters defined in this study are reported in Table [A1](#). The changes in nadir CCRF owing to changes roughness are hard to discern, especially relative to changes in thickness.





Figure A5. The effects of roughness on the forward scattering peak of the CCRF. (a) CCRF in the forward solar principle plane ($\phi_r = 0^\circ$) of optically thick first-year sea ice, modelled with a solar zenith angle $\theta_i = 60^\circ$ as a function of surface roughness. (b) Location of the CCRF peak of optically thick first-year sea ice on the forward solar principle plane ($\phi_r = 0^\circ$) as a function of solar zenith angle, θ_i for different surface roughness parameters.




Figure A6. BRF_{CCRF} of 50 cm, 100 cm and optically thick first-year sea ice, multi-year sea ice and melting sea ice with an increasing surface roughness. The incident angle is $\theta_i = 60^\circ$, and the results are reported for $\lambda = 500 \text{ nm}$.




Figure A7. BRF_{CCRF} of optically thick first-year sea ice, multi-year sea ice and melting sea ice with an increasing surface roughness at $\lambda = 500 \text{ nm}$. The incident angles are $\theta_i = 50^\circ$, $\theta_i = 70^\circ$ and $\theta_i = 80^\circ$. Note that the scale of the colour bar varies for the different illumination angles in order to visualise clearly the BRF pattern. **22**




Figure A8. BRF_{CCRF} of optically thick first-year sea ice, multi-year sea ice and melting sea ice with an increasing surface roughness for $\lambda = 400$, $\lambda = 800$ and $\lambda = 1300$. The incident angle is $\theta_i = 60^\circ$.

Table A1. Sea ice parameters used as input parameters for the PlanarRad model, based on literature values and detailed in the work of Lamare et al. (2016).

Sea ice type	Sea ice density (kg m^{-3})	Sea ice scattering coefficient (m^{-1})	Sea ice asymmetry parameter g	optically thick thickness (cm)	Thickness modelled (cm)
First year sea ice	800	120	0.98	185	50, 100, 185
Multi-year sea ice	800	600	0.98	375	50, 100, 375
Melting sea ice	800	24	0.98	2000	50, 100, 2000

References

- Aoki, T., Aoki, T., Fukabori, M., Hachikubo, A., Tachibana, Y., and Nishio, F.: Effects of snow physical parameters on spectral albedo and bidirectional reflectance of snow surface, *Journal of Geophysical Research: Atmospheres*, 105, 10219–10236, <https://doi.org/10.1029/1999JD901122>, 2000.
- Arnold, G. T., Tsay, S.-C., King, M. D., Li, J. Y., and Soulen, P. F.: Airborne spectral measurements of surface-atmosphere anisotropy for arctic sea ice and tundra, *International Journal of Remote Sensing*, 23, 3763–3781, <https://doi.org/10.1080/01431160110117373>, 2002.
- Bacour, C., Bréon, F.-M., Gonzalez, L., Price, I., Muller, J.-P., and Straume, A. G.: Simulating Multi-Directional Narrowband Reflectance of the Earth's Surface Using ADAM (A Surface Reflectance Database for ESA's Earth Observation Missions), *Remote Sensing*, 12, <https://doi.org/10.3390/rs12101679>, 2020.
- Ball, C. P., Marks, A. A., Green, P. D., MacArthur, A., Maturilli, M., Fox, N. P., and King, M. D.: Hemispherical-Directional Reflectance (HDRF) of Windblown Snow-Covered Arctic Tundra at Large Solar Zenith Angles, *IEEE Transactions on Geoscience and Remote Sensing*, 53, 5377–5387, <https://doi.org/10.1109/TGRS.2015.2421733>, 2015.
- Beine, H., Anastasio, C., Domine, F., Douglas, T., Barret, M., France, J., King, M., Hall, S., and Ullmann, K.: Soluble chromophores in marine snow, seawater, sea ice and frost flowers near Barrow, Alaska, *Journal of Geophysical Research: Atmospheres*, 117, <https://doi.org/https://doi.org/10.1029/2011JD016650>, 2012.
- Bourgeois, C. S., Calanca, P., and Ohmura, A.: A field study of the hemispherical directional reflectance factor and spectral albedo of dry snow, *Journal of Geophysical Research: Atmospheres*, 111, <https://doi.org/10.1029/2006JD007296>, d20108, 2006.
- Buckley, R. G. and Trodahl, H. J.: Scattering and absorption of visible light by sea ice, *Nature*, 326, 867–869, <https://doi.org/10.1038/326867a0>, 1987.
- Carlsen, T., Birnbaum, G., Ehrlich, A., Helm, V., Jäkel, E., Schäfer, M., and Wendisch, M.: Parameterizing anisotropic reflectance of snow surfaces from airborne digital camera observations in Antarctica, *The Cryosphere*, 14, 3959–3978, <https://doi.org/10.5194/tc-14-3959-2020>, 2020.
- Chang, H. and Charalampopoulos, T. T.: Determination of the Wavelength Dependence of Refractive Indices of Flame Soot, *Proceedings of the Royal Society of London A: Mathematical, Physical and Engineering Sciences*, 430, 577–591, <https://doi.org/10.1098/rspa.1990.0107>, 1990.
- Corbett, J. and Su, W.: Accounting for the effects of sastrugi in the CERES clear-sky Antarctic shortwave angular distribution models, *Atmospheric Measurement Techniques*, 8, 3163–3175, <https://doi.org/10.5194/amt-8-3163-2015>, 2015.
- Curry, J. A., Schramm, J. L., and Ebert, E. E.: Sea Ice-Albedo Climate Feedback Mechanism, *Journal of Climate*, 8, 240–247, [https://doi.org/10.1175/1520-0442\(1995\)008<0240:SIACFM>2.0.CO;2](https://doi.org/10.1175/1520-0442(1995)008<0240:SIACFM>2.0.CO;2), 1995.
- Ding, A., Jiao, Z., Dong, Y., Qu, Y., Zhang, X., Xiong, C., He, D., Yin, S., Cui, L., and Chang, Y.: An assessment of the performance of two snow kernels in characterizing snow scattering properties, *International Journal of Remote Sensing*, 40, 6315–6335, <https://doi.org/10.1080/01431161.2019.1590878>, 2019a.
- Ding, A., Jiao, Z., Dong, Y., Zhang, X., Peltoniemi, J. I., Mei, L., Guo, J., Yin, S., Cui, L., Chang, Y., and Xie, R.: Evaluation of the Snow Albedo Retrieved from the Snow Kernel Improved the Ross-Roujean BRDF Model, *Remote Sensing*, 11, <https://doi.org/10.3390/rs11131611>, 2019b.
- Dirmhirn, I. and Eaton, F. D.: Some Characteristics of the Albedo of Snow, *Journal of Applied Meteorology*, 14, 375–379, [https://doi.org/10.1175/1520-0450\(1975\)014<0375:SCOTAO>2.0.CO;2](https://doi.org/10.1175/1520-0450(1975)014<0375:SCOTAO>2.0.CO;2), 1975.

- 505 Doherty, S. J., Warren, S. G., Grenfell, T. C., Clarke, A. D., and Brandt, R. E.: Light-absorbing impurities in Arctic snow, *Atmospheric Chemistry and Physics*, 10, 11 647–11 680, <https://doi.org/10.5194/acp-10-11647-2010>, 2010.
- Dozier, J. and Painter, T. H.: Multispectral and hyperspectral remote sensing of alpine snow properties, *Annual Review of Earth and Planetary Sciences*, 32, 465–494, <https://doi.org/10.1146/annurev.earth.32.101802.120404>, 2004.
- Dozier, J., Davis, R. E., Chang, A. T. C., and Brown, K.: The Spectral Bidirectional Reflectance of Snow, in: *Spectral Signatures of Objects*
- 510 in Remote Sensing, edited by Guyenne, T. D. and Hunt, J. J., vol. 287 of *ESA Special Publication*, p. 87, 1988.
- Dumont, M., Brissaud, O., Picard, G., Schmitt, B., Gallet, J.-C., and Arnaud, Y.: High-accuracy measurements of snow Bidirectional Reflectance Distribution Function at visible and NIR wavelengths & comparison with modelling results, *Atmospheric Chemistry and Physics*, 10, 2507–2520, <https://doi.org/10.5194/acp-10-2507-2010>, 2010.
- Ehrlich, A., Bierwirth, E., Wendisch, M., Herber, A., and Gayet, J.-F.: Airborne hyperspectral observations of surface and cloud directional
- 515 reflectivity using a commercial digital camera, *Atmospheric Chemistry and Physics*, 12, 3493–3510, <https://doi.org/10.5194/acp-12-3493-2012>, 2012.
- Flanner, M. G., Zender, C. S., Randerson, J. T., and Rasch, P. J.: Present-day climate forcing and response from black carbon in snow, *Journal of Geophysical Research: Atmospheres*, 112, <https://doi.org/10.1029/2006JD008003>, 2007.
- Flanner, M. G., Shell, K. M., Barlage, M., Perovich, D. K., and Tschudi, M. A.: Radiative forcing and albedo feedback from the Northern
- 520 Hemisphere cryosphere between 1979 and 2008, *Nature Geoscience*, 4, 151–155, <https://doi.org/10.1038/ngeo1062>, 2011.
- France, J. L., King, M. D., Lee-Taylor, J., Beine, H. J., Ianniello, A., Domine, F., and MacArthur, A.: Calculations of in-snow NO₂ and OH radical photochemical production and photolysis rates: A field and radiative-transfer study of the optical properties of Arctic (Ny-Ålesund, Svalbard) snow, *Journal of Geophysical Research: Earth Surface*, 116, <https://doi.org/10.1029/2011JF002019>, 2011.
- France, J. L., Reay, H. J., King, M. D., Voisin, D., Jacobi, H. W., Domine, F., Beine, H., Anastasio, C., MacArthur, A., and Lee-Taylor, J.:
- 525 Hydroxyl radical and NO_x production rates, black carbon concentrations and light-absorbing impurities in snow from field measurements of light penetration and nadir reflectivity of onshore and offshore coastal Alaskan snow, *Journal of Geophysical Research: Atmospheres*, 117, <https://doi.org/10.1029/2011JD016639>, 2012.
- Gatebe, C. K. and King, M. D.: Airborne spectral BRDF of various surface types (ocean, vegetation, snow, desert, wetlands, cloud decks, smoke layers) for remote sensing applications, *Remote Sensing of Environment*, 179, 131 – 148, <https://doi.org/10.1016/j.rse.2016.03.029>,
- 530 2016.
- Goyens, C., Marty, S., Leymarie, E., Antoine, D., Babin, M., and Bélanger, S.: High Angular Resolution Measurements of the Anisotropy of Reflectance of Sea Ice and Snow, *Earth and Space Science*, 5, 30–47, <https://doi.org/10.1002/2017EA000332>, 2018.
- Hakala, T., Riihelä, A., Lahtinen, P., and Peltoniemi, J. I.: Hemispherical-directional reflectance factor measurements of snow on the Greenland Ice Sheet during the Radiation, Snow Characteristics and Albedo at Summit (RASCALS) campaign, *Journal of Quantitative Spectroscopy and Radiative Transfer*, 146, 280–289, <https://doi.org/10.1016/j.jqsrt.2014.04.010>, electromagnetic and Light Scattering by Non-spherical Particles XIV, 2014.
- 535 Hedley, J.: A three-dimensional radiative transfer model for shallow water environments, *Opt. Express*, 16, 21 887–21 902, <https://doi.org/10.1364/OE.16.021887>, 2008.
- Hedley, J.: PlanaRad, <http://www.planarrad.com>, 2015.
- 540 Hedley, J. D., Roelfsema, C. M., Phinn, S. R., and Mumby, P. J.: Environmental and Sensor Limitations in Optical Remote Sensing of Coral Reefs: Implications for Monitoring and Sensor Design, *Remote Sensing*, 4, 271, <https://doi.org/10.3390/rs4010271>, 2012.
- Henry, L. G. and Greenstein, J. L.: Diffuse radiation in the Galaxy, *Astrophysical Journal*, 93, 70–83, <https://doi.org/10.1086/144246>, 1941.

- Heygster, G., Alexandrov, V., Dybkjær, G., von Hoyningen-Huene, W., Girard-Ardhuin, F., Katsev, I. L., Kokhanovsky, A., Lavergne, T., Malinka, A. V., Melsheimer, C., Toudal Pedersen, L., Prikhach, A. S., Saldo, R., Tonboe, R., Wiebe, H., and Zege, E. P.: Remote sensing of sea ice: advances during the DAMOCLES project, *The Cryosphere*, 6, 1411–1434, <https://doi.org/10.5194/tc-6-1411-2012>, 2012a.
- Heygster, G., Alexandrov, V., Dybkjær, G., von Hoyningen-Huene, W., Girard-Ardhuin, F., Katsev, I. L., Kokhanovsky, A., Lavergne, T., Malinka, A. V., Melsheimer, C., Toudal Pedersen, L., Prikhach, A. S., Saldo, R., Tonboe, R., Wiebe, H., and Zege, E. P.: Remote sensing of sea ice: advances during the DAMOCLES project, *The Cryosphere*, 6, 1411–1434, <https://doi.org/10.5194/tc-6-1411-2012>, 2012b.
- Hudson, S. R., Warren, S. G., Brandt, R. E., Grenfell, T. C., and Six, D.: Spectral bidirectional reflectance of Antarctic snow: Measurements and parameterization, *Journal of Geophysical Research: Atmospheres* (1984–2012), 2006.
- Hudson, S. R., Kato, S., and Warren, S. G.: Evaluating CERES angular distribution models for snow using surface reflectance observations from the East Antarctic Plateau, *Journal of Geophysical Research: Atmospheres*, 115, <https://doi.org/10.1029/2009JD012624>, 2010.
- Jiao, Z., Ding, A., Kokhanovsky, A., Schaaf, C., Bréon, F.-M., Dong, Y., Wang, Z., Liu, Y., Zhang, X., Yin, S., Cui, L., Mei, L., and Chang, Y.: Development of a snow kernel to better model the anisotropic reflectance of pure snow in a kernel-driven BRDF model framework, *Remote Sensing of Environment*, 221, 198–209, <https://doi.org/10.1016/j.rse.2018.11.001>, 2019.
- Jin, Z. and Simpson, J.: Bidirectional anisotropic reflectance of snow and sea ice in AVHRR Channel 1 and 2 spectral regions. I. Theoretical analysis, *IEEE Transactions on Geoscience and Remote Sensing*, 37, 543–554, <https://doi.org/10.1109/36.739110>, 1999.
- Jin, Z. and Simpson, J. J.: Anisotropic Reflectance of Snow Observed from Space over the Arctic and Its Effect on Solar Energy Balance, *Remote Sensing of Environment*, 75, 63–75, [https://doi.org/10.1016/S0034-4257\(00\)00156-5](https://doi.org/10.1016/S0034-4257(00)00156-5), 2001.
- Joerg, P. C., Weyermann, J., Morsdorf, F., Zemp, M., and Schaepman, M. E.: Computation of a distributed glacier surface albedo proxy using airborne laser scanning intensity data and in-situ spectro-radiometric measurements, *Remote Sensing of Environment*, 160, 31–42, <https://doi.org/10.1016/j.rse.2014.12.017>, 2015.
- Khan, A., Dierssen, H., Schwarz, J., Schmitt, C., Chlus, A., Hermanson, M., Painter, T., and Mcknight, D.: Impacts of coal dust from an active mine on the spectral reflectance of Arctic surface snow in Svalbard, Norway: Coal mine impacts Arctic snow albedo, *Journal of Geophysical Research: Atmospheres*, 122, <https://doi.org/10.1002/2016JD025757>, 2017.
- King, M., France, J., Fisher, F., and Beine, H.: Measurement and modelling of UV radiation penetration and photolysis rates of nitrate and hydrogen peroxide in Antarctic sea ice: An estimate of the production rate of hydroxyl radicals in first-year sea ice, *Journal of Photochemistry and Photobiology A: Chemistry*, 176, 39–49, <https://doi.org/https://doi.org/10.1016/j.jphotochem.2005.08.032>, in Honour of Professor Richard P. Wayne, 2005.
- Kokhanovsky, A. A. and Breon, F.-M.: Validation of an Analytical Snow BRDF Model Using PARASOL Multi-Angular and Multispectral Observations, *IEEE Geoscience and Remote Sensing Letters*, 9, 928–932, <https://doi.org/10.1109/LGRS.2012.2185775>, 2012a.
- Kokhanovsky, A. A. and Breon, F.-M.: Validation of an Analytical Snow BRDF Model Using PARASOL Multi-Angular and Multispectral Observations, *IEEE Geoscience and Remote Sensing Letters*, 9, 928–932, <https://doi.org/10.1109/LGRS.2012.2185775>, 2012b.
- Kotchenova, S. Y., Vermote, E. F., Levy, R., and Lyapustin, A.: Radiative transfer codes for atmospheric correction and aerosol retrieval: intercomparison study., *Applied Optics*, 47, 2215–2226, 2008.
- Kuchiki, K., Aoki, T., Niwano, M., Motoyoshi, H., and Iwabuchi, H.: Effect of sastrugi on snow bidirectional reflectance and its application to MODIS data, *Journal of Geophysical Research: Atmospheres*, 116, <https://doi.org/https://doi.org/10.1029/2011JD016070>, 2011.
- Lamare, M. L., Lee-Taylor, J., and King, M. D.: The impact of atmospheric mineral aerosol deposition on the albedo of snow & sea ice: are snow and sea ice optical properties more important than mineral aerosol optical properties?, *Atmospheric Chemistry and Physics*, 16, 843–860, <https://doi.org/10.5194/acp-16-843-2016>, 2016.

- Lee-Taylor, J. and Madronich, S.: Calculation of actinic fluxes with a coupled atmosphere–snow radiative transfer model, *Journal of Geophysical Research: Atmospheres*, 107, ACH 22–1–ACH 22–10, <https://doi.org/10.1029/2002JD002084>, 2002.
- Leroux, C., Deuzé, J.-L., Goloub, P., Sergent, C., and Fily, M.: Ground measurements of the polarized bidirectional reflectance of snow in the near-infrared spectral domain: Comparisons with model results, *Journal of Geophysical Research: Atmospheres* (1984–2012), 1998.
- 585 Leroux, C., Lenoble, J., Brogneiz, G., Hovenier, J., and De Hann, J.: A model for the bidirectional polarized reflectance of snow, *Journal of Quantitative Spectroscopy and Radiative Transfer*, 61, 273–285, [https://doi.org/10.1016/S0022-4073\(97\)00221-5](https://doi.org/10.1016/S0022-4073(97)00221-5), 1999.
- Leroy, M. and Roujean, J. L.: Sun and view angle corrections on reflectances derived from NOAA/AVHRR data, *IEEE Transactions on Geoscience and Remote Sensing*, 32, 684–697, <https://doi.org/10.1109/36.297985>, 1994.
- Li, S. and Zhou, X.: Derivation and comparison of bi-directional reflectance functions of first-year and multi-year sea ice types
590 in the Southern Ocean, in: *IEEE International Geoscience and Remote Sensing Symposium*, vol. 3, pp. 1944–1946 vol.3, <https://doi.org/10.1109/IGARSS.2002.1026308>, 2002.
- Li, S. and Zhou, X.: Comparison among simulated sea ice surface bidirectional reflectance factor (BRF), hemispherical-directional reflectance factor (HDRF) and field measurements, in: *IGARSS 2004. 2004 IEEE International Geoscience and Remote Sensing Symposium*, vol. 2, pp. 903–905 vol.2, <https://doi.org/10.1109/IGARSS.2004.1368553>, 2004a.
- 595 Li, S. and Zhou, X.: Modelling and measuring the spectral bidirectional reflectance factor of snow-covered sea ice: an intercomparison study, *Hydrological Processes*, 2004b.
- Li, Z., Cihlar, J., Zheng, X., Moreau, L., and Ly, H.: The bidirectional effects of AVHRR measurements over boreal regions, *IEEE Transactions on Geoscience and Remote Sensing*, 34, 1308–1322, <https://doi.org/10.1109/36.544556>, 1996.
- Light, B., Maykut, G. A., and Grenfell, T. C.: A temperature-dependent, structural-optical model of first-year sea ice, *Journal of Geophysical
600 Research: Oceans*, 109, <https://doi.org/10.1029/2003JC002164>, c06013, 2004.
- Lim, A., Hedley, J. D., LeDrew, E., Mumby, P. J., and Roelfsema, C.: The effects of ecologically determined spatial complexity on the classification accuracy of simulated coral reef images, *Remote Sensing of Environment*, 113, 965–978, <https://doi.org/10.1016/j.rse.2009.01.011>, 2009.
- Lv, Y., Wu, D., and Sun, Z.: Effect of Black Carbon Concentration on the Reflection Property of Snow: A Comparison With Model Results,
605 *IEEE Transactions on Geoscience and Remote Sensing*, 56, 6823–6840, <https://doi.org/10.1109/TGRS.2018.2843817>, 2018.
- Lyapustin, A., Gatebe, C. K., Kahn, R., Brandt, R., Redemann, J., Russell, P., King, M. D., Pedersen, C. A., Gerland, S., Poudyal, R., Marshak, A., Wang, Y., Schaaf, C., Hall, D., and Kokhanovsky, A.: Analysis of snow bidirectional reflectance from ARCTAS Spring-2008 Campaign, *Atmospheric Chemistry and Physics*, 10, 4359–4375, <https://doi.org/10.5194/acp-10-4359-2010>, 2010.
- Malinka, A., Zege, E., Heygster, G., and Istomina, L.: Reflective properties of white sea ice and snow, *The Cryosphere*, 10, 2541–2557,
610 <https://doi.org/10.5194/tc-10-2541-2016>, 2016.
- Malinka, A., Zege, E., Istomina, L., Heygster, G., Spreen, G., Perovich, D., and Polashenski, C.: Reflective properties of melt ponds on sea ice, *The Cryosphere*, 12, 1921–1937, <https://doi.org/10.5194/tc-12-1921-2018>, 2018.
- Manninen, A. T.: Surface roughness of Baltic sea ice, *Journal of Geophysical Research: Oceans*, 102, 1119–1139, <https://doi.org/10.1029/96JC02991>, 1997.
- 615 Manninen, T., Anttila, K., Jääskeläinen, E., Riihelä, A., Peltoniemi, J., Räisänen, P., Lahtinen, P., Siljamo, N., Thölix, L., Meinander, O., Kontu, A., Suokanerva, H., Pirazzini, R., Suomalainen, J., Hakala, T., Kaasalainen, S., Kaartinen, H., Kukko, A., Hautecoeur, O., and Roujean, J.-L.: Effect of small-scale snow surface roughness on snow albedo and reflectance, *The Cryosphere*, 15, 793–820, <https://doi.org/10.5194/tc-15-793-2021>, 2021.

- Marks, A. and King, M.: The effect of snow/sea ice type on the response of albedo and light penetration depth (e-folding depth) to increasing black carbon, *The Cryosphere*, 8, 1625–1638, <https://doi.org/10.5194/tc-8-1625-2014>, 2014.
- Marks, A., Fragiaco, C., MacArthur, A., Zibordi, G., Fox, N., and King, M. D.: Characterisation of the HDRF (as a proxy for BRDF) of snow surfaces at Dome C, Antarctica, for the inter-calibration and inter-comparison of satellite optical data, *Remote Sensing of Environment*, 158, 407–416, <https://doi.org/10.1016/j.rse.2014.11.013>, 2015.
- Marks, A. A. and King, M. D.: The effects of additional black carbon on the albedo of Arctic sea ice: variation with sea ice type and snow cover, *The Cryosphere*, 7, 1193–1204, <https://doi.org/10.5194/tc-7-1193-2013>, 2013.
- Miao, Y., Peng, L., Xiao-wei, C., Ming-guang, T., Qing-kai, W., and Zhi-jun, L.: Field Observations of the Bidirectional Reflectance Characteristics of Lake Ice, *Spectroscopy and spectral analysis*, 40, 2453–2461, 2020.
- Middleton, W. E. K. and Mungall, A. G.: The Luminous Directional Reflectance of Snow*, *J. Opt. Soc. Am.*, 42, 572–579, <https://doi.org/10.1364/JOSA.42.000572>, 1952.
- Mishchenko, M. I., Dlugach, J. M., Yanovitskij, E. G., and Zakharova, N. T.: Bidirectional reflectance of flat, optically thick particulate layers: an efficient radiative transfer solution and applications to snow and soil surfaces, *Journal of Quantitative Spectroscopy & Radiative Transfer*, 1999.
- Mobley, C. D.: A numerical model for the computation of radiance distributions in natural waters with wind-roughened surfaces, *Limnology and Oceanography*, 34, 1473–1483, <https://doi.org/10.4319/lo.1989.34.8.1473>, 1989.
- Mobley, C. D.: *Light and Water: Radiative Transfer in Natural Waters*, Academic Press, 1994.
- Nicodemus, F. E., Richmond, J. C., Hsia, J. J., Ginsberg, I. W., and Limperis, T.: *Geometrical Considerations and Nomenclature for Reflectance*, U.S. Nat. Bureau Standards, 1977.
- Painter, T. H. and Dozier, J.: Measurements of the hemispherical-directional reflectance of snow at fine spectral and angular resolution, *Journal of Geophysical Research: Atmospheres*, 109, <https://doi.org/10.1029/2003JD004458>, 2004.
- Painter, T. H., Seidel, F. C., Bryant, A. C., McKenzie Skiles, S., and Rittger, K.: Imaging spectroscopy of albedo and radiative forcing by light-absorbing impurities in mountain snow, *Journal of Geophysical Research: Atmospheres*, 118, 9511–9523, <https://doi.org/10.1002/jgrd.50520>, 2013.
- Peltoniemi, J., Kaasalainen, S., Naranen, J., Matikainen, L., and Piironen, J.: Measurement of directional and spectral signatures of light reflectance by snow, *IEEE Transactions on Geoscience and Remote Sensing*, 43, 2294–2304, <https://doi.org/10.1109/TGRS.2005.855131>, 2005a.
- Peltoniemi, J., Hakala, T., Suomalainen, J., and Puttonen, E.: Polarised bidirectional reflectance factor measurements from soil, stones, and snow, *Journal of Quantitative Spectroscopy and Radiative Transfer*, 110, 1940–1953, <https://doi.org/10.1016/j.jqsrt.2009.04.008>, 2009.
- Peltoniemi, J. I., Kaasalainen, S., and Naranen, J.: Measurement of directional and spectral signatures of light reflectance by snow, *Geoscience and Remote Sensing, IEEE Transactions on*, 2005b.
- Peltoniemi, J. I., Gritsevich, M., Hakala, T., Dagsson-Waldhauserová, P., Arnalds, O., Anttila, K., Hannula, H.-R., Kivekäs, N., Lihavainen, H., Meinander, O., Svensson, J., Virkkula, A., and de Leeuw, G.: Soot on Snow experiment: bidirectional reflectance factor measurements of contaminated snow, *The Cryosphere*, 9, 2323–2337, <https://doi.org/10.5194/tc-9-2323-2015>, 2015.
- Perovich, D. K.: *The Optical Properties of Sea Ice.*, Monograph 96-1, U. S. Cold Reg. Res. and Eng. Lab., 1996.
- Perovich, D. K., Grenfell, T. C., Light, B., and Hobbs, P. V.: Seasonal evolution of the albedo of multiyear Arctic sea ice, *Journal of Geophysical Research: Oceans*, 107, <https://doi.org/10.1029/2000JC000438>, 8044, 2002.

- Peterson, I. K., Prinsenberg, S. J., and Holladay, J. S.: Observations of sea ice thickness, surface roughness and ice motion in Amundsen Gulf, *Journal of Geophysical Research: Oceans*, 113, <https://doi.org/10.1029/2007JC004456>, 2008.
- Pope, E. L., Willis, I. C., Pope, A., Miles, E. S., Arnold, N. S., and Rees, W. G.: Contrasting snow and ice albedos derived from MODIS, Landsat ETM+ and airborne data from Langjökull, Iceland, *Remote Sensing of Environment*, 175, 183–195, 2016.
- 660 Qu, X. and Hall, A.: Surface Contribution to Planetary Albedo Variability in Cryosphere Regions, *Journal of Climate*, 18, 5239 – 5252, <https://doi.org/10.1175/JCLI3555.1>, 2005.
- Qu, Y., Liang, S., Liu, Q., He, T., Liu, S., and Li, X.: Mapping Surface Broadband Albedo from Satellite Observations: A Review of Literatures on Algorithms and Products, *Remote Sensing*, 7, 990–1020, <https://doi.org/10.3390/rs70100990>, 2015.
- Qu, Y., Liang, S., Liu, Q., Li, X., Feng, Y., and Liu, S.: Estimating Arctic sea-ice shortwave albedo from MODIS data, *Remote Sensing of Environment*, 186, 32–46, <https://doi.org/https://doi.org/10.1016/j.rse.2016.08.015>, 2016a.
- 665 Qu, Y., Liang, S., Liu, Q., Li, X., Feng, Y., and Liu, S.: Estimating Arctic sea-ice shortwave albedo from MODIS data, *Remote Sensing of Environment*, 186, 32–46, <https://doi.org/10.1016/j.rse.2016.08.015>, 2016b.
- Qu, Y., Liu, Q., and Liu, S.: A Forward Kernel Function for Fitting in situ Measured Snow Bidirectional Reflectance Factor, *Spectroscopy and spectral analysis*, 36, 2749–2754, 2016c.
- 670 Redmond Roche, B. H. and King, M. D.: Quantifying the climatic impact of crude oil pollution on sea ice albedo, *The Cryosphere Discussions*, 2022, 1–36, <https://doi.org/10.5194/tc-2021-372>, 2022.
- Ren, S., Miles, E. S., Jia, L., Menenti, M., Kneib, M., Buri, P., McCarthy, M. J., Shaw, T. E., Yang, W., and Pellicciotti, F.: Anisotropy Parameterization Development and Evaluation for Glacier Surface Albedo Retrieval from Satellite Observations, *Remote Sensing*, 13, <https://doi.org/10.3390/rs13091714>, 2021.
- 675 Schaeppman-Strub, G., Schaeppman, M., Painter, T., Dangel, S., and Martonchik, J.: Reflectance quantities in optical remote sensing—definitions and case studies, *Remote Sensing of Environment*, 103, 27–42, <https://doi.org/10.1016/j.rse.2006.03.002>, 2006.
- Schlosser, E.: Optical studies of Antarctic sea ice, *Cold Regions Science and Technology*, 15, 289–293, [https://doi.org/10.1016/0165-232X\(88\)90075-4](https://doi.org/10.1016/0165-232X(88)90075-4), 1988.
- Stamnes, K., Hamre, B., Stamnes, J., Ryzhikov, G., Biryulina, M., Mahoney, R., Hauss, B., and Sei, A.: Modeling of radiation transport in coupled atmosphere-snow-ice-ocean systems, *Journal of Quantitative Spectroscopy and Radiative Transfer*, 112, 714 – 726, <https://doi.org/10.1016/j.jqsrt.2010.06.006>, 2011.
- 680 Stanton, B., Miller, D., Adams, E., and Shaw, J. A.: Bidirectional-reflectance measurements for various snow crystal morphologies, *Cold Regions Science and Technology*, 124, 110–117, <https://doi.org/10.1016/j.coldregions.2015.12.011>, 2016.
- Sun, Z. and Zhao, Y.: The effects of grain size on bidirectional polarized reflectance factor measurements of snow, *Journal of Quantitative Spectroscopy and Radiative Transfer*, 112, 2372–2383, <https://doi.org/10.1016/j.jqsrt.2011.05.011>, 2011.
- 685 Torrance, K. E. and Sparrow, E. M.: Theory for Off-Specular Reflection From Roughened Surfaces*, *J. Opt. Soc. Am.*, 57, 1105–1114, <https://doi.org/10.1364/JOSA.57.001105>, 1967.
- Tucker, W. B., Perovich, D. K., Gow, A. J., Weeks, W. F., and Drinkwater, M. R.: Physical Properties of Sea Ice Relevant to Remote Sensing, pp. 9–28, American Geophysical Union, <https://doi.org/10.1029/GM068p0009>, 2013.
- 690 Voisin, D., Jaffrezo, J.-L., Houdier, S., Barret, M., Cozic, J., King, M. D., France, J. L., Reay, H. J., Grannas, A., Kos, G., Ariya, P. A., Beine, H. J., and Domine, F.: Carbonaceous species and humic like substances (HULIS) in Arctic snowpack during OASIS field campaign in Barrow, *Journal of Geophysical Research: Atmospheres*, 117, <https://doi.org/https://doi.org/10.1029/2011JD016612>, 2012.

- Wang, L., Hu, X., and Chen, L.: Assessment of BRDF effect of Kunlun Mountain glacier on Tibetan Plateau as a potential pseudo-invariant calibration site, in: *Sensors, Systems, and Next-Generation Satellites XXI*, edited by Neeck, S. P., Bézy, J.-L., and Kimura, T., vol. 10423, pp. 424 – 431, International Society for Optics and Photonics, SPIE, <https://doi.org/10.1117/12.2278203>, 2017.
- Warren, S. G. and Brandt, R. E.: Optical constants of ice from the ultraviolet to the microwave: A revised compilation, *Journal of Geophysical Research: Atmospheres*, 113, <https://doi.org/10.1029/2007JD009744>, 2008.
- Warren, S. G., Brandt, R. E., and O’Rawe Hinton, P.: Effect of surface roughness on bidirectional reflectance of Antarctic snow, *Journal of Geophysical Research: Planets*, 103, 25 789–25 807, <https://doi.org/10.1029/98JE01898>, 1998.
- Weeks, W. F. and Ackley, S. F.: Growth conditions and the structure and properties of sea ice, in: *Physics of Ice Covered Seas: An Advanced Study Institute-Summer School*, Springer, 1994.
- Wu, H., Liang, S., Tong, L., and He, T.: Snow BRDF characteristics from MODIS and MISR data, in: *2011 IEEE International Geoscience and Remote Sensing Symposium*, pp. 3187–3190, <https://doi.org/10.1109/IGARSS.2011.6049896>, 2011.
- Wu, H., Liang, S., Tong, L., He, T., and Yu, Y.: Bidirectional Reflectance for Multiple Snow-Covered Land Types From MISR Products, *IEEE Geoscience and Remote Sensing Letters*, 9, 994–998, <https://doi.org/10.1109/LGRS.2012.2187041>, 2012.
- Xiong, C. and Shi, J.: Simulating polarized light scattering in terrestrial snow based on bicontinuous random medium and Monte Carlo ray tracing, *Journal of Quantitative Spectroscopy and Radiative Transfer*, 133, 177–189, <https://doi.org/10.1016/j.jqsrt.2013.07.026>, 2014.
- Yang, B., Zhao, H., and Chen, W.: Modeling polarized reflectance of snow and ice surface using POLDER measurements, *Journal of Quantitative Spectroscopy and Radiative Transfer*, 236, 106 578, <https://doi.org/10.1016/j.jqsrt.2019.106578>, 2019.
- Zege, E., Katsev, I., Malinka, A., Prikhach, A., Heygster, G., and Wiebe, H.: Algorithm for retrieval of the effective snow grain size and pollution amount from satellite measurements, *Remote Sensing of Environment*, 115, 2674–2685, <https://doi.org/10.1016/j.rse.2011.06.001>, 2011.
- Zege, E., Malinka, A., Katsev, I., Prikhach, A., Heygster, G., Istomina, L., Birnbaum, G., and Schwarz, P.: Algorithm to retrieve the melt pond fraction and the spectral albedo of Arctic summer ice from satellite optical data, *Remote Sensing of Environment*, 163, 153–164, <https://doi.org/10.1016/j.rse.2015.03.012>, 2015.